

Wireshark Setup (Kali Linux)

This document explains the **step-by-step setup of Wireshark** for PCAP-based network traffic analysis. This setup was used for **Project 6 – Network Traffic Analysis (PCAP)**.

1. System Requirements

- Operating System: **Kali Linux** (VM or bare metal)
 - RAM: Minimum **4 GB** (8 GB recommended)
 - Disk Space: ~2 GB free
 - Network: Not required for offline PCAP analysis
-

2. Installing Wireshark

Step 1: Update system packages

```
sudo apt update && sudo apt upgrade -y
```

Step 2: Install Wireshark

```
sudo apt install wireshark -y
```

Step 3: Allow non-root packet capture (recommended)

During installation, you will be prompted:

Allow non-superusers to capture packets?

Select: **Yes**

If skipped, configure manually:

```
sudo dpkg-reconfigure wireshark-common
```

```
sudo usermod -aG wireshark $USER
```

Reboot the system after this step.

3. Verifying Installation

Check Wireshark version:

```
wireshark --version
```

Launch Wireshark:

wireshark

Expected result:

- Wireshark GUI opens without errors
 - Interfaces and menu options are visible
-

4. PCAP-Based Analysis Setup (Offline Mode)

△ Live capture is **not required** for this project

Step 1: Download PCAP files

PCAP files can be downloaded from trusted sources such as:

- Malware Traffic Analysis >>>> >The pcap file used in this project is from this site<<<<<
- Blue Team Labs Online
- Wireshark Sample Captures

Step 2: Open PCAP file

- Open Wireshark
 - Click **File** → **Open**
 - Select the .pcap file
-

5. Recommended Wireshark Preferences

Navigate to:

Edit → Preferences

Recommended Settings

- **Name Resolution:** Disabled (to avoid DNS noise)
 - **Time Format:** Seconds Since Beginning of Capture
 - **Layout:** Three-pane default
-

6. Enabling Useful Columns

Right-click any column → **Column Preferences**

Add:

- Time
- Source
- Destination
- Protocol
- Length
- Info

These columns help during DNS, HTTP, and beaconing analysis.

7. Important Wireshark Tools Used

Tool	Purpose
Display Filters	Protocol-specific analysis
Statistics → Conversations	Identify top talkers
Statistics → Endpoints	IP activity analysis
Statistics → I/O Graphs	Detect spikes & beaconing
Follow Stream	View HTTP content

8. Display Filters Used in Project

`dns`

`http`

`udp.port == 53`

`http.request`

`ip.addr == <suspicious_ip>`

9. Common Issues & Fixes

Issue: No packets visible

- Ensure PCAP file is loaded
- Clear display filters

Issue: Time duration not visible

- Go to **View** → **Time Display Format** → **Seconds Since Beginning of Capture**

Issue: Permission denied

- Ensure user is in `wireshark` group
 - Reboot system
-

10. Project Usage Confirmation

Wireshark was used to:

- Analyze DNS queries
 - Inspect HTTP requests
 - Detect abnormal traffic spikes
 - Identify suspicious IP behavior
 - Observe potential beaconing patterns
-

11. Conclusion

Wireshark was successfully installed and configured for **offline PCAP analysis**. The setup supports SOC Level 1 and penetration testing fundamentals and aligns with real-world traffic analysis workflows.