



Name :

Roll No. :

Invigilator's Signature :

CS/B.Tech(CSE,IT,ECE(O),EIE(O) PWE EEE/SEM-5/EI-502/2009-10

2009

MICROPROCESSOR AND MICROCONTROLLER

Time Allotted : 3 Hours

Full Marks : 70

The figures in the margin indicate full marks.

*Candidates are required to give their answers in their own words
as far as practicable.*

GROUP – A

(Multiple Choice Type Questions)

1. Choose the correct alternatives for any *ten* of the following :

$$10 \times 1 = 10$$

- i) Whenever the PUSH instruction is executed the stack pointer is
 - a) decremented by 1
 - b) decremented by 2
 - c) incremented by 1
 - d) incremented by 2.
- ii) A single instruction to clear the lower four bits of the accumulator in 8085 microprocessor is
 - a) XRI OFH
 - b) ANI FOH
 - c) ANI OFH
 - d) XRI FOH.

a) 6 b) 5

c) 4 d) 3.

a) 13 b) 14

c) 15 d) 16.

a) Mode 1 b) Mode 0

c) Mode 2 d) Either (a) & (c).

a) F8h

b) FA h

c) FC h

d) F9 h.

a) CS AND SI b) DS and IP

c) CS and SP d) CS and IP.



viii) Mode 2 of 8253 is

- a) Square wave generator
- b) Rate generator
- c) Software trigger stroke
- d) Hardware trigger strobe.

ix) PSW is a register.

- a) 8 bit
- b) 16 bit
- c) 20 bit
- d) 32 bit.

x) If READY pin is grounded, it will introduce states into the bus cycle of 8086 microprocessor.

- a) wait
- b) idle
- c) wait and remain idle
- d) all of these.

xi) The call location for TRAP interrupt is

- a) 0000h
- b) 0020h
- c) 0024h
- d) 0034h.

xii) In order to enable TRAP interrupt, which of the following instructions is are needed ?

- a) EI only
- b) SIM only
- c) EI and SIM
- d) none of these.

xiii) In 8085 microprocessor, the addressable memory is

- a) 64 KB
- b) 1 MB
- c) 4 KB
- d) 16 KB.

- GROUP – B**

Answer any *three* of the following. $3 \times 5 = 15$

- | | |
|------|--------------|
| C000 | LXI SP, D050 |
| C003 | POP H |
| C004 | XRA A |
| C005 | MOV A, H |
| C006 | ADD L |
| C007 | MOV H, A |
| C008 | PUSH H |
| C009 | PUSH PSW |
| C00A | HLT |

D050	05
D051	40
D052	52
D053	03
D054	XX

4



4. Discuss the functions of following instruction of 8085 : 5×1

RAR, LHLD C020H, DAD, CALL D050H, DCX B

5. What are the advantages of having segmentation ? How does 8086 μ P support sementation ? $3 + 2$

6. What is subroutine ? What is the difference between CALL & JMP instructions ? $2 + 3$

GROUP – C

(Long Answer Type Questions)

Answer any *three* of the following. $3 \times 15 = 45$

7. a) How many ports are there in 8255 and what are they ?

- b) Discuss the different bits of the control word of 8255.

- c) Write down the MODE-0 control word for the following :

i) Port A = Input

ii) Port B not used

iii) Port C upper = Input, Port C lower = output.

- d) Discuss BSR operation of 8255. $2 + 5 + 3 + 5$



8. a) Explain how 20-bit physical address is generated in 8086 microprocessor.

b) What is the purpose of queue ? How many words does the queue store in the 8086 microprocessor ?

c) How does 8086 support pipelining ? Explain.

d) What are the advantages of having memory segmentation ? $3 + (1 + 3 + 5 + 3)$

9. a) Describe the priority scheme & EOI scheme of 8259.

b) Write down the format of ICW1 & ICW2 of 8259.

c) With respect to 8237 explain the DMA operation.

$$5 + 5 + 5$$

10. a) Write a program to find out the largest number, starting from D000 H of 10 numbers and store result in D050 H.

b) Write a program to find out square of a data using LookUp table.

$$7\frac{1}{2} + 7\frac{1}{2}$$



11. a) What are the vectored and non-vectored interrupts ?
- b) Explain the instruction RIM and SIM. Write the program for enable the RST-7·5, RST-6·5 and disable RST-5·5.
- c) Discuss how 8253 is used to generate square wave.
- d) What are the major components of 8259A interrupt controller ? Explain their functions.
- e) Write the BSR control word for setting PC_4 in 8255A.

$$2 + 5 + 3 + 3 + 2$$

=====