CS/B.TECH/ECE/EVEN/SEM-8/EC-802C/2015-16



MAULANA ABUL KALAM AZAD UNIVERSITY OF TECHNOLOGY, WEST BENGAL Paper Code :EC-802C RENEWABLE ENERGY

Time Allotted: 3 Hours

http://www.makaut.com

Full Marks: 70

The figures in the margin indicate full marks. Candidates are required to give their answers in their own words as far as practicable.

GROUP - A

(Multiple Choice Type Questions)

- Choose the correct alternatives for any ten of the $10 \times 1 = 10$ following:
 - Photo-voltaic (PV) cell is basically a
 - p-n junction
 - photo-transistor
 - amorphous p n junction c)
 - none of these.
 - Which of the following is not renewable energy source?
 - Hydropower
- Tidal power
- Geothermal
- Fuel cell.

8/80225

http://www.makaut.com

2

CS/B.TECH/ECE/EVEN/SEM-8/EC-802C/2015-16

- Capacity of a micro hydel power plant is
 - up to 100 kW
- 101 to 1000 kW
- 1 to 25 MW
- d) 100 MW.
- Bio-diesel can be mixed with which of the following?
 - Petrol

Diesel

Kerosene

- All of these.
- Bio-gas consist of
 - only methane
 - methane and carbon dioxide
 - only ethane
 - none of these
 - all of these.
- Most of potentially exploitable geothermal heat is stored in
 - water
 - dry rocks
 - c) air
 - steam aquifers. d)

8/80225

[Turn over

- vii) The turbine normally employed in tidal powder is
 - a) simple impulse type
 - propeller type b)
 - reaction type C)
 - reversible type.
- viii) Parabolic type of disc collector can generate temperature up to
 - 100°C

200°C b)

300°C c)

- 400°C.
- Output of wind turbine depends on air velocity ix)
 - proportionally a)
- exponentially

cubically c)

- to the power of 4.
- The range of wind speed favourable to the most of X) the wind turbine is
 - 1 to 4 m/s a)
- 25 to 40 m/s
- 40 to 50 m/s c)
- none of these.
- Per unit cost of power is high in case of
 - Biogas plant
 - Solar PV plant
 - Biomass gasifier plant c)
 - Wind turbine plant. d)

| Turn over

GROUP - B

CS/B.TECH/ECE/EVEN/SEM-8/EC-802C/2015-16

(Short Answer Type Questions)

Answer any three of the following. $3 \times 5 = 15$

- Mention the different types of geothermal resources 2. and indicate which one can be commercially utilized.
 - With a simple sketch explain how a liquid dominated geothermal resource can be used for power generation indicating the thermodynamic cycle followed. 2 + 3
- Explain briefly the impact of non-conventional energy 5 sources on India.
- Draw and explain the equivalent of an ideal and 5 practical solar PV cell.
- Draw the following:
 - Power vs speed characteristics of a wind turbine.
 - Block diagram depicting ethanol production from 3 + 2sugarcane.
- What is the economics and future prospect of tidal 5 energy?

8/80225

http://www.makaut.com

4

8/80225

http://www.makaut.com

http://www.makaut.com

3

GROUP - C

(Long Answer Type Questions)

Answer any three of the following. $3 \times 15 = 45$

- 7. Define 'Betz Limit' and derive the expression for maximum power coefficient for wind turbine.
 - Explain the following terms showing velocity duration and power duration curve of wind energy:
 - cutin speed **(1)**
 - rated wind speed (ii)
 - cutout speed. (111)

7 + 8

http://www.makaut.com

- What are the advantages and disadvantages of Biodiesel over the conventional mineral Diesel oil? Explain with example. 15
- 9. describe Briefly manufacturing process commercial Multicrystalline Silicon cell. Highlight the steps taken in manufacturing the minimize wastage of material.

CS/B.TECH/ECE/EVEN/SEM-8/EC-802C/2015-16

- A house has a power requirement of 400 W for 4 hours every night. A PV array made up of modules with single crystalline silicon cells, a battery storage system and inverter is to be designed for this load. It is also to be taken care that one night's requirement will have to be taken care even if there is not sunshine in the day. Calculate number of PV modules and batteries required. Given (i) Solar radiation is available for average 6 hours daily and average global radiation flux incident on array is 650 W/M sq. (ii) Battery rating 12V, 120 AH, depth of discharge = 0.7. charging and discharging efficiency = 0.9. (iii) Inverter efficiency at full load = 0.85. 8 + 7(iv) Module size = $1.191 \text{ M} \times 0.533 \text{ M}$.
- Describe the basic principle of operation of an MHD 10. a) generator. Derive expressions for maximum power generation per unit volume of generator.
 - With the help of schematic diagram explain the operation of closed cycle MHD generating system.

7 + 8

8/80225 5 [Turn over

http://www.makaut.com

8/80225

http://www.makaut.com

http://www.makaut.com

CS/B.TECH/ECE/EVEN/SEM-8/EC-802C/2015-16

- 11. Write notes on any three of the following: 3×5
 - Magneto hydrodynamic energy conversion. a)
 - Microhydel generation. b)
 - Advantages of non-conventional sources over conventional sources.
 - Biodiesel.
 - Wave energy. e)

8/80225