Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

UNION OF INDIA India

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

Rule SPECIFICATION-OF-MAXIMUM-GROSS-VEHICLE-WEIGHT-AND-MAXII of 1996

- Published on 18 October 1996
- Commenced on 18 October 1996
- [This is the version of this document from 18 October 1996.]
- [Note: The original publication document is not available and this content could not be verified.]

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle WeightPublished Vide Notification No. S.O. 728(E), dated 18.10.1996.

17.

/764S.O. 416(E), dated 8-6-1989-Superseded by S.O. 479(E), dated 4-7-1996S.O. 681(E), dated 30-8-1989 in partial modification of S.O. 416(E), dated 8-6-1989-Superseded by S.O. 479(E), dated 4-7-1996S.O. 479(E), dated 4-7-1996-Superseded by S.O.728(E), dated 18-10-1996

1.

In exercise of the powers conferred by sub-section (1) of section 58 of the Motor Vehicles Act, 1988 (59 of 1988) and in supersession of the notification of the Government of India in the Ministry of Surface Transport S.O. No. 479 (E), dated the 4th July, 1996, the Central Government hereby specifies that in relation to the transport vehicles (other than motor cabs) of various categories detailed in the Schedule below, the maximum gross vehicle weight and the maximum safe axle weight of each axle of such vehicles shall, having regard to the size, nature and number of tyres and maximum weight permitted to be carried by the tyres as per rule 95 of the Central Motor Vehicles Rules, 1989, be(i)vehicle manufacturers rating of the gross vehicle weight and axle weight respectively for each make and model as duly certified by the testing agencies for compliance of rule 126 of the Central Motor Vehicles Rules, 1989, or(ii)the maximum gross vehicle weight and the maximum safe axle weight of each vehicle respectively as specified in the Schedule below for the

1

relevant category, or(iii)the maximum load permitted to be carried by the tyre(s) as specified in the rule 95 of the Central Motor Vehicles Rules, 1989, for the size and number of the tyres fitted on the axle (s) of the relevant make and model, whichever is less:Provided that the maximum gross vehicle weight in respect of all such transport vehicles, including multi-axle vehicles shall not be more than the sum total of all the maximum safe axle weight put together subject to the restrictions, if any, on the maximum gross vehicle weight given in the said Schedule.

SCHEDULE

Transport Vehicles Category	Max GVW Tonnes	Maximum Safe Axle Weight	
1	2	3	4
I Rigid Vehicles			
(i)	Two Axle	9.00	
	One tyre on front axle, and		3 tonnes on front axle
	Two tyres on rear axle,		6 tonnes on rear axle
(ii)	Two Axle	12.0	
	Two tyres on each axle		6 tonnes on front axle
			6 tonnes on rear axle
(iii)	Two Axle	16.2	
	Two tyres on front axle, and		6 tonnes on front axle
	Four tyres on rear axle		10.2 tonnes on rear axle
(iv)	Three Axle	25.0	
	Two tyres on front axle, and		6 tonnes on front axle
	Eight tyres on rear tandem axle		19 tonnes on rear tandem axle
(v) [[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]	[Four Axle [Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]	31. [o [Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]	
	[Four tyres on front axle, and [Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]		[12 tonnes on two front axle [Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]
	[Eight tyres on rear tandem axle [Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]		[19 tonnes on rear tandem axle] [Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

II Semi-Articulated

Vehicles

(i) Two Axle Tractor 26.4 Single Axle Trailer **Tractor:** 6 tonnes on front axle 2 tyres on front axle 4 tyres on rear axle 10.2 tonnes on rear axle Trailer: 10.2 tonnes on single 4 tyres on single axle trailer axle (ii) Two Axle Tractor 35.2 Tandem Axle Trailer Tractor: 2 tyres on front axle 6 tonnes on front axle 4 tyres on rear axle 10.2 tonnes on rear axle Trailer: 8 tyres on tandem axle 19 tonnes on tandem axle Two Axle Tractor (iii) 40.2 Three Axle Trailer Tractor: 2 tyres on front axle 6 tonnes on front axle 4 tyres on rear axle 10.2 tonnes on rear axle Trailer: 12 tyres on 3 axles 24 tonnes on 3 axles (iv) Three Axle Tractor 35.2 Single Axle Trailer Tractor: 6 tonnes on front axle 2 tyres on front axle 8 tyres on rear axle 19 tonnes on rear axle Trailer: 10.2 tonnes on single 8 tyres on single axle axle Three Axle Tractor (v) 44.0 Tandem Axle Trailer Tractor: 2 tyres on front axle 6 tonnes on front axle 19 tonnes on rear 8 tyres on tandem axle tandem axle

Trailer:

8 tyres on tandem axle 19 tonnes on tandem axle

III Truck-Trailer Combinations

(i) Two Axle Truck

Two Axle Trailer

Truck:

2 tyres on front axle 6 tonnes on front axle 4 tyres on rear axle 10.2 tonnes on rear axle

Trailer:

4 tyres on front axle

10.2 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on front axle

(ii) Three Axle Truck 45.4

Two Axle Trailer (restricted to 44.0

tonnes)

Truck:

2 tyres on front axle 6 tonnes on front axle

8 tyres on rear tandem 19 tonnes on rear axle tandem axle

Trailer:

4 tyres on front axle

10.2 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

(iii) Three Axle Truck 45.4

Three Axle Trailer (restricted to 44.0

tonnes)

Truck:

2 tyres on front axle 6 tonnes on front axle 4 tyres on rear axle 10.2 tonnes on rear axle

Trailer:

4 tyres on rear axle 6 tonnes on front axle

Trailer:

4 tyres on rear axle 10.2 tonnes on front axle

8 tyres on rear tandem 19.0 tonnes on rear

axle tandem axle

(iv) Three Axle Truck 54.2

Three Axle Trailer (restricted to 44.0

tonnes)

Truck:

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

2 tyres on front axle8 tyres on rear tandem19 tonnes on rear

axle tandem axle

Trailer:

4 tyres on front axle 10.2 tonnes on front axle

8 tyres on rear tandem 19.0 tonnes on rear

axle tandem axle