

New Okhla Industrial Development Area Building Regulations, 2010

UTTAR PRADESH

India

New Okhla Industrial Development Area Building Regulations, 2010

Rule

NEW-OKHLA-INDUSTRIAL-DEVELOPMENT-AREA-BUILDING-REGULATIONS of 2010

- Published on 30 October 2010
- Commenced on 30 October 2010
- [This is the version of this document from 30 October 2010.]
- [Note: The original publication document is not available and this content could not be verified.]

New Okhla Industrial Development Area Building Regulations, 2010Published vide Notification No. 2213/77-4-10-158N./85, dated 30.10.2010Last Updated 6th July, 2019No. 2213/77-4-10-158N./85. - In exercise of the powers under sub-section (2) of section 9 and section 19 of the Uttar Pradesh Industrial Area Development Act 1976 (U.P. Act no-6 of 1976) read with section 21 of the Uttar Pradesh General Clauses Act, 1904 (U.P. Act no-1 of 1904) and in supersession of notification no. 6435/77-4-06-158N./85 dated December 05 of 2006, the New Okhla Industrial Development Authority hereby makes the following regulations with the prior approval of the State Government to regulate the erection of buildings within the New Okhla Industrial Development Area;Chapter -1 Preliminary

1. Short title, commencement and application.

- 1.1 These regulations may be called the New Okhla Industrial Development Area Building Regulations, 2010.1.2They shall come into force with effect from the date of their publication in Gazette.1.3Chapter 1 to IV shall apply to building activities within the urbanisable area and Chapter V, shall apply to the area designated for agricultural use by the Authority.1.4These regulations shall be applicable for New Okhla Industrial Development Area.1.5Chapter VI shall apply to the plots allotment to the farmers against their land acquisition (5% to 7% of the acquired land as per policy of the Authority)1.6The plots on which map has already been sanctioned and construction has already been started or completed, the allottee may be allowed to revise the same building plan or submit the new plan as per prevailing regulations for that part of building where construction has not started or any new addition required in building.1.7F.A.R., Ground coverage, setbacks and

density as indicated in these regulations shall not be applicable in respect of those plots which were allotted on auction or tender basis and group housing prior to the coming into operation of these regulations. However the calculation of FAR and Ground Coverage in the new buildings in such plots shall be done as per these regulations. The purchasable F.A.R and Ground coverage as per applicability may be allowed.1.8Notwithstanding any thing contained in these regulations, the special provisions contained in the-(a)lease deed executed before commencement of these regulations, and(b)bids accepted by the Authority before commencement of these regulations shall continue to be effective unless amended with the consent of the lessee/sub-lessee

2. Definitions.

- In these regulations, unless the context otherwise requires,-2.1"Act" means Uttar Pradesh Industrial Area Development Act, 1976 (U.P. Act No.6 of 1976.2.2"Air conditioning" means the process of treating air so as to control simultaneously its temperature, humidity, cleanliness and distribution to meet the requirement of conditioned space.2.3"Alteration" means the structural change, such as addition to the area or height or the removal of part of a building, or construction of cutting into or removal of any wall, partition, column, beam, joint, floor or other support, or a change to the fixtures or equipments of the building.2.4"Applicant" means the person who has legal title to a land or building and includes,(i)An agent or trustee who receives the rent on behalf of the owner;(ii)An agent or trustee who receives the rent of or is entrusted with or is concerned with any building devoted to religious or charitable purposes;(iii)A receiver, executor or administrator or a manager appointed by any Court of competent jurisdiction to have the charge, or to exercise the rights of the owner; and(iv)A mortgagee in possession.2.5"Approved" means approved by the New Okhla Industrial Development Authority.2.6"Area" means the Industrial Development Area as notified for the New Okhla Industrial Development Authority.2.7"Authorised Officer" means an officer authorized by the Chief Executive Officer.2.8"Atrium" - A sky lighted central area, often containing plants, in modern buildings especially for common area.2.9"Balcony" means a horizontal projection including a handrail or balustrade to serve as sitting out place.2.10"Basement or Cellar" means the lower storey of a building below or partly below ground level.2.11"Building" means any permanent structure or erection or part of a structure or erection which is intended to be used for residential, commercial, industrial, institutional, recreational or other purposes for the use and benefit of human being whether in actual use or not.2.12"Building activity" means erection, re-erection, making material alteration, or demolition of any building.2.13"Building height" means the vertical distance measured in the case of the flat roofs from the top level of the adjoining drain to the highest point of the building and in the case of sloping roof the mid point between the eaves level and the ridge. Architectural features serving no other functions except that of the decoration shall be excluded for the purpose of measuring heights.2.14"Building line or envelope" means a line up to which the plinth of a building may be lawfully extended. It includes lines specifically indicated or to be indicated in any scheme or layout plan or in these regulations.2.15"Canopy" means a projection over any entrance and if provided in setbacks shall be either cantilevered or supported on columns.2.16"Chajja" means a sloping or horizontal structure overhung usually provided for protection from sun and rain or for Architectural considerations.2.17"Direction" means the direction issued by the Authority under Section 8 of the Act, and would include, unless the context otherwise indicates, any executive instructions issued here under.2.18"Drain" means a conduit or channel for

the carriage of storm water or other used water.2.19"Drainage" means the removal of any liquid by a system constructed for this purpose.2.20"Dwelling Unit" means an independent housing unit with separate facilities for living, cooking and sanitary requirements.2.21"Evergreen tree" means tree that remains green for most part of the year and sheds leaves slowly throughout the year.2.22"Existing building or use" means building structure or its use as sanctioned/approved by the competent authority, or existing before the declaration of the notified area of respective Authority.2.23"Extended Basement" means the construction of floor(s) below the ground leaving a minimum setback of 6.0 metre all-round from the plot boundary for the purpose of fire tender movement. The top slab of basement to flush with the ground level and such slab to be designed for fire tender load with adequate mechanized ventilation.2.24"Floor" means the lower surface in the storey on which one normally walks in building.2.25"Floor Area Ratio (FAR)" means the quotient obtained by dividing the total covered area (plinth area) on all floors by the area of plot.2.26"Foundation" means that part of the structure, which is in direct contact and transmitting loads to the ground.2.27"Green Building" A green building is one which uses less water, optimizes energy efficiency, conserves natural resources, generates less waste and provides healthier spaces for occupants, compared to a conventional building.2.28"Group Housing" means a premises of size not less than 2000 sq. mtrs. comprising of either residential flats or a cluster of flats and independent houses/villas, with basic amenities like parking, park, convenience shop, public utilities, etc.2.29"Hazardous Buildings" means a building or part of a building which is used for the storage, handling, manufacturing or processing of highly combustible or explosive materials or products which are liable to burn with extreme rapidity or which may produce poisonous fumes or explosions, or the storage or handling or manufacturing or processing of highly corrosive, toxic or noxious alkalis, acids or other liquids or chemicals producing flame, fumes or explosive, poisonous, irritant or corrosive gases and the storage, handling or processing of any material producing explosive mixtures of dust or which result in the division of matter into the fine particles subject to spontaneous ignition.2.30"Hard Landscape" means the Civil work component of landscape architecture such as pavement, walkways, roads, retaining walls, sculptures, street activities, fountains and other built environment.2.31"Hedge" means number of shrubs or trees (often similar species) planted closely together in the line. A hedge may be pruned to shape or allowed to grow to assume its natural shape.2.32"Jali" means A grill or screen made of metal, brick, ferro-cement, wood or any other material which is placed in front of a window, door or any opening or piece of machinery in order to protect it.2.33"Layout Plan" means a plan of the entire site showing location of plots/building blocks, roads, open spaces, entry/exits, parking, landscaping etc. indicating the activity for all land parcels.2.34" Technical Person" means an architect/civil engineer/town planner recognized by the Authority as per Appendix 12.2.35"Loft" means an intermediary floor between two floors or a residual space in a pitched roof above normal floor level with a maximum height of 1.5 metres and which is constructed or adopted for storage purpose.2.36"Development Plan" means the Development Plan/Master Plan of the Authority in respect of the Area prepared by the Authority.2.37"Mezzanine floor" means an intermediate floor, between two floors, above ground level, accessible only from the lower floor.2.38"Multi Level Parking" means a separate block or a part of any building on a property to be used primarily for parking of vehicles through mechanized or conventional methods,.2.39"Mumty or Stair cover" means a structure with a covering roof over staircase and its landing built to enclose only the stairs for the purpose of providing protection from weather and not used for human habitation.2.40"Mixed Land use" means mixing/planning of

compatible uses, horizontally or vertically, on a property, such as commercial, offices, residential or institutional.2.41"Occupancy" means the main purpose for which a building or a part of a building is used or intended to be used and classification of a building according to occupancy shall deem to include subsidiary occupancies which are contingent upon it.2.42"Open Space" means a space forming an integral part of the plot left open to the sky.2.43"Owner" means a person, group of persons, a company, trust, registered body, State or Central Government and its departments, undertakings and like in whose name the property stands registered in the relevant records.2.44"Parking space" means a space enclosed or unenclosed to park vehicles together with a driveway connecting the parking space with a street permitting ingress and egress of the vehicles.2.45"Permit" means a permission or authorization in writing by the Authority to carry out the work regulated by these regulations.2.46"Planning and Development Directions" means Directions issued by the Authority under Section 8 of the Act for defining architectural features, facades of the buildings, maintenance of amenities etc. from time to time, and would include, unless the context otherwise indicates, any executive instructions issued hereunder.2.47"Pergola" means a perforated slab constructed in such a manner that at least 50% of which is open to sky.2.48"Purchasable FAR" means the additional FAR, which an old allottee can purchase over and above the FAR that was specifically allowed to him at the time of allotment. The maximum purchasable FAR shall be allowed up to the maximum limit of applicable FAR in these regulations.2.49"Plinth" means a portion between the surface of the surrounding ground and surfaced floor immediately above the ground.2.50"Plot" means a piece of land enclosed by definite boundaries.2.51"Podium parking" means floor/floors above ground, of maximum 2.4mtrs.height each below the bottom of beam, if served by a ramp for movement of vehicles for entry and exit from parking area or alternatively mechanized parking as per standard plan by the registered company undertaking such construction and duly approved by the competent Authority. Ramp for podium shall not be allowed in the setbacks.2.52"Refuge Area" meansFor all building exceeding 24 metres height, refuge area of 15 sq mtrs shall be provided as follows:(i). The refuge area shall be provided on the periphery of the plot or preferably on a cantilever projection and open to air on atleast one side protected with suitable railings.(a)The floors above 24 metres and up to 39 metres- one refuge area on the floor immediately above 24 metres.(b)For floors above 39 metres - one refuge area on the floor immediately above 39 metres and so on after every 15mtrs.(ii)Residential flats in multistoreyed buildings with balconies need not be provided with refuge area, however flats without balcony shall provide refuge area as above.2.53"Road/Street/Right of Way" means any highway, street, lane, pathway, alley, stairway, passage way, carriage way, footway square, bridge, whether a thorough -fare or not, place on which the public have a right of passage, access or have passed and had access uninterruptedly for a specified period or whether existing or proposed in any scheme, and includes all bunds, channels, ditches, storm water drains, culverts, side walks, traffic islands, roadside trees and hedges, retaining walls, fences, barriers and railings within the street lines.2.54"Road/Street Line" means the line defining the side limits of a street/road.2.55"Road/Street Width" means distance between boundaries of the road measured at right angles to the course of the road.2.56"Rain Water Harvesting" means utilizing rain water for recharging of ground water, sanitation, irrigation etc. by adopting various techniques approved by the Authority.2.57"Service floor" means a storey of maximum 2.40 mtrs. height below the beam between any two storeys to be used for running electrical cables, water or sewerage lines, service ducts or AC ducts and services and their maintenance only.2.58"Setback" means a specified line

parallel to the plot boundaries.2.59"Soft Landscape" means the natural elements in a landscape design, such as plant materials and the soil itself.2.60"Storage" means a place where goods of non hazardous nature are stored and including bank safe vault and cold storage.2.61"Table" means a table annexed to these regulations.2.62"To abut" with its geometrical variations and cognate expressions means abutting on road in such a manner that any portion of the building is on the road boundary.2.63"Temporary Building" means any structure or erection or part of structure or erection which is intended to be used only for temporary purpose for a definite period and which is made of temporary and quickly removable building material such as canvas cloths, straw, mat, hay, tarpaulin, asbestos sheets/plastic sheets, etc, without any permanent foundation, wall, beam, column, slab using briks, stone, reinforcement concrete and such other materials of permanent nature.2.64"Unsafe Building" building which structurally and constructionally unsafe or insanitary or not provided with adequate means of egress or which constitute a fire hazard or otherwise dangerous to human life or which in relation to existing use constitute a hazard to safety or health or public welfare, by reason of inadequate maintenance, dilapidation or abandonment.2.65"Urbanisable Area" means the area earmarked for any of the following uses in the Development Plan/Master Plan.(i)Residential;(ii)Commercial;(iii)Industrial;(iv)Institutional;(v)Green area(vi)Transportation, and(vii)Any other Special uses as specified in the Development Plan/Master Plan/Scheme duly approved by the Authority.

3. Note.

- The words and expressions used but not defined in these regulations and defined in the Act, shall have the meanings assigned to them in the Act, If not defined in the Act or these regulations, shall have the meaning assigned to them in the Master Plan/Development Plan, National Building Code, Indian Standard Institution Code as amended from time to time. In case of any contradiction, the provisions of the Act shall prevail.

4. Building permit.

- No person shall erect any building or a boundary wall or fencing without obtaining a prior permit thereof, from the Chief Executive Officer or an Officer authorized by the Chief Executive Officer for this purpose.

5. Application for building permit.

(1)Every person who intends to erect a building within the Industrial Development Area shall give application in the Form given at Appendix - 1.(2)The application for building permit shall be accompanied by documents as mentioned in checklist annexed to Appendix - 1.(3)Such application shall not be considered until the applicant has paid the fees mentioned in Regulation no. 10.(4)In case of objections, the fees so paid shall not be refunded to the applicant but the applicant shall be allowed to resubmit the plan without any additional fees after complying with all the objections within a period of sixty days from the date of receipt of the objection order. If plan is submitted after sixty days, fresh plan fee shall be charged.(5)No application for building permit shall be necessary

for the following additions/alterations provided they do not violate any of the provisions regarding general building requirements, structure stability and fire safety requirements specified in National Building Code.....(a)Whitewashing and painting;(b)Plastering, patch work, flooring.(c)Renewal of roof at the same height;(d)Reconstruction of portions of building damaged by any natural calamity to the same extent as previously approved;(e)Internal additions/alterations within the building envelop certified and supervised by a Technical Person ;(f)Digging or filling of earth;

6. Information Accompanying Application for Layout Plan or Building Permit.

- 6.1 Layouts regarding sub-division of landThe site plan shall show,(i)The boundaries of the plot and the name and number of the properties and road abutting the plot;(ii)Plot number of the property on which the building is intended to be erected;(iii)All existing buildings and physical features standing on, over or under the site;(iv)Building envelope at each floor level in relation to the site;(v)The total plot area and the break-up of area under different uses, roads and open space with their percentages with reference to the total area of the plot;(vi)Total floor area ratio, ground coverage and height of the building of each category proposed;(vii)Setbacks of total plot as well as individual proposed plots;(viii)Details of setback, floor area ratio, ground coverage, on each irregular shaped plots in the proposed layout on at least 1 : 500 scale;(ix)Sewerage and drainage lines up to discharge point and water supply lines;(x)Details of boundary wall, plinth, culvert and ramp, trees;(xi)Scale used and the direction of north point relating to plan of proposed building;(xii)Parking plans indicating the parking spaces for all the buildings;(xiii)Landscape plan;(xiv)Location and size of temporary structures like stores, labour hutments, site office and such like, and(xv)Electrical load requirement.(1)Building Plan : For any proposed structure, requirement of building plan shall be as per clause 6.2, 6.3 and 6.4 as the case may be.(2)Service Plans - Details of private water supply and sewage disposal system independent of the Municipal Services, if any and rain water harvesting system, solar passive architecture as per Uttar Pradesh Government orders.(3)Specification - General specification of materials to be used in different parts of the building as given in Appendix -6.(4)Documents - as per Checklist 1C annexed to Appendix 1.6.2Residential building on plots other than group housing (flatted):(1)The plan shall show-(i)Key Plan - A key plan drawn to a scale of not less than 1:1000 shall be submitted along with the application for a building permit showing the boundary locations of the site with respect to neighbourhood landmarks;(ii)The boundaries of the plot and the name/number of the properties and road abutting the plot;(iii)Plot number of the property on which the building is intended to be erected;(iv)All existing building and physical features standing on, over or under the site,(v)Building envelope at each floor level in relation to the site,(vi)The total plot area and the break-up of covered areas on each floor with their percentages with reference to the total area of the plot;(vii)Total height of the building;(viii)Setbacks;(ix)Details of projections and structures in setbacks;(x)Sewerage and drainage lines upto discharge point, rain water harvesting and water supply lines;(xi)Details of boundary wall and its plinth, culvert and ramp, trees, concealing of water tank on roof with jali;(xii)Car parking, if applicable;(xiii)Scale used and the direction of north point relating to plan of proposed building;(2)Documents as per Checklist 1-B enclosed with Appendix -1.(3)Specification: General specifications of materials to be used in different parts of the building as given in Appendix -6.6.3Other buildings6.3.1The site plan shall show:-(i)The boundaries of the plot and the name/number of the properties and roads abutting to the plot;(ii)Plot number of the

property on which the building is intended to be erected;(iii)All existing buildings and physical features standing on, over or under the site;(iv)Building envelope at each floor level in relation to the site;(v)The total area and the break-up of covered areas on each floor with their percentages with reference to the total area of the plot;(vi)Total height of the building;(vii)Setbacks;(viii)Details of projections and structures in setbacks;(ix)Sewerage and drainage lines upto discharge point and water supply lines;(x)Details of boundary wall, plinth, culvert and ramp, trees;(xi)Scale used and the direction of north point relating to plan of proposed building;(xii)Parking plan indicating the parking spaces of all the buildings;(xiii)Landscape plan;(xiv)Location and size of temporary structures like stores, labour hutments, site office; and(xv)Electrical load requirement.(xvi)Location and details of facilities to be provided for physically challenged persons.

6.3.2 Building Plan. - The plan of the building, elevations and sections shall be drawn to a scale not less than 1:200(i)The plan shall include all floor plans of the building together with the covered area;(ii)The plan shall specify the use of all parts of the building;(iii)The plan shall show water supply, sewerage, drainage lines and the like;(iv)The plan shall include sectional drawing showing clearly the thickness of walls, size and spacing of framing members and floor slabs. The sections shall also indicate the height of the rooms and the parapet. At least one cross section shall be taken through the staircase;(v)The plan shall show all street elevations;(vi)The plan shall include terrace plan indicating the drainage and the slope of the roof;(vii)The plan shall give dimension of the permissible projections in setbacks;(viii)The plan shall give direction of the north point in relation to the plan and scale used.

6.3.3 Building plans for all types of multi-storeyed buildings. - For multi-storeyed buildings which are more than 15 metres in height, the following additional information shall be indicated in the building plans in addition to those mentioned in regulation 6.3.2;(i)Access for fire appliances and vehicles and details of vehicular turning circle and clear motorable access way around the building;(ii)Size (width) of main and alternate staircase along with balcony, corridors and ventilated lobby approach;(iii)Location and details of lift enclosures;(iv)Location and size of fire lift;(v)Smoke stop lobby doors, if provided;(vi)Refuge area, refuge chutes, refuge chamber, service ducts, etc. if any;(vii)Air conditioning system, if provided, with position of dampers, mechanical ventilation system, electrical services, boilers, gas pipes or the like;(viii)Details of exits including provision of ramps for hospital and special lifts;(ix)Location of generator, transformer and switch gear room;(x)Smoke exhaustor system, if any;(xi)Details of fire alarm system;(xii)Location of centralized control, connecting all fire alarm system, built in fire protection arrangements and public address system;(xiii)Location and dimension of static water storage tank and pump rooms with fire fighting inlets for mobile pump and water storage tank;(xiv)Location and details of first aid and fire fighting equipment and installations;(xv)Location and details of fixed fire protection installations such as sprinklers, wet risers, hose -reels, drenchers, CO2 installation, etc.(xvi)Location and details of facilities to be provided for physically challenged persons.

6.3.4 Service Plans. - Details of private water supply and sewage disposal system independent of the Municipal Services, if any and rain water harvesting system and solar passive architecture as per the Government of Uttar Pradesh orders.

6.3.5 Specification. - General specification of materials to be used in different parts of the building as given in Appendix -6.6.3.6

Documents. - as per Checklist 1B annexed to Appendix 1.6.4

Temporary Building

6.4.1 The site plan shall show:-(i)The boundaries of the plot and the name/number of the properties and roads abutting the plot;(ii)Plot number of the property on which the building is intended to be erected;(iii)All existing buildings and physical features standing on, over or under the site;(iv)Total height of the building;(v)Setbacks;(vi)Details of projections and

structures in setbacks;(vii)Sewerage and drainage lines upto discharge point and water supply lines;(viii)Scale used and the direction of north point relating to plan of proposed building;(ix)Location and size of temporary structures like stores, labour hutments, site office or such like temporary structures.6.4.2Building Plan. - The plans shall be submitted for building other than labour hutment. The plan of the building, elevations and sections accompanying the application shall be drawn to a scale not less than 1:200(i)The plan shall include all floor plans of the building together with the covered area;(ii)The plan shall specify the use of all parts of the building;(iii)The plan shall show water supply, sewerage, drainage lines and the like;(iv)The plan shall include sectional drawing showing clearly the thickness of walls, size and spacing of framing members and floor slabs. The sections shall also indicate the height of the rooms and the parapet;(v)The plan shall show all street elevations;(vi)The plan shall give indication of the north point in relation to the plan and scale used.6.4.3Specification. - General specification of materials to be used in different parts of the building as given in Appendix -6.6.4.4Documents. - as per Checklist 1 D annexed to Appendix 1.

7. Site.

- plan shall be drawn to a scale as follow:Table

| Site area | Scale |
|-----------------------------|-------------------------|
| Up to 0.1 hectare | Not less than 1:200 |
| Up to 0.1 hectare-1 hectare | Not less than 1:500 |
| More than 1 hectare | Not less than 1:1000 |

8. Recommended notation for colouring of plans.

- The site and building plans shall be coloured as specified in the table given below. Where items of work are not identified, the colouring notation used shall be indexed:

| S. No. | Item | Site Plan | Building Plan |
|--------|--------------------------------------------------------|------------------------|------------------------|
| 1. | Plot lines | Thick green | Thick green |
| 2. | Existing street | Green | |
| 3. | Permissible building line | Thick dotted green | |
| 4. | Existing work (Outline) | Green | Green |
| 5. | Work proposed to be demolished | Yellow hatched | Yellow hatched |
| 6. | Proposed-a) Additions/Alterations.b) Entirely new work | Red Not to be coloured | Red Not to be coloured |
| 7. | Drainage | Red dotted | Red dotted |

8. Water Supply

Green dotted thin

Green dotted
thin**9. Preparation and signing of Plans.**

- All plans shall be prepared and signed by Technical Person as per Appendix - 12.

10. Building permit fee, completion fees, temporary building permit fees and calculation thereof.

(1) Applicant shall deposit building permit fees as follows: (i) For all type of buildings Rs. 15.00 per square metre covered area on all floors. (ii) For layout plan - Re. 1/- per square metre plot area upto for first 4.0ha and Rs. 0.50 per square metre for balance area. (2) In case of re-erection of existing building after demolition, permit fees chargeable shall be the same as erection of new buildings. (3) The permit fee for revised plan of a building which has already been sanctioned, shall be one fourth of the fee chargeable on the fresh plan, subject to the condition that the covered area of the building shall not increase. In case of increased covered area fresh permit fee will be charged. (4) The area covered in the basement, stilt, podium, services area and all other covered area as the case may be, shall be counted towards the covered area for purpose of calculation of permit fees. (5) The revalidation fee of a building permit for 5 years shall be 10 per cent of the fresh building permit fee, if the application is made within the period of validity of the building permit. The application is made after the validity period, then the revalidation fee shall be original building permit fee. (6) In case of construction without applying for building permit a compounding charges at the rate of Rs. 1000/- per square metre of covered area shall be levied, provided all the provisions as per Building Regulations are complied with. (7) In case of construction without revalidation, a fees of Rs 10 per square metre of covered area shall be levied if all provisions as per byelaws are complied with. (8) In case of revision in layout plan, permit fees shall be charged @ Rs. 0.50 per sq mtrs. for portion of plot area of which the layout is submitted for sanction or completion. (9) Malba charges of Rs 10.00 per square metre shall be levied over total covered area for all buildings on the plot up to 2000 sqmtr, Rs 5.00 per sqmtr on plots of 2001 to 10000 sqmtr, and Rs. 2.00 per sqmtr. on plots above 10000 sqmtr. (10) The applicant shall deposit completion fees as follows: (i) For all type of buildings Rs 10/- square metre of covered area on all floors. (ii) For layout plan - Rs. 0.5/- per square metre plot area for first 4.0 ha acres and Rs. 0.25 per square metre for balance area. (iii) In case even after two objection letters issued by Authority if rectification of all objections is not done then Rs. 500/- shall be levied towards site visit fees for each subsequent visit. (11) The applicant shall deposit 25 percent of the building permit fees for temporary structures other than labour hutments as per individual use of the structure. For labour hutments fees shall be Rs 0.25 per square metre of covered area. Temporary structure shall be allowed till completion of the building. (12) Water, sewer and other service connection charge shall be paid as levied by the Authority. (13) The Authority shall be competent to revise the rate/amount of fees/charges mentioned in these Regulation.

11. Withdrawal of application.

- The applicant may withdraw his application for a building permit at any time prior to the sanction and such withdrawal shall terminate all proceedings with respect to such applications but the fees paid shall in no case be refunded.

12. Scrutiny of the building permit.

- (i) The Authorized Officer shall verify or cause to be verified the facts given in the application for permit, and enclosures. The title of the land shall also be verified. All documents submitted with the plans should be self attested by the owner and Architect/Authorised Technical person.(ii)The Authorized Officer shall examine the information listed in regulation 6.3 for residential buildings on plots (other than Group Housing).(iii)For layout plan, buildings and other temporary structures the Technical Person shall provide the information in regulation 6.3, 6.4 and 6.5 respectively and provision of fire safety requirements, public convenience, safety provisions and other relevant laws. The Authorised/Technical Person shall also be responsible for all other provisions as per Building Regulations, Planning and Development Directions, National Building Code, Indian Standard Institution standards and such other provisions as required by the Authority from time to time.(iv)The Owner and Technical Person shall jointly and severally liable and all of them shall submit indemnity bond in favour of the Authority against violation of these Regulations, Planning and Development Directions and provisions of National Building Code.(v)The Authority, however reserves the right to perform test checks by complete scrutiny of any of the plans submitted for approval.(vi)In case of any violation, the Technical Person shall be black listed under intimation to concerned registration organisation from practicing in the Industrial Development Area for a period of 5 years.(vii)In case owner is found responsible for violation, action may be taken as per provision in lease deed.

13. Sanction or refusal of building permit.

(1)After filing of the application for building permit duly certified by the Technical Person as per Appendix 4, the applicant can commence the construction in accordance with the requirements of Zoning Regulations of Development Plan/Master Plan, these Regulations or Planning, Development Directions and terms of lease deed. In case any objections are found during scrutiny of the plans, the same shall be got rectified by the applicant and if any violations are found during or after the construction, the owner shall be required to rectify the same to the satisfaction of the Authority within a period of 30 days from the date such violations are intimated to the owner. In case the owner fails to comply, the Authority shall ensure compliance and the expenditure incurred on doing so shall be recovered from the owner before issue of occupancy certificate.(2)If within sixty days of the receipt of the application, refusal or sanction is not granted, the application with its annexures shall be deemed to have been allowed and the permit sanctioned, provided such fact is immediately brought to the notice of the Chief Executive Officer in writing by the applicant within twenty days after the expiry of the period of sixty days but nothing herein shall be construed to authorize any person to do anything in contravention of the Master Plan, lease conditions, these Regulations and Planning and Development Directions issued under Section 8 of the Uttar Pradesh Industrial Area

Development Act, 1976.(3)In case of refusal:-(a)the Authorised Officer shall give reasons and quote the relevant provision of the regulations which the plan contravenes, as far as possible in the first instance itself and ensure that no new objections are raised when they are resubmitted after compliance of earlier objections.(b)The Authority shall demolish the unauthorised construction at the expense and cost of the owner/lessee/sub-lessee. In case the owner/lessee/sub-lessee fails to pay the above said cost, the same may be recovered from him as arrear of land revenue.(4)Once the plans have been scrutinised and objections, if any, have been pointed out, the applicant shall modify the plans to comply with the objections raised and re-submit them. If the objections remain unremoved for a period of sixty days, the permit shall be refused and the plan shall stand rejected and fee submitted shall be forfeited..(5)When Allottee submits the application for seeking the occupancy certificate without actually completing the building, inspection shall be done within 30days. If during the inspection for issue of completion certificate any building is found incomplete the allottee will be penalised 50% of occupancy charges or Rs. 5000/- which ever is more and his/her/their application for occupancy shall be rejected. On such rejection of application the allottee will be required to apply afresh along with penalty charges and time extension charges if required. The action against all the concerned Technical person who has prepared the plan will be taken in following steps(i)First time - Warning to concerned Technical person(ii)Second time - black listed in Authority for one year.(iii)Third time - refer to Council of Architecture/ITPI/MIC for cancellation of Registration.

14. Appeal against refusal or sanction with modification of a building permit.

- Any applicant aggrieved by an order of refusal of a building permit or its sanction under these regulations or directions, may appeal to the Chairman of the Authority within sixty days from the date of communication of such order. Such appeal shall be accompanied by a true copy of the order appealed against, and receipt of appeal fee which shall be 50% of the original plan fee.The decision of the Chairman on such appeal shall be final, conclusive and binding. The chairman shall provide opportunity of hearing to all concern parties with regard to the disputed map.The appeal may be referred after sixty days of communication of such order if within 30 days after the previous period of sixty days he satisfies the chairman that he was prevented by sufficient causes from not filing of appeal and not thereafter

15. Duration of validity of a building permit.

(1)A layout plan or building plan permit sanctioned under these regulations shall remain valid for the period of only 5 years. In case part completion has been taken on the plot, then also validity of layout plan or building plan permit shall remain for 5 years. If there is any alteration/revision in the plan, fresh revised plan permit shall be required.(2)Validity of a building permit for a temporary structure shall be 5 years. Temporary structures shall be removed immediately after the construction of building is over.(3)After lapses of validity period the applicant shall be liable to remove all such structures and completion certificate shall not be granted without removal of such structures.

16. Additions or alterations during construction.

- If any external additions or alterations from the sanctioned plans are intended to be made, permission of the Chief Executive Officer shall be obtained in writing before the proposed additions/alterations are carried out. It shall be incumbent upon the applicant to whom a building permit has been sanctioned to submit amended plans for such additions or alterations. The provisions relating to an application for permit shall also apply to such amended plans mutadis mutandis as given in Regulation 13 (2).

17. Cancellation of permit for building activity.

- If at any time after the issuance of permit, the Chief Executive Officer is satisfied that such permit was sanctioned in consequence of any material misrepresentation or fraudulent statement contained in the application given or the information furnished, the Chief Executive Officer may, after giving an opportunity to the applicant of being heard, cancel such permit and any work done thereunder shall be deemed to have been done without permit. The Technical Person found responsible for the same shall be blacklisted and debarred for 5 years from practicing in the notified area. If the owner is found responsible for violations, action may be taken as per lease deed.

18. Work to be carried out in full accordance of Zoning Regulations, Building Regulations and Directions.

- Neither granting of the permit nor the approval of drawings and specifications, nor inspection made by the Authority during such erection shall in any way relieve the owner of such building from full responsibility for carrying out the work in accordance with the requirements of Zoning Regulations of Master Plan, these Regulations and/or Planning Directions. In case any violations are found during construction or after obtaining occupancy certificate the owner shall be required to rectify the same to the satisfaction of the Authority within a period of 30 days from the time such violations are intimated to the owner. In case the owner fails to comply, the Authority shall ensure compliance and the expenditure incurred on doing so shall be recovered from the owner before issue of occupancy certificate. In case occupancy certificate has already been obtained, such expenditure if not paid within stipulated time, shall be recovered from the owner, as arrears of land revenue.

19. Documents at site.

- The following documents shall be kept at site during the construction of the building and for such a period thereafter as required by the Authority: (i) A copy of building permit. (ii) Copy of approved drawings. If the above documents are found missing for two consecutive visits by the Authorized Officer of the Authority a penalty of Rs. 1000/- shall be levied for each such lapse. In case building permit has not been granted and applicant has applied for building permit then copy of receipt of documents shall be kept (wherever applicable) at site.

20. Notice for issue of occupancy certificate.

- Every owner shall have to submit a notice of completion of the building to the Authority regarding completion of work described in the building permit as per Appendix-9 accompanied by the documents as per checklist annexed with Appendix-9.20.1.1Occupancy certificate necessary for occupation. - No building erected, re-erected, shall be occupied in whole or part until the issue of occupancy certificate by the Chief Executive Officer in the Form given in Appendix-11. Provided that if the Chief Executive Officer fails to issue the occupancy certificate or send any intimation showing his inability to issue such certificate within 90 days of the date of receipt of application for occupancy certificate an intimation to this effect shall have to be sent to the Authority by the owner for occupying the building. In case objections are intimated by the Chief Executive Officer or by an authorized officer showing inability to issue occupancy certificate the owner shall take necessary action to remove the objections. If the objections remain un-removed for a period of 6 months the application for issue of occupancy certificate shall stand automatically rejected. Thereafter the Chief Executive Officer shall take suitable action for removal of unauthorised construction with fee. Thereafter, the applicant has to apply afresh with fee for occupancy certificate and in such case time extension shall not be required.20.1.2Issue of occupancy certificate regarding Multi Storey Buildings. - Without prejudice to the provision of regulation 20.1.1, In case of multi storey building the work shall also be subjected to the inspection of the Chief Fire Officer, Uttar Pradesh Fire Service and the occupancy certificate shall be issued by the Chief Executive Officer only after the clearance from the Chief Fire Officer regarding the completion of work from the fire protection point of view. Other certificates such as fees, structural safety, water harvesting, etc also have to be submitted alongwith the completion drawings.20.2"Unsafe building" An unsafe building shall be considered to constitute danger to public safety hygiene and sanitation and shall be restored by repair or demolished or dealt with as otherwise directed by the Chief Executive Officer of the Authority.20.3"Unauthorised development" In case of unauthorised development, the Chief Executive Officer or an authorized officer by the Chief Executive Officer shall -(i)Take suitable action which may include demolition of unauthorized works, sealing of premises, prosecution and criminal proceedings against the offenders in pursuance of relevant Acts in force.(ii)Take suitable action against the technical person concerned.20.4"Temporary occupation" - Where the Chief Executive Officer on the certificate of the technical personnel is satisfied that the temporary occupation of a building or any portion thereof before its completion does not adversely affect public welfare may permit temporary occupation in the Form given in Appendix-11A of such building or portion thereof as the case may be, for such period as he deems fit.

Chapter - IIIGeneral RequirementsSite Requirements

21. Distance from electric lines.

- No verandah, balcony or like shall be allowed to be erected or any additions or alterations made to any building within the distance between the building and any overhead electric supply line as indicated below.

| | Vertically | Horizontally |
|----------------------------|------------|--------------|
| (a) Low and medium voltage | 2.4 metres | 1.2 metres |

| | | |
|------------------------------------------------------|------------------------------------------------------|---------------------------------------------------------|
| (b) High voltage lines upto and including 33000volts | 3.7 metres | 1.8 metres |
| (c) Extra high voltage lines | 3.7m + (0.305 metres forevery additional 33000volts) | 1.8mtrs+ (0. 305 metresfor every additional33000 volts) |

22. Site and land use pattern.

- Notwithstanding anything contained in these regulations, no building permit on any site shall be sanctioned if;-(i)the proposed land use does not correspond to the land use in the Development Plan/Master Plan/Layout Plan(ii)the construction of any building is for public worship, which in the opinion of the Authority will affect the religious feelings of any class or persons in the vicinity thereof.(iii)the use of building or place will be a source of annoyance to, or injurious to the health of the inhabitants of the neighbourhood.

23. Means of Access.

- No building shall be erected so as to deprive any other building of the means of access.

24. Ground coverage, Floor Area Ratio, Height and Setbacks.

- 24.1 Residential Buildings on plots (other than flatted group housing).(1)Ground coverage, Floor Area Ratio, height and setbacks shall be as per Table-I appended to these regulations. However, the set back shall be applicable as per regulations prevailing at the time of initial allotment of sector.(2)Other provisions:(i)The directions of side, rear set back and gate shall be as per the Setback/Layout Plan and directions prepared by the Authority from time to time.(ii)In case of plots being amalgamated with the approval of the Authority, the set back lines in front and adjoining property are to be followed as per Setback Plan.(iii)Subdivision of individual residential plot or building constructed on it shall not be allowed.(iv)Only two dwelling units and a servant quarter shall be allowed upto a plot size of 100sqmtrs. For plots above 100 sqmtrs and upto 500sqmtrs maximum three dwelling units shall be allowed. For plots above 500 sqmtrs. maximum four dwelling units shall be allowed. In density calculation 4.5 person per dwelling unit shall be considered in all kind of residential plots. Each servant quarter shall be counted as half dwelling unit.(v)Stilt parking shall be allowed upto maximum height of 2.4 mtrs upto bottom of beam free from FAR for plot size of 112 sq mtrs and above. However, in case stilt is not provided, parking may be allowed in the setbacks.(vi)No construction of any kind shall be permitted beyond the building envelope (on set backs) except-(a)A chajja (projection) of maximum width of 0.75 metres at lintel or roof level. No construction of any type shall be permitted over such projections.(b)Underground water tanks with top flush with the adjoining ground level.(c)In plots of 200 square metre and above, if required, a temporary guard room of porta cabin 1.5 metre x 1.5 metre shall be permitted after approval by the Authority.(d)Canopy projections of 4.5 metre X. 2.4 metre in front or side set backs (maximum 2 numbers) in plots where front set back is 4.5 metre or more and only one such canopy in side set back where front set back is less than 4.5 metre. No construction of any type shall be permitted over the canopy projection. The canopy may be supported by circular column of

maximum 30 centimetres diameter or rectangular columns of 30 centimetres x 30 centimetre size.(e)Open Plinth steps:(i)Open plinth steps and plinth ramp in front and rear setback.(ii)Open plinth steps and plinth ramps beyond a depth of 6mtrs in side setback.(f)In case of corner plots upto 200 square metre category, load bearing columns max size 300 milimetre X 300 milimetre in side setback maximum 2 numbers may be permitted.(g)Other features as mentioned in Table 3.(h)Open ramps for movement of vehicles in side setback only.(i)Balcony upto 1.5 m width (upto 1.0 m width where setback is less than 3.0 m)(j)No enclosure of any type shall be allowed on the balcony, neither shall be compoundable.(k)The inner courtyard can be covered by a temporary coverage, at a height of 1.5mtrs. above roof level. If covered at roof level, it shall not be permissible.(l)The internal changes within the building envelope are permissible without any revision submission.(vii)FAR shall also include(i)Mezzanine(ii)Pergola shall be counted towards Floor Area Ratio calculation if closed from three or more than three sides.(viii)Floor Area Ratio shall not include -(i)A cantilever projection (in setbacks) of a width of 0.75 metre at any level. No construction of any type or any material shall be permitted over projections other than mentioned herewith.(ii)Canopy projections of 4.5 metre X 2.4 metre in front or side set back (maximum 2 numbers), in plots where front set back is 4.5 metre or more and only one such canopy in side setback where front setback is less than 4.5 metres.(iii)Basement, (only single basement) equivalent to ground coverage shall be permitted, if used for parking, services and storage.(iv)Stilt area of non-habitable height proposed to be used for parking, landscaping etc.(v)Loft upto 1.5 metre height(vi)Other features as mentioned in Table 3.(vii)Open ramps for movement of vehicles in side setback only.(viii)Balconies (upto 1.50mtrs. width, If Balcony of more than 1.50mtrs. width is proposed, then 1/4th of its area shall be counted in FAR), Cupboard (0.60m wide), Staircase, Lift, Mumty for staircase, and Bay wndows.(ix)Basement:(i)Basement area shall not exceed beyond building envelope.(ii)The height of any basement shall be maximum 1.5 metre from bottom of the slab above the top level of the external drain.The maximum height of the basement from floor to ceiling shall be 4.5 metres.(iii)Basement shall be allowed upto a distance of 2.0 mtrs. from the adjacent plot on the basis of structure stability certificate.(x)Minimum requirement for sanction/completion: 40 sqm or 50 percent of maximum permissible ground coverage(whichever is more) with provisions of a functional toilet/bath and kitchen Provision of following items in building shall be mandatory for issue of occupancy certificate.(a)Flooring;(b)Electrical wiring whereas electrical fittings shall not be mandatory.(c)Plumbing and fittings in at least one toilet and kitchen(d)Trees as per Table no. 6 or direction issued from time to time which ever is higher;(e)Number plate;(f)Boundary wall shall be mandatory.(g)Internal and external finishing (Plastering and whitewashing shall not be mandatory);(h)House shall be lockable i.e. all external doors and windows shall have to be provided with grill provided in the windows then fixing of glasses in the windows panes shall not be mandatory;(i)No violation of Building Regulations, Zonal Plan Regulations and Master Plan should be there in the building at the time of issue of occupancy certificate.24.2Group Housing (Flatted and cluster type)(I)Minimum Plot Area- 2000 square metre. However, the Authority may revise this limit by recording the reason .(II)Maximum permissible -

| | | |
|-------|------------------|-------------------------------------------------------------------------------------------------------------|
| (i) | Ground coverage | 35 percent up to 40000 sq mtrs and 40% above 40000 sq.mtrs. |
| (ii) | Floor Area Ratio | 2.75 |
| (iii) | Height | No limit. For buildings above 30 metres in height, clearance from Airport Authority shall have to be taken. |

- (iv) Density(Family size 4.5) As mentioned in the sector Layout Plan or decided by the Authority for a particular scheme.

24.2.1 Other Provisions: - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except (i) A Chajja (projection) of maximum width of 0.75 metre at lintel or roof level. No construction of any type or any material shall be permitted over projections other than mentioned herewith. (ii) Underground water tanks with top flush with the adjoining ground level. (iii) Watchman Shelters and Watch Towers with following provisions: (iv) No projection of watchman shelters and watch towers shall be allowed outside the plot line. (v) Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------------------|-------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 acres | 45 square metres | 24 square metres | 5 square metres |
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi) The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders. (a) Metre room as per norms of Electricity Authority. (b) Open transformers without any permanent enclosure keeping in view the necessary safety requirements. (c) Other features as mentioned in Table 3 (d) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains. (e) Any other feature, primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (f) Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire tender. (2) Floor Area Ratio shall include. - (i) Mezzanine (ii) The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage. (iii) Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides. (iv) Metre room as per Electricity Authority norms. (3) Floor Area Ratio shall not include: (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre. No construction of any type or any material shall be permitted over projections. (ii) Basement(s), shall be permissible within the setback line on each floor. However maximum permissible area under basement shall be limited up to: (a) Basement area, if used for services, storage etc. then maximum area under such facilities shall

be equivalent to maximum permissible ground coverage.(b)Basement area/Podium parking as defined in parking table, if used for parking, then area equivalent to parking requirement shall be permitted.(c)In plots bigger than 10000 sq mtrs. The basement shall be allowed in setback area after leaving a minimum setback of 6.0 mtrs.(iii)Basement, if put to any use other than mentioned above, shall be included in the FAR of the building.(iv)Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc.(v)Balconies upto 1.5 metre width free from FAR(in case it is more than 1.5 m, 1/2 of area beyond 1.5 m shall be included in FAR) may be projected in open setbacks provided 6 mtrs. clear space is available for fire tender movement.(vi)Other features as mentioned in Table 3.(vii)Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains.(viii)Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose, however it can be landscaped with approval of the Chief Executive Officer on case to case basis.(ix)Atrium shall be kept free from FAR and ground coverage. In case any commercial activity is proposed in Atrium or any saleable area or any other structure which is counted in FAR & ground coverage, its respective area shall be added in total FAR & ground coverage.(x)Any other feature purely ornamental in nature and not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(xi)Additional 5% of the plot area as ground coverage will be allowed for dedicated multi level parking in plots bigger than 10000 sq mtrs.(xii)In multistorey buildings service floor may be allowed after 4 floors. Maximum of 3 service floors may be allowed in a building. Service floor shall not be counted in FAR and maximum height of service floor shall be 2.40 mtrs. from floor to bottom of the beam.(4)All the common facilities prescribed below will have to be provided and shall be counted in the prescribed FAR of Group Housing. - Shops and community facilities as per population norms as specified in the earlier lease deed. In case of plots where minimum population required for provision of convenient shopping is not achieved then:-(a)Area for shopping and commercial activities equivalent to 1.0 percent permissible FAR of the plot area shall be allowed.(b)Minimum four kiosks of 4 sq.m of carpet area and two shops of 10sqm carpet area shall be provided mandatorily.(c)Maximum height of shops and kiosks shall be 4.0 metre from floor to ceiling.(d)However shops may be allowed as integral part of Group housing building on the ground floor.(5)15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy. Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metres.

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtrs lobby in front of each lift (excluding area of corridor beyond the lift).

6. Fire escape staircases

7. Toilet blocks for visitors, drivers, guards etc on ground floor only.

8. Mumty, machine room for lifts.

9. Cupboards upto a depth of 0.60 mtr.and 1.80 mtrs.in length.

10. Bay window upto a depth of 0.60mtr.and 2.0 mtrs length.

11. Refuge area as per definition for fire evacuation in National Building Code, 2005.

12. Sewage treatment plant, water treatment plant, garbage collection centre, Electric sub-station, service ducts, community hall, religious building, milk and vegetable booth, school & creche.

13. Covered walkways and pathways.

14. Any other utilities and facilities as decided by the Chief Executive Officer depending upon its requirement.

(6)Distance between two adjacent building blocks. - Distance between two adjacent building blocks shall be minimum 6 mtrs. to 16 mtrs, depending on the height of blocks. For building height up to 18 mtrs., the spacing shall be 6mtrs.and thereafter the spacing shall be increased by 1metre for every addition of 3 mtrs. in height of building subject to a maximum spacing of 16 mtrs. as per National Building Code -2005. If the blocks have dead-end sides facing each other, than the spacing shall be maximum 9 mtrs. instead of 16 mtrs. Moreover, the allottee may provide or propose more than 16 mtrs space between two blocks.(7)The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from the boundary line of such buildings by recording the reasons.(8)In density calculation each servant quarter will be reckoned as half dwelling unit. (standard size of the family for a dwelling unit for density purpose is 4.5 persons)(9)A group housing shall conform to the provisions of the Sector Plan and Zonal Development Plan or scheme (if any) of the area, in terms of setbacks, ground coverage, Floor Area Ratio and height restrictions.(10)The provisions contained in this regulation shall not

apply to housing for economically weaker sections and low income group schemes undertaken by the State Government, Authority or any other public body approved in this behalf by the State Government. The Authority may decide the norms for setback, Ground coverage F.A.R. height, density, parking etc. for specific projects of these groups depending upon the size of plot, width of Road, availability of infrastructure, etc. by recording the reasons.(11)The internal height of the basement (floor to ceiling) shall be minimum 2.4mtrs from bottom of beam and maximum 4.5 metres, except wherever height of equipments such as electric generator, air conditioner, fire hydrant etc is more than 4.5 metres, additional height equivalent to height of equipments may be permitted. In case of Automatic/semi automatic/mechanised parking facility also more than 4.5 mtrs, additional height may be allowed by the Chief Executive Officer depending upon the technology and requirement of space. .(12)The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured.(13)Toilet block for visitors, drivers etc. comprising of minimum a water closet, a bath and 2 urinals shall be provided on the ground floor.(14)In case of group housing having more than two storey, steps must be taken to ensure water at higher floors. For this purpose booster pumps and overhead tanks may be installed.(15)At least one of the lifts provided shall be of the specification of goods lift.(16)Minimum requirement for sanction/completion: Minimum covered area required for completion shall be as per lease deed or Memorandum of Understanding or as follows:-

| S. No. | Size of Plot(Sq. Mtrs.) | Minimum Built up Area(As % of TotalPermissible Far) |
|--------|--------------------------------------------------------------|-----------------------------------------------------|
| 1. | Upto 4000 Sq. Mtrs. | 50% |
| 2. | Exceeding 4000 Sq. Mtrs. but not exceeding 10000Sq. Mtrs. | 40% |
| 3. | Exceeding 10000 Sq. Mtrs. but not exceeding20000 Sq. Mtrs. | 35% |
| 4. | Exceeding 20000 Sq. Mtrs. but not exceeding100000 Sq. Mtrs. | 30% |
| 5. | Exceeding 100000 Sq. Mtrs. but not exceeding200000 Sq. Mtrs. | 25% |
| 6. | Exceeding 200000 Sq. Mtrs. but not exceeding400000 Sq. Mtrs. | 20% |
| 7. | Above 400000 Sq. Mtrs. | 15% |

Note: (i) No further time extension shall be required if the completion has been taken by the allottee as per table mentioned above. The above mentioned completion requirement shall be applicable in all allotments. In the old allotments, the provisions of project report or lease deed or previous options may be followed.(ii)However validity of plans may be granted to the allottee in multiples of 5 years after taking completion of minimum area,(iii)In all the projects of 40 hectares and above, blockwise temporary Occupancy may be allowed subject to a minimum of 1,00,000sqm built up area, the building completed with all mandatory provisions of services and the allottee shall segregate these blocks for the purpose of security during construction period.(17)Provision of following item in building shall be mandatory for issue of completion certificate: - (i) Flooring;/i.e

hard surface and completely finished floors for common areas or/and public use areas.(ii)Electrical wiring;(iii)Plumbing work to be complete.(iv)Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher;(v)Number plate and illumination board as per direction amended or direction issued from time-to-time;(vi)Internal and external finishing (Plastering may not be mandatory);(vii)Boundary wall and gates shall be mandatory;(viii)Buildings shall be lockable i.e. all external doors and windows shall be provided. In case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory;(ix)No violation should be there in the overall building or site at the time of issue of occupancy certificate;(x)Any other special provision as mentioned in the lease deed;(xi)In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable.24.3Industrial Buildings: - Ground coverage, Floor Area Ratio and height

| S. No. | Plot Area (square metre) | Maximum Ground coverage (%) | Maximum Floor Area Ratio | Maximum Height in mtrs |
|--------|------------------------------------|-----------------------------|--------------------------|------------------------|
| 1. | Upto 1000 | 60 | 1.50 | 18 |
| 2. | Above 1000 but not exceeding 12000 | 60 | 1.30 | 24 |
| 3. | Above 12000 | 55 | 1.00 | No Limit |
| 4. | Flatted Factories | 35 | 1.40 | 24 |

24.3.1Other Provisions: - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except(i)No construction of any type or any material shall be permitted over projections other than mentioned herewith.(ii)Underground water tanks with top flush with the adjoining ground level.(iii)Watchman Shelters and Watch Towers with following provisions:(iv)No projection of watchman shelters and watch towers shall be allowed outside the plot line.(v)Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------------------|-------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 acres | 45 square metres | 24 square metres | 5 square metres |
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi) The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders. (a) Metre room as per norms of Electricity Authority. (b) Open transformers without any permanent enclosure keeping in view the necessary safety requirements. (c) Other features as mentioned in Table 3 (d) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains. (e) Any other feature, primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (f) Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire tender. (2) Floor Area Ratio shall include. - (i) Mezzanine (ii) The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage. (iii) Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides. (iv) Metre room as per Electricity Authority norms. (3) Floor Area Ratio shall not include: (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre. No construction of any type or any material shall be permitted over projections. (ii) Basement(s), shall be permissible within the setback line on each floor. However maximum permissible area under basement shall be limited up to: (a) Basement area, if used for services, storage etc. then maximum area under such facilities shall be equivalent to maximum permissible ground coverage. (b) Basement area/Podium parking as defined in parking table, if used for parking, then area equivalent to parking requirement shall be permitted. (c) In plots bigger than 10000 sq mtrs. The basement shall be allowed in setback area after leaving a minimum setback of 6.0 mtrs. (iii) Basement, if put to any use other than mentioned above, shall be included in the FAR of the building. (iv) Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc. (v) Balconies (Upto 1.5 metres width free) from FAR may be projected in open setbacks provided 6 mtrs. clear space is available for fire tender movement. (vi) Other features as mentioned in Table 3. (vii) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains. (viii) Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose. However it can be landscaped with approval of the Chief Executive Officer on case to case basis. (ix) Atrium shall be kept free from FAR and ground coverage. In case any commercial activity is proposed in Atrium or any saleable area or any other structure which is counted in FAR & ground coverage, its respective area shall be added in total FAR & ground coverage. (x) Any other feature purely ornamental in nature and not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (xi) Additional 5% of the plot area as ground coverage will be allowed for dedicated multi level parking in plots bigger than 10000 sq mtrs (excluding green areas). (xii) In multistorey buildings service floor may be allowed after 4 floors. Maximum of 3 service floors may be allowed in a building. Service floor shall not be counted in FAR and maximum height of service floor shall be 2.40 mtrs. from floor to bottom of the beam. (4) 15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be

counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy. Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metre .

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtr lobby in front of each lift.

6. Fire escape staircases

7. Toilet blocks for visitors, drivers, guards etc on ground floor only.

8. Mumty, machine room for lifts.

9. Cupboards upto a depth of 0.60 mtr and 1.80 mtrs.in length.

10. Refuge area as per definition for fire evacuation in National Building Code, 2005

11. Sewage treatment plant, water treatment plant, garbage collection centre, Electric sub-station, service ducts.

12. Covered walkways and pathways.

13. Any other utilities and facilities as decided by the Chief Executive Officer depending upon its requirement.

(5)Distance between two adjacent building blocks. - Distance between two adjacent building blocks shall be minimum 6 mtrs. to 16 mtrs, depending on the height of blocks. For building height up to 18 mtrs., the spacing shall be 6mtrs.and thereafter the spacing shall be increased by 1metre for every addition of 3 mtrs. in height of building subject to a maximum spacing of 16 mtrs. as per NATIONAL BUILDING CODE, 2005. If the blocks have dead-end sides facing each other, than the spacing shall be maximum 9 mtrs. instead of 16 mtrs. Moreover, the allottee may provide or propose more than 16 mtrs space between two blocks.(6)The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from

the boundary line of such buildings by recording the reasons.(7)The internal height of the basement (floor to ceiling) shall be minimum 2.4 mtrs from bottom of beam and maximum 4.5 metre. Except wherever height of equipments such as electric generator, air conditioner, fire hydrant etc. is more than 4.5 metre, additional height equivalent to height of equipments may be permitted. In case of Automatic/semi automatic/mechanised parking facility also more than 4.5 mtrs, additional height may be allowed by the Chief Executive Officer depending upon the technology and requirement of space. .(8)The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured.(9)Toilet block for visitors, drivers etc. comprising of minimum a water closet, a bath and 2 urinals shall be provided on the ground floor.(10)At least one of the lifts provided shall be of the specification of goods lift.(11)Minimum requirement for sanction/completion: Minimum covered area required for completion shall be as per lease deed or Memorandum of Understanding or as follows:-

| S. No. | Size of Plot(Sq. Mtrs.) | Minimum Built up Area(As % of TotalPermissible Far) |
|--------|--------------------------------------------------------------|-----------------------------------------------------|
| 1. | Upto 4000 Sq. Mtrs. | 50% |
| 2. | Exceeding 4000 Sq. Mtrs. but not exceeding 10000Sq. Mtrs. | 40% |
| 3. | Exceeding 10000 Sq. Mtrs. but not exceeding20000 Sq. Mtrs. | 35% |
| 4. | Exceeding 20000 Sq. Mtrs. but not exceeding100000 Sq. Mtrs. | 30% |
| 5. | Exceeding 100000 Sq. Mtrs. but not exceeding200000 Sq. Mtrs. | 25% |
| 6. | Exceeding 200000 Sq. Mtrs. but not exceeding400000 Sq. Mtrs. | 20% |
| 7. | Above 400000 Sq. Mtrs. | 15% |

Note: (i) No further time extension shall be required if the completion has been taken by the allottee as per table mentioned above. The above mentioned completion requirement shall be applicable in all allotments. In the old allotments, the provisions of project report or lease deed or previous options may be followed.(ii)However validity of plans may be granted to the allottee in multiples of 5 years after taking completion of minimum area,(iii)In all the projects of 40 hectares and above, block wise temporary Occupancy may be allowed subject to a minimum of 1,00,000 sqm built up area, the building completed with all mandatory provisions of services and the allottee shall segregate these blocks for the purpose of security during construction period.(12)Provision of following item in building shall be mandatory for issue of completion certificate. - (i) Flooring;/i.e hard surface and completely finished floors for common areas or/and public use areas.(ii)Electrical wiring;(iii)Plumbing work to be complete.(iv)Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher;(v)Number plate and illumination board as per direction amended or direction issued from time-to-time;(vi)Internal and external finishing (Plastering may not be mandatory);(vii)Boundary wall and gates shall be mandatory;(viii)Buildings shall be lockable i.e. all external doors and windows shall be provided. In

case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory;(ix)No violation should be there in the overall building or site at the time of issue of occupancy certificate;(x)Any other special provision as mentioned in the lease deed;(xi)In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable.

24. [4 [Substituted by Notification No. 875/77-4-19-158N-85TC, dated 13.3.2019.] Commercial Buildings

| SI. No. | Use | Maximum Ground Coverage (Percentage) |
|---------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| 1 | Convenient Shopping Centre | 50% |
| 2 | Sector Shopping | 50% |
| 3 | Sub-District Centre, Shopping/Commercial use along Master Plan roads and other Master Plan level Shopping/Commercial Centre | 50% |
| 4 | Hotel | 40% |
| 5 | Banks | 40% |
| 6 | Cinema Multiplex Complex | 40% |
| 7 | Ware Housing Godowns | 60% |
| 8 | City Centre | 50%] |

24.4.1 Other Provisions. - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except (i) A Chajja (projection) of maximum width of 0.75 metre at lintel or roof level. No construction of any type or any material shall be permitted over projections other than mentioned herewith. (ii) Underground water tanks with top flush with the adjoining ground level. (iii) Watchman Shelters and Watch Towers with following provisions: (iv) No projection of watchman shelters and watch towers shall be allowed outside the plot line. (v) Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------|------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 | 45 square metres | 24 square metres | 5 square |

| | acres | | | metres |
|---|-------------------------------------------|-------------------------------------------------|------------------|-----------------|
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi) The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders. (a) Metre room as per norms of Electricity Authority. (b) Open transformers without any permanent enclosure keeping in view the necessary safety requirements. (c) Other features as mentioned in Table 3 (d) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains. (e) Any other feature, primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (f) Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire tender. (2) Floor Area Ratio shall include. - (i) Mezzanine (ii) The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage. (iii) Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides. (iv) Metre room as per Electricity Authority norms. (3) Floor Area Ratio shall not include. - (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre. No construction of any type or any material shall be permitted over projections. (ii) Basement(s) shall be permissible within the setback line on each floor. However maximum permissible area under basement shall be limited up to: (a) Basement area, if used for services, storage etc. then maximum area under such facilities shall be equivalent to maximum permissible ground coverage. (b) Basement area/Podium parking as defined in parking table, if used for parking, then area equivalent to parking requirement shall be permitted. (c) In plots bigger than 10000 sq mtrs. The basement shall be allowed in setback area after leaving a minimum setback of 6.0 mtrs. (iii) Basement, if put to any use other than mentioned above, shall be included in the FAR of the building. (iv) Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc. (v) Balconies (upto 1.5 metre width) free from FAR may be projected in open setbacks provided 6 mtrs. clear space is available for fire tender movement. (vi) Other features as mentioned in Table 3. (vii) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains. (viii) Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose, however it can be landscaped with approval of the Chief Executive Officer on case to case basis. (ix) [Atrium shall be kept free from FAR and ground coverage with the condition that in case of commercial plots of more than 5000 sqm the maximum ground coverage shall be inclusive of Atrium. In case any commercial activity is proposed in Atrium or any saleable area or any other structure which is counted in FAR and ground coverage, its respective area shall be added in total FAR and ground coverage.] [Substituted by Notification No. 875/77-4-19-158N-85TC, dated 13.3.2019.] (x) Any other feature purely ornamental in nature and

not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(xi)Additional 5% of the plot area as ground coverage will be allowed for dedicated multi level parking in plots bigger than 10000 sq mtrs (excluding green areas).(xii)In multistorey buildings service floor ,may be allowed after 4 floors. Maximum of 3 service floors may be allowed in a building. Service floor shall not be counted in FAR and maximum height of service floor shall be 2.40 mtrs. from floor to bottom of the beam.(4)15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy. Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metre .

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtr lobby in front of each lift (excluding area of corridor beyond the lift).

6. Fire escape staircases

7. Toilet blocks for visitors, drivers, guards etc on ground floor only.

8. Mumty, machine room for lifts.

9. Cupboards upto a depth of 0.60 mtr and 1.80 mtrs.in length.

10. Refuge area as per definition for fire evacuation in National Building Code, 2005.

11. Sewage treatment plant, water treatment plant, garbage collection centre Electric sub-station, service ducts.

12. Covered walkways and pathways.

13. Any other utilities and facilities as decided by Chief Executive Officer depending upon its requirement.

(5) Distance between two adjacent building blocks. - Distance between two adjacent building blocks shall be minimum 6 mtrs. to 16 mtrs, depending on the height of blocks. For building height up to 18 mtrs., the spacing shall be 6mtrs. and thereafter the spacing shall be increased by 1metre for every addition of 3 mtrs. in height of building subject to a maximum spacing of 16 mtrs. as per NATIONAL BUILDING CODE, 2005. If the blocks have dead-end sides facing each other, than the spacing shall be maximum 9 mtrs. instead of 16 mtrs. Moreover, the allottee may provide or propose more than 16 mtrs space between two blocks. (6) The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from the boundary line of such buildings by recording reasons. (7) The internal height of the basement (floor to ceiling) shall be minimum 2.4 mtrs from bottom of beam and maximum 4.5 metre. Except wherever height of equipments such as electric generator, air conditioner, fire hydrant etc. is more than 4.5 mete, additional height equivalent to height of equipments may be permitted. In case of Automatic/semi automatic/mechanised parking facility also more than 4.5 mtrs, additional height may be allowed by the Chief Executive Officer depending upon the technology and requirement of space. (8) The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured. (9) Toilet block for visitors, drivers etc. comprising of minimum a water closet, a bath and 2 urinals shall be provided on the ground floor. (10) At least one of the lifts provided shall be of the specification of goods lift. (11) Minimum requirement for sanction/completion: - Minimum covered area required for completion shall be as per lease deed or Memorandum of Understanding or as follows:-

| S. No. | Size of Plot(Sq. Mtrs.) | Minimum Built up Area(As % of Total Permissible Far) |
|--------|---------------------------------------------------------------|------------------------------------------------------|
| 1. | Upto 4000 Sq. Mtrs. | 50% |
| 2. | Exceeding 4000 Sq. Mtrs. but not exceeding 10000 Sq. Mtrs. | 40% |
| 3. | Exceeding 10000 Sq. Mtrs. but not exceeding 20000 Sq. Mtrs. | 35% |
| 4. | Exceeding 20000 Sq. Mtrs. but not exceeding 100000 Sq. Mtrs. | 30% |
| 5. | Exceeding 100000 Sq. Mtrs. but not exceeding 200000 Sq. Mtrs. | 25% |
| 6. | Exceeding 200000 Sq. Mtrs. but not exceeding 400000 Sq. Mtrs. | 20% |
| 7. | Above 400000 Sq. Mtrs. | 15% |

Note: (i) No further time extension shall be required if the completion has been taken by the allottee as per table mentioned above. The above mentioned completion requirement shall be applicable in all allotments. In the old allotments, the provisions of project report or lease deed or previous options may be followed. (ii) However validity of plans may be granted to the allottee in multiples of 5 years after taking completion of minimum area, (iii) In all the projects of 40 hectares and above, block wise temporary Occupancy may be allowed subject to a minimum of 1,00,000 sqm built up

area, the building completed with all mandatory provisions of services and the allottee shall segregate these blocks for the purpose of security during construction period.(12)Provision of following item in building shall be mandatory for issue of completion certificate. - (i) Flooring;/i.e hard surface and completely finished floors for common areas or/and public use areas.(ii)Electrical wiring;(iii)Plumbing work to be complete.(iv)Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher;(v)Number plate and illumination board as per direction amended or direction issued from time-to-time;(vi)Internal and external finishing (Plastering may not be mandatory);(vii)Boundary wall and gates shall be mandatory;(viii)Buildings shall be lockable i.e. all external doors and windows shall be provided. In case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory;(ix)No violation should be there in the overall building or site at the time of issue of occupancy certificate;(x)Any other special provision as mentioned in the lease deed;(xi)In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable.24.5Institutional.

| Sl. No. | Use | Maximum ground coverage | Maximum FAR | Maximum height in metres |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------|--------------------------|
| 1. | All Higher Educational Institutions, e.g.Engineering, Management, Degree college, Research and TrainingCentre, Film/Audio/Vedio Studio, University, vocationalinstitute ,etc. | 35% | 1.50 | No limit |
| 2. | Higher Secondary School | 40% | 1.50 | 24.0 |
| 3. | Nursery School/Creche/Primary School | 40% | 1.50 | 15.0 |
| 4. | Religious Building | 35% | 1.20 | No limit |
| 5. | Dispensary/Health care & Social Assistanceservices, & Clinic, Clinical lab | 30% | 1.50 | 20.0 |
| 6. | Hospital in any system of medicine, Naturopathycentre, Nursing Home Specialized Health Centre, Trauma Centre. | 30% | 2.75 | No limit |
| 7. | Government, Semi-Government, Corporate Offices &other offices. | 30% | 2.00 | No limit |
| 8. | Museum, Art Gallery and Exhibition Centre, ArtCentre. | 30% | 1.50 | No limit |
| 9. | Information Technology and InformationTechnology Enabled Services, Biotech Park | 30% | 2.00 | No limit |
| 10. | Community Centre, Club Building and BaratGhar/Gym, Spa/Health Club, Fire Station, Police Station, PostOffice, Library & other such facilities. | 30% | 1.50 | 24.0 |
| 11. | Dharamshala/Lodge/Guest House/Hostel | 30% | 2.50 | No Limit |
| 12. | Dharam Kanta , Petrol Pump & Gas godown | 30% | 0.50 | 15.0 |
| 13. | Old age home, orphanage, reformatory | 30% | 1.50 | 15.0 |

| | | | | |
|-----|------------------------------------------------------------|-----|------|----------|
| 14. | Convention/Conference/Socio Cultural/Social Welfare Centre | 30% | 1.50 | No Limit |
| 15. | Other Utilities | 30% | 1.00 | 15.0 |

24.5.1 Other Provisions. - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except. (i) A Chajja (projection) of maximum width of 0.75 metre at lintel or roof level. No construction of any type or any material shall be permitted over projections other than mentioned herewith. (ii) Underground water tanks with top flush with the adjoining ground level. (iii) Watchman Shelters and Watch Towers with following provisions: (iv) No projection of watchman shelters and watch towers shall be allowed outside the plot line. (v) Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------------------|-------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 acres | 45 square metres | 24 square metres | 5 square metres |
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi) The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders. (a) Metre room as per norms of Electricity Authority. (b) Open transformers without any permanent enclosure keeping in view the necessary safety requirements. (c) Other features as mentioned in Table 3 (d) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains. (e) Any other feature, primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (f) Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire tender. (2) Floor Area Ratio shall include. - (i) Mezzanine (ii) The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage. (iii) Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides. (iv) Metre room as per Electricity Authority norms. (3) Floor Area Ratio shall not include. - (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre. No construction of any type or any material shall be permitted over projections. (ii) Basement(s), shall be permissible within the setback line on each floor. However maximum permissible area under basement shall be limited up

to:(a)Basement area, if used for services, storage etc. then maximum area under such facilities shall be equivalent to maximum permissible ground coverage.(b)Basement area/Podium parking as defined in parking table, if used for parking, then area equivalent to parking requirement shall be permitted.(c)In plots bigger than 10000 sq mtrs. The basement shall be allowed in setback area after leaving a minimum setback of 6.0 mtrs.(iii)Basement, if put to any use other than mentioned above, shall be included in the FAR of the building.(iv)Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc.(v)Balconies (upto 1.5metre width) free from FAR may be projected in open setbacks provided 6 mtrs. clear space is available for fire tender movement.(vi)Other features as mentioned in Table 3.(vii)Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains.(viii)Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose, however it can be landscaped with approval of the Chief Executive Officer on case to case basis.(ix)Atrium shall be kept free from FAR and ground coverage. In case any commercial activity is proposed in Atrium or any saleable area or any other structure which is counted in FAR & ground coverage, its respective area shall be added in total FAR & ground coverage.(x)Any other feature purely ornamental in nature and not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(xi)Additional 5% of the plot area as ground coverage will be allowed for dedicated multi level parking/podium parking in plots bigger than 10000 sq mtrs (excluding green areas).(xii)In multistorey buildings service floor may be allowed after 4 floors. Maximum of 3 service floors may be allowed in a building. Service floor shall not be counted in FAR and maximum height of service floor shall be 2.40 mtrs. from floor to bottom of the beam.(4)15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy. Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metre .

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtr lobby in front of each lift (excluding area of corridor beyond the lift).

6. Fire escape staircases

7. Toilet blocks for visitors, drivers, guards etc on ground floor only.

8. Mumty, machine room for lifts.

9. Cupboards upto a depth of 0.60mtrs.and 1.80mtrs.in length.

10. Bay window upto a depth of 0.60mtrs.and 2.0m length.

11. Refuge area as per definition for fire evacuation and National Building Code, 2005.

12. Sewage treatment plant, water treatment plant, garbage collection centre, Electric sub-station, service ducts.

13. Covered walkways and pathways.

14. Any other utilities and facilities as decided by Chief Executive Officer depending on its requirement.

(5)Distance between two adjacent building blocks. - Distance between two adjacent building blocks shall be minimum 6 mtrs. to 16 mtrs, depending on the height of blocks. For building height up to 18 mtrs., the spacing shall be 6mtrs.and thereafter the spacing shall be increased by 1metre for every addition of 3 mtrs. in height of building subject to a maximum spacing of 16 mtrs. as per NATIONAL BUILDING CODE, 2005. If the blocks have dead-end sides facing each other, than the spacing shall be maximum 9 mtrs. instead of 16 mtrs. Moreover, the allottee may provide or propose more than 16 mtrs space between two blocks.(6)The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from the boundary line of such buildings by recording the reasons.(7)The internal height of the basement (floor to ceiling) shall be minimum 2.4 mtrs from bottom of beam and maximum 4.5 metre. Except wherever height of equipments such as electric generator, air conditioner, fire hydrant etc. is more than 4.5 metre additional height equivalent to height of equipments may be permitted. In case of Automatic/semi automatic/mechanised parking facility also more than 4.5 mtrs, additional height may be allowed by the Chief Executive Officer depending upon the technology and requirement of space. .(8)The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured.(9)Toilet block for visitors, drivers etc. comprising of minimum a water closet, a bath and 2 urinals shall be provided on the ground floor.(10)At least one of the lifts provided shall be of the specification of goods lift.(11)Minimum requirement for sanction/completion. - Minimum covered area required for completion shall be as per lease deed or Memorandum of Understanding

or as follows:-

| S. No. | Size of Plot(Sq. Mtrs.) | Minimum Built up Area(As % of Total Permissible Far) |
|--------|---------------------------------------------------------------|------------------------------------------------------|
| 1. | Upto 4000 Sq. Mtrs. | 50% |
| 2. | Exceeding 4000 Sq. Mtrs. but not exceeding 10000 Sq. Mtrs. | 40% |
| 3. | Exceeding 10000 Sq. Mtrs. but not exceeding 20000 Sq. Mtrs. | 35% |
| 4. | Exceeding 20000 Sq. Mtrs. but not exceeding 100000 Sq. Mtrs. | 30% |
| 5. | Exceeding 100000 Sq. Mtrs. but not exceeding 200000 Sq. Mtrs. | 25% |
| 6. | Exceeding 200000 Sq. Mtrs. but not exceeding 400000 Sq. Mtrs. | 20% |
| 7. | Above 400000 Sq. Mtrs. | 15% |

Note: (i) No further time extension shall be required if the completion has been taken by the allottee as per table mentioned above. The above mentioned completion requirement shall be applicable in all allotments. In the old allotments, the provisions of project report or lease deed or previous options may be followed. (ii) However validity of plans may be granted to the allottee in multiples of 5 years after taking completion of minimum area. (iii) In all the projects of 40 hectares and above, block wise temporary Occupancy may be allowed subject to a minimum of 1,00,000 sqm built up area, the building completed with all mandatory provisions of services and the allottee shall segregate these blocks for the purpose of security during construction period. (12) Provision of following item in building shall be mandatory for issue of completion certificate. - (i) Flooring; i.e. hard surface and completely finished floors for common areas or/and public use areas. (ii) Electrical wiring; (iii) Plumbing work to be complete. (iv) Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher; (v) Number plate and illumination board as per direction amended or direction issued from time-to-time; (vi) Internal and external finishing (Plastering may not be mandatory); (vii) Boundary wall and gates shall be mandatory; (viii) Buildings shall be lockable i.e. all external doors and windows shall be provided. In case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory; (ix) No violation should be there in the overall building or site at the time of issue of occupancy certificate; (x) Any other special provision as mentioned in the lease deed; (xi) In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable. 24.6 Green Areas.

| Sl. No. | Use | Maximum ground coverage | Maximum FAR | Maximum height in metres |
|---------|----------------------------------------------------------------------|-------------------------|-------------------------|--------------------------|
| 1. | Sports and Amusement Complex, Stadia, Swimming Pool, Shooting Range, | 20% | 0.40 + 0.20 purchasable | 24.0 |

Recreational Green/Park complex with sports facilities

Low Density Sports & Amusement

| | | | | |
|----|----------------------------------------------------|------------|-------------------------|---------------------------------|
| 2. | Complex, Recreational Club, Social Cultural Centre | 10% | 0.20 + 0.10 purchasable | 24.0 |
| 3. | Institutional Green | 35% | 0.80 + 0.20 purchasable | Only for Institutional activity |
| 4. | Nursery | 50 sq mtrs | 50 sq mtrs | 6.0 |

24.6.1 Other Provisions. - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except. (i) A Chajja (projection) of maximum width of 0.75 metre at lintel or roof level. No construction of any type or any material shall be permitted over projections other than mentioned herewith. (ii) Underground water tanks with top flush with the adjoining ground level. (iii) Watchman Shelters and Watch Towers with following provisions: (iv) No projection of watchman shelters and watch towers shall be allowed outside the plot line. (v) Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------------------|-------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 acres | 45 square metres | 24 square metres | 5 square metres |
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi) The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders. (a) Metre room as per norms of Electricity Authority. (b) Open transformers without any permanent enclosure keeping in view the necessary safety requirements. (c) Other features as mentioned in Table 3 (d) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains. (e) Any other feature, primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (f) Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire

tender.(2)Floor Area Ratio shall include. - (i) Mezzanine(ii)The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage.(iii)Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides.(iv)Metre room as per Electricity Authority norms.(3)Floor Area Ratio shall not include. - (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre . No construction of any type or any material shall be permitted over projections.(ii)Basement area equivalent to maximum permissible ground coverage for services, storage and parking.(iii)Basement, if put to any use other than mentioned above, shall be included in the FAR of the building.(iv)Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc.(v)Balconies (upto 1.5metre width) free from FAR may be projected in open setbacks provided 6 mtrs. clear space is available for fire tender movement.(vi)Other features as mentioned in Table 3.(vii)Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains.(viii)Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose, however it can be landscaped with approval of the Chief Executive Officer on case to case basis.(ix)Any other feature purely ornamental in nature and not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(4)15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy. Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metre .

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtr lobby in front of each lift(excluding area of corridor beyond the lift).

6. Fire escape staircases

7. Toilet blocks for visitors, drivers, guards etc on ground floor only.

8. Mumty, machine room for lifts.

9. Cupboards upto a depth of 0.60 mtr and 1.80 mtrs. in length.

10. Bay window upto a depth of 0.60 mtr and 2.0 m length.

11. Refuge area as per definition for fire evacuation in National Building Code, 2005.

12. Sewage treatment plant, water treatment plant, garbage collection centre Electric sub-station, service ducts.

13. Covered walkways and pathways.

14. Any other utilities and facilities as decided by Chief Executive Officer depending upon its requirement.

(5)Distance between two adjacent building blocks - Distance between two adjacent building blocks shall be minimum 6 mtrs. to 16 mtrs, depending on the height of blocks. For building height up to 18 mtrs., the spacing shall be 6mtrs.and thereafter the spacing shall be increased by 1metre for every addition of 3 mtrs. in height of building subject to a maximum spacing of 16 mtrs. as per NATIONAL BUILDING CODE, 2005. If the blocks have dead-end sides facing each other, than the spacing shall be maximum 9 mtrs. instead of 16 mtrs. Moreover, the allottee may provide or propose more than 16 mtrs space between two blocks.(6)The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from the boundary line of such buildings by recording the reasons.(7)The internal height of the basement (floor to ceiling) shall be minimum 2.4 mtrs from bottom of beam and maximum 4.5 metre. Except wherever height of equipments such as electric generator, air conditioner, fire hydrant etc. is more than 4.5 metre, additional height equivalent to height of equipments may be permitted. In case of Automatic/semi automatic/mechanised parking facility also more than 4.5 mtrs, additional height may be allowed by the Chief Executive Officer depending upon the technology and requirement of space. .(8)The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured.(9)Toilet block for visitors, drivers etc. comprising of minimum a water closet, a bath and 2 urinals shall be provided on the ground floor.(10)At least one of the lifts provided shall be of the specification of goods lift.(11)Minimum requirement for sanction/completion. - Minimum covered area required for completion shall be as per lease deed or Memorandum of Understanding or as follows:-

| S. No. | Size of Plot(Sq. Mtrs.) | Minimum Built up Area(As % of TotalPermissible Far) |
|--------|-------------------------|-----------------------------------------------------|
|--------|-------------------------|-----------------------------------------------------|

| | | |
|----|---------------------------------------------------------------|-----|
| 1. | Upto 4000 Sq. Mtrs. | 50% |
| 2. | Exceeding 4000 Sq. Mtrs. but not exceeding 10000Sq. Mtrs. | 40% |
| 3. | Exceeding 10000 Sq. Mtrs. but not exceeding 20000 Sq. Mtrs. | 35% |
| 4. | Exceeding 20000 Sq. Mtrs. but not exceeding 100000 Sq. Mtrs. | 30% |
| 5. | Exceeding 100000 Sq. Mtrs. but not exceeding 200000 Sq. Mtrs. | 25% |
| 6. | Exceeding 200000 Sq. Mtrs. but not exceeding 400000 Sq. Mtrs. | 20% |
| 7. | Above 400000 Sq. Mtrs. | 15% |

Note: (i) No further time extension shall be required if the completion has been taken by the allottee as per table mentioned above. The above mentioned completion requirement shall be applicable in all allotments. In the old allotments, the provisions of project report or lease deed or previous options may be followed. (ii) However validity of plans may be granted to the allottee in multiples of 5 years after taking completion of minimum area, (iii) In all the projects of 40 hectares and above, block wise temporary Occupancy may be allowed subject to a minimum of 1,00,000 sqm built up area, the building completed with all mandatory provisions of services and the allottee shall segregate these blocks for the purpose of security during construction period. (12) Provision of following item in building shall be mandatory for issue of completion certificate. - (i) Flooring; i.e. hard surface and completely finished floors for common areas or/and public use areas. (ii) Electrical wiring; (iii) Plumbing work to be complete. (iv) Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher; (v) Number plate and illumination board as per direction amended or direction issued from time-to-time; (vi) Internal and external finishing (Plastering may not be mandatory); (vii) Boundary wall and gates shall be mandatory; (viii) Buildings shall be lockable i.e. all external doors and windows shall be provided. In case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory; (ix) No violation should be there in the overall building or site at the time of issue of occupancy certificate; (x) Any other special provision as mentioned in the lease deed; (xi) In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable.

| Sl. No. | Use | Maximum ground coverage | Maximum FAR | Maximum height in metres |
|---------|---------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|--------------------------|
| 1. | Bus Terminal, ISBT, Light Rail Transit Terminal, Bus Depots/workshop, Booking Officers, Transport Nagar | 30% | 2.00 | No limit |
| 2. | Any other item not covered in this table | To be decided by the Authority | To be decided by the Authority | To be decided by the |

24.7.1 Other Provisions. - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except. (i) A Chajja (projection) of maximum width of 0.75 metre at lintel or roof level. No construction of any type or any material shall be permitted over projections other than mentioned herewith. (ii) Underground water tanks with top flush with the adjoining ground level. (iii) Watchman Shelters and Watch Towers with following provisions: (iv) No projection of watchman shelters and watch towers shall be allowed outside the plot line. (v) Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------------------|-------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 acres | 45 square metres | 24 square metres | 5 square metres |
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi) The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders. (a) Metre room as per norms of Electricity Authority. (b) Open transformers without any permanent enclosure keeping in view the necessary safety requirements. (c) Other features as mentioned in Table 3 (d) Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains. (e) Any other feature, primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis. (f) Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire tender. (2) Floor Area Ratio shall include - (i) Mezzanine (ii) The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage. (iii) Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides. (iv) Metre room as per Electricity Authority norms. (3) Floor Area Ratio shall not include. - (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre. No construction of any type or any material shall be permitted over projections. (ii) Basement(s) shall be permissible within the setback line on each floor. However maximum permissible area under basement shall be limited up to: (a) Basement area, if used for services, storage etc. then maximum area under such facilities shall be equivalent to maximum permissible ground coverage. (b) Basement area/Podium parking as

defined in parking table, if used for parking, then area equivalent to parking requirement shall be permitted.(c)In plots bigger than 10000 sq mtrs. The basement shall be allowed in setback area after leaving a minimum setback of 6.0 mtrs.(iii)Basement, if put to any use other than mentioned above, shall be included in the FAR of the building.(iv)Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc.(v)Balconies (upto 1.5metre width) free from FAR may be projected in open setbacks provided 6 mtrs. clear space is available for fire tender movement.(vi)Other features as mentioned in Table 3.(vii)Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains.(viii)Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose, however it can be landscaped with approval of the Chief Executive Officer on case to case basis.(ix)Atrium shall be kept free from FAR and ground coverage. In case any commercial activity is proposed in Atrium or any saleable area or any other structure which is counted in FAR & ground coverage, its respective area shall be added in total FAR & ground coverage.(x)Any other feature purely ornamental in nature and not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(xi)Additional 5% of the plot area as ground coverage will be allowed for dedicated multi level parking in plots bigger than 10000 sq mtrs (excluding green areas).(xii)In multistorey buildings service floor ,may be allowed after 4 floors. Maximum of 3 service floors may be allowed in a building. Service floor shall not be counted in FAR and maximum height of service floor shall be 2.40 mtrs. from floor to bottom of the beam.(4)15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy.Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metre .

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtr lobby in front of each lift (excluding area of corridor beyond the lift).

6. Fire escape staircases

- 7. Toilet blocks for visitors, drivers, guards etc on ground floor only.**
- 8. Mumty, machine room for lifts.**
- 9. Cupboards upto a depth of 0.60 mtr and 1.80 mtrs. in length.**
- 10. Refuge area as per definition for fire evacuation in National Building Code, 2005.**
- 11. Sewage treatment plant, water treatment plant, garbage collection centre, Electric sub-station, service ducts.**
- 12. Covered walkways and pathways.**
- 13. Any other utilities and facilities as decided by Chief Executive Officer depending upon its requirement.**

(5)Distance between two adjacent building blocks. - Distance between two adjacent building blocks shall be minimum 6 mtrs. to 16 mtrs, depending on the height of blocks. For building height up to 18 mtrs., the spacing shall be 6mtrs.and thereafter the spacing shall be increased by 1metre for every addition of 3 mtrs. in height of building subject to a maximum spacing of 16 mtrs. as per NATIONAL BUILDING CODE, 2005. If the blocks have dead-end sides facing each other, than the spacing shall be maximum 9 mtrs. instead of 16 mtrs. Moreover, the allottee may provide or propose more than 16 mtrs space between two blocks.(6)The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from the boundary line of such buildings by recording the reasons.(7)The internal height of the basement (floor to ceiling) shall be minimum 2.4 mtrs from bottom of beam and maximum 4.5 metre. Except wherever height of equipments such as electric generator, air conditioner, fire hydrant etc. is more than 4.5 metre, additional height equivalent to height of equipments may be permitted. In case of Automatic/semi automatic/mechanised parking facility also more than 4.5 mtrs, additional height may be allowed by the Chief Executive Officer depending upon the technology and requirement of space. .(8)The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured.(9)Toilet block for visitors, drivers etc. comprising of minimum a water closet, a bath and 2 urinals shall be provided on the ground floor.(10)At least one of the lifts provided shall be of the specification of goods lift.(11)Minimum requirement for sanction/completion. - Minimum covered area required for completion shall be as per lease deed or Memorandum of Understanding or as follows:-

| S. No. | Size of Plot(Sq. Mtrs.) | Minimum Built up Area(As % of TotalPermissible Far) |
|--------|-------------------------|-----------------------------------------------------|
|--------|-------------------------|-----------------------------------------------------|

| | | |
|----|---------------------------------------------------------------|-----|
| 1. | Upto 4000 Sq. Mtrs. | 50% |
| 2. | Exceeding 4000 Sq. Mtrs. but not exceeding 10000 Sq. Mtrs. | 40% |
| 3. | Exceeding 10000 Sq. Mtrs. but not exceeding 20000 Sq. Mtrs. | 35% |
| 4. | Exceeding 20000 Sq. Mtrs. but not exceeding 100000 Sq. Mtrs. | 30% |
| 5. | Exceeding 100000 Sq. Mtrs. but not exceeding 200000 Sq. Mtrs. | 25% |
| 6. | Exceeding 200000 Sq. Mtrs. but not exceeding 400000 Sq. Mtrs. | 20% |
| 7. | Above 400000 Sq. Mtrs. | 15% |

Note: (i) No further time extension shall be required if the completion has been taken by the allottee as per table mentioned above. The above mentioned completion requirement shall be applicable in all allotments. In the old allotments, the provisions of project report or lease deed or previous options may be followed. (ii) However validity of plans may be granted to the allottee in multiples of 5 years after taking completion of minimum area, (iii) In all the projects of 40 hectares and above, block wise temporary Occupancy may be allowed subject to a minimum of 1,00,000 sqm built up area, the building completed with all mandatory provisions of services and the allottee shall segregate these blocks for the purpose of security during construction period. (12) Provision of following item in building shall be mandatory for issue of completion certificate. - (i) Flooring; i.e. hard surface and completely finished floors for common areas or/and public use areas. (ii) Electrical wiring; (iii) Plumbing work to be complete. (iv) Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher; (v) Number plate and illumination board as per direction amended or direction issued from time-to-time; (vi) Internal and external finishing (Plastering may not be mandatory); (vii) Boundary wall and gates shall be mandatory; (viii) Buildings shall be lockable i.e. all external doors and windows shall be provided. In case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory; (ix) No violation should be there in the overall building or site at the time of issue of occupancy certificate; (x) Any other special provision as mentioned in the lease deed; (xi) In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable. 24.8 General Provisions for Building/projects in regulations 24.1, 24.2, 24.3, 24.4, 24.5, 24.6, 24.7. - (1) (i) Category of buildings mentioned in the above regulations is indicative only. If there is any variation in the zoning regulations of Development Plan/Master Plan, the provisions of Master Plan shall prevail. (ii) In case of mixed land use Ground coverage and F.A.R shall be determined on the basis of prime use/activity as decided in the scheme. (2) Total height shall be counted from top of external drain to top of the building except for • Illuminated boards • Water Tanks, mummy and machine room • Other such structures with non usable height. (3) Minimum permissible setbacks shall be as per Table no. 1 and 2. If there is no mention in the lease deed then as per Building Regulations prevailing at the time of allotment. (4) Maximum permissible density shall be as per lease deed. Maximum density variation of - 50 percent and +5 percent shall be allowed in Group Housing. (5) The above regulations are for general applications. (6) The Authority

shall however prepare and provide Architectural control drawing/Architectural control for each commercial project.(7)Notwithstanding anything contained in these regulations, the Authority may where it considers expedient to do so, having regard to the special features of a particular zone/sector and the width of road abutting and the Development Plan, permit such ground coverage FAR, height and setback in relation to a building or a group of buildings by recording the reasons.(8)Provisions of Ground coverage, FAR, building height, parking etc., for Information Technology (IT) and Information Technology and Enabled Services in Industrial plots shall be applicable as per the provisions for Information Technology and Information Technology and Enabled Services in Institutional plots. This provision is applicable for those plots which were originally allotted for IT/ITES.(9)In case of any activity other than listed above mentioned regulations (24.1 to 24.7), the ground coverage and FAR shall be decided by the Authority keeping in view the similar kind of activities mentioned in these regulations.(10)For buildings of height above, 30 metres necessary clearance from Airport Authority of India shall be taken. Total height of the building shall be counted from the top of the external drain to top of the building without exemption.(11)The above regulations are for general applications.(12)Purchasable FAR shall be available only for those allottees whose allotment was based on specific FAR.(13)For Horticulture Nursery, the following provisions shall be applicable:(i)Green house up to maximum 10 percent of plot area.(ii)Watchman shelters as per clause (v) of sub clause (I) of 24.6.1 and also permitted in setbacks.(iii)Metre room as per norms of Electricity Authority and shall also be permitted in setbacks.(iv)Shops and support facilities shall be permitted maximum upto 15 sq mtrs included in permitted Ground Coverage.(v)Setback shall be as per Table 2.(14)[The applicant who shall construct Green Building on a plot of 5000 sq mtrs and above for any use may be allowed an additional FAR of 5% of the permissible/availed FAR (excluding additional 15% of prescribed FAR for services), free of cost, after submission of pre-certificate for green building from below mentioned rating agencies, provided that the applicant fulfills the following conditions:- [Substituted by Notification No. 2842/LXXVII-4-17-158 N-85 TC, dated 7.12.2017 (w.e.f. 30.10.2010).](i)The Building/Design of the building is rated by Leadership in Energy and Environmental Design (LEED) as Gold or Platinum or the Building/Design of the building is rated as 4 or 5 star by the Government of India or the Building/Design of the building is rated by Indian Green Building Council (IGBC) as Gold or Platinum.(ii)The Building has been completed fulfilling the parking and landscaping norms of the prevailing regulations.(iii)The applicant has made sufficient provisions for using the additional FAR.Note: The applicant has to submit a final rating certificate for green building from LEED/GRIHA/IGBC at the time of applying for completion certificate. A compliance certificate, the Authority, after every five years. In case he fails to submit this compounding fees of the FAR given free of cost at the rate of 200% of the cost of purchasable FAR.](15)The Authority is authorized to permit additional height at focal points wherever it is considered appropriate by recording the reasons.(16)Enclosure of balcony in any type of building shall not be permitted or/and compounded. Enclosure shall be considered as illegal construction.24.9Informal Sector.

(1) Plotted Development

- | | |
|---------------------|----------------------|
| I. Plot Size | : 20-25 square metre |
| II. Ground Coverage | : 80 percent |
| III. FAR | : 2.00 |

- IV. Height : 10 metre maximum
- V. Setback : 1.5 metre in front
Main vehicular roads shall not be less than 9.0metres and access
- VI. Roads : to plots shall be provided throughroads/passages not less than 6.0 metres.
- VII. Open space : May be provided in a group or Cluster
- (2) Flatted Development
 - I. Ground coverage : 40 percent
 - II. FAR : 2.00
 - III. Setback : 9.0 front 3.0 metre rear and 3.0 metre sidesetback
 - IV. Height : No Limit
 - V. Balcony : 0.9 metre wide.
 - VI. Roads : Main vehicular roads 12 metre
 - VII. Other spaces : 60 percent (Open + Roads + Parks)
 - VIII. Individual toilets or group may be provided
- (3) Dormitory
 - I. Ground coverage/FAR : 40 percent/1.60
 - II. Setback : 9.0 in front 3.0 metre and 3.0 in side setback
 - III. Height : 15 metre (Maximum)
 - IV. Balcony : 0.9 metre wide.

Common facilities for development. - (i) Toilet blocks.(ii)Proposed plantation on road side has to be ever green trees planted 10 metre centre to centre.(iii)Provisions for community facilities like Creche, Balwadi, Health care centre etc. to be made as per population requirement.(iv)The population size of unit shall be 2.5 person per unit or as decided by the Authority.(v)The number of Dwelling Units permissible will be equivalent to number of members in the registered society or as decided by the Authority with the maximum variation of ± 10 percent.24.10Layout and Sub-Division of Land. - 1. All provisions shall be as per sub-division regulations in master plan approved by the Authority. In case of any special provision in lease deed, the conditions of lease deed shall prevail.

2. Setbacks, FAR, ground coverage and height permissible on the sub divided plot shall be as per maximum permissible in each individual use in these Regulations

24.11Standards for facilities for group housing projects as per following population norms:

| S. No. | Use premises | Service population per unit | Minimum area per unit (in ha) |
|--------|-----------------------|-----------------------------|--------------------------------|
| a) | Education | | |
| 1. | Nursery school/creche | 10000 | 0.10 |

| | | | |
|----|-------------------------------------------|-------------------------------------|-------|
| 2. | Senior Secondary school | 20000-30000 | 0.80 |
| 3. | College | 80000-100000 | 1.0 |
| b) | Health | | |
| 1. | Nursing home/Dispensary | 15000-20000 | 0.10 |
| 2. | Hospital | 100000 | 2.0 |
| c) | Socio - Cultural | | |
| 1. | Community Hall and library | 25000 | 0.40 |
| 2. | Recreational club | 100000 | 1.00 |
| d) | Shopping | | |
| 1. | Convenient shopping/Local/sector shopping | 1% of permissible group housing FAR | |
| e) | Other community facilities | | |
| 1. | Milk booths | 10000-15000 | 0.020 |
| 2. | Religious building | 25000-35000 | 0.100 |
| f) | Recreation/Green Parks | | |
| 1. | Park and Play Ground | 15% of plot area | |
| g) | Utilities | | |
| 1. | Overhead tank | As per requirement | |
| 2. | Electric sub station | As per requirement | |
| 3. | Auto cum taxi stand | 25000 | 0.050 |
| 4. | Police Chowki | 25000 | 0.050 |
| 5. | Petrol pump/Gas station | 50000-100000 | 0.200 |

Note : (i) Provision of these facilities is mandatory in Group Housing/Residential schemes.

However, the Authority may allow more numbers for social/community facilities (Non-commercial) and more areas as per requirement of any project within the limits of permissible FAR.(ii)For facilities like Nursery School/Creche, Nursing Home, Dispensary, convenient shops, etc. instead of earmarking plots, the permissible FAR may be planned on Ground Floor of Group housing Blocks or as separate building blocks within the permissible ground coverage. The allottee shall be free to plan the facilities either in the form of plots or building blocks.24.12Provision of Social and Physical Infrastructure at Sector Level (Zone R) (If facilities are provided as per sector norms then in individual group housing pockets the facilities indicated in regulation 24.11 shall not be applicable)

| S. No. | Use premises | Service population per unit | Unit Area (in Ha) |
|--------|----------------------------|-----------------------------|--------------------|
| a) | Education | | |
| 1. | Creche and Day Care Centre | 5000-25,000 | 0.100 |
| 2. | Nursery School | 5,000-7,500 | 0.100 |
| 3. | Primary School | 7,500-15,000 | 0.200 |
| 4. | Senior Secondary School | 15,000-25,000 | 0.800 |

| | | | |
|----|----------------------------------------------------------------|--------------------|-----------------------------|
| b) | Health | | |
| 1. | Dispensary | 7,500-15,000 | 0.100 |
| 2. | Nursing Home | 5,000-7,500 | 0.100 |
| c) | Shopping | | |
| 1. | Convenient shopping Centres. Sector shopping cum servicecentre | 7,500-15,000 | 0.5000 |
| 2. | Kiosks/hawker area | | |
| d) | Other community facilities | | |
| 1. | Community Centre | 7,500-15,000 | 0.4000 |
| 2. | Milk and Vegetable Booth | 5,000-7,500 | 0.020 |
| e) | Recreation | | |
| 1. | Park and Play Ground | 15% of plot/sector | Min area per unit 0.2500 |
| f) | Utilities | | |
| 1. | Electric Sub-Station 11KV | As per requiremen | 0.050 |
| 2. | Auto Cum Taxi Stand | As per requiremen | 0.050 |

24.13 Note :- In special circumstances the Authority may, relax any of the provisions mentioned herewith in the regulation no. 24.12 by recording the reasons. 24.14 Note :- Provisions of minimum parking and landscaping requirement shall be as per Table 5 and Table 6 respectively. However, the Authority may stipulate higher provisions in future as per requirement and issue directions in this regard. Chapter - IV 25. Structural Safet.- Fire Safety and Service. - 25.1 Fire Safety

Requirements(a) Building shall be so planned, designed and constructed so as to ensure fire safety and this shall be done in accordance with Part IV 'Fire Protection' of the National Building Code of India as amended from time to time.(b) In case of multi-storeyed buildings above 15 metre in height, building which are more than three storeys and building with more than 400 square metres ground floor coverage and all other buildings of industrial, storage, assembly and hazardous type building scheme, provisions of Uttar Pradesh Agni Nivaran aur Agni Suraksha Adhinium (Act no. 6 of 2005) shall apply. 25.2 Structural Design. - The structural design of any item of masonry, timber, plain concrete and steel in a building shall be carried out in accordance with Part VI (Structural Design, Section-1, Boards, Section-2, Section-5, Contrete, Section-6 Steel, as the case may be) of National Building Code of India NATIONAL BUILDING CODE, 2005 prepared by Indian Standard Institution and as prevalent at the time of execution of the works. 25.3 Quality of Material and Workmanship. - All materials and workmanship shall be of good quality conforming generally to accepted standards of Public Work Department of Uttar Pradesh, Indian Standards Specifications and Codes as included in Part V Building Materials and Part VII Constructional Practices and Safety of National Building Code of India 2005 as amended from time to time. 25.4 Building Services. - The planning design and installation of electrical installations, air-conditioning and heating work, installation of lifts and escalators in a building shall be carried out in accordance with Part VIII (Building Services, Section 2, Electrical Installations, Section 3, Air-conditioning and heating, Section-5, Installation of lifts and escalators, as the easy may be) of National Building Code of India

2005 prepared by Indian Standard Institution and as prevalent at the time of execution of the work.

25.5 Plumbing. - The planning design, construction and installation of water supply, drainage and sanitation and gas supply system in building shall be in accordance with the Part IX (Plumbing Services Section I, Water Supply Section 1, Drainage and Sanitation, Section-1, Gas Supply, section 2) of National Building Code of India prepared by Indian Standard Institution as amended from time to time.

25.6 Water supply requirements - The requirements of water supply in a building shall be in accordance with the provision of National Building Code as amended from time to time.

25.7 Sanitary Fitting. - (1) Subject to the provision of any law for the time being in force, the sanitary fittings and installations in building shall be in accordance with the provisions of National Building Code as amended from time to time. (2) Every factory building within the area shall be provided with such latrines and urinals as may be prescribed by or under the provisions of the Factories Act 1948 as amended from time to time.

25.8 Structural Safety for Natural Hazard Protection. - For buildings more than three storeys (including ground floor) or more than 12.0 metre height and important facilities like water works, overhead tank, telephone exchange, bridges and culverts, electric substation, transmission towers, the requirements specified in the Indian Standard Code and Guidelines and other documents shall be observed for structural safety and natural hazards protection of buildings. The details of the relevant codes and guidelines are given in Appendix 8- A/B/C/D.

25.9 Provision for Physically Handicapped. - Provisions for physically handicapped persons shall be made in all buildings and facilities used by public in accordance with the provision of Part III, Annex D of National Building Code -2005.

25.10 Note:- All the provisions made in the building which are not specifically provided in these regulations shall be as per the provisions of National Building Code, Indian Standard Institution Code as amended from time to time. The technical person shall be responsible for ensuring the same as per Appendix-4.

25.11 Note:- The Owner, Technical Person shall be fully responsible for all provisions to be made in accordance with clause 25.1, 25.2, 25.3, 25.4, 25.5, 25.6, 25.7, 25.8, 25.9 & 25.10. A certificate to this effect shall be given as per Appendix-4.

26. Construction of Farm House Building in Agricultural Use Zone.

- **26.1 Minimum size of plot**-Minimum size of a plot for farm house shall not be less than 1.0 hectare.

26.2 Maximum coverage and FAR

| | |
|-------------------------------------------------------------------|-------------------------------------------------------------------|
| (a) Maximum permissible ground coverage for all types of activity | 10 percent |
| (b) Maximum permissible FAR | 0.15 |
| (c) Residential accommodation of watch and ward/maintenance staff | 15 percent of permissible FAR |
| (d) Maximum height | 10.0 m |
| (e) Setbacks | Front/side abutting road 15.0 metre and all other sides 9.0 metre |

26.3 Other provisions. - (a) The maximum permissible floor area includes the area of mezzanine floor also. (b) The maximum height of boundary wall shall be 3.0 mtrs from external drain top. (c) Running creeper or flowering creeper will be planted all along the wall. (d) Minimum 50

percent of the total area of the farm house shall be under plantation/cultivation. At least 100 trees per hectares have to be planted out of which at least 50 percent shall be evergreen trees.(e)Basement within the outer walls of the buildings equivalent to the area of ground coverage shall be allowed. In the event of open areas falling within the outer walls of the buildings, maximum area of the basement may be allowed equivalent to double the area of the ground coverage.(f)Minimum requirement for sanction and completion shall be 25% of permissible FAR.26.4Water supply, sewerage and drainage. - (a) In case of a plot for a farm house having dwelling unit the owner thereof shall be responsible to make lawful arrangements for potable water in the farm house.(b)The owner shall be responsible to provide drains in the farm house to be used for rain water and in case of dairy farm, open or closed sanitary drains to clean sheds, as may be required by the Authority.(c)The owner shall be responsible to provide septic tank with necessary dispersion trenches for disposal of human and animal wastes in the farm house within his own premises.26.5Electrification. - The owner of a farm house shall obtain electric connection directly from the appropriate authority authorised for distribution on such terms and conditions and at his own cost as decided by the appropriate authority.26.6Other Provisions. - (1) No construction of any kind shall be permitted beyond the building envelope (on setbacks) except(i)A Chajja (projection) of maximum width of 0.75 metre at lintel or roof level. No construction of any type or any material shall be permitted over projections other than mentioned herewith.(ii)Underground water tanks with top flush with the adjoining ground level.(iii)Watchman Shelters and Watch Towers with following provisions:(iv)No projection of watchman shelters and watch towers shall be allowed outside the plot line.(v)Maximum height of watchman shelter shall be 4 metres and for watch towers 15 metres. Total area, as mentioned below, under such shelters shall be split up in desired number of watch man shelter and watch towers as follows:

| Sr. No. | Plot Size | Total area for watchman shelter and watchtower | Maximum area under each watchman shelter | Maximum area under each watch tower |
|---------|-------------------------------------------|-------------------------------------------------|------------------------------------------|-------------------------------------|
| 1 | Upto 0.5 acres | 15 square metres | 15 square metres | 5 square metres |
| 2 | Above 0.5 acres upto 10 acres | 30 square metres | 24 square metres | 5 square metres |
| 3 | Above 10 acres upto 25 acres | 45 square metres | 24 square metres | 5 square metres |
| 4 | Above 25 acres upto 50 acres | 60 square metres | 24 square metres | 5 square metres |
| 5 | Above 50 acres for an additional 50 acres | An additional 10 square metres and part thereof | 24 square metres | 5 square metres |

(vi)The following features shall be permitted after leaving minimum 6 mtrs. open corridor for fire tenders.(a)Metre room as per norms of Electricity Authority.(b)Open transformers without any permanent enclosure keeping in view the necessary safety requirements.(c)Other features as mentioned in Table 3(d)Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide swing, culverts on drains.(e)Any other feature,

primarily ornamental in nature, not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(f)Open generator set, filtration plant, Electrical distribution equipments, feeder pillars, telephone distribution equipments may be permitted in open setback as a service utility provided after leaving clear space for fire tender.(2)Floor Area Ratio shall include. - (i) Mezzanine(ii)The shafts provided for lifts shall be taken for covered area calculations only on one floor and included in ground coverage.(iii)Pergola, shall be counted towards Floor Area Ratio if closed from three or more than three sides.(iv)Metre room as per Electricity Authority norms.(3)Floor Area Ratio shall not include. - (i) A cantilever projection at any level (in setbacks) of a width of 0.75 metre . No construction of any type or any material shall be permitted over projections.(ii)Basement shall be for storage, services and parking only. It shall not be more than permissible ground coverage.(iii)Basement, if put to any use other than mentioned above, shall be included in the FAR of the building.(iv)Stilt area of non-habitable height 2.40 metres from bottom of beam proposed to be used for parking, landscaping etc.(v)Balconies (upto 1.5metre width) free from FAR may be projected in open setbacks provided 6 mtr clear space is available for fire tender movement.(vi)Other features as mentioned in Table 3.(vii)Rockery, well and well structures, water pool, swimming pool (if uncovered), uncovered platform around tree, tank, fountain, bench, chabutra with open top and unenclosed by side walls, compound wall, gate, slide, swing, uncovered staircase (unenclosed and uncovered on three sides except for 0.9 metre high railing/wall and open to sky), overhead tanks on top of buildings, open shafts, culverts on drains.(viii)Open ramps with no area enclosed below it of usable height. If used for approach to the entrance of the building, then the height as per requirement may be considered. The space under the ramp shall not be used for any commercial purpose, however it can be landscaped with approval of the Chief Executive Officer on case to case basis.(ix)Any other feature purely ornamental in nature and not enclosing or covering space of commercial use may be permitted by the Chief Executive Officer on case to case basis.(4)15% of prescribed FAR shall be added towards common areas, which shall include the following built structures. The structures on ground will be counted in Ground Coverage. - 1. Canopy projections of area as mentioned in table 4, no construction of any type shall be permitted over the canopy. Canopy, if cantilevered and no structure on it having a size of 2.4m x 4.5m shall not be counted in Ground Coverage.

2. Loft up to maximum height of 1.5 metre .

3. Air-conditioning plant, electrical installation, generator room, water works, water tank etc.

4. Watchmen/Security shelters and watch towers

5. Garbage shafts , lift shafts and 10 sq mtr lobby in front of each lift (excluding area of corridor beyond the lift).

6. Fire escape staircases

7. Toilet blocks for visitors, drivers, guards etc on ground floor only.

8. Mumty, machine room for lifts.

9. Cupboards upto a depth of 0.60 mtr and 1.80 mtrs. in length.

10. Bay window upto a depth of 0.60 mtr and 2.0 m length.

**11. Sewage treatment plant, water treatment plant, garbage collection centre
Electric sub-station, service ducts.**

12. Covered walkways and pathways.

**13. Any other utilities and facilities as decided by the Chief Executive Officer
depending upon its requirement.**

(5)The Authority shall have a right to impose such restriction and limitations as to the number of storey and extent of height of the building as he considers fit where protected areas, ancient or historical monuments lie within a radius of one and half kilometre from the boundary line of such buildings by recording the reasons.(6)The height of basement shall be maximum 1.5 metres upto bottom of the slab above the top of the drain. In case the basement is flush with the ground level adequate light and ventilation shall be ensured.(7)Provision of following item in building shall be mandatory for issue of completion certificate. - (i) Flooring;/i.e hard surface and completely finished floors for common areas.(ii)Electrical wiring;(iii)Plumbing work to be complete.(iv)Parking and landscaping as per Table no. 5 and Table no. 6 respectively or as per directions issued from time to time whichever is higher;(v)Number plate and illumination board as per direction amended or direction issued from time-to-time;(vi)Internal and external finishing (Plastering may not be mandatory);(vii)Boundary wall and gates shall be mandatory;(viii)Buildings shall be lockable i.e. all external doors and windows shall be provided. In case grill is provided in the windows the fixing of glass in the windows pane shall not be mandatory;(ix)No violation should be there in the overall building or site at the time of issue of occupancy certificate;(x)Any other special provision as mentioned in the lease deed;(xi)In case of completion of whole project, all temporary structures to be removed. In case if any special clause is mentioned in the lease deed or Memorandum of Understanding then the requirement mentioned in the same shall be applicable.Chapter-VI

27. Construction on Plots allotted to the farmers against land acquisition (5% or 6% or 7%) in planned village abadi Expansion scheme or in sectors.

- 27.1 Setback Ground coverage and FAR shall be as per the following table :-

| S. No. | Size of Plot (Sq.mtr.) | Ground Coverage (In %age) | Front Setback (Mtr.) | Rear Setback (Mtr.) | Side Setback (Mtr.) | Maximum FAR |
|--------|------------------------|---------------------------|----------------------|---------------------|---------------------|-------------|
| 1 | Upto 50.0 | 75 | 1.5 | 1.5 | - | 1.8 |
| 2 | 51 to 75 | 75 | 1.5 | 2.0 | - | 1.8 |
| 3 | 76 to 120 | 75 | 2.0 | 2.4 | - | 1.8 |
| 4 | 121 to 200 | 75 | 3.0 | 2.4 | - | 1.8 |
| 5 | 201 to 300 | 75 | 3.5 | 3.0 | - | 1.8 |
| 6 | 301 to 400 | 65 | 4.0 | 3.0 | 3.0 | 1.8 |
| 7 | 401 to 500 | 65 | 4.5 | 3.5 | 3.0 | 1.8 |
| 8 | 501 to 750 | 60 | 5.0 | 3.5 | 3.0 | 1.5 |

Note:- (i) Maximum building height in all size of plots shall be 15 Metres.(ii)Total height shall be counted from top of drain to top of building without exception.(iii)In case the permissible ground coverage is not achieved within setbacks, the setbacks of the preceding category may be followed. In special cases where ground coverage is not achieved in the preceding category also, then Chief Executive Officer may relax the setbacks to the extent he considers fit.(iv)In the Residential Plots with in the permissible FAR and Ground Coverage equivalent of 40 % area of rear Set Back construction shall be allowed on either side/both side in the rear set back.27.2Note:- Basement shall be permitted within the building line only i.e. area after leaving setbacks.The internal height of the basement (floor to ceiling) shall be minimum 2.4 metre and maximum 4.5 metre and shall be used for parking and storage only.All formalities as per clause (viii) of sub regulation (2) of regulation 24.1will have to be completed for construction of basement.27.3Use of the Plot. - On plots allotted in planned village expansion scheme or in sectors (5% or 6%or 7%):Non - Residential activities shall be allowed maximum upto 50 percent of the total permissible ground coverage on payment of prescribed charges and it should be a part of the following activities.....

1. Dharmshala/Night shelter/baratghar

2. Dispensary/clinic/laboratory

3. Hostel

4. Guest House/lodging house

5. Motor garage and workshop

6. Office for professionals - out of which minimum 50% of the space shall be used for self use.

7. Restaurant

8. Vending booth/kiosks

9. Bank

10. Post Office

11. Telegraph Office

12. Creche and Day-care centre

13. Retail shop

14. Telecommunication tower (only ground based)

No activity whatsoever other than those mentioned above shall be allowed. Allottees under this category will intimate in advance and provide an undertaking to the Authority that the proposal is in conformity with the bye-laws and other regulations prevalent at that time.

27.4 Fees for Conversion of use. - (i) On roads of ROW upto 12.00 metre -prevailing residential rate revised from time to time.(ii)On roads of ROW above 12.0 metre and up to 18.0 metres. 1.25 times of the prevailing residential rate revised from time to time.(iii)On roads of ROW above 18.0 metre and up to 24.0 metres. 1.50 times of the prevailing residential rate revised from time to time.(iv)On roads of ROW above 24.0 metre and up to 45.0 metres. 2.00 times of the prevailing reserved residential rate as per plot size, revised from time to time.(v)For corner plot 5% additional of above mentioned charges shall be levied.

27.5 Other Provisions. - (i) Safety requirements shall be as per National Building Code and Uttar Pradesh Agani Nivaran Avam Agani Suraksha Adhiniyam, 2005 .(ii)Items permissible in the setback and calculation of Floor Area Ratio shall be done as per regulation 24.(iii)Provisions of parking, loading and unloading spaces:(a)Parking space to be provided for motor vehicles, shall not be less than 20 square metres in open area (under stilts; 30square metre) and for scooters and cycles the parking spaces provided shall not be less than 3 square metres and 1.40metre respectively.(b)parking space for other vehicles shall be provided as per table-5.(iv)Boundary wall height provision shall be as per prevailing direction issued by the Authority from time to time.

27.6 Fees for Sanction and completion of building plans. - Plan processing fees shall be as per regulation 10

27.7 Regarding Commercial activities. - (1) On plots situated along the 30.0m and above wide roads, commercial activities shall be allowed in addition to the activities as mentioned in regulation 27.3.(2)The activities as mentioned in sub regulation (i) above and in regulation 27.3 shall also be allowed on the allotted plots of those farmers whose land was acquired and due to any special circumstances a part of land has been returned to them as per lease back policy of the Authority.

Chapter-VII

28. Purchasable Far.

- 28.1 Note:- Provision of purchasable FAR in Group Housing, Commercial, Institutional, Industrial, Sport and amusement complex, recreational greens and Low Density Sports plot may be considered, where: (i) The Plots exist on 24 mtrs. and above wide road. (ii) The construction has not started. OR The allottee wants to construct a new additional building within the limits of permissible ground coverage. OR The allottee wants to construct new building on the vacant plot. OR The allottee has already constructed building within purchasable F.A.R limits OR Purchaseable F.A.R may be allowed on minimum 18.0 mtrs. and above road width for institutional and industrial use. Note: The Purchasable FAR shall be allowed up to the maximum limit of the applicable FAR in the Building Regulations. 28.2 Purchasable FAR shall be allowed with the following provisions/conditions. - (i) No construction shall be allowed beyond the limit of maximum permissible ground Coverage. (ii) Parking facilities shall be provided within the plot as per the provisions of the building bylaws. (iii) No objection certificate from the Airport Authority of India/Competent Authority shall be obtained for the height of the building. (iv) Structural design duly checked and verified by the I.I.T/N.I.T./Government Engineering College shall be submitted along with the proposal in case where additional floors are being proposed. (v) No objection certificate from Fire Safety and Environmental Clearance shall be obtained from the Competent Authorities. (vi) Purchasable FAR shall be applicable only on the basis of assessment of planned and available physical infrastructure. (vii) Use of purchaseable FAR shall be governed by the terms and conditions of lease deed. (viii) In case where purchasable FAR is allowed, the Authority shall permit increase in the height of building as per requirement. (ix) Additional Proportionate residential units shall be allowed on the purchaseable FAR for Group Housing. Note:- (i) Purchasable FAR is an enabling provision. It shall not be allowed to any Allottee as a matter of right. (ii) With the consideration of Traffic density, conditions of approach road, availability of physical infrastructure, distance from the protected area and heritage sites or in the light of planning the Authority may identify the zones/areas where purchasable FAR shall not be allowed. (iii) In case of mixed land use permitted in any pocket/plot: (a) Permissible FAR for various uses shall be as applicable for respective use including the purchasable FAR. (b) The total FAR in the pocket/plot shall be subject to the overall permissible FAR for the pocket/plot. (c) Purchasable FAR shall be calculated on the basis of the FAR of the individual uses within that pocket/plot. 28.3 Calculation Method for the rate of charges of Purchasable FAR. - Rate assessment for purchasable FAR shall be calculated in proportion to the land requirement for additional built up area. The Fraction of land value shall be charged from the allottee on the basis of following formula: $-C = L_e \times R_c \times P$
 $PC = \text{Charge}$
 $L_e = \text{Proportionate Land required against purchasable FAR}$
 $i.e. F_p \times 100 / FAR$
 $F_p = \text{Allowed Additional covered area (sq.mtr.) as per purchasable FAR. FAR = Permissible Floor Area Ratio as per Building Regulations.}$
 $R_c = \text{Prevailing sector rate or allotment rate of related plot (on the basis of auction/sealed bid) whichever is higher.}$
 $P = \text{Value of purchasable Factor is as follows:}$
 - Group Housing = 0.40
 - Commercial = 0.60
 - Institutional/Institutional green* = 0.30
 - Industrial = 0.30
 - Green/sport/recreational Areas = 0.20
 28.4 Note. - * (i) The purchasable FAR in institutional green plot shall only be permissible for the institutional use in the plot. (ii) The purchaseable FAR shall be allowed to a maximum permissible FAR allowed for the particular use above the constructed building. If the allottee has done the construction before sanctioning, the compounding charge of un-sanctioned area shall be payable at the rate of Rs. 200/- per sq mtr. This penalty shall

be over and above the fee charged for purchase able FAR. In case the construction is beyond the limit of purchasable F.A.R the allottee will have to first remove the extra construction beyond permitted F.A.R., then allottee may be allowed the extra purchasable F.A.R.(iii)[The Authority may also allow additional ground coverage upto the maximum limit of 50% in Commercial plots of more than 5000 sqm area on the basis of additional charges.] [Substituted by Notification No. 875/77-4-19-158N-85TC, dated 13.3.2019.]Additional Charges for Purchasable Ground Coverage shall be calculated as follows:
$$C = L \times 0.30 \times R$$
$$C = \text{Cost of additional purchasable ground coverage}$$
$$L = \text{Land required under ground cover for additional ground coverage}$$
$$R = \text{Rate of land per sq.mt. (current reserve price or auction/bid/allotment rate whichever is higher)}$$
0.30 is a constant factor for purchasable ground coverage. However, additional coverage will not be considered in the setback area.(iv) Increase in FAR of industrial plots prior to the commencement of these regulations shall continue to be allowed free of cost. But the increase of FAR of industrial plots notified in these Regulations shall be allowed on purchasable basis. Purchasable FAR may be allowed up to 2.0 FAR in the Industrial plots.

Chapter VIII

29. Provisions of parking, loading and unloading spaces.

- Parking may be provided in open, under stilt, or underground in basements or separate block plots for multi level parking through mechanized methods or conventional ramps. Other option in selected areas is through podium parking. Creation of underground parking below parks and open spaces without disturbing the green areas on the surface may be considered only in exceptional cases as per policy approved by the Authority. Surface parking shall be allowed in setback after leaving clear space of 7.5mtrs., and fulfilling the requirement of tree plantation and Fire Tender movement.29.1 Other Provisions. - (1) Multi-level Parking plots -(i) Multi-level parking facility should preferably be developed in the designated parking spaces/plots.(ii) In order to compensate the cost of multi level parking in designated areas and also to fulfill the growing need of parking spaces within urban areas, a maximum 25% of ground floor covered area may be utilized as commercial space. The balance covered area may be utilized on top floors for office use on a plot designated or planned for parking facility.(iii) In addition to the required parking spaces for maximum permissible FAR, 3 times additional space for parking component shall be provided.(iv) Maximum ground coverage shall be 70%.(v) For development of multilevel parking, models should be worked out to encourage the private sector initiative without commercial component.(vi) Multi level parking facility shall be allowed in all type of plots.(2) Basement Parking. - (i) In plots larger than 10000 sq.mtrs., the basement shall be allowed upto minimum setback of 6.0mtrs. There will be no restriction on the number of levels of basement subject to mechanical ventilation as per provisions in National Building code - 2005, water proofing and structural safety. Evergreen trees shall have to be planted in setback as per landscaping norms of these byelaws.(ii) Height of first basement above ground level will be maximum 1.5 mtrs below the roof slab. Where stilt or podium parking is permitted, the first basement roof will be leveled with the ground and the roof slab of the extended basement up to envelop line shall be designed for the fire tender load.(iii) The height of basements from floor to ceiling shall be maximum up to 4.5 mtrs.(iv) The ramp within setbacks shall be permissible subject to free and convenient movement of

fire tender.(v)Adequate fire safety, light and ventilation and air change through mechanical means shall be provided as per provisions in National Building Code, 2005.(vi)The basements may be used only for parking, services like fire rooms and storage of non-hazardous materials.(3)Podium Parking. - For adequate parking space, podium parking up to maximum two floors may be permitted within the envelope line, only for parking, with the following conditions;(i)Minimum plot area = 10000 sqmtrs.(ii)Minimum width of the road = 18 mtrs.(iii)Minimum set back at the ground level will be 7.5 mtrs. all around where stilt and one storey podium will be permitted, however, other floors of podium parking may be permitted with larger set back.(iv)The height of one level of podium will be maximum 2.4mtrs.from floor to the bottom of beam.(v)Podium levels will not be enclosed by any material on the outer periphery except with one metre high metal Jali/mesh for safety.(vi)Adequate sprinklers, exits, ramps and fire fighting provisions as per provisions in National Building Code - 2005 will be provided.(vii)Structural safety measures as per BIS codes and for fire tender movement will be ensured.(viii)Ramp for podium shall not be allowed in the setback.(ix)Services and storage shall be allowed upto the extent of permissible ground coverage.(4)Mechanised Parking. - (i) Mechanized multi level parking will be permitted subject to the following;(ii)Minimum plot size = 1000 sq.mtrs.(iii)Minimum width of road = 18mtrs.(iv)ECS = 18 sq. mtrs. or as per the design and Technology.(v)Clear Height of one level = 2.1mtrs.(vi)Adequate safety measures for mechanical equipments.(vii)Backup of electricity through automatic generators.(viii)The company shall ensure proper maintenance, structural safety equipment and machinery.(5)Underground Parking. - Parking facilities can be created under the open spaces/parks (except heritage park), playground without disturbing the green areas on the surface and surrounding environment. The approvals from the concerned Authority are mandatory after following due process of public hearing before taking up such works. The guidelines for approval are as follows;(i)Minimum area of open spaces/park/playground = 5000 sq.mtrs.(ii)Minimum width of abutting road = 18mtrs.(iii)Up to 50% of the area to be utilized for underground parking with minimum two basements.(iv)Ramps to be provided with not more than 1:10 slope.(v)Maximum height from the road level shall be 0.5 mtrs with provision for mechanized light and ventilation.(vi)Minimum set back from the boundary of the park will be 1.5 mtrs for the purpose of staircase and ramps.(vii)Fire & structural safety measures shall be as per National Building Code, - 2005.(viii)Minimum depth of the earth shall be 0.5mtrs.for planting shrubs and grass.(ix)Adequate drainage for irrigation facilities and for water proofing shall be mandatory.(x)The Authority may consider to relax the minimum area limit depending upon the requirement in a particular area.(a)When parking space is to be provided for motor vehicles, it shall not be less than 20 square metre in open area and 30 square metre in basement and in stilts and for scooters and cycles the parking spaces provided shall not be less than 3 square metres and 1.40 square metres respectively.(b)For buildings of different types, parking space for vehicles shall be provided as specified in table No.5-(6)Extended Basement. - The basement shall be allowed within the setback only for parking purpose all around the plot boundary after leaving a minimum setback of 6.0mtrs. for fire tender movement. The top of the slab shall be flushed with the ground level and the roof shall be designed to take the load of the fire tender with mechanized ventilation.TABLE No. 1 (See regulation 24.1)Ground Coverage, FAR and Setbacks in Residential Plots

| S. No. | Size of Plot (Sq.mtr.) | Ground Coverage (In %age) | Front Setback (Mtr.) | Rear Setback (Mtr.) | Side Setback (Mtr.) | Maximum FAR |
|--------|------------------------|---------------------------|----------------------|---------------------|---------------------|-------------|
|--------|------------------------|---------------------------|----------------------|---------------------|---------------------|-------------|

| | | | | | | |
|---|------------|----|-----|-----|-----|-----|
| 1 | Upto 50.0 | 75 | 1.5 | 1.5 | - | 1.8 |
| 2 | 51 to 75 | 75 | 1.5 | 2.0 | - | 1.8 |
| 3 | 76 to 120 | 75 | 2.0 | 2.4 | - | 1.8 |
| 4 | 121 to 200 | 75 | 3.0 | 2.4 | - | 1.8 |
| 5 | 201 to 300 | 75 | 3.5 | 3.0 | - | 1.8 |
| 6 | 301 to 400 | 65 | 4.0 | 3.0 | 3.0 | 1.8 |
| 7 | 401 to 500 | 65 | 4.5 | 3.5 | 3.0 | 1.8 |
| 8 | 501 to 750 | 60 | 5.0 | 3.5 | 3.0 | 1.5 |

Note:- (i) Maximum building height in all size of plots shall be 15 Metres.(ii)Total height shall be counted from top of drain to top of building without exception.(iii)In case the permissible ground coverage is not achieved within setbacks, the setbacks of the preceding category may be followed. In special cases where ground coverage is not achieved in the preceding category also, then Chief Executive Officer may relax the setbacks to the extent he considers fit.(iv)In the Residential Plots with in the permissible FAR and Ground Coverage equivalent of 40 % area of rear Set Back construction shall be allowed on either side/both side in the rear set back.TABLe No. - 2(See regulation 24.2, 24.3, 24.4, 24.5, 24.6, 24.7)Setbacks for all category and uses of plots other than individual residential Plots

| S. No. | Plot Size (in square metre) | Front (in metre) | Rear (in metre) | Side (1) (in metre) | Side (2) (in metre) |
|--------|-----------------------------|------------------|-----------------|---------------------|---------------------|
| 1. | Up to 150 | 3.0 | 1.5 | 0 | 0 |
| 2. | Above 151 upto 300 | 3.0 | 3.0 | 0 | 0 |
| 3. | Above 301 upto 500 | 4.5 | 3.0 | 3.0 | 0 |
| 4. | Above 501 upto 2000 | 6.0 | 3.0 | 3.0 | 3.0 |
| 5. | Above 2001 upto 6000 | 7.5 | 6.0 | 4.5 | 4.5 |
| 6. | Above 6001 upto 12000 | 9.0 | 6.0 | 6.0 | 6.0 |
| 7. | Above 12001 upto 20,000 | 12.0 | 7.5 | 7.5 | 7.5 |
| 8. | Above 20,001 upto 40,000 | 15.0 | 9.0 | 9.0 | 9.0 |
| 9. | Above 40,001 | 16.0 | 12.0 | 12.0 | 12.0 |

Notes: (1) Specific setbacks shall be as per scheme/layout/zonal plan prepared by the Authority whenever such a plan is prepared by the Authority.(2)In case the permissible coverage is not achieved within setbacks, the setbacks of the preceding category may be followed.TABLe No. - 3(See regulation 24.2, 24.3, 24.4, 24.5, 24.6, 24.7)Features permitted in the setbacks of the plots after leaving 6.0m clear space for fire tender

| S. No. | Features | Description |
|--------|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. | Decorative Column | Columns purely decorative and not load bearing shall be permitted in setback. Such columns of any material and number shall be permitted but maximum size of each column shall not exceed 0.30mtrs x 0.30mtrs |

2. Buttresses Buttresses, any number, shall be permitted insetback up to maximum width of 0.750 mtrs in setback.
3. Moulding, Cornices and Murals Murals, moulding and cornices if provided alongunder any projection shall be permitted upto a maximum width of 150 millimetre over and above the maximum permissible dimensionsof a projection or a canopy.
4. Planters and Sun Control Devices Projection in form of planter, cantileveredfins, egg crates and other sun control devices shall be permittedin setback upto maximum width of 0.750 metre. Maximum depth ofsuch planters shall not exceed 0.600 metre.
5. Jali Jali of any material shall be permitted overprojections which are primarily meant to cover windowAir-conditioning units and dessert cooler. Maximum width of suchjalies shall not be more than 0.75 mtrs.
6. Casing Enclosure to cover Rain Water pipe Casing/enclosures of any material to cover rainwater pipe shall be permitted in setback upto depth of maximum 0.50mtrs and maximum width of 0.75mtrs

Table No. - 4(See regulation 24.2, 24.3, 24.4, 24.5, 24.6, 24.7)Area under canopy in buildings other than residential buildings

S. No. Plot Size (in square metre) Minimum area under canopy (in sqmtrs.)

- | | | |
|----|--------------------------|---------------------------|
| 1. | Upto 150 | Nil |
| 2. | Above 150 upto 300 | 12 (Only in side setback) |
| 3. | Above 300 upto 500 | 25 |
| 4. | Above 500 upto 2000 | 40 |
| 5. | Above 2000 upto 4000 | 55 |
| 6. | Above 4000 upto 10,000 | 70 |
| 7. | Above 10,000 upto 20,000 | 85 |
| 8. | Above 20,000 upto 40,000 | 100 |
| 9. | Above 40,000 | 115 |

Note: Minimum width of canopy shall be 1.8 mtrs. TABLE No. - 5 Provision of Parking Requirement

- | SI. No. | Building/plot | Parking space |
|---------|----------------------------------------|-------------------------------------------------------------------------|
| 1. | (a) Group Housing | One ECS/parking space per 80 square metres of permissible FAR area. |
| | (b) Hostel, Lodges, Guest house Hotel. | One parking space for every 2 guest rooms. |
| 2. | Educational Building | One parking space for every 100 square metres of permissible FAR area . |
| | (a) IT/ITES, Offices, and Institution | One parking space for 50 square metre of permissible FAR area. |
| | (b) Auditorium | One Parking space per 15 seats |
| | (c) Bus parking | One bus parking per 750 square metre of permissible FAR area. |

| | | |
|-----|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | (d) Off street parking | Higher Secondary School 4.5 mtrs. off street parking depth in the entire frontage with boundary wall shifted back and front set back will be considered from property line and in other institutions upto 4.5 mtrs. in half the width of the front of the plot would be required for providing off street parking on roads of 18.0 mtrs or more width. |
| | (e) Residential area | One parking space per 150 sq mtrs. of permissible FAR area, in plot size of 112 sq mtrs. and above. |
| 3. | Medical | One parking space for every 65 sq mtrs. of permissible FAR area. One ambulance for every 375 sq mtrs of permissible FAR area. |
| 4. | Commercial | One parking space for 30 sq mtrs of permissible FAR area. |
| 5. | Industrial | One parking space per 100 sq mtrs of permissible FAR area. |
| 6. | Storage | One parking space for 100 sq mtrs of permissible FAR area. |
| 7. | Loading/Unloading | One parking space for every 100 sq mtrs. for industries and storage building |
| 8. | Multiplex/Cinema | One parking space per 15 seats. |
| 9. | Religious | One parking space per 100 sq mtrs of permissible FAR area. |
| 10. | Utilities (Fire Station, Police Stations, Post Office, Taxi Stand etc.) | One parking space per 100 sq mtrs of permissible FAR area. |
| 11. | Recreational | One parking space per 50 sq mtrs of permissible FAR area. |
| 12. | One ECS | =13.75 sq mtrs, |
| 13. | Area Requirement | 30 sq mtrs. per ECS in basement/stilt/podium/covered parking and 20 sq mtrs for surface parking |

Note: (I) Notwithstanding anything contained in these directions/regulations the Chief Executive Officer may where having regard to the features of a particular sector and the width of a road abutting any building/plot and the master plan consider it expedient to do so order for the preparation of architectural control detailed drawing for any of all the major projects specifically, especially of non residential character which may or may not deviate partly or wholly from the provisions of these regulations. For such purpose, Chief Executive Officer may constitute a committee, which shall submit its report to him for final decision. (II) Helipad may be permitted on the roof top of buildings above 60 mtrs. height subject to the clearance from Airport Authority and structural safety from I.I.T/N.I.T. (III) Development of parking facilities may be permitted proportionately on the basis of proposed phase wise development. However, provision of parking facilities has to be made on the basis of maximum permissible F.A.R. (IV) Parking norms are revised from time to time. Parking facilities have to be provided on the basis of revised norms for new proposed construction. Parking facility developed on the basis of old norms for old construction may be allowed to continue. If no parking facility has been developed, provisions have to be made on the basis of new norms for the entire old and proposed construction. TABLE No. - 6 Provisions for Landscaping

1. (a) Institutional, commercial, office/Industrial units/group housing, farm house shall be required to plant a minimum number of trees in their premises as follows.

| Plot size (in square metre) | Number of trees required | Minimum open space to be kept for landscaping |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Upto 2000 | One tree per 100 square metre of open space out of which minimum 50 percent to be in the category of evergreen trees.* | 25 percent of open area. In case of industrial plots no soft landscaping is required |
| Above 2000 to 12000 | One tree per 100 square metre of open space out of which minimum 50 percent trees to be in the category of evergreen trees. | 25 percent of open area |
| More than 12000- | One tree per 100 square metre of open space out of which minimum 50 percent to be in the category of evergreen trees. | 50 percent of open area |

(b) In case of plotted development in group housing plantation provision shall be as per Landscape Master Plan and following norms shall be followed. (i) On 18.0 metre and 24.0 metre wide road, alternate variety of evergreen and ornamental trees shall be planted @ 7.5 metre centre to centre. (ii) On road upto 12 metre ornamental trees will be planted @ 5 metre centre to centre of single variety in each pocket. (c) Recreational, Institutional Green: In addition to the requirement as mentioned in clause (a) detailed landscape plan will have to be got approved by the Authority as per specification in Landscape Master Plan and landscape manual approved by the Authority.

2. Residential plots other than group housing (flatted) :-

(i) One tree in every plot for plot size upto 120 square metre. (ii) Two trees in every plot for plot size above 120 and upto 300 square metre. (iii) One tree additional in every 100 sqm for plot above 300 square metre.

3. The minimum height of plantation of sapling should be 3.6 mtrs at the time of occupancy.

* Evergreen Tree: Tree that remains green for most part of the year and sheds leave slowly throughout the year, having height more than 2.0 mtrs, with a well distinguished trunk, Appendix-I {See regulation 5} Form for first application to erect, re-erect, demolish or to make material alteration in a building To, The Chief Executive Officer, New Okhla Industrial Development Authority, Noida, Uttar Pradesh. Sir, I hereby make application that I intend to erect/re-erect/demolish or to make material alteration in the building on Plot No in Sector....., Noida in accordance with the New Okhla Industrial Development Area Building Regulations and Planning and Development Directions and I enclose herewith the documents as per checklist 1-A/1-B/1-C/1-D annexed to this

application. I request that the construction may be approved and permission accorded to me to execute the work. Signature of the applicant Name of applicant (in Block letters). Address of the applicant : Dated :- (i) Note - Strike out which is not applicable. Checklist - 1 A (For buildings on individual residential plots) (i) Ownership documents; copies of allotment letter (transfer letter/memo or mutation letter in case of transfer) possession certificate, the lease deed (transfer deed in case of transfer), and dimension plan issued by the Authority. (ii) Form for first application to erect, re-erect, demolish or to make material alteration in a building (Appendix 1) (iii) Certificate prescribed in Appendix- 2 for undertaking the supervision by the Technical Person. Any change of the technical personnel during construction work shall be intimated to the Chief Executive Officer in writing. (iv) Structural stability certificate from the Architect/Structural Engineers as per Appendix-3. (v) Certificate for sanction of Building Plan as per Appendix-4. (vi) Where basement is proposed to be constructed, Indemnity bond on Rs. 100/- stamp paper duly attested by a Notary, shall have to be submitted. (vii) Specification of proposed building as per Appendix -6. (viii) Application for drainage of premises as per Appendix-7. (ix) Photocopy of the registration of the Technical Person as per Appendix 12 duly authenticated with plot number for which it is submitted. (x) In case of demolition photo of existing building. (xi) Soft copy of drawings in CD. (xii) In case of revalidation and revision original sanctioned plan to be submitted. (xiii) Photocopy of receipt of fees deposited, and such other charges, if any, as required by the Authority from time to time. (xiv) Three copies of drawings (one cloth mounted) duly signed by the Technical Person and Owner. (xv) Any other document as may be required by the Authority from time to time. CHECKLIST - 1 B (For buildings other than those on individual residential plots) (i) Ownership documents; copies of allotment letter, possession certificate, the lease deed (transfer deed in case of transfer), and dimension plan issued by the authority. (ii) Form for first application to erect, re-erect, demolish or to make material alteration in a building (Appendix 1). (iii) Certificate prescribed in Appendix- 2 for undertaking the supervision by the Technical Person. Any change of the technical personnel during construction work shall be intimated to the Chief Executive Officer in writing. (iv) Structural stability certificate from the Architect/Structural Engineers as per Appendix-3. (v) Certificate for sanction of Building Plan as per Appendix-4. (vi) Where basement is proposed to be constructed, Indemnity bond on Rs. 100/- stamp paper duly attested by a Notary, shall have to be submitted. (vii) Specification of proposed building as per Appendix -6. (viii) Application for drainage of premises as per Appendix-7. (ix) Photocopy of the registration of the Technical Person as per Appendix 12 duly authenticated with Plot No. for which it is submitted. (x) Photocopy of receipt of fees deposited, and such other charges, if any, as required by the Authority from time to time. (xi) Three copies of drawings (one cloth mounted) duly signed by the Technical Person and owner. (xii) Certificate of registered structural engineer and owner regarding earthquake resistance of the building as per Appendix 8(A)/8(B)/8(C), where-ever applicable. (xiii) Two copies of the drawings giving details of provisions for fire safety, security as per National Building Code. (xiv) Approval from the competent authority in case of hazardous buildings. (xv) Soft copies of the drawings in compact disc. (xvi) Valid time extension, where- ever applicable. (xvii) NOC from Airport Authority if building is more than 30.0 mtrs high. (xviii) NOC from Ministry of environment if covered area is more than 20,000 sq mtrs. (xix) Any other document as may be required by the Authority from time to time. (xx) In case of revision and revalidation original sanction plan to be surrendered/submitted as the case may be. Checklist - 1C (For layouts and sub-division of plots) (i) Ownership documents; copies of allotment letter (transfer/mutation letter in case of

transfer) possession certificate, lease deed (transfer deed in case of transfer), and dimension plan issued by the Authority.(ii)Form for first application to develop, redevelop or to make material alteration. (Appendix 1).(iii)Certificate prescribed in Appendix- 2 for undertaking the supervision by the Technical Person. Any change of the technical personnel during development work shall be intimated to the Chief Executive Officer in writing.(iv)Structural stability certificate from the Architect/Structural Engineers as per Appendix-3.(v)Certificate for sanction of Layout Plan as per Appendix-4.(vi)Specification of proposed layout development as per Appendix-6.(vii)Application for drainage of premises as per Appendix-7.(viii)Photocopy of the registration of the Technical Person as per Appendix 12 duly authenticated with Plot number for which it is submitted.(ix)Application form for water and sewer connection (where-ever applicable).(x)Photocopy of receipt of fees deposited, and such other charges, if any, as required by the Authority from time to time.(xi)Three copies of drawings (one cloth mounted) duly signed by the Licensed Technical Person and owner.(xii)Certificate of registered structural engineer and owner regarding earthquake resistance of the building as per Appendix 8(A)/8(B)/8(C), where-ever applicable.(xiii)Three copies of the drawings giving details of provisions for fire safety, security as per National Building Code.(xiv)Soft copies of the drawings.(xv)Valid time extension letter, where-ever applicable.(xvi)Any other document as may be required by the Authority from time to time.(xvii)In case of revision and revalidation original sanction plan to be surrendered/submitted as the case may be.

Checklist - 1D (For Temporary Structures)(i)Ownership documents; copies of allotment letter (transfer letter in case of transfer) possession certificate, lease deed (transfer deed in case of transfer), and dimension plan issued by the Authority.(ii)Form for first application to erect, re-erect, demolish or to make material alteration in a building (Appendix 1).(iii)Certificate prescribed in Appendix- 2 for undertaking the supervision by the technical person. Any change of the technical personnel during construction work shall be intimated to the Chief Executive Officer in writing.(iv)Certificate for sanction of Building Plan as per Appendix-4.(v)Specification of proposed building as per Appendix -6.(vi)Photocopy of the registration of the Technical Person as per Appendix 12 duly authenticated with Plot number for which it is submitted.(vii)Application form for water and sewer connection (where-ever applicable).(viii)Photocopy of receipt of fees deposited, and such other charges, if any, as required by the Authority from time to time.(ix)Three copies of drawings (one cloth mounted) duly signed by the Technical Person and owner.(x)Valid time extension letter , if applicable.(xi)Any other document as may be required by the Authority from time to time.(xii)In case of revision and revalidation original sanction plan to be surrendered/submitted as the case may be.

Appendix-2(See Appendix-1 Checklist 1A, 1B, 1C and 1D)Form for supervision of Building WorkTo,The Chief Executive Officer,New Okhla Industrial Development Authority,Noida, Uttar Pradesh.Sir,I hereby certify that the erection/re-erection and material alteration/demolition in/of building/site on Plot numberin Sector..... , Noida shall be carried out under my supervision and I certify that all the material (type and grade) and the workmanship of the work shall be generally in accordance with the general and detailed specifications submitted along with and that the work shall be carried out according to the sanctioned plan.

Signature of Technical Person.....Name of Technical Person.....License number of Technical Person.....Address of the Technical Person.....Date:

Note - Strike out which is not applicable.

Appendix-3(See Appendix-1 Checklist 1A, 1B and 1C)For Structural Stability

Certificate To, The Chief Executive Officer, New Okhla Industrial Development Authority, Noida, Uttar Pradesh. Sir, I hereby certify that the structural design of the Building on Plot number.....in Sector....., Noida shall be done by me/us and carried out in accordance with Part/IV structural design of National Building code of India corrected upto date. Signature of Technical PersonName of the Technical Person.....License number of the Technical Person.....Address of Technical Person.....Dated: Appendix - 4 (See regulation 25.10 & 25.11) Certificate of Sanction of Layout Plan/Building Plan (To be given by Technical Person as per Appendix 12) It is certified that the plans and all other drawings submitted for approval for building/Layout Plan on Plot number in Sector , Noida have been prepared in accordance with the New Okhla Industrial Area Development Regulations and the - Planning and Development Directions (as amended upto date), National Building Code, Indian Standard Institution Code and all other provisions as given in Chapter V, as applicable. Signature of Technical PersonName of the Technical PersonRegistration numberAddress of Technical PersonEnclosure- Attested photocopy of the certificate of Technical Person.- Building Plan and all prescribed documents. Dated : Place : Appendix-5 (See Appendix Number 1 Checklist 1A, 1B and 1C) Indemnity Bond In consideration of the New Okhla Industrial Development Authority, a body constituted under section-3 read with Section 2(d) of the Uttar Pradesh Industrial Area Development Act, 1976 (U.P. Act no. 6 of 1976) (hereinafter referred to as 'the promisee' - which expression shall unless the context otherwise require, includes its successors and assigns) having sanctioned the construction of the basement in the building plans of the House/Factory building to be constructed on Industrial/Residential/Institutional/Commercial/Recreational Plot number in Sector , Noida situated in the New Okhla Industrial Development Area in District Gautam Budh Nagar, Uttar Pradesh. On production of the bond of Indemnity by..... son ofaged about years resident of (hereinafter called the 'promisor' which expression shall unless the context otherwise require includes his/her heirs, executors, administrators, representatives and permitted assigns) to implement the promises of any loss or damage caused in respect of construction of basement referred to above the promisor hereby agrees to execute this bond of Indemnity. Now therefore this deed Witnesseth as follows In consideration of the promisee having sanctioned the construction of the basement in the building plan of the factory/residential building to be constructed in Industrial/Residential/Institutional/Commercial/Recreational Plot number Sector situated in the Noida, District Gautam Budh Nagar, I the promisor agrees to indemnify the New Okhla Industrial Development Authority and at all times holds himself liable for all damages and losses caused to the adjoining building (s) on account of the construction of basement referred to above and further undertakes to indemnify the promisee New Okhla Industrial Development Authority any such amount to the full extent which the promisee may have or to be required to pay to any person (s) having rights in the adjoining properties on account of the construction of the basement by way of compensation or otherwise and further to pay all costs and expenses which the promisee may have to spend in

defending any action in the Court of Law regarding thereto. In witness whereof the promisor executed this Bond of Indemnity at New Okhla Industrial Development Area, District Gautam budhnagar..... on day of.....(Promisor), Witness:

1.

.....

2.

.....Appendix-6 See regulation 6.1, 6.2, 6.3, 6.4 General Specifications Sheet New Okhla Industrial Development Authority Specification of proposed building

1. Total Plot Area..... square metre./Basement existingsquare metres/Basement proposedsquare metres/Ground floor existing square metre/Ground Floor Proposed square metre.

2. First Floor existingsquare metres/First Floor Proposedsquare metres. Second Floor existingsquare metres/Second Floor Proposed..... .. square metres.

3. Mezzanine Floor existing square metres/Mezzanine Floor Proposedsquare metres.

4. The purpose for which it is intended to use the building
.....

5. Specification to be used in the construction of the

(i) Foundation(ii) Walls
.....(iii) Floors
.....(iv) Roofs
.....

6. Number of storeys the building will consist
.....

7. Approximate number of persons proposed to be accommodated

.....

8. The number of latrines to be provided

.....

9. Whether the site has been built upon before or not

.....

10. Source of water to be used for building purpose

.....

Signature of the Applicant.....Full ame
(In Block Letters).....Address

.....Appendix-7(See Appendix
1 Checklist 1A, 1B and 1C)New Okhla Industrial Development Authority(To be submitted in
duplicate)Application for Draia ge of PremisesToThe Chief Executive Officer,New Okhla Industrial
Development Authority,Noida, Uttar Pradesh.Sir,I/We, the undersigned hereby apply for
permission to drain the premises on Plot number.....in

Sector....., Noida. The sanitary arrangement and drains
for the premises are shown in the accompanying plans and sections in duplicate and described in
the Appendix - 6 (submitted in duplicate) and the premises are open to inspection by the Officers of
New Okhla Industrial Development Authority. I/we undertake to carry out the work in accordance
with the provisions of New Okhla Industrial Development Authority Building Regulations 2010 and
to pay the Authority the cost of connection to the sewer at the rate given in the scheme of
fees.Signature of the Applicant.....Full Name (In Block
Letters).....Address

.....Name of the Technical Person carrying out
work.....License

number.....Address of the Technical
Person.....Dated:Appendix - 8(A)(See regulation

umber 25.2)Kindly (☐) tick the relevant codes that have been followedStructural Safety and Natural
Hazard Protection of Buildings Requirements specified in the following Indian Standards, Codes
and guidelines and other documents needs to be observed for structural safety and natural hazard
protection of buildings etc:-(a)For General Structural Safety

**1. IS : 1905 - 1987 "Code of practice for structural safety of buildings;
masonry walls" Indian Standards Institution, March 1981.**

- 2. IS : 1904 - 1978 "Code of practice for structural safety of buildings; foundation" Indian Standards Institution.**
- 3. IS : 456 - 2000 "Code of practice for plain and Reinforced Concrete" Indian Standards Institution, September 2000.**
- 4. IS : 800 - 1984 "Code of practice for general construction in steel" Indian Standards Institution, February 1985.**
- 5. IS : 883 - 1966 "Code of practice for design of structural timbers in buildings; " Indian Standards Institution, March 1967 Besides any other relevant Indian Standards will need to be referred to**

(b)For Earthquake protection.

- 1. IS : 1893 - 1984 "Criteria for Earthquake resistant Design of Structures (Fourth Revision)" June 1986**
- 2. IS : 13920 - 1993 "Ductile detailing of reinforced concrete structures subjected to Seismic forces - Code of Practice" November 1993**
- 3. IS : 4326 - 1993 "Earthquake Resistant Design and Construction of Buildings - Code of Practice (Second Revision)" October 1993**
- 4. IS : 13828 - 1993 "Improving Earthquake Resistance of Low Strength Masonry Buildings - Guidelines" August 1993.**
- 5. IS : 13827 - 1993 "Improving Earthquake Resistance of Earthen Building Guidelines" October 1993**
- 6. IS : 13935 - 1993 "Repair and Seismic Strengthening of Buildings - Guidelines" November 1993.**
- 7. Improving Earthquake Resistance of Building-Guidelines" by expert group, Government of India, Ministry of Urban Affairs and Employment, published by Building Materials and Technology Promotion Council 1998.**

8. The National Building Code of India 1983 For location of the building in hazard prone area of earthquakes, cyclone or wind storms and floods, reference may be made to the following:

9. "Vulnerability Atlas of India" by expert group, Government of India, Ministry of Urban Affairs and Employment, published by Building Materials and Technology Promotion Council 1997.

Note : 1. As and when anyone of the above referred standards and documents is revised, the design and construction of Buildings thereafter must satisfy the latest version for approval of building plans by the Authority. The above information is factually correct. Signature of owner with date
Signature of the Engineer who will supervise the construction (with qualification and experience as mentioned in Appendix 12)
Name (Block) Name (Block)

.....Address:Legible Seal:(with address)
Signature of the Technical Person who will supervise the construction
Name (Block)
.....Registration number.Legible Seal with address :
.....Appendix -8 (B)(See regulation number 25.2) 4.1 Building Information Schedule

1. Building Address Plot number Sector Town: Noida
2. Building function & Locations
 - 2.1 Use Institutional Commercial Industrial *
 - 2.2 Importance Ordinary Important Hazardous *
 - 2.3 Seismic Zone
(Design Intensity Used V(IX) IV(VIII) III(VII) II(VI) IS:1893
3. Design *EQ Factor $\alpha_h = \dots\dots$ $I = \dots\dots$ $\alpha_h = \dots\dots$ IS:1893
4. Foundation
 - 4.1 Soil type at site (Note 2) Rock/stiff Liquefiable
Medium Soft
Expensive (Bearing
IS:1904 Capacity.)
 - 4.2 Type of Foundation Strip Indiv.Col. Footings/Raft Bearing Piles Friction Piles IS:1893
5. Load Bearing Wall Buildings
 - 5.1 Building Category A($\alpha_h < \alpha_5$) B($\alpha_h = \alpha_5$ to α_6) C($\alpha_h \alpha_6$ to α_8) D($\alpha_h \alpha_8$ to $\alpha_9 \alpha_2$) E($\alpha_h > 0.12$) IS: 4326
 - 5.2 Bearing Walls Brick Stone Solid Block Hollow Block Adobe
 - 5.3 Mortar (Note 4) C:S=1..... C:L:S=1..... L:S=1..... Clay Mud *

| | | | | | | |
|------|--------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------|---------------------------------------|--------------------|--------------|
| 5.4 | Floors | Reinforce Concrete Slabs | Stone Slabs on Joists | Prefab flooring elements | * | |
| 5.5 | Roof Structure R.C. Slab | Flat like floors/pitched | Trussed/Raftered/A Frame/Slopping | | | |
| 5.6 | Roof Covering | CGI Sheetting | *AC Sheetting | Clay tiles/Slate | Woodshingle | |
| 5.7 | Opening in walls | Control used on sizes? | Control used on location? | Strengthening around? | IS:4326 | |
| | | Yes/No | Yes/No | Yes/No | IS:13828 | |
| 5.8 | Bands Provided | Plinth Band | Lintel Band | Roof/Eave Band | Gable Band | Ridge Band |
| | | Yes/No | Yes/No | Yes/No | Yes/No | |
| 5.9 | Vertical Bars | At corners of rooms | At jambs of openings | | | |
| | | Yes/No/NA | Yes/No/NA | | | |
| 5.10 | Stiffening of Prefab R.C. Screed & BandPeripheral band and Diagonal Planks and Floors/Roofs connectorsalround band | IS:4326 | | | | |
| 6. | Steel/R.C. frame buildings | | | | | |
| 6.1 | Building shape Both axes near symmetrical Oneaxis near symmetrical/Unsymmetrical (torsion considered) | | | | | |
| 6.2 | Infills/partitions | | Out of plane stability check? Yes/No | In Plane stiffness considered? Yes/No | IS:1893,IS:4326 | |
| 6.3 | Ductile Detailing of IS:13920 | | Beams? | Columns? | Beam/column Joint? | Sheer Walls? |
| | R.C. Frames | Yes/No | Yes/No | Yes/No | Yes/No | |
| 6.4 | Ductile Detailing of SP6(6) | | Beams? | Columns? | Beam/column Joint? | |

Steel
Frames Yes/No Yes/No Yes/No

Notes 1. Encircle the applicable Data point or insert information.

2. Stiff.N>30:Medium.N=10.3:Soft.N<10:Liquefiable,poorly graded sands with N<15 under Water Table (see Note 5 of Table 1 in IS:1893)

Where N: Standard Penetration (I:2131 - 1981)

3. * Means any other. Specify.

C = Cement, S=Sand, L= LimeThe above information is factually correct.Signature of the owner with dateSignature of the Engineer who will supervise the construction (with qualification and experience as mentioned in Appendix 12)Name (Block)Address:Legible Seal:(with address)Name (Block)AddressSignature of the Technical Person who will supervised the construction* R.C. stands for Reinforce Concrete* CGI stands for Corrugated Galvanised Iron* B.C. stands for Bearing Capacity* EQ stands for Earth Quake*AC stands for Asbestos CorrogatedName (Block)Registration Number.Legible Seal :With addressAppendix - 8(C)(See regulation Number 25.2)Certificate(The certificate to be submitted with the application for building permission alongwith the building drawings and Building Information Schedule)

1. Certified that the building plans submitted for approval also satisfy the safety requirements as stipulated in the Indian Standard Codes, guidelines and documents specified in the Appendix 8A regarding earthquake safety awareness and the information given in the attached Building Information Schedule is factually correct to the best of my knowledge and understanding.

2. It is also certified that the structural design including safety from natural hazards including earth quake has been prepared by duly qualified civil engineer along with qualification and experience as mentioned in Appendix 12.

3. Location/Address of Building

Plot number _____Sector _____Town: Noida

4. Particulars of Building

1. Ground Coverage (square metre)

2. Total covered area (square metre)

3. Total Numbers of Floors above ground.

Signature of owner with date _____ Signature of the Engineer who will supervise the construction (with qualification and experience as mentioned in Appendix 12) _____ Name (Block) _____ Name (Block) _____ Address: _____ Legible Seal: (with address) _____ Address _____ Signature of the Technical Person who will supervised the construction _____ Name (Block) _____ Registration number _____ Legible Seal : _____ (with address) _____ Appendix - 8D (See regulation No. 25.2) Certificate (To be submitted with the application for obtaining occupancy certificate)

1. Certified that the building for which completion plan has been submitted for approval conforms to the requirements of relevant Indian Standard Codes and National Building Code as referred in Appendix 8-A in respect of Structural Safety in general and natural hazards including earthquake in particular.

2. It is also certified that the building has been constructed as per approved foundation and structural designs provided by the Structural Engineer and is certified to be based on relevant Indian Standard Code and National Building Code as referred above and the building is safe for occupancy.

3. Location/Address of Building

Plot number _____ Sector _____ Town : Noida

4. Particulars of Building

1. Ground Coverage (square metre)

2. Total covered area (square metre)

3. Total Numbers of Floors above ground.

Signature of owner with date _____ Signature of the Engineer who will supervise the construction (with qualification and experience as mentioned in Appendix 12) _____ Name (Block) _____ Name (Block) _____

.....Name (Block)Address:Legible Seal:(with address)Address
Signature of the Technical Person who will supervised the
 constructionName (Block)Registration numberLegible Seal :
(with address).....Appendix -9(See regulation no. 20)Form for
 Occupancy Certificate for Building WorkToThe Chief Executive Officer,New Okhla Industrial
 Development Authority,Noida, Uttar Pradesh.Sir,I hereby certify that the
 erection/re-erection/material alteration/demolition in/on building on Plot number
in Sector.....in Noida has been supervised by me and the completion plan
 along with the required documents are attached herewith. The plans were sanctioned vide letter
 number..... dated.....and the work has been completed to my best
 satisfaction. The workmanship and all the materials which have been used are strictly in accordance
 with the general, detailed specification. No provision of the regulations, directions, conditions,
 prescribed or order issued there under have been transferred in the course of work. The land is fit
 for construction for which it has been developed or re-developed.Signature of the Technical Person
-Name and address of the Technical
 PersonDated:Note - Strike out the words which
 are not applicable.Checklist - 9A (For buildings on individual residential plots)(i)3 copies of
 drawings (one set cloth bounded) duly signed by Technical Person and owner.(ii)Completion fees, as
 applicable.(iii)Valid time extension certificate, if applicable.(iv)Photographs of the building from
 front and side setbacks.(v)Photocopy of registration of Technical Person signing the plan and
 Appendices.(vi)Copy of receipt of payment of Water, Sewer connection charges, Metre charges and
 any other charges as may be required by the Authority.(vii)Compact Disc of the building plan
 submitted.(viii)Any other document as may be required from time to time.Checklist - 9B (For
 buildings on Plots other than individual residential plots)(i)3 copies of drawings (one set cloth
 bounded) duly signed by Technical Person and owner.(ii)Completion fees.(iii)Valid time extension
 certificate, if applicable.(iv)Photographs of the building from front and side setbacks.(v)Photocopy
 of registration of Technical Person signing the plan and Appendices.(vi)No Objection Certificate
 from Chief Fire Officer, wherever applicable.(vii)No Objection Certificate from Explosive
 Department, wherever applicable.(viii)Certificate from owner and structural Engineer regarding
 earthquake resistance of building as per Appendix 8/A/B/D, if applicable(ix)Copy of receipt of fees
 deposited with Power Company.(x)Copy of receipt of payment of Water, Sewer connection charges,
 Metre charges if not submitted at the time of plan approval, and any other charges as may be
 required by the Authority.(xi)Compact Disc of the building plan submitted.(xii)Any other document
 as may be required from time to time.(xiii)NOC for Environment from Environment Department if
 applicable.(xiv)Affidavit regarding rain water harvesting.(xv)Photographs of the building/site and
 all documents to be self attested by the applicant.Checklist - 9C (For buildings layout and
 sub-division of land)(i)3 copies of drawings (one set cloth bounded) duly signed by Technical
 Person, and owner.(ii)Completion fees.(iii)Valid time extension certificate if
 applicable.(iv)Photographs of the site from all sides.(v)Photocopy of registration of Technical Person
 signing the plan and appendices.(vi)No Objection Certificate from Chief Fire Officer, wherever
 applicable.(vii)No Objection Certificate from Explosive Department, wherever
 applicable.(viii)Certificate from owner and Structural Engineer regarding earthquake resistance of
 building as per Appendix 8/A/B/D. if applicable.(ix)Copy of receipt of fees deposited with Power
 Company Limited.(x)Copy of receipt of payment of water/sewer connection charges, Metre charges

if not submitted at the time of plan approval, and any other charges as may be required by the Authority.(xi)Compact Disc of the building plan submitted.(xii)Any other document as may be required from time to time.Note: All documents and photographs should be self attested by the allottee and the technical person.Appendix -10{See regulation no. 20.1}Form for Sanction or refusal of Building PermitFromThe Chief Executive Officer,New Okhla Industrial Development Authority,Noida, Uttar

Pradesh,To:.....Sir,With reference to your application numberdated.....for grant of permit for the erection/re-erection/material alteration/demolition in/of building on Plot number.....in Sector....., in Noida I have to inform you that the sanction has been granted/refused by the Authority on the following conditions.

- 1.
- 2.
- 3.
- 4.

Office StampSignatureOffice communication numberName of the OfficerDesignation of the OfficerDatedNote - Strike out which is not applicable.Appendix -11{See regulation number 20.1}Form for Occupancy CertificateFromThe Chief Executive Officer,New Okhla Industrial Development Authority,Noida, Uttar

Pradesh,To:.....Sir,I hereby certify that the erection/re erection/alteration/demolition of building on Plot number.....in Sector....., Noida completed under the supervision of Technical Person or name.....has been inspected by the officers of the Authority and declare that the building conforms in all respects to the requirements of the regulations in respect of occupancy. Structural safety based upon the structural stability certificate and the completion certificate submitted by the concerned Technical Personnel for fire safety, hygienic and sanitary conditions inside and the surrounding and is fit for occupation.Signature

.....NameDesignation

.....DatedAppendix - 11A(See regulation

No.20.4)Form for Temporary Occupancy CertificateFrom,The Chief Executive Officer,New Okhla Industrial Development Authority,Noida, Uttar

Pradesh.To:.....Sir.I hereby certify that the erection/re-erection/material alteration/demolition on plot No.Sector..... Noida completed under the supervision of licensed Architect/Engineer/Draftsman/Group License No. has been inspected by me/officers of the Authority and declare that the building does not conforms in respect of the following requirements of the Regulations/Directions as amended upto date.

- 1.
- 2.
- 3.
- 4.
- 5.

However, a temporary occupancy certificate is being issued for a period of subject to the condition that the above mentioned defects/discrepancies will be got corrected and a fresh completion certificate is submitted to the Chief Executive Officer for further necessary action. Office stamp Office (communication)..... No. Signature Name of the office..... Designation Dated : Note :..... Strike out the works which are not applicable. Appendix -12 Qualification of Technical Personnel for Preparation of Schemes for Building Permit and Supervision (i) The qualifications of the technical personnel and their competence to carry out different jobs for building permit and supervision by the Authority shall be as hereinafter indicated. (ii) Architects 2.1 Qualification - The qualification of Architect will be the Associate Membership of the Indian Institute of Architects or such Degree or Diploma which makes him eligible for such membership or qualification mentioned in Schedule -XIV of Architects Act. 1972 and registered with the Council of Architecture as per provisions of the Architects Act. 1972. 2.2 An Architect shall be competent to carry out work related to building permit and shall be entitled to submit the following: (i) All plans and related information connected with building permit. (ii) Structural details and calculations for building on plots upto 500 square metre and upto four storeys height, and (iii) Certificate of supervision for all buildings. (iv) Layout Plan upto 2 hectares (iii) Engineers 3.1 Qualification - The qualification for Engineers will be Associate/Corporate Membership (Civil) of the Institution of Engineers or such degree/diploma in Civil, Municipal, or Structural Engineering which makes him eligible for such membership or which is recognized by the Uttar Pradesh Public Service Commission for the post of Assistant Engineer. An engineer shall be competent to carry out the work related to building permit and shall be entitled to submit the following: (i) Building plans for plots upto 1000 sqm. (ii) Structural details and service detail and calculations for all buildings. (iii) Certificate of supervision for all buildings. (iv) Structural Calculation and details for building mentioned shall be as follows:

| Sr No. | Type of Building | Number of years of experience for Structural Engineer for structural design and supervision | | Other Details |
|--------|------------------|---------------------------------------------------------------------------------------------------------|-----------------------------------|------------------|
| | | Graduate Civil | Post Graduate Structural Engineer | |

Engineer

| | | | | |
|---|-------------------------------------------------------------------------------------------------------------------------------------|----------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Multistoreyed/important facility buildings which are upto 4 storeys or 12 metre high or 2500 square metre covered area | 5 years | 3 years | |
| 2 | Multistoreyed important facility buildings which are upto 8 storeys or 24 metre high or 5000 square metre covered area | 9 years | 7 years | |
| 3 | Multistoreyed/important facility buildings which are above 8 stories or above 24 metre high or above 5000 square metre covered area | 10 years | 8 years | Copy of structural design to be signed by Professor of Structural Design of Indian Institute of Technology/N.I.T, or any other recognized technical institutes. |

(v) Town Planner (for layout plans):- The minimum qualification for a town planner shall be post-graduate degree or post graduate diploma in town and country planning/urban planning which makes him eligible for Associate Membership of the Institute of Town Planners, India or recognized by the Public Service Commissions for the Post of Assistant Town Planner. A Town Planner shall be competent to carry out work related to building permit and shall be entitled to submit the layout plans. (vi) Group or Agency:- When a group or agency comprising of qualified Architect/Engineer Town Planner is practicing then the qualification and competence of work will be the combination of the individual qualification and competence given under paras 2,3 and 4 above.