

TOSBIT - USER MANUAL

Topic - 1: Introduction

Overview

- **Tosbit** is an open-source relational database under continuous development & maintainance on **GitHub**.
- It aims at providing a **good performance, compressed media file storage, easy server setup** & many more features.
- The file system follows a CSV-like storage pattern, with extension of `.tosbit`.
- This pattern contains the data separated by commas & spaces, which can be skipped during various operations, thus saving computation time.
- Also **Tosbit** relies on operating system's buffers, Linux in this case, for high performance.
- This makes it very portable across various architectures.

Target Users

- **Embedded system vendors** relying on **Linux** for their products.
- Bodies which want to **store files** while not discarding relational properties.
- Also those who prefer to use an **open-source relational database** for security reasons.
- This also targets at new **learners** due to its simple syntax grammar which are easier to grasp than other databases.

Limitations

- Because this project is currently in prototype phase, there are some important functionalities missing which would be added soon as we progress.
- These include selective `SELECT`, `UPDATE` & `DELETE` operations.
- Though non-selective operations are there in prototype version.
- Other functionalities which are missing includes `JOIN` & aggregate functionalities.
- Feature for storing compressed media file is available, but only on client side without transfer over server.
- These all absence will be addressed soon one-by-one, as this project is under continuous development & this prototype is just showcase of its fraction of abilities in future.

Topic - 2: System Requirements

Hardware Requirements

- Hardware requirements are currently limited to the **x86** and **x86_64** architecture currently.
- Very soon it will include **ARM** & **RISC-V** support for users.

Software Requirements

- Currently, **Tosbit** is limited to **Debian derived Linux systems**.
- For example, **Debian**, **Ubuntu**, **Mint**, **Pop!_OS** & **Zorin OS** etc.
- Soon, packages for other Linux distros will be available.
- However, there are currently no plan for **Windows** & **MacOS**.
- Software in Linux required for running **Tosbit** is just **xz Compressor** & **GCC**.
- But developers have to install **CMake** & **GNU Debugger** (optional but advised) too.

Third-Party Tools

- Right now, no third-party tool is required to run **Tosbit**.
- Its made too lightweight with all natively crafted components from scratch, not requiring any heavy imported tool.

Topic - 3: Installation & Setup

For Release Users

These installation steps are for those who are willing to download the release:

1. Get the `.tar.gz` file from **GitHub**.

```
wget https://github.com/Gourav-334/Tosbit/releases/download/v0.1.0-beta/Tosbit_v0.1.0-beta.tar.gz
```

2. Extract this `.tar.gz` file.

```
tar -xzf Tosbit_v0.1.0-beta.tar.gz
```

3. Allow permission to it.

```
chmod +x Tosbit_v0.1.0-beta/*
```

4. Navigate inside the directory.

```
cd Tosbit_v0.1.0-beta
```

5. Try running engine or server.

```
./engine
./server 8080          # Create account in engine first before running
server.
```

For Developers

For installation by developers having cloned the repository, follow the given steps (assuming you to be in parent directory of repository):

1. Install required tools for our database:

```
bash scripts/alpinelinux.sh      # Only for Alpine Linux.
bash scripts/arch.sh             # Only for Arch, Manjero & EndeavourOS.
bash scripts/fedora.sh           # Only for Fedora, RHEL, Rocky &
AlmaLinux.
bash scripts/opensuse.sh         # Only for openSUSE.
bash scripts/ubuntu.sh           # Only for Debian & Ubuntu.
bash scripts/voidlinux.sh        # Only for Void Linux.
```

2. Set up environment using CMake:

```
cd exec
bash remake.sh 0
bash remake.sh 1
cd build
cmake ..
make
cd ../..
```

OR

2. Alternatively (but discouraged), use Bash scripts for compilation & linking:

```
cd scripts
bash compileAll.sh
bash linkAll.sh
cd ..
```

3. **(Optional)** Run the server component with an argument telling what port to run it on:


```
cd exec/build
./server 8080
cd ../..
```

4. Try running Tosbit engine now:

```
cd exec/build
./engine
cd ../../
```

Topic - 4: Database Schema

Entity-Relationship Diagram



- As the diagram above shows, the user interacts with the **engine**.
- And an abstraction is provided for various components like the **profile manager**, **syntax parser** (query processor) & **driver manager** (if used).

File System

- data/
 - db_name/
 - tbl_name/
 - details.tosbit
 - rows.tosbit
 - metadata.tosbit
 - tables.tosbit
 - metadata.tosbit
 - databases.tosbit
 - metadata.tosbit

- logs/
- users/
 - user.tosbit

NOTE: Dots (.) in code sections below are spaces, added for clarity.

1. details.tosbit (data/db_name/tbl_name/)

```
name.....,string,unique.,5.\n
age.....,int...,regular,4.
```

1. Attribute name
2. Data type
3. Key type
4. Length of largest value in an attribute.

2. metadata.tosbit (data/db_name/tbl_name/)

```
10,10,6.
```

1. Length of largest attribute name (larger than 10)
2. Length of largest data type name (larger than 10)
3. Length of largest key type (larger than 6)

3. tables.tosbit (data/db_name/)

```
table1.....\n
table2.....
```

1. Table's name

4. metadata.tosbit (data/db_name/)

```
6.
```

1. Length of largest table.

5. database.tosbit (data/)

```
db1.....\n
db2.....\n
mydb.....
```

1. Name of database
2. Name of its largest tables.

6. `metadata.tosbit ( data/ )`

```
10
```

1. Length of largest database name (larger than 10).

7. `logs/`

- `logs/` directory contains all the log history in **JSON** format.
- These are easy to access in the local file system.

8. `user.tosbit ( users/ )`

- `user/tosbit` contains all the user credential in encrypted form.

Case-Insensitive Syntax

- **Tosbit** supports writing case-insensitive commands.
- But that is considered only for its own keywords.
- For user defined entities like databases, tables & attributes etc, the parser considers each ASCII character different.
- This insensitivity comes from the fact that **Tosbit** consists of **DFA-based parsers**, which can be easily mapped to same states.

Full uppercase:

```
MAKE DB mydb
```

Full lowercase:

```
make db mydb
```

Mixed:

```
mAkE dB mydb
```

Unrestrictive Spaces

- There can be multiple spaces between two keywords or written entities.
- But whole command (including) spaces must be under 512 bytes or characters.

- There can be spaces around operators (= , < , > , <= , >= , | , &) & dots (.) too.
- Spaces aren't required between keywords or entities written around paranthesis.

Common way:

```
SELECT tbl2.(@) WHERE (score>7)
```

Sticked:

```
SELECT tbl2.(@)WHERE(score>7)
```

Space around operators:

```
SELECT tbl2.(@) WHERE (score > 7)
```

All together:

```
SELECT tbl2.(@)WHERE(score > 7)
```

Data Types

- **Tosbit** currently supports 5 data types as following.

Current data types:

1. INT - Integer (upto 32-digit)
2. FLOAT - Floating point number (upto 32-digit with decimal point)
3. STRING - String (upto 32-bytes)
4. BOOL - Boolean (either true or false)
5. MEDIA - A file in user file system

Key Types

- Currently, **Tosbit** supports three types of keys.

Current key types:

- **Regular key:** The default key type to each attribute.
- **Unique key:** Limited to one attribute in a table, defined with \$ suffix to attribute's name.
- **File key:** For media files, unique too but not limited to one attribute in a table.

Relationship Among Tables

- After implementation of JOIN operations, we will see relationships among tables soon.
- Currently, there is no strong relation among tables, other than being under same database.

Log Information

- Logs present in logs/ in clusters.
- Individual log files contain main five information.

Information stored in logs:

1. Username
2. Time stamp
3. Longitude & latitude
4. Command executed

Topic - 5: Query Commands

Comments

- Comments are useful for helping log readers know what the database user was doing.
- Whatever is written between two @ is considered a comment.
- But it mustn't interfere with another command, else expect an error or strange behaviour.

```
@ This is a comment! @
```

- In the case above, This is a comment is our comment (with all the spaces).
- And this command is stored in log along with other user information.

Opening Database

- In order to access tables in a database, one has to open it.
- This is because otherwise one has to always explicitly mention in commands what database they are referring to.
- Such a repetitive process makes passing command very cumbersome.
- That's why we tell the engine just once, which database to use.

```
OPEN DB db_name
```

- Here, db_name is the sample name of a database.
- Database can contain a set of tables.

Table Structure

- User can check out structure of a table using the command given below.

```
SHOW STRUCT tbl_name
```

- `tbl_name` here is sample name of a table.
- This will display all the attributes contained in the table with their data type & key types.

All Databases

- We can see name of all databases listed using the `SHOW` command.

```
SHOW ALL DB
```

All Tables

- Like previous one, this command is for listing all tables in an opened database.

```
SHOW ALL TABLES
```

Making Table

- For creating a new table in a database, we pass all its attribute names with their respective data types.

```
MAKE TABLE tbl_name(INT $sno, STRING name, MEDIA photo)
```

- Here, `tbl_name` is sample name of a table.
- The `$` prefix in `sno` declared attribute `sno` as **unique**.
- So, `sno` is linked to a **unique key**.
- Even the data types we defined above can be written *case-insensitively*.

```
MAKE TABLE tbl_name(int $sno, stRiNg name, medIa photo)
```

- The command will still work as alternative to previous command.

Making Database

- Similar to previous command we discussed, this one doesn't require any argument.
- By using this command, we tell engine to define a container for a different set of tables.

```
MAKE DB db_name
```

- Here, `db_name` is sample name of the database.

Deleting Table

- As the name says, this command is used for deleting a table, including every row it contains & its properties.

```
DELETE TABLE tbl_name
```

- Here, `tbl_name` is sample name of a table.

Deleting Database

- Similar to previous command, this command deletes a whole database.
- This removes all the tables it contained, all the rows those tables contained & properties of those tables.

```
DELETE DB db_name
```

- Here, `db_name` is sample name of a database.

Clearing Table

- Using this command clears a table of all the rows it contains.
- But preserves the properties & structure of the table.

```
CLEAR TABLE tbl_name
```

- Here, `tbl_name` is sample name of a table.

Clearing Database

- Like the previous command, it clears a database of all its contained tables.
- But it preserves the database as a container.

```
CLEAR DB db_name
```

- Here, `db_name` is sample name of a database.

Pushing Row

- We push rows to table using the `PUSH` command.
- Inside the paranthesis, we pass value for each attribute in order of their definition.

```
PUSH TO tbl_name(1, User, 7.5)
```

- In sample command above, we are assuming that table `tbl_name` contains three attributes.
- Where the first one is an integer, second is string & third one is a floating point decimal number.
- If we would be having a media attribute (`MEDIA`), the terminal asks user prompt to enter file's address (absolute or relative).
- For multiple media files multiple prompts are asked.

Display Of Rows

- We can check out all the contained rows in a table using `SELECT` command.

```
SELECT tbl_name.(@)
```

- `tbl_name` is name of table.
- `@` means we are requesting to display all attributes/columns.
- In future there will be integration with the `WHERE` clause for more dynamic & flexible usage.

Updating Rows

- We can update all the rows for some selected attributes with `UPDATE` command.

```
UPDATE tbl_name.(rank=Colonel, pay=100000)
```

- In command above, table `tbl_name` is updated with its attribute `rank` & `pay` changed to mentioned values.
- It makes changes to all the rows, but sooner there will be integration with `WHERE` clause for selective control.
- Also, the mention of attributes to change can be written in any order.

```
UPDATE tbl_name.(pay=1000000, rank=Colonel)
```

- The command above will still work alternative to previous one.

Topic - 6: Tosbit API

Introduction

- A user can very painlessly connect to a **Tosbit** server through `libtosbitAPI.a`, a static library for Tosbit's driver manager.
- This doesn't discriminate with any kind of application **C** (with **GCC**) uses.
- Sooner, Tosbit's APIs will be available for other compilers targeting many other languages too.

Example Usage

Follow the given steps for using in-code Tosbit in C:

1. Navigate to `exec/build/` & create a C source (`.c`) file:

```
cd exec/build
touch myfile.c
```

2. Open this file with your favorite code editor, I would be using **GNU Nano**:

```
nano myfile.c
```

3. Write the following code in it:

```
#include "../include/driver_manager.h"

int main(void)
{
    /* Enter 'Username', 'Password' & 'Hostname' as per your entered
    credentials. */

    setConnection("Username", "Password", "Hostname", 8080, "Username",
    "Password", FALSE);

    interpret("SHOW ALL DB");
    interpret("MAKE DB mydb");
    interpret("SHOW ALL DB");

    endConnection();

    return 0;
}
```

4. Link against `tosbitAPI.a` static library:

```
gcc myfile.c -I../include -L../lib -ltosbitAPI -o myfile
```

5. Run the server:

```
./server 8080
```

NOTE: If it doesn't work, try changing port number argument here & in code too.

6. Run the created executable:

```
./myfile
```

- This was a very basic tutorial on very painlessly using in-code **Tosbit** using **GCC**.
- Users should take note that they are free to modify the directory structure & customize their way of usage.
- And there is no worry of space in **embedded systems** regarding it, because linking is just a one time process.

Topic - 7: Limitations & Future Plan

Limitations

- Selective operations
- Join operations
- Serverless C connection
- Unrestrictive strings
- No aggregation function
- Absence of B+ tree
- No role-based access control
- No server backup function
- Non-standard encryption

Future Plan

- In future the plan is to add more operations to **Tosbit**.
- Make it more dynamic than it is right now.
- Also make it more secured with better techniques.
- Fine tuning for embedded systems & other architectures like **RISC-V**.

Bottlenecks

- There are no major bottleneck noticed so far in **Tosbit**.
- But the performance might be little inconsistent for not directly writing data to disk.
- So, the performance for using Linux's buffers is better, but inconsistent.

Topic - 8: Conclusion

Current Key Features

- Commenting
- Listing entities
- Making/creation of entities
- Clearing & deleting of entities
- Writing data to tables
- Updating entries

Full Documentation

- [GitHub](#)
-