

Experiment-5

Student Name: Gourav Sharma

Branch: BE-CSE

Semester: 5th

Subject Name: DAA

UID: 23BCS10857

Section/Group: 23BCS_KRG_3A

Subject Code: 23CSH-301

1. Aim: Sort a given set of elements using the Quick sort method and determine the time required to sort the elements. Repeat the experiment for different values of n , the number of elements in the list to be sorted. The elements can be read from a file or can be generated using the random number generator.

2. Objective: To understand and implement the Quick Sort algorithm in C++ for sorting a set of elements. The objective is to help students learn the divide-and-conquer strategy, efficient in-place sorting, pivot selection, recursive function implementation, and analysis of time complexity in best, average, and worst-case scenarios, thereby strengthening their understanding of sorting algorithms and their practical applications in data handling.

3. Procedure:

1. Start.
2. Define a swap() function to exchange two integers.
3. Define partition() function:
 - Choose the last element as pivot.
 - Initialize index $i = \text{low} - 1$.
 - Traverse from low to high - 1:
 - If element $<$ pivot, increment i and swap with array[i].
 - Swap array[$i + 1$] with pivot.
 - Return $i + 1$ as pivot index.
4. Define quickSort() function:
 - If low $<$ high:
 - Call partition() to get pivot index pi .
 - Recursively call quickSort() for subarray before pivot (low to $pi - 1$).
 - Recursively call quickSort() for subarray after pivot ($pi + 1$ to high).
5. In main(), initialize the array, call quickSort(), and display the sorted array.
6. End.

4. Code:

```
#include <iostream>
using namespace std;
void swap(int &a, int &b) {
    int temp = a;
    a = b;
    b = temp;
}
int partition(int array[], int low, int high) {
    int pivot = array[high];
    int i = low - 1;
    for (int j = low; j < high; j++) {
        if (array[j] < pivot) {
            i++;
            swap(array[i], array[j]);
        }
    }
    swap(array[i + 1], array[high]);
    return i + 1;
}

void quickSort(int array[], int low, int high) {
    if (low < high) {
        int pi = partition(array, low, high);
        quickSort(array, low, pi - 1);
        quickSort(array, pi + 1, high);
    }
}

int main() {
    int data[] = {5, 2, 9, 1, 7, 3};
    int n = sizeof(data) / sizeof(data[0]);
    quickSort(data, 0, n - 1);
    for (int i = 0; i < n; i++) {
        cout << data[i] << " ";
    }
    return 0;
}
```

5. Observations:

```
1 2 3 5 7 9  
c:\Users\singh\Desktop\VS Code\CPP>
```

6. Time Complexity:

Case	Time Complexity
Best Case	$O(n \log n)$
Average Case	$O(n \log n)$
Worst Case	$O(n^2)$

7. Learning Outcome:

- ❖ Learned how to implement the Quick Sort algorithm using C++ functions.
- ❖ Understood the divide-and-conquer strategy and the role of partitioning in sorting.
- ❖ Gained practical experience in recursively sorting subarrays around a pivot.
- ❖ Strengthened understanding of array manipulation and in-place sorting techniques.
- ❖ Learned to analyze the time complexity of sorting algorithms in best, average, and worst cases.