Pizza Sales Sql queries

Postgresql

```
CREATE TABLE pizza_sales (
   pizza_id INT,
   order_id INT,
   pizza_name_id VARCHAR(50),
   quantity INT,
   order_date DATE,
   order_time TIME,
   unit_price NUMERIC(6,2),
   total_price NUMERIC(8,2),
   pizza_size VARCHAR(10),
   pizza_category VARCHAR(50),
   pizza_ingredients TEXT,
   pizza_name VARCHAR(100)
);
 select * from pizza_sales;
```

Key Performance Indicators :

-- Total Revenue

select sum(total_price) as Total_Revenue from pizza_sales;

	total_revenue numeric
1	817860.05

-- Average order value

select (sum(total_price)/ count(distinct(Order_id))) as Average_Order_Value from pizza_sales

	average_order_value numeric
1	38.3072622950819672

--Total pizza sold

select sum(quantity) as Total_pizza_sold from pizza_sales;

	total_pizza_sold bigint
1	49574

--Total orders

select count(distinct(order_id)) as Total_orders from pizza_sales;

	total_orders bigint
1	21350

-- Average pizza sold

select cast(sum(quantity) as decimal(10,2))/cast(count(distinct order_id) as decimal(10,2)) from pizza_sales

	?column? numeric
1	2.3219672131147541

Requirements :

-- Daily trends

SELECT TO_CHAR(order_date, 'Day') AS day_name,count(distinct order_id) as Total_orders FROM pizza_sales group by TO_CHAR(order_date, 'Day')

	day_name text	total_orders bigint
1	Friday	3538
2	Monday	2794
3	Saturday	3158
4	Sunday	2624
5	Thursday	3239
6	Tuesday	2973
7	Wednesday	3024

-- Montly trends

select to_char(order_date,'Month') as month_name ,count(distinct order_id) as Total_order from pizza_sales

group by to_char(order_date,'Month')

	month_name text	total_order bigint
1	April	1799
2	August	1841
3	December	1680
4	February	1685
5	January	1845
6	July	1935
7	June	1773
8	March	1840
9	May	1853
10	November	1792
11	October	1646
12	September	1661

-- Percentage of sales by pizza size

```
SELECT  pizza_size, ROUND(SUM(total_price) * 100 / (SELECT SUM(total_price) FROM pizza_sales),2) AS percentage_sales FROM pizza_sales

GROUP BY pizza_size;
```

	pizza_size character varying (10)	percentage_sales numeric
1	S	21.77
2	XXL	0.12
3	XL	1.72
4	M	30.49
5	L	45.89

--Percentage of sales by pizza category;

```
SELECT

   pizza_category,

   ROUND(SUM(total_price) * 100 / (SELECT SUM(total_price) FROM pizza_sales),2) AS percentage_sales

FROM pizza_sales

GROUP BY pizza_category;
```

	pizza_category character varying (50)	percentage_sales numeric
1	Supreme	25.46
2	Chicken	23.96
3	Veggie	23.68
4	Classic	26.91

-- Top 5 best sellers by Revenue , total quantity and total orders

```
SELECT
    pizza_name,
    SUM(total_price) AS total_revenue,
    SUM(quantity) AS total_quantity,
    COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY total_revenue DESC
LIMIT 5;
```

	pizza_name character varying (100)	total_revenue numeric	total_quantity bigint	total_orders bigint
1	The Thai Chicken Pizza	43434.25	2371	2225
2	The Barbecue Chicken Pizza	42768.00	2432	2273
3	The California Chicken Pizza	41409.50	2370	2197
4	The Classic Deluxe Pizza	38180.50	2453	2329
5	The Spicy Italian Pizza	34831.25	1924	1822

-- Top 5 least pizza sellers by Revenue , total quantity and total orders

```
SELECT
    pizza_name,
    SUM(total_price) AS total_revenue,
    SUM(quantity) AS total_quantity,
    COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales
GROUP BY pizza_name
```

ORDER BY total_revenue asc

LIMIT 5;

	pizza_name character varying (100)	total_revenue numeric	total_quantity bigint	total_orders bigint
1	The Brie Carre Pizza	11588.50	490	480
2	The Green Garden Pizza	13955.75	997	976
3	The Spinach Supreme Pizza	15277.75	950	918
4	The Mediterranean Pizza	15360.50	934	912
5	The Spinach Pesto Pizza	15596.00	970	945