

ALL TRACKS > ALGORITHMS > STRING ALGORITHMS > > PROBLEM

# Sonya and string shifts

Attempted by: 112 / Accuracy: 18% / ★★★☆

Tag(s): Medium-Hard

**PROBLEM** 

**EDITORIAL** 

**MY SUBMISSIONS** 

**ANALYTICS** 

The problem "Sonya and string shifts " doesn't have any editorial. You can contribute it by sending editorial in markdown format to moderator@hackerearth.com.

#### Author Solution by Boris Sokolov

```
1. #include <bits/stdc++.h>
 2. using namespace std;
 4. const int INF = 2e9;
 5. const int N = (int)1e6 + 9;
 6. const int alphabet = 26;
 7.
 8. char s[N];
 9. int p[N], cnt[N], c[N], pn[N], cn[N], ans[N];
10. vector<int> v[N];
11.
12. int main() {
13.
           int n;
14.
           scanf("%d\n", \&n);
15.
           gets(s);
           memset(cnt, 0, alphabet * sizeof(int));
16.
17.
           for (int i = 0; i < n; ++i) {
18.
                    ++cnt[s[i] - 'a'];
19.
20.
           for (int i = 1; i < alphabet; ++i) {</pre>
21.
                    cnt[i] += cnt[i - 1];
22.
23.
           for (int i = 0; i < n; ++i) {
24.
                    p[--cnt[s[i] - 'a']] = i;
25.
           c[p[0]] = 0;
26.
27.
           int classes = 1;
28.
           for (int i = 1; i < n; ++i) {
29.
                    if (s[p[i]] != s[p[i - 1]]) {
30.
                            ++classes;
31.
32.
                    c[p[i]] = classes - 1;
33.
           for (int h = 0; (1 << h) < h; ++h) {
```

```
for (int i = 0; i < n; ++i) {
35.
36.
                             pn[i] = p[i] - (1 << h);
37.
                             if (pn[i] < 0) {
38.
                                     pn[i] += n;
39.
                             }
40.
                    memset(cnt, 0, classes * sizeof(int));
41.
42.
                    for (int i = 0; i < n; ++i) {
                             ++cnt[c[pn[i]]];
43.
44.
                    }
45.
                    for (int i = 1; i < classes; ++i) {</pre>
46.
                             cnt[i] += cnt[i - 1];
47.
                    }
48.
                    for (int i = n - 1; i \ge 0; --i) {
49.
                             p[--cnt[c[pn[i]]]] = pn[i];
50.
51.
                    cn[p[0]] = 0;
52.
                    classes = 1;
53.
                    for (int i = 1; i < n; ++i) {
54.
                             int mid1 = (p[i] + (1 << h)) % n;
                             int mid2 = (p[i - 1] + (1 << h)) % n;
55.
                             if (c[p[i]] != c[p[i - 1]] || c[mid1] != c[mid2]) {
56.
57.
                                     ++classes;
58.
                             }
59.
                             cn[p[i]] = classes - 1;
60.
                    memcpy(c, cn, n * sizeof(int));
61.
62.
63.
           vector<int> minShifts;
           for (int i = 0; i < n; ++i) {
64.
65.
                    if (minShifts.empty() || minShifts.back() > p[i]) {
66.
                             minShifts.push_back(p[i]);
67.
                    }
68.
69.
           int q;
70.
           scanf("%d", &q);
71.
           for (int i = 0; i < q; ++i) {
72.
                    int k;
73.
                    scanf("%d", &k);
74.
                    v[k].push_back(i);
75.
76.
           int cur = INF;
77.
           for (int k = 0; k < n; ++k) {
78.
                    while (!minShifts.empty() && minShifts.back() <= k) {</pre>
79.
                             cur = minShifts.back();
80.
                             minShifts.pop_back();
81.
82.
                    for (int i = 0; i < v[k].size(); ++i) {</pre>
83.
                             ans[v[k][i]] = cur;
84.
                    }
85.
86.
           for (int i = 0; i < q; ++i) {
87.
                    printf("%d\n", ans[i]);
           }
88.
```

```
89. return 0;
90.}
```

#### **Tester Solution**

```
#include <cstdio>
#include <iostream>
#include <algorithm>
#include <vector>
#include <queue>
#include <stack>
#include <set>
#include <map>
#include <cstring>
#include <cstdlib>
#include <cmath>
#include <string>
#include <memory.h>
#include <sstream>
#include <complex>
#define REP(i,n) for(int i = 0, _n = (n); i < _n; i++)
#define REPD(i,n) for(int i = (n) - 1; i \ge 0; i--)
#define FOR(i,a,b) for (int i = (a), b = (b); i \le b; i + +)
#define FORD(i,a,b) for (int i = (a), b = (b); i \ge b; i - -)
#define FORN(i,a,b) for(int i=a;i<b;i++)</pre>
#define FOREACH(it,c) for ( typeof((c).begin()) it=(c).begin();it!=(c).end();it+
#define RESET(c,x) memset (c, x, sizeof (c))
#define sqr(x) ((x) * (x))
#define PB push_back
#define MP make pair
#define F first
#define S second
#define Aint(c) (c).begin(), (c).end()
#define SIZE(c) (c).size()
\#define\ DEBUG(x)\ \{\ cerr\ <<\ \#x\ <<\ "=" << x <<\ endl;\ \}
#define PR(a,n) {cerr<<#a<<" = "; FOR(_,1,n) cerr << a[_] << ' '; cerr <<endl;}
#define PRO(a,n) {cerr<<#a<<" = ";REP( ,n) cerr << a[ ] << ' '; cerr << endl;}
#define ll long long
using namespace std;
const double PI = 2.0 * acos (0.0);
typedef pair <int, int> PII;
#define SZ(x) ((int)(x.size()))
#define maxn 2000009
#define maxlogn 22
```

```
string s;
int n;
int sa[maxn],tam[maxn],inv[maxn],key[maxn],lcp[maxn],posa[maxn],myrank[maxn];
int rmq[maxn][maxlogn],LOG[maxn];
int ans[maxn];
void initSA() {
    int i,h,x;
    memset(tam, 0, sizeof(tam));
    FOR(i,1,n) tam[s[i]]++;
    FOR(i,1,256) tam[i] += tam[i-1];
    cout << n << " done" << endl;</pre>
    FORD(i,n,1) sa[tam[s[i]]--] = i;
    x = 0;
    posa[0] = 1;
    key[sa[1]] = 0;
    FOR(i,2,n) {
         if (s[sa[i]] != s[sa[i-1]]) posa[++x] = i;
         key[sa[i]] = x;
    }
    h = 1;
    while (h < n) {
         FOR(i,1,n) tam[i]=sa[i];
         FOR(i,1,n) if (tam[i] > h) {
             x = tam[i] - h;
              sa[posa[key[x]]] = x;
              posa[key[x]]++;
         }
         x = 0;
         posa[0] = 1;
         tam[sa[1]] = 0;
         FOR(i,2,n) {
              if ((key[sa[i-1]] < key[sa[i]]) || ((key[sa[i-1]] == key[sa[i]]) &&</pre>
                  posa[++x] = i;
              tam[sa[i]] = x;
         FOR(i,1,n) key[i] = tam[i];
         if (x == n-1) break;
         h = h << 1;
    }
    FOR(i,1,n) myrank[sa[i]]=i;
}
void initLCP() {
    int i,j,h = 0,x;
    s[n + 1] = 0;
    int result = 0;
    FOR(i,1,n) inv[sa[i]] = i;
    FOR(i,1,n)
         if (inv[i] == 1) lcp[1] = 0;
```

```
else {
              x = inv[i];
              j = sa[x - 1];
              while (s[j + h] == s[i + h]) h++;
              lcp[x] = h;
              if (h > 0) h--;
         }
}
void initRMQ() {
    LOG[1]=0;
    FOR(i,2,n) if((1 << (LOG[i-1]+1))==i) LOG[i]=LOG[i-1]+1; else LOG[i]=LOG[i-1];
    FOR(i,1,n) rmq[i][0]=lcp[i];
    FOR(j,1,LOG[n]) {
         FOR(i,1,n-(1<< j)+1) {
              rmq[i][j]=min(rmq[i][j-1],rmq[i+(1<<(j-1))][j-1]);
         }
    }
}
int getRMQ(int x,int y) {
    int len=LOG[y-x+1];
    return min(rmq[x][len],rmq[y-(1<<len)+1][len]);</pre>
}
int getLCP(int x,int y) {
    x=myrank[x];
    y=myrank[y];
    if(x==y) return n-x+1;
    if(x>y) swap(x,y);
    return getRMQ(x+1,y);
}
int main() {
    ios_base::sync_with_stdio(0);
    int N,q;
    cin >> N >> s >> q;
    S = " " + S;
    n=s.length();
    initSA();
    initLCP();
    initRMQ();
    int curind=1,curmin=inv[1];
    for(int i=2; i<=N; i++){</pre>
         if(inv[i]<curmin){</pre>
              if(getLCP(inv[i], curmin) < N)</pre>
                   curind=i,curmin=inv[i];
```

```
ans[i]=curind;
    for(int i=0; i<q; i++){
         int x;
         cin >> x;
         printf("%d\n", max(0, ans[x+1]-1));
    }
}
```

## COMMENTS (2) 2

SORT BY: Relevance▼



Join Discussion...

Cancel

Post



SHUBHAM PANDEY 5 months ago

please explain something this code dosen't mean anything

▲ 0 votes • Reply • Message • Permalink



Prakhar Agrawal 4 months ago

How can we submit the editorial for the above question?

▲ 0 votes • Reply • Message • Permalink

#### **ABOUT US**

Blog

**Engineering Blog** 

Updates & Releases

Team

Careers

In the Press

#### **HACKEREARTH**

API

Chrome Extension

CodeTable

HackerEarth Academy

Developer Profile

Resume

Get Badges

Campus Ambassadors

#### **DEVELOPERS**

**AMA** 

Code Monk

Judge Environment

Solution Guide

Problem Setter Guide

Practice Problems

HackerEarth Challenges

College Challenges

Get Me Hired College Ranking

Privacy Organise Hackathon

Terms of Service Hackathon Handbook

Competitive Programming

Open Source

### **EMPLOYERS**

**Developer Sourcing** 

Lateral Hiring

Campus Hiring

Hackathons

**FAQs** 

Customers

#### **REACH US**



Illrd Floor, Salarpuria Business Center, 4th B Cross Road, 5th A Block, Koramangala Industrial Layout, Bangalore, Karnataka 560095, India.

contact@hackerearth.com

**\( +91-80-4155-4695** 

**\** +1-650-461-4192











© 2016 HackerEarth