



ALL TRACKS > ALGORITHMS > STRING ALGORITHMS > > PROBLEM

4

LIVE EVENTS

Unique Gems

Attempted by: 170 / Accuracy: 76% / ★★★★★

Tag(s): Algorithms, Hard, Suffix Arrays

PROBLEM

EDITORIAL

MY SUBMISSIONS

ANALYTICS

Setter's solution:

We need to count the number of substrings that occur exactly once.

This can be formulated as the number of substrings occurring ≥ 1 times - number of substrings occurring ≥ 2 times.

The former is simply the number of distinct substrings.

The latter can be solved by observing the lcp array in detail.

IS THIS EDITORIAL HELPFUL?



Yes, it's helpful



No, it's not helpful

7 developer(s) found this editorial helpful.

Author Solution by [Ankit Srivastava](#)

```
t) {
```

```
| c == -1;
```



```
eamWriter(outputStream));
```

```
At(o2));
```

len characters
first len characters

the end of the string
ollowed by 0-symbol
 && sa[i - 1] + len < n && r[sa[i - 1] + len / 2] == r[sa[i] + len / 2] ? rank[sa
 's

characters
by second len characters
e already sorted

```
At(i + h) == s.charAt(j + h)) {
```

Tester Solution

```
1. #include <cstdio>
2. #include <cmath>
3. #include <iostream>
4. #include <set>
5. #include <algorithm>
6. #include <vector>
7. #include <map>
8. #include <cassert>
9. #include <string>
10. #include <cstring>
11. #include <queue>
12.
13. using namespace std;
14.
15. #define rep(i,a,b) for(int i = a; i < b; i++)
16. #define S2(x,y) scanf("%d%d",&x,&y)
17. #define P(x) printf("%d\n",x)
18. #define all(v) v.begin(),v.end()
19. #define sz size()
20. #define F first
21. #define S second
22.
23. typedef long long int LL;
24. typedef pair<int, int > pii;
25. typedef vector<int > vi;
26.
27. const int N = 100001;
28.
```

```

29. string s;
30. vector<pii > ranks;
31.
32. pair<int, pii > v[N];
33. int tag[N][22];
34. int mxPow;
35. int n;
36.
37. void buildSA(string &s) {
38.     n = s.sz;
39.     rep(i,0,n) {
40.         v[i].F = s[i] - 'a' + 1;
41.         v[i].S.F = -1;
42.         v[i].S.S = i;
43.         tag[i][0] = v[i].F;
44.     }
45.
46.     int len = 1;
47.     int j = 0;
48.     while(len < n) {
49.         len += len;
50.         j++;
51.
52.         rep(i,0,n) {
53.             v[i].F = tag[i][j-1];
54.             if(i+len/2 < n) v[i].S.F = tag[i+len/2][j-1];
55.             else v[i].S.F = -1;
56.             v[i].S.S = i;
57.         }
58.         sort(v, v+n);
59.
60.         int tagId = 1;
61.         tag[v[0].S.S][j] = 1;
62.         rep(i,1,n) {
63.             if(v[i].F != v[i-1].F || v[i].S.F != v[i-1].S.F) {
64.                 tagId++;
65.             }
66.             tag[v[i].S.S][j] = tagId;
67.         }
68.     }
69.     mxPow = j;
70. }
71.
72. int lcp(int x, int y) {
73.
74.     int res = 0;
75.     for(int i = mxPow; i >= 0; i--) {
76.         if(tag[x][i] == tag[y][i]) {
77.             res += 1 << i;
78.             x += 1 << i;
79.             y += 1 << i;
80.         }
81.         if(x >= n || y >= n) break;
82.     }

```

```
83.         return res;
84.     }
85.
86. int main() {
87.     int t;
88.     cin >> t;
89.     assert(t >= 1 && t <= 10);
90.     while(t--) {
91.         cin >> s;
92.         buildSA(s);
93.         int n = s.sz;
94.         assert(n > 0 && n <= 100000);
95.
96.         ranks.clear();
97.         rep(i,0,n) {
98.             ranks.push_back(make_pair(tag[i][mxPow], i));
99.         }
100.        // P(ranks.sz);
101.        sort(all(ranks));
102.
103.        // cout << s << endl;
104.        // rep(i,0,n) printf("%d %d\n",ranks[i].F, ranks[i].S);
105.        // P(mxPow);
106.
107.        LL ans = 0;
108.        rep(i,0,n) {
109.            int mx = 0;
110.            if(i-1 >= 0) mx = max(mx, lcp(ranks[i-1].S, ranks[i].S);
111.            if(i+1 < n) mx = max(mx, lcp(ranks[i+1].S, ranks[i].S);
112.            // P(mx);
113.
114.            ans += n - ranks[i].S - mx;
115.        }
116.        cout << ans << endl;
117.    }
118.    return 0;
119. }
```

ABOUT US

Blog

Engineering Blog

Updates & Releases

HACKEREARTH

API

Chrome Extension

CodeTable

DEVELOPERS

AMA

Code Monk

Judge Environment

[Team](#)
[Careers](#)
[In the Press](#)

[HackerEarth Academy](#)
[Developer Profile](#)
[Resume](#)
[Get Badges](#)
[Campus Ambassadors](#)
[Get Me Hired](#)
[Privacy](#)
[Terms of Service](#)

[Solution Guide](#)
[Problem Setter Guide](#)
[Practice Problems](#)
[HackerEarth Challenges](#)
[College Challenges](#)
[College Ranking](#)
[Organise Hackathon](#)
[Hackathon Handbook](#)
[Competitive Programming](#)
[Open Source](#)

EMPLOYERS

[Developer Sourcing](#)
[Lateral Hiring](#)
[Campus Hiring](#)
[Hackathons](#)
[FAQs](#)
[Customers](#)

REACH US



IIIrd Floor, Salarpuria Business Center,
4th B Cross Road, 5th A Block,
Koramangala Industrial Layout,
Bangalore, Karnataka 560095, India.

✉ contact@hackerearth.com

☎ +91-80-4155-4695

☎ +1-650-461-4192



© 2016 HackerEarth