```
int fourthBit(int number)
 1
 2
3 √ {
 4
   int binary[32];
 5
   int i=0;
 6
    while(number>0)
 7
8 + {
    binary[i]=number%2;
 9
   number/=2;
10
11
   i++;
12
13
   if(i>=4)
14 ▼ {
15 | return binary[3];
```

```
11   i++;
12  }
13   if(i>=4)
14  {
15   return binary[3];
16  }
17   else
18   return 0;
19  }
```

	Test	Expected	Got	
<b>~</b>	<pre>printf("%d", fourthBit(32))</pre>	0	0	~
~	<pre>printf("%d", fourthBit(77))</pre>	1	1	~

```
Troug brusacroi (Toug ii, Toug b)
 2
3 ⋅ {
 5
   int count=0;
   for(long i=1;i<=n;++i)</pre>
 6
 7 ▼ {
   if(n%i==0)
 8
9 ₹ {
7 ▼ {
   if(n%i==0)
8
9 🕶 {
10 | count++;
   if(count==p)
11
12 √ {
13
   return i;
14
15
13
   return i;
14
15
   }
16
17 return 0;
```

	Test	Expected	Got	
~	<pre>printf("%ld", pthFactor(10, 3))</pre>	5	5	~
~	<pre>printf("%ld", pthFactor(10, 5))</pre>	0	0	~
~	<pre>printf("%ld", pthFactor(1, 1))</pre>	1	1	<b>~</b>

```
int myFunc(int n)
 1
2 * {
3
   while(n%10==0||n%20==0)
4 √ {
5
   if(n%20==0)
6 ▼ {
 7
   n/=20;
8
9 v else{
10
    n/=10;
11
12
13
    return n==1?1:0;
14
```

	Test	Expected	Got	
~	<pre>printf("%d", myFunc(1))</pre>	1	1	~
~	<pre>printf("%d", myFunc(2))</pre>	0	0	~
~	<pre>printf("%d", myFunc(10))</pre>	1	1	~
~	printf("%d", myFunc(25))	0	0	~
~	<pre>printf("%d", myFunc(200))</pre>	1	1	~

```
int powerSum(int x, int m, int n)
 2
 3 ▼
    {
 4
         int p=pow(m,n);
 5
         if (p==x)
 6 🕶
 7
             return 1;
 8
 9
         if(p>x)
10 ⋅
             return 0;
11
12
    return powerSum(x-p,m+1,n)+powerSum(x,m+1,n);
13
14
   }
```

	Test	Expected	Got	
~	printf("%d", powerSum(10, 1, 2))	1	1	<b>~</b>

Passed all tests! 🗸