```
2
 3
    #include<string.h>
 4
 5
     int main()
 6 ▼
    {
     char str1[1000000], str2[1000000];
 7
     int flag=1;
 8
    scanf("%s",str1);
scanf("%s",str2);
 9
10
    int a=strlen(str1);
11
    int b=strlen(str2);
12
    lif(a==b)
13
```

```
16 ▼ {
    while(str1[i]!=str2[i])
17
18 ▼ {
19
    for(int j=0; j<=i; j++)
20 ▼ {
21
    if(str1[j]<'z')</pre>
22
    str1[j]++;
23
    else
24 🔻
25
    flag=0;
26
    break;
27
28
    if(flag==0)
29
    break;
30
    }
```

```
29
    break;
30
    }
    }
31
32
    }
    }
33
34
    else
35
    flag=0;
36
    if(flag==0)
37
    printf("NO");
38
    else
    printf("YES");
39
40
    return 0;
41
    }
```

	Input	Expected	Got	
~	abaca cdbda	YES	YES	~

Passed all tests! ✓

```
2
3
    #include<string.h>
4
5
    int main()
6 ₹ {
7
    int n,flag=0;
8
    char temp;
    scanf("%d",&n);
9
   char words[n][14];
10
    for(int i=0;i<n;i++)</pre>
11
   scanf("%s",words[i]);
12
```

```
15
   {strcpy(reverse,words[i]);
16
    int size=strlen(reverse);
17
18
19
    for(int k=0;k<size/2;k++)</pre>
20 ▼ {
21
    temp=reverse[k];
    reverse[k]=reverse[size-k-1];
22
23
    reverse[size-k-1]=temp;
24
25
    for(int j=i+1;j<n;j++)</pre>
26 ▼ {
    if(strcmp(reverse,words[j])==0)
27
20
```

```
break;
30
31
    }
32
   if(flag==1)
33
34
    break;
35
36
    int len=strlen(reverse);
    printf("%d %c ",len,reverse[len/2]);
37
38
    return 0;
39
   }
```

Input	Expected	Got	
4 abc def feg cba	3 b	3 b	

Passed all tests! <

```
#include<stdio.h>
 1
 2
 3
    #include<string.h>
 4
 5
    int main()
6 → {
 7
   int n;
 8
    scanf("%d",&n);
9
    char res[n][21];
10
    int rate[n];
11
    for(int i=0;i<n;i++)
12 🗸 | {
13
    scanf("%s",res[i]);
    scanf("%d",&rate[i]):
14
15
```

```
scant("%q",&rate[1]);
14
15
16
    int max=rate[0];
17
    char ans[20];
18
    strcpy(ans,res[0]);
19
    for(int i=1;i<n;i++)</pre>
20 → {
21
    if(rate[i]>max)
22 ▼ {
23
    max=rate[i];
24
    strcpy(ans,res[i]);
25
26
    else if(rate[i]==max)
```

```
26  else if(rate[i]==max)
27  {
28   if(strcmp(res[i],ans)<0)
29   strcpy(ans,res[i]);
30  }
31  }
32  printf("%s",ans);
33  return 0;}</pre>
```

	Input	Expected Got	
~	3 Pizzeria 108 Dominos 145 Pizzapizza 4	Dominos Dominos	~

Passed all tests! 🗸

```
2
3
    #include<string.h>
4
5
    int main()
6 ▼ {
7
   int t;
8
    scanf("%d",&t);
9
    while(t--)
10 √ {
11
    int flag=1;
12
    char s[100000];
13
   scanf("%s",s);
14
   int bectuland
```

```
16 ▼ {
17
    for(int i=0;i<10;i++)
18 → {
19
    if(s[0]=='0')
20 ₹ {
21
    flag=0;
22
    break;
23
    }
24
    if(s[i]<'0'||s[i]>'9')
25 ▼ {
26
    flag=0;
27
    break;
28
29
   1}
```

```
else
31
    flag=0;
32
    if(flag==1)
33
    printf("YES\n");
34
    else
35
    printf("NO\n");
36
37
    return 0;
38
39
   }
```

	Input	Expected	Got	
~	3	YES	YES	~
	1234567890	NO	NO	
	0123456789	NO	NO	
	0123456.87			

Passed all tests! 🗸