Rajalakshmi Engineering College

Name: GOUTHAM R

Email: 240801088@rajalakshmi.edu.in

Roll no: 240801088 Phone: 8531871809

Branch: REC

Department: I ECE FA

Batch: 2028

Degree: B.E - ECE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

240801088

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

Output Format

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 4
1 2 3 4
5
Output: Data entered in the list:
node 1 : 1
node 2 : 2
node 3 : 3
node 4 : 4
Invalid position. Try again.

Answer

void DIListcreation(int n) {
int i, num;
struct node *fnNode;
```

```
if (n >= 1) {
    stnod
        stnode = (struct node *)malloc(sizeof(struct node));
        if (stnode == NULL) {
           printf("Memory allocation failed.\n");
           return;
        }
        scanf("%d", &num);
         stnode->num = num;
        stnode->preptr = NULL;
        stnode->nextptr = NULL;
         ennode = stnode;
        for (i = 2; i \le n; i++) {
           fnNode = (struct node *)malloc(sizeof(struct node));
           scanf("%d", &num);
           fnNode->num = num;
           fnNode->preptr = ennode;
           fnNode->nextptr = NULL;
           ennode->nextptr = fnNode;
           ennode = fnNode;
    void DIListDeleteFirstNode() {
      if (stnode == NULL) return;
      struct node *toDelete = stnode;
      stnode = stnode->nextptr;
      if (stnode != NULL)
         stnode->preptr = NULL;
      free(toDelete);
if (ennode == NULL) return;
    void DlListDeleteLastNode() {
```

```
240801088
ennode = ennode->preptr;
       struct node *toDelete = ennode;
      if (ennode != NULL)
         ennode->nextptr = NULL;
      else
         stnode = NULL:
      free(toDelete);
    void DIListDeleteAnyNode(int pos) {
      int i:
      struct node *toDelete;
      if (pos == 1) {
         DlListDeleteFirstNode();
         return;
      toDelete = stnode;
      for (i = 1; i < pos && toDelete != NULL; i++) {
         toDelete = toDelete->nextptr;
      }
      if (toDelete == NULL) return;
                                                      240801088
      if (toDelete->nextptr == NULL) {
         DlListDeleteLastNode();
         return:
      toDelete->preptr->nextptr = toDelete->nextptr;
      toDelete->nextptr->preptr = toDelete->preptr;
      free(toDelete);
    }
    void displayDlList(int mode) {
      struct node *tmp;
      int nodeNumber = 1;
if (mode == 1)
printf("D-
         printf("Data entered in the list:\n");
```

240801088

240801088

240801088

```
240801088
                                                                           240801088
       else
         printf("After deletion the new list:\n");
      tmp = stnode;
       while (tmp != NULL) {
         printf("node %d: %d\n", nodeNumber, tmp->num);
         nodeNumber++;
        tmp = tmp->nextptr;
      }
    }
    Status: Correct
                                                                    Marks: 10/10
                                                                           240801088
240801088
                         240801088
```

240801088

240801088

240801088

240801088

240801088

240801088

240801088

240801088