

◆ Problem Statement (Simple Words)

You are given a string s consisting only of characters 'L' and 'R'.

A string is called **balanced** if:

Number of 'L' == Number of 'R'

Your task is to **split the string into the maximum number of balanced substrings** and return that count.

□ Example

Input: $s = \text{"RLRLLRLRL"}$

Output: 4

Possible splits:

"RL" | "RRL" | "RL" | "RL"

Each substring has equal 'L' and 'R'.

● APPROACH 1: Using TWO Counters (Lcount & Rcount)

💡 Idea

- Traverse the string
 - Count 'L' and 'R' separately
 - Whenever $Lcount == Rcount$, one balanced string is formed
-

□ Dry Run (Step by Step)

Input

$s = \text{"RLRLLRLRL"}$

Index Char Lcount Rcount Balanced? Result

0	R	0	1	✗	0
1	L	1	1	✓	1
2	R	1	2	✗	1
3	R	1	3	✗	1
4	L	2	3	✗	1

Index Char Lcount Rcount Balanced? Result

5	L	3	3	✓	2
6	R	3	4	✗	2
7	L	4	4	✓	3
8	R	4	5	✗	3
9	L	5	5	✓	4

✓ **Final Answer = 4**

Complexity

- **Time:** $O(n)$
- **Space:** $O(1)$

Code – TWO Counter Approach

C++

```
class Solution {
public:
    int balancedStringSplit(string s) {
        int L = 0, R = 0, result = 0;

        for (char c : s) {
            if (c == 'L') L++;
            else R++;

            if (L == R) result++;
        }
        return result;
    }
};
```

Java

```
class Solution {  
    public int balancedStringSplit(String s) {  
        int L = 0, R = 0, result = 0;  
  
        for (char c : s.toCharArray()) {  
            if (c == 'L') L++;  
            else R++;  
  
            if (L == R) result++;  
        }  
        return result;  
    }  
}
```

Python

```
class Solution:  
    def balancedStringSplit(self, s: str) -> int:  
        L = R = result = 0  
  
        for c in s:  
            if c == 'L':  
                L += 1  
            else:  
                R += 1  
  
            if L == R:  
                result += 1  
  
        return result
```

□ APPROACH 2: Using ONE Counter (Optimized)

💡 Key Observation

- Treat 'L' as **+1**
 - Treat 'R' as **-1**
 - When counter becomes **0**, a balanced string is found
-

🔍 Dry Run (One Counter)

Index Char Count Balanced? Result

0	R	-1	✗	0
1	L	0	✓	1
2	R	-1	✗	1
3	R	-2	✗	1
4	L	-1	✗	1
5	L	0	✓	2
6	R	-1	✗	2
7	L	0	✓	3
8	R	-1	✗	3
9	L	0	✓	4

✓ Final Answer = 4

🕒 Complexity

- Time: $O(n)$
 - Space: $O(1)$ ✓ (best)
-

💻 Code – ONE Counter Approach (Recommended)

C++

```
class Solution {  
public:  
    int balancedStringSplit(string s) {
```

```
int count = 0, result = 0;

for (char c : s) {
    if (c == 'L') count++;
    else count--;

    if (count == 0) result++;
}

return result;
};
```

Java

```
class Solution {
    public int balancedStringSplit(String s) {
        int count = 0, result = 0;

        for (char c : s.toCharArray()) {
            if (c == 'L') count++;
            else count--;

            if (count == 0) result++;
        }

        return result;
    }
}
```

Python

```
class Solution:
    def balancedStringSplit(self, s: str) -> int:
        count = result = 0
```

```
for c in s:
    count += 1 if c == 'L' else -1
    if count == 0:
        result += 1

return result
```

Final Comparison

Approach	Variables	Space	Interview
----------	-----------	-------	-----------

Two Counters L & R	$O(1)$	Good
--------------------	--------	------

One Counter Single	$O(1)$	★ Best
--------------------	--------	--------