



# NEXUS INTERVIEW GUIDE

BY DEVOPS SHACK

---

## DevOps Shack

# 200 Real Time Nexus Artifact Management Interview Questions and Answers

1. **What is Nexus Repository Manager?**
  - **Answer:** Nexus is a repository manager used for storing, managing, and accessing artifacts required for development and deployment. It supports multiple formats like Maven, npm, Docker, etc.
2. **Differentiate between Nexus OSS and Nexus Pro.**
  - **Answer:** OSS is the open-source version with basic features. Pro includes advanced features like staging, procurement, and security integrations.
3. **What are the types of repositories in Nexus?**
  - **Answer:** Nexus supports:
    - Hosted Repository: Stores artifacts locally.
    - Proxy Repository: Caches artifacts from remote repositories.
    - Group Repository: Aggregates multiple repositories.
4. **What formats does Nexus support?**
  - **Answer:** Nexus supports Maven, npm, Docker, PyPI, NuGet, RubyGems, and more.
5. **What is a proxy repository?**
  - **Answer:** A proxy repository caches dependencies from a remote repository (e.g., Maven Central) for faster and reliable access.



---

**6. How would you configure a proxy repository for Maven Central in Nexus?**

- **Answer:** Navigate to Repositories, create a new proxy repository, provide the remote URL (<https://repo1.maven.org/maven2>), and set a suitable name.

**7. What steps would you follow to create a hosted Docker repository?**

- **Answer:** Go to Repositories, create a new hosted repository, select Docker (hosted), configure the HTTP port, and set the desired write/read permissions.

**8. Explain how you would aggregate multiple repositories into a group repository.**

- **Answer:** Use the group repository option in Nexus. Select repositories to include, set the order of priority, and give the group a name.

**9. How would you handle the disk space issue in Nexus?**

- **Answer:** Use repository clean-up policies, enable blob storage compaction, and configure retention rules for old artifacts.

**10. How do you migrate repositories from Nexus OSS to Nexus Pro?**

- **Answer:** Use the [Backup/Restore](#) feature or export repositories using Nexus CLI, then import them into the Pro version.

**11. How do you create a new role in Nexus?**

- **Answer:** Go to Roles, create a new role, assign permissions like repository read/write access, and assign users/groups.

**12. What are content selectors in Nexus?**

- **Answer:** Content selectors are used to define fine-grained access to specific paths or artifacts in repositories.

**13. How would you set up LDAP authentication in Nexus?**

- **Answer:** Go to Security → Realms, configure LDAP settings like server URL, bind credentials, and user base DN.

#### 14. How do you secure your Nexus instance?

- **Answer:**
  - Use HTTPS.
  - Enable firewall rules.
  - Restrict anonymous access.
  - Regularly update Nexus.
  - Use strong admin passwords.

#### 15. How would you audit who uploaded/deleted an artifact?

- **Answer:** Enable Audit Logs under System, where actions are logged with details of users and timestamps.

#### 16. How do you optimize Nexus performance for large artifact repositories?

- **Answer:**
  - Use blob stores.
  - Configure caching for proxy repositories.
  - Increase JVM memory.
  - Archive unused repositories.

#### 17. What would you do if Nexus slows down due to high CPU usage?

- **Answer:** Analyze logs for long-running tasks, optimize database connections, and clear old Nexus tasks.

#### 18. How do you manage Nexus blob storage efficiently?

- **Answer:** Use multiple blob stores based on repository needs, and schedule compaction tasks to remove unused blobs.

#### 19. How do you configure Maven to use Nexus for dependency resolution?

- **Answer:** Update the `settings.xml` file with the Nexus repository URL under `<repositories>` and `<pluginRepositories>` tags.



---

**20. How would you integrate Nexus with Jenkins for artifact publishing?**

- **Answer:** Use Jenkins plugins like Pipeline Maven Integration or Nexus Artifact Uploader, configure repository credentials, and define pipeline scripts for artifact deployment.

**21. Explain the process of deploying Docker images to Nexus from a CI/CD pipeline.**

- **Answer:**
  - Create a Docker (hosted) repository in Nexus.
  - Configure `docker login` with Nexus credentials.
  - Use `docker push` in the pipeline to upload images.

**22. What happens if the Jenkins build fails to upload an artifact to Nexus?**

- **Answer:**
  - Check credentials in Jenkins.
  - Ensure the repository is accessible.
  - Verify the artifact does not already exist (depending on overwrite policy).

**23. What would you do if a proxy repository fails to fetch artifacts?**

- **Answer:**
  - Check remote repository URL.
  - Ensure network connectivity.
  - Review Nexus logs for proxy errors.

**24. Artifacts are not visible after deployment. What could be the issue?**

- **Answer:**
  - Ensure correct repository.
  - Check for permission issues.
  - Verify the artifact upload logs.

**25. How would you troubleshoot `HTTP 401 Unauthorized` errors when accessing a repository?**

- **Answer:** Verify user credentials, check permission assignments, and ensure the `Anonymous Access` is configured appropriately.

## 26. What steps would you take if Nexus is not starting?

- **Answer:**
  - Review logs in `nexus.log`.
  - Check Java version compatibility.
  - Ensure sufficient system resources.

## 27. How does Nexus handle artifact versioning and retention?

- **Answer:** Nexus uses clean-up policies to remove older versions of artifacts based on defined criteria like age or quantity.

## 28. How do you set up a high-availability Nexus cluster?

- **Answer:** Nexus Pro supports clustering using OrientDB for data replication. Configure the `orientdb-server-config.xml` file for HA.

## 29. Explain Nexus API usage for automating repository management.

- **Answer:** Use the Nexus REST API for tasks like creating repositories, managing users, and automating artifact uploads.

## 30. How does Nexus handle artifact conflict resolution in a group repository?

- **Answer:** Nexus resolves artifacts based on repository order within the group.

## 31. What is the default admin username for Nexus Repository Manager?

- **Answer:** The default admin username is `admin`, and the password is stored in the `admin.password` file located in the Nexus data directory.

## 32. What is the purpose of the Nexus Cleanup Policies?

- **Answer:** Cleanup Policies help to manage and delete old or unused artifacts to save disk space.



### 33. What is the difference between a hosted and proxy repository?

- **Answer:** A hosted repository is used to store internal or locally created artifacts, while a proxy repository caches artifacts from remote repositories.

### 34. How do you check the Nexus version you are using?

- **Answer:** Go to **System** → **Support** → **System Information** or check the version in the `nexus.log` file.

### 35. What is the default port on which Nexus runs?

- **Answer:** Nexus runs on port `8081` by default.

### 36. How would you configure a Nexus repository for npm packages?

- **Answer:**
  - Create an npm (hosted) repository for internal packages.
  - Create an npm (proxy) repository for npmjs.org.
  - Create a group repository combining the two and configure `.npmrc` to use the group repository URL.

### 37. How do you set up HTTPS for Nexus?

- **Answer:** Generate a keystore, configure the `jetty-https.xml` file in the Nexus configuration directory, and restart Nexus.

### 38. How can you automate repository creation in Nexus?

- **Answer:** Use the Nexus REST API or scripting feature in Nexus Pro to automate repository creation.

### 39. Explain the use of Blob Stores in Nexus.

- **Answer:** Blob Stores manage storage for artifacts in Nexus. You can create multiple blob stores for better organization and performance.



#### 40. How do you create a Maven snapshot repository in Nexus?

- **Answer:**
  - Create a hosted repository.
  - Select the Maven 2 format and enable the "Allow Redeploy" option.
  - Use the naming convention `*-snapshots`.

#### 41. How does Nexus handle artifact metadata?

- **Answer:** Nexus generates and manages metadata for Maven repositories, such as `maven-metadata.xml`, to track artifact versions and dependencies.

#### 42. How would you monitor and manage Nexus logs?

- **Answer:** Use the Nexus UI under **Administration** → **Support** → **Logs** or access log files directly in the `/sonatype-work/nexus3/log` directory.

#### 43. What are the different tasks available in Nexus?

- **Answer:** Examples include:
  - Compact blob store.
  - Purge unused components.
  - Rebuild repository index.
  - Rebuild metadata.

#### 44. How would you configure Nexus to store Docker images securely?

- **Answer:**
  - Set up a Docker (hosted) repository.
  - Configure HTTPS and enable authentication.
  - Use repository-level roles for access control.





**45. What would you do if you encounter a 404 Not Found error when accessing a repository?**

- **Answer:**
  - Verify the repository URL.
  - Check if the repository is enabled and has components.
  - Review proxy configuration for remote repositories.

**46. How do you configure cleanup policies for a Maven repository?**

- **Answer:** Define criteria such as artifact age or snapshot retention under **Administration** → **Repository** → **Cleanup Policies**, and apply the policy to the repository.

**47. How does Nexus handle multiple versions of the same artifact?**

- **Answer:** It retains versions based on repository settings and clean-up policies. For snapshots, only the latest versions are retained unless configured otherwise.

**48. What is staging in Nexus Pro, and how is it used?**

- **Answer:** Staging allows you to deploy artifacts to a temporary repository for validation before promoting them to production.

**49. Explain the concept of repository routing rules in Nexus.**

- **Answer:** Routing rules define which requests are allowed or blocked for a repository, improving performance and security.

**50. How would you integrate Nexus with HashiCorp Vault for secret management?**

- **Answer:** Use Vault to manage credentials and configure Nexus to fetch secrets dynamically using the Vault API or an integration plugin.

**51. How would you handle a failed repository index rebuild?**

- **Answer:**
  - Check Nexus logs for errors.



- Ensure sufficient disk space.
- Retry the task after resolving issues.

## 52. How would you migrate artifacts from Nexus OSS to Artifactory?

- **Answer:** Export artifacts from Nexus using a repository export feature or API and import them into Artifactory using the JFrog CLI.

## 53. What are the best practices for organizing repositories in Nexus?

- **Answer:**
  - Separate repositories by project or team.
  - Use group repositories for common access.
  - Apply clean-up policies to manage storage.

## 54. How do you analyze slow artifact downloads from Nexus?

- **Answer:**
  - Check network latency.
  - Review proxy repository cache settings.
  - Increase repository worker threads.

## 55. What would you do if the Nexus UI becomes unresponsive?

- **Answer:**
  - Check JVM memory usage.
  - Analyze system logs.
  - Restart the service and increase JVM heap size if necessary.

## 56. How would you configure Nexus for artifact upload in GitLab CI?

- **Answer:**
  - Use GitLab CI scripts with Nexus credentials.
  - Configure the `curl` or `mvn deploy` command for uploading artifacts.



**57. Explain how Nexus integrates with Kubernetes for artifact management.**

- **Answer:** Deploy Nexus as a container in Kubernetes, expose it via an ingress controller, and use it to manage container images and Helm charts.

**58. How do you use Nexus with Terraform?**

- **Answer:** Store Terraform modules in a Nexus repository and configure Terraform to pull modules using a repository URL.

**59. What is the role of Nexus in a microservices architecture?**

- **Answer:** Nexus manages container images, Helm charts, and dependencies for microservices, ensuring consistency across builds and deployments.

**60. How do you ensure high availability of Nexus in a production environment?**

- **Answer:**
  - Use clustering with Nexus Pro.
  - Set up a load balancer.
  - Use shared blob storage.

**61. How do you configure Nexus for multiple regions?**

- **Answer:** Use multiple Nexus instances in different regions with replication enabled or set up a central Nexus with optimized proxy repositories.

**62. Explain Nexus's capability for artifact tagging.**

- **Answer:** Nexus allows tagging of artifacts for easier categorization and retrieval. Tags can be applied via the UI or API.

**63. How would you handle concurrent artifact uploads causing conflicts?**

- **Answer:** Enable staging repositories or configure Nexus to overwrite existing artifacts.

**64. What would you do if Nexus fails to start after an upgrade?**

- **Answer:**



- Check compatibility with the existing database and JVM.
- Review logs for errors.
- Roll back to the previous version if necessary.

#### 65. How do you automate artifact promotion in Nexus?

- **Answer:** Use the Nexus REST API or scripting with custom logic to promote artifacts between repositories.

#### 66. How can you access Nexus Repository Manager logs?

- **Answer:** Logs are accessible via the UI under **Administration** → **Support** → **Logs** or in the `nexus.log` file located in the Nexus data directory.

#### 67. What are Nexus repository cleanup policies used for?

- **Answer:** They are used to define rules for automatically removing older or unused artifacts to save storage space.

#### 68. What is the difference between Snapshot and Release repositories?

- **Answer:**
  - **Snapshot:** Stores artifacts under development; version changes frequently.
  - **Release:** Stores stable versions for production use; version does not change.

#### 69. How can you reset the Nexus admin password?

- **Answer:** Delete the `admin.password` file in the Nexus data directory. On restart, a new default password will be generated.

#### 70. How can Nexus act as a private Docker registry?

- **Answer:** Nexus supports Docker repositories. It can store, manage, and serve container images for private use.



### 71. How would you configure an npm proxy repository in Nexus?

- **Answer:**
  1. Go to **Repositories** → **Create Repository**.
  2. Select npm (proxy).
  3. Configure the remote URL (`https://registry.npmjs.org/`) and save the repository.

### 72. What are Nexus Repository Lifecycle Policies?

- **Answer:** Lifecycle policies automate actions like promoting, releasing, or cleaning up artifacts based on criteria.

### 73. How do you backup and restore a Nexus repository?

- **Answer:** Use the **Backup/Restore** feature under **Administration** → **System** → **Backup/Restore**, or manually back up the `sonatype-work` directory.

### 74. How would you troubleshoot repository connection errors in Nexus?

- **Answer:**
  - Verify the remote repository URL.
  - Check network/firewall rules.
  - Analyze Nexus logs for specific errors.

### 75. Explain the process of artifact version promotion in Nexus.

- **Answer:** Artifacts can be promoted from a staging repository to a release repository using either the UI or Nexus API.

### 76. How do you configure Nexus as a Helm chart repository?

- **Answer:**
  1. Create a new hosted Helm repository in Nexus.
  2. Push Helm charts using `helm push` or upload them via the UI.
  3. Use the repository URL in your `helm repo add` command.



---

**77. What are NXRM scripts, and how are they used?**

- **Answer:** NXRM (Nexus Repository Manager) scripts allow automation of repository management tasks using Groovy scripts.

**78. How do you monitor Nexus repository health?**

- **Answer:**
  - Use the **Health Check** feature for repositories.
  - Monitor system metrics like memory, disk space, and CPU usage via the Nexus UI.

**79. How would you handle an artifact that failed to deploy due to a **403 Forbidden** error?**

- **Answer:**
  - Verify user permissions for the repository.
  - Check the deployment policy settings of the repository.

**80. What are the key performance tuning tips for Nexus in high-traffic environments?**

- **Answer:**
  - Increase JVM heap size.
  - Use a dedicated database server (for Nexus Pro).
  - Optimize blob storage configurations.

**81. How would you secure a Docker repository in Nexus?**

- **Answer:**
  - Enable HTTPS.
  - Use repository roles for access control.
  - Disable anonymous access.
  - Regularly audit repository logs.

**82. Explain how you can integrate Nexus with CI/CD pipelines for artifact management.**



- **Answer:**

- Configure build tools (e.g., Maven, npm, Docker) to use Nexus repositories for dependencies.
- Use plugins in CI/CD tools (e.g., Jenkins, GitLab CI) for artifact upload/download.

### 83. How do you enable repository mirroring in Nexus?

- **Answer:** Use proxy repositories to mirror remote repositories automatically.

### 84. Artifacts are duplicated in a group repository. How would you resolve this?

- **Answer:**

- Ensure repositories in the group have unique content.
- Adjust the order of repositories in the group.

### 85. How do you migrate artifacts between two Nexus instances?

- **Answer:**

- Export artifacts from the source instance using a repository export task.
- Import them into the target instance.

### 86. How do you integrate Nexus with Terraform?

- **Answer:** Publish Terraform modules to a hosted Maven or raw repository and configure `source` in Terraform to point to the Nexus repository.

### 87. How would you use Nexus to manage Python packages?

- **Answer:**

- Create a PyPI (proxy/hosted) repository in Nexus.
- Configure `pip.conf` or `requirements.txt` to use the Nexus repository URL.

### 88. How can Nexus be integrated with Kubernetes?

- **Answer:** Deploy Nexus as a container in a Kubernetes cluster and configure it to manage Helm charts, Docker images, or other artifacts.



---

**89. Explain the use of Nexus REST API for repository automation.**

- **Answer:** The Nexus REST API provides endpoints for creating repositories, managing artifacts, and automating administrative tasks.

**90. How would you configure Nexus to manage multiple project teams?**

- **Answer:**
  - Create separate repositories for each team.
  - Assign roles and permissions specific to each team.

**91. How do you handle a failed backup task in Nexus?**

- **Answer:**
  - Check disk space and permissions.
  - Retry the task after fixing the issue.

**92. What are some ways to reduce artifact storage in Nexus?**

- **Answer:**
  - Enable cleanup policies.
  - Compact blob storage.
  - Use content compression.

**93. How do you set up Nexus for geographically distributed teams?**

- **Answer:**
  - Use Nexus Pro with repository replication.
  - Set up local proxy repositories for regional teams.

**94. What would you do if Nexus blob storage exceeds capacity?**

- **Answer:**
  - Add a new blob store.
  - Migrate repositories to the new blob store.

**95. Explain the disaster recovery process for Nexus.**

- **Answer:**

- Restore the `sonatype-work` directory from a backup.
- Reconfigure system settings if necessary.

**96. How does Nexus manage concurrent downloads from a repository?**

- **Answer:** Nexus handles concurrent requests using repository worker threads, configurable in repository settings.

**97. What is the impact of enabling anonymous access in Nexus?**

- **Answer:** It can lead to unauthorized access to artifacts and security vulnerabilities. It should be disabled for production.

**98. How do you secure Nexus REST API endpoints?**

- **Answer:**
  - Use API tokens or credentials for authentication.
  - Restrict access using roles and permissions.

**99. How would you handle repository corruption in Nexus?**

- **Answer:**
  - Repair or rebuild the repository index.
  - Restore from a backup if necessary.

**100. What are Nexus staging rules, and how are they used?**

- **Answer:**
  - Staging rules validate artifacts during deployment, ensuring they meet quality and policy standards.

**101. How can you create and enforce artifact naming conventions in Nexus?**

- **Answer:** Use routing rules or create custom Groovy scripts to enforce naming conventions when artifacts are uploaded.

**102. What are the best practices for repository naming in Nexus?**



- **Answer:**

- Use consistent prefixes or suffixes (`team-`, `project-`).
- Clearly indicate type (e.g., `maven-releases`, `npm-proxy`).
- Avoid spaces or special characters.

### 103. How would you configure Nexus to handle large file uploads efficiently?

- **Answer:**

- Increase the HTTP request size in Nexus configuration.
- Use a blob store optimized for large artifacts.
- Tune JVM heap size for better memory handling.

### 104. What steps would you take to troubleshoot frequent Nexus service crashes?

- **Answer:**

- Review JVM heap size settings.
- Check logs for errors.
- Monitor system resources (CPU, memory, disk).
- Ensure database connectivity.

### 105. How do you implement disaster recovery for Nexus in a multi-node setup?

- **Answer:**

- Configure shared storage for blob stores.
- Use Nexus Pro clustering for redundancy.
- Implement periodic backups of configuration and repositories.

### 106. How would you integrate Nexus with Jenkins declarative pipelines?

**Answer:** Use Jenkins Nexus plugins to upload/download artifacts. Example pipeline:

```
pipeline {  
  
    stages {  
  
        stage('Deploy to Nexus') {
```



```
steps {  
  
  nexusArtifactUploader(  
  
    credentialsId: 'nexus-credentials',  
  
    groupId: 'com.example',  
  
    artifactId: 'my-app',  
  
    version: '1.0.0',  
  
    repositories: [[  
  
      url:  
'http://nexus.example.com/repository/maven-releases/',  
  
      nexusVersion: 'nexus3'  
  
    ]]  
  
  )  
  
}  
  
}
```

### 107 . How do you integrate Nexus with GitLab CI for artifact management?

- **Answer:**

- Configure `.gitlab-ci.yml` to upload artifacts to Nexus using `curl` or Nexus CLI.



Example:

```
deploy:
```

```
script:
```

```
    - curl -u username:password --upload-file target/app.jar  
    http://nexus.example.com/repository/releases/com/example/app  
/1.0.0/app.jar
```

**108. Explain the process of deploying Helm charts from Nexus to Kubernetes.**

● **Answer:**

- Push the Helm chart to a hosted Helm repository in Nexus.

Add the Nexus repository in Helm using:

```
helm repo add my-nexus  
http://nexus.example.com/repository/helm-hosted/
```

Deploy the chart:

```
helm install my-app my-nexus/my-chart
```

**109. How can you automate Nexus repository creation using Terraform?**

**Answer:** Use the Nexus Provider in Terraform to define repository configurations as code.

Example:

```
provider "nexus" {  
  
    url = "http://nexus.example.com" username  
    = "admin"  
  
    password = "admin123"  
  
}
```





```
resource "nexus_repository" "maven_releases"

{
  name = "maven-releases"

  format = "maven2"

  type = "hosted"
}
```

#### 110 . How do you manage environment-specific artifacts in Nexus?

- **Answer:**
  - Use separate repositories for each environment (e.g., `dev`, `qa`, `prod`).
  - Tag artifacts with environment metadata.

#### 111 . What steps would you take to migrate Nexus repositories to a new server?

- **Answer:**
  - Backup the `sonatype-work` directory.
  - Install Nexus on the new server.
  - Restore the `sonatype-work` directory and update the `nexus.properties` file.

#### 112 . How do you configure Nexus for multi-format repositories?

- **Answer:** Use separate repositories for each format (e.g., Maven, npm) or group them using a group repository for unified access.

#### 113 . What is the impact of blob store corruption, and how do you resolve it?

- **Answer:** Corrupted blobs can make artifacts inaccessible. Resolve by:
  - Running a blob store integrity check.
  - Restoring from a backup if needed.

#### 114 . How would you troubleshoot failed artifact downloads in a proxy repository?



- **Answer:**

- Check the remote repository URL.
- Review Nexus logs for proxy errors.
- Ensure the cache is not corrupted.

### 115 . How do you implement cross-region artifact replication in Nexus?

- **Answer:** Use Nexus Pro's repository replication feature to synchronize artifacts across regions.

### 116 . How do you secure sensitive data in Nexus configurations?

- **Answer:**
  - Use encrypted passwords for repository credentials.
  - Secure Nexus configurations with file system permissions.
  - Enable HTTPS for secure communication.

### 117 . Explain the process of role-based access control (RBAC) in Nexus.

- **Answer:**
  - Define roles with specific permissions.
  - Assign roles to users or groups.
  - Apply roles to repositories for granular access control.

### 118 . How do you audit artifact changes in Nexus?

- **Answer:** Enable audit logging under **Administration** → **System** → **Logging** to track artifact uploads, deletions, and modifications.

### 119 . What is the significance of staging repositories in Nexus Pro?

- **Answer:** Staging repositories act as temporary holding areas for artifacts, allowing quality checks before promoting them to production.

### 120 . How do you enforce artifact upload policies in Nexus?

- **Answer:** Use routing rules to block or allow specific artifact uploads based on patterns.



**121. What are some common performance bottlenecks in Nexus, and how do you address them?**

- **Answer:**
  - **Bottlenecks:** High CPU usage, insufficient memory, large blob storage.
  - **Solutions:** Optimize JVM heap, compact blob storage, use repository cleanup policies.

**122. How do you enable caching for proxy repositories in Nexus?**

- **Answer:** Configure caching policies under the repository settings, specifying the cache TTL (time-to-live).

**123. What is blob compaction, and when should it be used?**

- **Answer:** Blob compaction removes unused storage space in blob stores. It should be scheduled during off-peak hours.

**124. How do you scale Nexus for large enterprises?**

- **Answer:**
  - Use Nexus Pro clustering.
  - Distribute repositories across multiple blob stores.
  - Implement a load balancer.

**125. How would you troubleshoot slow artifact downloads from Nexus?**

- **Answer:**
  - Check network latency.
  - Optimize repository caching.
  - Increase worker thread limits in repository settings.

**126. What is the impact of enabling HTTP/HTTPS proxy in Nexus?**

- **Answer:** HTTP/HTTPS proxies allow Nexus to route outbound requests through a proxy server, enhancing security and enabling requests in restricted network environments.

**127. How would you implement a repository structure for a microservices architecture in Nexus?**

- **Answer:**
  - Create individual repositories for each microservice (e.g., `service1-maven`, `service2-docker`).
  - Use group repositories to consolidate access for shared dependencies.

**128. Explain the purpose of Nexus Health Check feature.**

- **Answer:** It identifies vulnerabilities and outdated components in repositories, helping maintain security compliance.

**129. How do you handle a repository that becomes inaccessible after a server restart?**

- **Answer:**
  - Verify repository configurations in `nexus.properties`.
  - Check logs for startup errors.
  - Ensure blob storage paths are correct.

**130. What is the role of the `nexus-context-path` parameter?**

- **Answer:** It defines the context path under which Nexus operates (e.g., `/nexus`), used for customizing the Nexus URL.

**131. How do you restrict anonymous access to Nexus repositories?**

- **Answer:** Disable anonymous access under **Administration** → **Security** → **Anonymous Access**, and enforce authentication.

**132. How do you configure Nexus for SSO (Single Sign-On)?**

- **Answer:** Use an external identity provider like SAML, LDAP, or OAuth, and configure Nexus Realms to authenticate users via SSO.

**133. Explain the process of encrypting Nexus repository credentials.**

- **Answer:** Nexus encrypts credentials stored in `config.xml`. Ensure this file is secured with proper file system permissions.

**134. How do you audit and track user actions in Nexus?**

- **Answer:** Enable **Audit Logs** under **System Logging** to capture details of uploads, deletions, and configuration changes.

**135. What measures can you take to ensure Nexus complies with GDPR?**

- **Answer:**
  - Anonymize user data.
  - Regularly audit and purge unnecessary logs.
  - Enable HTTPS for secure data transmission.

**136. How does Nexus Pro handle repository replication across multiple sites?**

- **Answer:** Nexus Pro supports repository replication, allowing artifacts to be synchronized across instances in different locations.

**137. What is the purpose of the Procurement Suite in Nexus Pro?**

- **Answer:** It enforces policies on which artifacts can be used from external repositories, ensuring compliance and reducing risks.

**138. Explain Smart Proxy in Nexus Pro.**

- **Answer:** Smart Proxy enables two Nexus instances to communicate, automatically synchronizing artifacts between repositories.

**139. How do you configure Nexus to work with an external database?**

- **Answer:** Nexus Pro allows integration with an external database (e.g., PostgreSQL). Update the `nexus.properties` file with database connection details.

**140. What is a Routing Rule in Nexus Pro, and how is it implemented?**

- **Answer:** Routing rules control access to specific paths within repositories. Create a rule, define allowed/blocked patterns, and apply it to a repository.

**141. How do you restore Nexus from a backup?**

- **Answer:**
  - Stop Nexus.
  - Replace the `sonatype-work` directory with the backup.
  - Restart Nexus and verify the data.

**142. What steps would you take to ensure Nexus high availability?**

- **Answer:**
  - Use clustering (Pro feature).
  - Configure shared blob storage.
  - Deploy a load balancer in front of Nexus instances.

**143. How do you recover from a corrupted blob store in Nexus?**

- **Answer:**
  - Run the **Blob Store Integrity Check** task.
  - Restore missing blobs from a backup.

**144. What is the impact of an incorrectly configured cleanup policy?**

- **Answer:** Artifacts may be prematurely deleted, causing builds to fail.  
Regularly review and test cleanup policies.

**145. How do you validate the consistency of a repository after a disaster recovery?**

- **Answer:**
  - Verify artifact accessibility.
  - Check blob store integrity.
  - Rebuild repository indexes.

**146. How do you configure Jenkins to use Nexus for dependency management?**

**Answer:** Update `settings.xml` to include Nexus repository URLs for `<repositories>` and `<pluginRepositories>`.





Example:

```
<repository>

  <id>nexus</id>

  <url>http://nexus.example.com/repository/maven-releases/</url>

</repository>
```

**147. Explain how GitHub Actions can be used with Nexus for artifact management.**

- **Answer:**
  - Use `actions/setup-java` to configure Maven/Gradle.
  - Use `curl` or Nexus REST API to upload artifacts.

Example:

```
- name: Upload Artifact

  run: curl -u username:password --upload-file
./target/app.jar
http://nexus.example.com/repository/releases/com/example/app
/1.0.0/app.jar
```

**148. How do you handle environment-specific configurations in Nexus for CI/CD?**

- **Answer:**
  - Use separate repositories for `dev`, `qa`, and `prod`.
  - Configure repository URLs dynamically in CI/CD pipelines.

**149. How would you set up automated artifact promotion in Nexus?**

- **Answer:** Use Nexus REST API to move artifacts between repositories based on CI/CD pipeline stages.



## 150. How can Nexus be integrated into a Helm-based Kubernetes deployment pipeline?

---

- **Answer:** Push Helm charts to a Nexus Helm repository and configure the pipeline to pull charts from Nexus for deployment.

### 151. What do you do if a repository index fails to rebuild?

- **Answer:**
  - Check logs for errors.
  - Ensure sufficient disk space.
  - Restart Nexus and retry the task.

### 152. How do you resolve slow artifact uploads in Nexus?

- **Answer:**
  - Optimize network bandwidth.
  - Increase Nexus worker thread count.
  - Configure blob stores for better performance.

### 153. How would you handle an artifact deployment failure due to

#### 409 Conflict?

- **Answer:** Ensure overwrite policies are correctly configured, or use a unique version for the artifact.

### 154. What steps would you take to troubleshoot repository permission issues?

- **Answer:**
  - Verify user roles and permissions.
  - Check content selectors.
  - Review the repository configuration.

### 155. How do you recover Nexus from a failed upgrade?

- **Answer:**
  - Roll back to the previous version using backups.



- Verify compatibility before retrying the upgrade.
- 

**156. What are the JVM tuning recommendations for Nexus?**

● **Answer:**

- Allocate at least 2 GB of heap memory (`-Xmx2g`).
- Use garbage collection tuning for larger instances.
- Monitor memory usage with tools like JVisualVM.

**157. How do you scale Nexus for handling large Docker repositories?**

● **Answer:**

- Use separate blob stores for Docker artifacts.
- Implement a dedicated Docker registry instance.
- Optimize repository cache settings.

**158. What are Nexus cleanup policies, and how do they improve performance?**

- **Answer:** Cleanup policies remove unused or outdated artifacts, reducing storage usage and improving query performance.

**159. How do you optimize repository caching for proxy repositories?**

- **Answer:** Configure a high TTL (time-to-live) for cached components to reduce remote fetches.

**160. What are the benefits of using multiple blob stores in Nexus?**

- **Answer:** It allows better organization, scalability, and performance for large datasets.

**161. How do you integrate Nexus with AWS S3 for blob storage?**

● **Answer:**

- Configure an S3 bucket.
- Add S3 as a blob store in Nexus under **Administration** → **Repository** → **Blob Stores**.



- Use it as storage for new or existing
- 

**162. What are the steps to deploy Nexus in a Kubernetes cluster?**

● **Answer:**

- Create a Kubernetes deployment and service for Nexus.
- Mount persistent storage for blob data.
- Expose the service using an ingress controller or LoadBalancer.

**163. How do you manage Nexus backups in a cloud environment?**

● **Answer:**

- Use cloud-native tools like AWS Backup or Azure Backup to snapshot the Nexus storage.
- Regularly back up the `sonatype-work` directory and configuration files.

**164. What are the steps to configure Nexus as a Terraform module repository?**

● **Answer:**

- Create a **Raw (hosted)** repository.
- Upload Terraform modules to the repository.
- Use the Nexus repository URL as the `source` in Terraform configurations.

**165. How would you configure Nexus with Azure Blob Storage?**

● **Answer:**

- Create a blob container in Azure.
- Configure Azure Blob Storage as a blob store in Nexus.
- Assign the blob store to repositories.

**166. How do you synchronize artifacts between two Nexus instances in different cloud environments?**

● **Answer:**

- Use repository replication (Nexus Pro).



- Schedule periodic artifact exports and imports using Nexus CLI or
- 

**167. What are the best practices for deploying Nexus in a hybrid cloud environment?**

● **Answer:**

- Use centralized Nexus in the primary cloud region.
- Enable repository replication for regional access.
- Use cloud-specific blob stores for performance optimization.

**168. How do you set up Nexus with Google Cloud Storage for artifact storage?**

● **Answer:**

- Create a bucket in Google Cloud Storage.
- Add it as a blob store in Nexus configuration.
- Assign the blob store to repositories.

**169. How do you configure a CI/CD pipeline in AWS CodePipeline to use Nexus?**

● **Answer:**

- Use CodeBuild to pull dependencies and upload artifacts to Nexus.

Example buildspec:

```
version: 0.2 phases:
```

```
  build:
```

```
    commands:
```

```
      - mvn deploy
```

```
      -DrepositoryUrl=http://nexus.example.com/repository/releases  
      /
```

**170. What is the impact of using Nexus with multiple cloud regions, and how do you mitigate latency?**



Answer:

---

- **Impact:** Increased latency and network traffic.
- **Mitigation:** Use regional proxy repositories or content delivery networks (CDNs).

### 171. How do you monitor Nexus metrics in Prometheus/Grafana?

- **Answer:**

- Use the Nexus Prometheus plugin.
- Expose metrics at `/service/metrics`.
- Configure Prometheus to scrape metrics and visualize in Grafana.

### 172. What steps would you take to troubleshoot Nexus startup failures?

- **Answer:**

- Check the `nexus.log` file for errors.
- Verify Java version compatibility.
- Ensure blob store paths and database connections are correct.

### 173. How do you optimize Nexus for high artifact upload traffic?

- **Answer:**

- Scale horizontally with additional nodes (Pro feature).
- Increase thread pool size in repository settings.
- Optimize network throughput.

### 174. What would you do if a repository index becomes corrupted?

- **Answer:**

- Rebuild the index via **Repository Settings** → **Rebuild Index**.
- Check for disk space and database integrity.

### 175. How do you set up alerts for Nexus service failures?

- **Answer:**





Use external monitoring tools like Nagios, Prometheus, or CloudWatch.

Set up email/SMS notifications for downtime or performance degradation.

---

**176. How do you automate repository creation using the Nexus REST API?**

● **Answer:**

Use a POST request to the `/service/rest/v1/repositories` endpoint with JSON payload:

```
{  
  
  "name": "my-repo",  
  
  "format": "maven2",  
  
  "type": "hosted",  
  
  "storage": { "blobStoreName": "default" }  
}
```

**177. What is the use of Groovy scripting in Nexus?**

- **Answer:** Groovy scripts automate tasks like repository creation, artifact promotion, and user management.

**178. How do you create a scheduled task in Nexus for artifact cleanup?**

● **Answer:**

- Navigate to **Tasks** → **Create Task**.
- Select **Cleanup Snapshots** or other tasks.
- Configure schedule and scope.

**179. How would you implement role-based automation in Nexus using scripts?**

- **Answer:** Use Groovy scripts or the REST API to create roles, assign permissions, and link them to users.



## 180. How do you configure an automated cleanup policy for multiple repositories?

---

- **Answer:** Create a global cleanup policy and apply it to repositories using the Nexus API or UI.

## 181. What would you do if blob storage compaction causes Nexus downtime?

- **Answer:**
  - Schedule compaction during off-peak hours.
  - Increase JVM memory to handle the task efficiently.

## 182. How do you troubleshoot Nexus network connectivity issues?

- **Answer:**
  - Test repository URLs with `curl` or `ping`.
  - Check firewall rules.
  - Verify proxy settings.

## 183. How do you recover artifacts deleted by an incorrect cleanup policy?

- **Answer:**
  - Restore artifacts from a backup.
  - Disable the policy and verify its criteria.

## 184. What steps would you take if Nexus becomes unresponsive during high traffic?

- **Answer:**
  - Increase worker threads.
  - Analyze JVM heap usage.
  - Add more nodes for load distribution (Pro feature).

## 185. How do you handle timeouts in proxy repositories?

- **Answer:**
  - Increase connection timeout in repository settings.
  - Ensure remote repository availability.

## 186. How would you configure Nexus for a multi-tenant environment?



- **Answer:**

---

- Create separate repositories for each tenant.
- Use content selectors and roles for access control.

**187. How do you enable artifact version locking in Nexus?**

- **Answer:** Use repository policies to prevent overwriting or redeployment of release versions.

**188. How do you implement blue-green deployments with Nexus and Docker?**

- **Answer:**
  - Use separate repositories (**blue** and **green**) for Docker images.
  - Switch deployment environments using load balancers.

**189. What would you do if Nexus fails to resolve dependencies from a proxy repository?**

- **Answer:**
  - Check if the dependency exists in the remote repository.
  - Clear the repository cache and retry.

**190. How do you migrate from Artifactory to Nexus?**

- **Answer:**
  - Export artifacts from Artifactory using its export feature.
  - Use Nexus API or CLI to import artifacts into Nexus.

**191. What are the best practices for managing large repositories in Nexus?**

- **Answer:**
  - Use cleanup policies for unused artifacts.
  - Separate repositories by project or team.
  - Monitor blob storage usage.

**192. How do you manage artifact promotion across environments in Nexus?**



**Answer:** Use staging repositories or scripts to promote artifacts from dev to qa

to prod.

**193. How would you set up a Nexus proxy for a private GitHub package registry?**

- **Answer:**

- Create a proxy repository with the GitHub package registry URL.
- Authenticate using GitHub personal access tokens.

**194. What are the benefits of tagging artifacts in Nexus?**

- **Answer:** Tags help categorize and search artifacts efficiently, especially in large repositories.

**195. How do you implement audit trails in Nexus?**

- **Answer:** Enable **Audit Logs** and regularly review them for user and repository actions.

**196. How do you prevent unauthorized Docker image downloads in Nexus?**

- **Answer:**

- Require authentication for Docker repositories.
- Disable anonymous access.
- Assign permissions to roles.

**197. How would you migrate Nexus repositories to a different blob store?**

- **Answer:**

- Create a new blob store.
- Use the **Blob Store Migration** task in Nexus Pro.

**198. How do you configure Nexus for cross-project dependency sharing?**

- **Answer:** Use group repositories to combine multiple project repositories and provide unified access.



## 199. What are the risks of enabling anonymous access in Nexus, and how can you mitigate them?

---

- **Answer:** Risks include unauthorized access and data leakage. Mitigation:
  - Disable anonymous access.
  - Use role-based permissions.

## 200. How do you optimize Nexus for high-availability deployments?

- **Answer:**
  - Deploy Nexus in a cluster.
  - Use shared storage for blob data.
  - Configure a load balancer.