NAME

ModifyNewLineChar.pl - Modify new line char(s)

SYNOPSIS

ModifyNewLineChar.pl File(s)...

ModifyNewLineChar.pl [-h, --help] [-m, --mode Unix | Mac | Windows] [-o, --overwrite] [-r, --root rootname] [-w, --workingdir dirname] File(s)...

DESCRIPTION

Modify new line char(s) in ASCII files to interchange among Unix, Windows, and Mac formats.

OPTIONS

-h, --help

Print this help message.

-m, --mode Unix | Mac | Windows

New line char(s) mode. Possible values: *Unix, Mac, or Windows*. Default: *Unix*. Here are default values for new line char(s): *Unix - In; Windows: IrIn; Mac - Ir*

-o, --overwrite

Overwrite existing files.

-r, --root rootname

New text file name is generated using the root: <Root>.<Ext>. Default new file name: <InitialFileName><Mode>.<InitialFileExt>. This option is ignored for multiple input files.

-w, --workingdir dirname

Location of working directory. Default: current directory.

EXAMPLES

To use Unix new line char and generate NewSample1.csv file, type:

% ModifyNewLineChar.pl -m Unix -r NewSample1 -o Sample1.csv

To use Mac new line char and generate NewSample1.sdf file, type:

% ModifyNewLineChar.pl -m Mac -r NewSample1 -o Sample1.sdf

To use Windows new line chars and generate NewSample1.csv file, type:

% ModifyNewLineChar.pl -m Windows -r NewSamplel -o Samplel.csv

AUTHOR

Manish Sud <msud@san.rr.com>

SEE ALSO

ModifyTextFilesFormat.pl

COPYRIGHT

Copyright (C) 2019 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.