
NAME

RDKitUtil

SYNOPSIS

import RDKitUtil

DESCRIPTION

RDKitUtil module provides the following functions:

GenerateBase64EncodedMolStrings, GetInlineSVGForMolecule, GetInlineSVGForMolecules, GetMolName, GetSVGForMolecule, GetSVGForMolecules, IsMolEmpty, MolFromBase64EncodedMolString, MolToBase64EncodedMolString, MoleculesWriter, ReadAndValidateMolecules, ReadMolecules, ReadMoleculesFromMol2File, ReadMoleculesFromMolFile, ReadMoleculesFromPDBFile, ReadMoleculesFromSDFFile, ReadMoleculesFromSMILESFile, WriteMolecules

FUNCTIONS

GenerateBase64EncodedMolStrings

```
GenerateBase64EncodedMolStrings(Mols, PropertyPickleFlags =  
Chem.PropertyPickleOptions.AllProps)
```

Setup an iterator for generating base64 encoded molecule string from a RDKit molecule iterator. The iterator returns a list containing a molecule index and encoded molecule string or None.

The molecules are pickled using RDKit Mol.ToBinary() function before their encoding.

Arguments:

iterator: RDKit molecules iterator.
PropertyFlags: RDKit property pickle options.

Returns:

object : Base64 encoded molecules iterator. The iterator returns a list containing a molecule index and an encoded molecule string or None.

The following property pickle flags are currently available in RDKit:

```
Chem.PropertyPickleOptions.NoProps  
Chem.PropertyPickleOptions.MolProps  
Chem.PropertyPickleOptions.AtomProps  
Chem.PropertyPickleOptions.BondProps  
Chem.PropertyPickleOptions.PrivateProps  
Chem.PropertyPickleOptions.AllProps
```

Example(s):

```
EncodedMolsInfo = GenerateBase64EncodedMolStrings(Mols)  
for MolIndex, EncodedMol in EncodedMolsInfo:  
    if EncodedMol is not None:  
        Mol = MolFromBase64EncodedMolString(EncodedMol)
```

GetInlineSVGForMolecule

```
GetInlineSVGForMolecule(Mol, Width, Height, Legend = None, AtomListToHighlight =  
None, BondListToHighlight = None, BoldText = True, Base64Encoded = True)
```

Get SVG image text for a molecule suitable for inline embedding into a HTML page.

Arguments:

Mol (object): RDKit molecule object.
Width (int): Width of a molecule image in pixels.
Height (int): Height of a molecule image in pixels.
Legend (str): Text to display under the image.
AtomListToHighlight (list): List of atoms to highlight.
BondListToHighlight (list): List of bonds to highlight.
BoldText (bool): Flag to make text bold in the image of molecule.
Base64Encoded (bool): Flag to return base64 encoded string.

Returns:

str : SVG image text for inline embedding into a HTML page using "img"

```
tag:  or  
tag: 
```

GetInlineSVGForMolecules

```
GetInlineSVGForMolecules(Mols, MolsPerRow, MolWidth, MolHeight, Legends = None,  
AtomListsToHighlight = None, BondListsToHighlight = None, BoldText = True,  
Base64Encoded = True)
```

Get SVG image text for molecules suitable for inline embedding into a HTML page.

Arguments:

Mols (list): List of RDKit molecule objects.
MolsPerRow (int): Number of molecules per row.
Width (int): Width of a molecule image in pixels.
Height (int): Height of a molecule image in pixels.
Legends (list): List containing strings to display under images.
AtomListsToHighlight (list): List of lists containing atoms to highlight for molecules.
BondListsToHighlight (list): List of lists containing bonds to highlight for molecules.
BoldText (bool): Flag to make text bold in the image of molecules.
Base64Encoded (bool): Flag to return base64 encoded string.

Returns:

str : SVG image text for inline embedding into a HTML page using "img"
tag: or
tag:

GetMolName

```
GetMolName(Mol, MolNum = None)
```

Get molecule name.

Arguments:

Mol (object): RDKit molecule object.
MolNum (int or None): Molecule number in input file.

Returns:

str : Molname corresponding to _Name property of a molecule, generated from specieid MolNum using the format "Mol%d" % MolNum, or an empty string.

GetSVGForMolecule

```
GetSVGForMolecule(Mol, Width, Height, Legend = None, AtomListToHighlight = None,  
BondListToHighlight = None, BoldText = True)
```

Get SVG image text for a molecule suitable for viewing in a browser.

Arguments:

Mol (object): RDKit molecule object.
Width (int): Width of a molecule image in pixels.
Height (int): Height of a molecule image in pixels.
Legend (str): Text to display under the image.
AtomListToHighlight (list): List of atoms to highlight.
BondListToHighlight (list): List of bonds to highlight.
BoldText (bool): Flag to make text bold in the image of molecule.

Returns:

str : SVG image text for writing to a SVG file for viewing in a browser.

GetSVGForMolecules

```
GetSVGForMolecules(Mols, MolsPerRow, MolWidth, MolHeight, Legends = None,  
AtomListsToHighlight = None, BondListsToHighlight = None, BoldText = True)
```

Get SVG image text for molecules suitable for viewing in a browser.

Arguments:

Mols (list): List of RDKit molecule objects.
MolsPerRow (int): Number of molecules per row.
Width (int): Width of a molecule image in pixels.
Height (int): Height of a molecule image in pixels.
Legends (list): List containing strings to display under images.
AtomListsToHighlight (list): List of lists containing atoms to highlight for molecules.
BondListsToHighlight (list): List of lists containing bonds to highlight for molecules.
BoldText (bool): Flag to make text bold in the image of molecules.

Returns:

str : SVG image text for writing to a SVG file for viewing in a browser.

IsMolEmpty

IsMolEmpty(Mol)

Check for the presence of atoms in a molecule.

Arguments:

Mol (object): RDKit molecule object.

Returns:

bool : True - No atoms in molecule; Otherwise, false.

MolFromBase64EncodedMolString

MolFromBase64EncodedMolString(EncodedMol)

Generate RDKit molecule object from a base64 encoded string.

Arguments:

str: Base64 encoded molecule string.

Returns:

object : RDKit molecule object or None.

MolToBase64EncodedMolString

MolToBase64EncodedMolString(Mol, PropertyPickleFlags =
Chem.PropertyPickleOptions.AllProps)

Encode RDKit molecule object into a base64 encoded string. The properties can be optionally excluded. The molecule is pickled using RDKit Mol.ToBinary() function before their encoding.

Arguments:

Mol (object): RDKit molecule object.
PropertyPickleFlags: RDKit property pickle options.

Returns:

str : Base64 encode molecule string or None.

The following property pickle flags are currently available in RDKit:

Chem.PropertyPickleOptions.NoProps
Chem.PropertyPickleOptions.MolProps
Chem.PropertyPickleOptions.AtomProps
Chem.PropertyPickleOptions.BondProps
Chem.PropertyPickleOptions.PrivateProps
Chem.PropertyPickleOptions.AllProps

MoleculesWriter

MoleculesWriter(FileName, **KeyWordArgs)

Set up a molecule writer.

Arguments:

FileName (str): Name of a file with complete path.
**KeywordArgs (dictionary) : Parameter name and value pairs for writing and processing molecules.

Returns:

RDKit object : Molecule writer.

The file extension is used to determine type of the file and set up an appropriate file writer.

ReadAndValidateMolecules

ReadAndValidateMolecules(FileName, **KeywordArgs)

Read molecules from an input file, validate all molecule objects, and return a list of valid and non-valid molecule objects along with their counts.

Arguments:

FileName (str): Name of a file with complete path.
**KeywordArgs (dictionary) : Parameter name and value pairs for reading and processing molecules.

Returns:

list : List of valid RDKit molecule objects.
int : Number of total molecules in input file.
int : Number of valid molecules in input file.

The file extension is used to determine type of the file and set up an appropriate file reader.

ReadMolecules

ReadMolecules(FileName, **KeywordArgs)

Read molecules from an input file without performing any validation and creation of molecule objects.

Arguments:

FileName (str): Name of a file with complete path.
**KeywordArgs (dictionary) : Parameter name and value pairs for reading and processing molecules.

Returns:

list : List of RDKit molecule objects.

The file extension is used to determine type of the file and set up an appropriate file reader.

ReadMoleculesFromMol2File

ReadMoleculesFromMol2File(FileName, Sanitize = True, RemoveHydrogens = True)

Read molecule from a Tripos Mol2 file.

Arguments:

FileName (str): Name of a file with complete path.
Sanitize (bool): Sanitize molecules.
RemoveHydrogens (bool): Remove hydrogens from molecules.

Returns:

list : List of RDKit molecule objects.

ReadMoleculesFromMolFile

ReadMoleculesFromMolFile(FileName, Sanitize = True, RemoveHydrogens = True, StrictParsing = True)

Read molecule from a MDL Mol file.

Arguments:

FileName (str): Name of a file with complete path.
Sanitize (bool): Sanitize molecules.
RemoveHydrogens (bool): Remove hydrogens from molecules.

```
StrictParsing (bool): Perform strict parsing.
```

Returns:

```
list : List of RDKit molecule objects.
```

ReadMoleculesFromPDBFile

```
ReadMoleculesFromPDBFile(FileName, Sanitize = True, RemoveHydrogens = True)
```

Read molecule from a PDB file.

Arguments:

```
FileName (str): Name of a file with complete path.  
Sanitize (bool): Sanitize molecules.  
RemoveHydrogens (bool): Remove hydrogens from molecules.
```

Returns:

```
list : List of RDKit molecule objects.
```

ReadMoleculesFromSDFFile

```
ReadMoleculesFromSDFFile(FileName, Sanitize = True, RemoveHydrogens = True,  
StrictParsing = True)
```

Read molecules from a SD file.

Arguments:

```
FileName (str): Name of a file with complete path.  
Sanitize (bool): Sanitize molecules.  
RemoveHydrogens (bool): Remove hydrogens from molecules.  
StrictParsing (bool): Perform strict parsing.
```

Returns:

```
list : List of RDKit molecule objects.
```

ReadMoleculesFromSMILESFile

```
ReadMoleculesFromSMILESFile(FileName, SMILESDelimiter = ' ', SMILESColIndex = 0,  
SMILESNameColIndex = 1, SMILESTitleLine = 1, Sanitize = 1)
```

Read molecules from a SMILES file.

Arguments:

```
SMILESDelimiter (str): Delimiter for parsing SMILES line  
SMILESColIndex (int): Column index containing SMILES string.  
SMILESNameColIndex (int): Column index containing molecule name.  
SMILESTitleLine (int): Flag to indicate presence of title line.  
Sanitize (int): Sanitize molecules.
```

Returns:

```
list : List of RDKit molecule objects.
```

WriteMolecules

```
WriteMolecules(FileName, Mols, **KeyWordArgs)
```

Write molecules to an output file.

Arguments:

```
FileName (str): Name of a file with complete path.  
Mols (list): List of RDKit molecule objects.  
**KeyWordArgs (dictionary) : Parameter name and value pairs for writing and  
processing molecules.
```

Returns:

```
int : Number of total molecules.  
int : Number of processed molecules written to output file.
```

The file extension is used to determine type of the file and set up an appropriate file writer.

AUTHOR

Manish Sud <msud@san.rr.com>

COPYRIGHT

Copyright (C) 2019 Manish Sud. All rights reserved.

The functionality available in this file is implemented using RDKit, an open source toolkit for cheminformatics developed by Greg Landrum.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.