Orvexa Cloud
Login Credentials

Demo, seed, and local accounts from the product source

16 October 2026 • v1.0 • Orvexa Tech Private Limited

This sheet lists every login ID and password that ships in the Orvexa Cloud codebase. Use it for local Vite and for a database that was filled with npm run seed. It does not contain Render, Atlas, Cloudflare, or GitHub secrets.

Live production warning

The free-plan API at orvexa-api-nskw.onrender.com was not seeded. These demo passwords were tested against that API and were rejected. Production admin and seller passwords live in Mongo on Atlas. They are not in git and are not printed here.

1. Where to sign in

Surface	Live URL	Local
Admin portal	https://orvexa-cloud.pages.dev/	http://localhost:8443/admin
Seller (Lunar)	https://orvexa-cloud.pages.dev/t/lunar/dashboard	http://localhost:8443/t/lunar/dashboard
Storefront (Lunar)	https://orvexa-cloud.pages.dev/t/lunar	http://localhost:8443/t/lunar
API health	https://orvexa-api-nskw.onrender.com/api/health	http://localhost:5000/api/health

On pages.dev use /admin, /t/<slug>, and /t/<slug>/dashboard. Do not use orvexacloud.in for this stack — that host is an older site. api.orvexacloud.in and admin.orvexacloud.in have no DNS.

2. Super Admin

Field	Value
Name	Orvexa Tech Super Admin
Login ID / email	admin@orvexatech.com
Demo aliases	admin@platform.com or admin
Password	admin@password
Role	super_admin
Works on live Render?	No live API returned invalid credentials

Production admin

Render generated ADMIN_BOOTSTRAP_KEY. Call POST /api/auth/admin/bootstrap once with that key, an email, and a new password. The published default key orvexa_bootstrap_2026 is rejected. After bootstrap, sign in with the email you chose.

3. Seller / store owner (demo + seed)

Store	Owner	Login ID	Password
The Lunar Clothing	Gowreesh KP	gowreesh@thelunarclothing.com	lunar@password
Silk Haus	Kavya Menon	kavya@silkhaus.in	silk@password
Khadi Studio	Arjun Patel	arjun@khadistudio.co	khadi@password
Bloom & Weave	Kavita Reddy	kavita@bloomweave.in	bloom@password

Seed password pattern is <slug>@password. Slugs: lunar, silkhaus, khadistudio, bloomweave. Seed also lists applicant pooja@bloomweave.com (pending, not an owner). Live seller login with lunar@password was rejected; Lunar exists in Atlas with a different password hash.

4. Storefront shopper (demo)

Field	Value
Name	Priya Sharma
Email	priya.sharma@example.com
Phone	+91 98765 43210
Password	lunar123
Scope	Demo localStorage shopper not an API user

5. When these passwords work

Environment	Admin / seller	Shopper
Local Vite (DEV)	Yes demo mode on	Yes
Local API after npm run seed	Yes seed writes these hashes	No
Live Pages + Render	No	No

Do not seed production. seed.ts refuses NODE_ENV=production and Atlas URIs that are not clearly staging, test, dev, or local.

6. Production secrets not in this file

System	Where the secret lives
Live Super Admin	Mongo admin hash; Render ADMIN_BOOTSTRAP_KEY
Live sellers	Mongo tenant passwordHash; forgot-password mail
MongoDB Atlas	Atlas + Render MONGODB_* URIs
Render / Cloudflare / GitHub	Those dashboards not app logins
JWT / signup HMAC	Render JWT_SECRET, JWT_REFRESH_SECRET, SIGNUP_SIGNING_SECRETS

GitHub Actions must only receive deploy hooks and CLOUDFLARE_API_TOKEN. Application passwords and JWT keys stay on Render. Source for demo rows: src/api/auth.ts, src/api/shopper-accounts.ts, server/src/scripts/seed.ts.

(c) 2026 Orvexa Tech Private Limited - Login credentials v1.1 - Demo values plus live bootstrap

7. How to turn on live login

Do not run npm run seed against Atlas. Create one super admin with the Render ADMIN_BOOTSTRAP_KEY, then set the Lunar owner password. After the admin exists, delete ADMIN_BOOTSTRAP_KEY from Render.

7.1 Copy ADMIN_BOOTSTRAP_KEY from Render

Render -> service orvexa-api -> Environment. Copy ADMIN_BOOTSTRAP_KEY. It is not the published string orvexa_bootstrap_2026.

7.2 Create the first super admin (PowerShell)

```
$env:API_BASE = "https://orvexa-api-nskw.onrender.com"
$env:ADMIN_BOOTSTRAP_KEY = "<paste from Render>"
$env:ADMIN_EMAIL = "hello@orvexatech.com"
$env:ADMIN_PASSWORD = "<at least 12 characters>"
$env:CONFIRM_PRODUCTION_BOOTSTRAP = "yes"
npm run admin:bootstrap
```

201 = created. 409 = admin already exists, skip to 7.3. 403 = wrong key.

7.3 Set the Lunar seller password

```
$env:API_BASE = "https://orvexa-api-nskw.onrender.com"
$env:ADMIN_EMAIL = "hello@orvexatech.com"
$env:ADMIN_PASSWORD = "<admin password from 7.2>"
$env:STORE_SLUG = "lunar"
$env:SELLER_PASSWORD = "<at least 8 characters>"
npm run seller:set-password
```

Admin sign-in: https://orvexa-cloud.pages.dev/ with the 7.2 email and password. Seller sign-in: https://orvexa-cloud.pages.dev/t/lunar/dashboard as gowreesh@thelunarclothing.com with the 7.3 password. Do not write those live passwords into git.