

CONSUMER SSD

Experience lightning-fast responsiveness and upgrade your everyday computing. Boot up in seconds, load applications instantly, and enjoy a smoother workflow.

MP500G4

MiPhi MP500G4 PCIe Gen 4 Solid State Drive

- Operating Temperature is from 0 to 70 Celsius
- Provides up to 2TB capacity
- Supports PCIe Gen 4.0 x 4 NVMe 1.4



MP500G4

DATA SHEET

CONSUMER SSD

SPECIFICATIONS

	2TB	1TB	512GB
MODEL NUMBER	MP5021200T	MP5021100T	MP5021512G
INTERFACE	PCIe 4.0 x4	PCIe 4.0 x4	PCIe 4.0 x4
NAND Flash	3D TLC/QLC	3D TLC/QLC	3D TLC/QLC
FORM FACTOR	M.2 2280	M.2 2280	M.2 2280
PERFORMANCE²			
Sequential Read up to (Mb/s)	5000 MB/s	5100 MB/s	5100 MB/s
Sequential Write up to (MB/s)	4200 MB/s	4800 MB/s	4600 MB/s
Random Read	780K IOPS	500K IOPS	250K IOPS
Random Write	800K IOPS	700K IOPS	350K IOPS
DWPD	0.33	0.33	0.33
UBER	<10-16 bits	<10-16 bits	<10-16 bits
WARRANTY	5 Years	5 Years	5 Years

(1) 1 GB = 1,000,000,000 bytes

(2) Sequential Performance is based on CrystalDiskMark v8, 1 GB range, command size =1MB, QD=32, Thread=1 , and test drive set as secondary
Random Performance is based on CrystalDiskMark v8, 1 GB range, ,command size =4KB, QD=32, Thread=16 , and test drive set as secondary
Numbers are estimated value.



The data within this specification is subject to change by Miphi without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2024 Miphi Semicon India Private Limited. All rights reserved

Find more information and resources at: miphi.in