Expt No : 11a
Date 3/10/26

Simulate Static routing Configuration using Cisco Packet Tracer

Aim

To simulate a static routing Configuration using using Cisco Packet Tracer

Procedure:

* Open Cisco Packet Tracer and Create the given network topology
* Connect 3 routers and PCs using suitable cable
* Configuration IP address for routers and PC's
* Enable all router interface using no shut down
* Configure static router on Router 0, router 1, router 2 using ip mobil.
* Set main and back up router using different administrative distance values
* Test Connectivity
* Use Tracer to Verify the routing path
* Disconnect the main link and verify that the look up router works
* Thus a static routing is successfully Configured and Verified.

```
C:\>ping 30.0.0.100

Pinging 30.0.0.100 with 32 bytes of data:

Reply from 30.0.0.100: bytes=32 time<1ms TTL=126
Reply from 30.0.0.100: bytes=32 time<1ms TTL=126
Reply from 30.0.0.100: bytes=32 time<1ms TTL=126
Reply from 30.0.0.100: bytes=32 time<1ms TTL=126

Ping statistics for 30.0.0.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>tracert 30.0.0.100

Tracing route to 30.0.0.100 over a maximum of 30 hops:

  1    0 ms      3 ms      0 ms      10.0.0.1
  2    *         *         *         Request timed out.
  3    0 ms      0 ms      0 ms      20.0.0.2
  4    0 ms      0 ms      0 ms      30.0.0.100

Trace complete.
```

RESULT:

Thus a static routing is successfully configured and verified using CISCO Packet Tracer