Expt No : 11b Simulate RIP using CISCO packet Tracer

Date : 3/10/24

AIM:

To Simulate RIP using (3 routers and 2PC's) Cisco Packet Tracer

PROCEDURE:

* Create the Topology with 3 routers and 2PC's
* Connect the devices using Suitable Cables
* Assign the given IP address to both PC's
* Configure fast ethernet and Serial Interface of all routers
* Enable Interface using no shutdown
* Set Clock rate & 4000 and bandwidth bps on DE Serial Interface
* Enable RIP on all routers using router RIP
* Add directly connected network using the network command
* Test Connectivity using ping 20.0.0.0.2 to Verify the selected route
* Disconnect the direct route 0_router2 link and we tracert again to Verify RIP selects the alternate route

```
C:\>ping 20.0.0.2

Pinging 20.0.0.2 with 32 bytes of data:
Reply from 20.0.0.2: bytes=32 time<1ms TTL=126
Reply from 20.0.0.2: bytes=32 time<1ms TTL=126
Reply from 20.0.0.2: bytes=32 time<1ms TTL=126
Reply from 20.0.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 20.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>tracert 20.0.0.2

Tracing route to 20.0.0.2 over a maximum of 30 hops:

  1      <1 ms     <1 ms     <1 ms    10.0.0.1
  2       1 ms      1 ms      1 ms    192.168.1.250
  3       2 ms      2 ms      2 ms    192.168.1.245
  4       3 ms      3 ms      3 ms    20.0.0.2
Trace complete.
```

RESULT:

Thus we simulated RIP using CISCO Packet Tracer