

# Rajalakshmi Engineering College

Name: Gowtham M  
Email: 241501059@rajalakshmi.edu.in  
Roll no: 241501059  
Phone: 8778441691  
Branch: REC  
Department: I AIML AD  
Batch: 2028  
Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 6\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John and Mary are collaborating on a project that involves data analysis. They each have a set of age data, one sorted in ascending order and the other in descending order. However, their analysis requires the data to be in ascending order.

Write a program to help them merge the two sets of age data into a single sorted array in ascending order using merge sort.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of age values in each dataset.

The second line consists of N space-separated integers, representing the ages of participants in John's dataset (in ascending order).

The third line consists of N space-separated integers, representing the ages of participants in Mary's dataset (in descending order).

### **Output Format**

The output prints a single line containing space-separated integers, which represents the merged dataset of ages sorted in ascending order.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

1 3 5 7 9

10 8 6 4 2

Output: 1 2 3 4 5 6 7 8 9 10

### **Answer**

```
#include <stdio.h>
```

```
// You are using GCC
```

```
void merge(int arr[], int left[], int right[], int left_size, int right_size) {
```

```
    //Type your code here
```

```
    int i=0,j=0,k=0;
```

```
    while(i<left_size && j<right_size){
```

```
        if(left[i]<right[j]){
```

```
            arr[k++]=left[i++];
```

```
        }else if(left[i]>right[j]){
```

```
            arr[k++]=right[j++];
```

```
        }else{
```

```
            arr[k++]=left[i];
```

```
            i++;
```

```
            j++;
```

```
        }
```

```
    }
```

```
    while(i<left_size) arr[k++]=left[i++];
```

```
    while(j<right_size) arr[k++]=right[j++];
```

```
}
```

```

void mergeSort(int arr[], int n) {
    //Type your code here
    if(n<2) return;

    int mid=n/2;
    int left[mid],right[n-mid];

    for(int i=0;i<mid;i++)
        left[i]=arr[i];
    for(int i=mid;i<n;i++)
        right[i-mid]=arr[i];

    mergeSort(left,mid);
    mergeSort(right,n-mid);
    merge(arr,left,right,mid,n-mid);
}

int main() {
    int n, m;
    scanf("%d", &n);
    int arr1[n], arr2[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr1[i]);
    }
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr2[i]);
    }
    int merged[n + n];
    mergeSort(arr1, n);
    mergeSort(arr2, n);
    merge(merged, arr1, arr2, n, n);
    for (int i = 0; i < n + n; i++) {
        printf("%d ", merged[i]);
    }
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10