

Rajalakshmi Engineering College

Name: Gowtham M
Email: 241501059@rajalakshmi.edu.in
Roll no: 241501059
Phone: 8778441691
Branch: REC
Department: AI & ML - Section 3
Batch: 2028
Degree: B.E - AI & ML

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 8_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Write a program to validate the email address and display suitable exceptions if there is any mistake.

Create 3 custom exception classes as below

DotException AtTheRateException DomainException

A typical email address should have a "." character, and a "@" character, and also the domain name should be valid. Valid domain names for practice be 'in', 'com', 'net', or 'biz'.

Display Invalid Dot usage, Invalid @ usage, or Invalid Domain message based on email id.

Get the email address from the user, validate the email by checking the

above-mentioned criteria, and print the validity status of the input email address.

Input Format

The first line of input contains the email to be validated.

Output Format

The output prints a Valid email address or an Invalid email address along with the suitable exception

If email ends with . or contains not exactly one . after @, it throws:

DotException: Invalid Dot usage

Invalid email address

If @ appears not exactly once, it throws:

AtTheRateException: Invalid @ usage

Invalid email address

If the part after the last dot is not among accepted domains:

DomainException: Invalid Domain

Invalid email address

If all conditions satisfied then print:

Valid email address

Refer to the sample input and output for format specifications.

Sample Test Case

Input: sample@gmail.com

Output: Valid email address

Answer

```
import java.util.*;

class DotException extends Exception {
    public DotException(String msg) {
        super(msg);
    }
}

class AtTheRateException extends Exception {
    public AtTheRateException(String msg) {
        super(msg);
    }
}

class DomainException extends Exception {
    public DomainException(String msg) {
        super(msg);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        String email = sc.nextLine().trim();

        try {
            validateEmail(email);
            System.out.println("Valid email address");
        } catch (DotException e) {
            System.out.println("DotException: " + e.getMessage());
            System.out.println("Invalid email address");
        } catch (AtTheRateException e) {
```

```

        System.out.println("AtTheRateException: " + e.getMessage());
        System.out.println("Invalid email address");
    } catch (DomainException e) {
        System.out.println("DomainException: " + e.getMessage());
        System.out.println("Invalid email address");
    }
}

public static void validateEmail(String email)
    throws DotException, AtTheRateException, DomainException {

    if (email.startsWith(".") || email.endsWith(".") ||
        email.contains("..") || email.contains("@.") || email.contains(".@")) {
        throw new DotException("Invalid Dot usage");
    }

    if (email.startsWith("@") || email.endsWith("@") ||
        email.indexOf('@') != email.lastIndexOf('@')) {
        throw new AtTheRateException("Invalid @ usage");
    }

    int atIndex = email.indexOf('@');
    int dotIndex = email.lastIndexOf('.');

    if (dotIndex < atIndex || dotIndex == -1) {
        throw new DotException("Invalid Dot usage");
    }

    String domain = email.substring(dotIndex + 1);
    List<String> validDomains = Arrays.asList("in", "com", "net", "biz");
    if (!validDomains.contains(domain)) {
        throw new DomainException("Invalid Domain");
    }
}
}

```

Status : Correct

Marks : 10/10