

40.Illustrate the various File Access Permission and different types of users in Linux.

Aim

To understand and demonstrate file access permissions and the types of users in Linux.

File Access Permissions

In Linux, file permissions define how files and directories are accessed by users. These permissions are represented as:

Read (r): Allows viewing the content of a file or directory.

Write (w): Allows modifying the content of a file or adding/deleting files in a directory.

Execute (x): Allows running a file as a program or accessing a directory.

Permission Categories

Owner (u): The user who owns the file.

Group (g): A group of users with shared access.

Others (o): All other users on the system.

Permissions are displayed using the **ls -l** command, where:

First character: File type (- for a file, d for a directory).

Next 3 characters: Permissions for the owner (e.g., rwx).

Next 3 characters: Permissions for the group (e.g., r-x).

Last 3 characters: Permissions for others (e.g., r--). **Algorithm:**

Open a terminal and create a file/directory using touch or mkdir.

Check the current permissions using the ls -l command.

Modify permissions using the chmod command.

`chmod [permissions] [filename]`

Permissions can be set symbolically (u, g, o) or numerically (e.g., 777).

Validate the changes by checking permissions again with `ls -l`

Code:

Below is an example script that demonstrates file permission changes: bash

Copy code

```
#!/bin/bash
```

```
# Step 1: Create a file echo "Creating a file
named 'example.txt'..." touch example.txt
```

```
# Step 2: Display default permissions
echo "Default permissions for
'example.txt':" ls -l example.txt
```

```
# Step 3: Modify permissions to give full access to the owner, read/execute for group, and no
access to others chmod u=rwx,g=rx,o= example.txt echo "Modified permissions for
'example.txt':" ls -l example.txt
```

```
# Step 4: Modify permissions numerically to 777 (full access for everyone)
chmod 777 example.txt echo "Permissions after setting to
777:" ls -l example.txt
```

```
# Clean up rm
example.txt
echo "File 'example.txt' deleted."
```

OUTPUT:

```
$ ls -l
-rwxr-xr-- 1 owner group 1024 Dec 16 14:25 example.txt
```

Result:

Demonstrated the default file permissions in Linux.

Successfully modified file permissions using both symbolic and numeric modes.

Observed how permissions affect access for the owner, group, and others.