

# Error Handling in LLM Applications

## 1. Introduction to Error Handling in LLM Applications

Error handling is a critical component of any production-ready Large Language Model (LLM) application. Since LLMs depend on probabilistic models, external APIs, and network-based services, failures can occur at multiple stages. Proper error handling ensures system stability, graceful degradation, and a reliable user experience.

## 2. Why Error Handling is Important

Without robust error handling, LLM applications may crash, return misleading outputs, or expose sensitive information. Error handling helps in:

- Maintaining application uptime
- Improving user trust
- Preventing cascading failures
- Simplifying debugging and monitoring

## 3. Categories of Errors in LLM Systems

### 3.1 Input Validation Errors

These errors occur when user input is invalid or malformed.

Examples:

- Empty or null prompts
- Unsupported characters or encoding
- Excessively long inputs
- Invalid request formats

Mitigation:

- Validate input length and format
- Reject empty prompts early
- Apply schema validation before API calls

### 3.2 Token and Context Window Errors

LLMs have fixed context limits. Exceeding these limits causes request failures.

Examples:

- Context length exceeded
- Token overflow errors

Mitigation:

- Chunk large text inputs
- Use sliding window techniques
- Summarize text before processing

### 3.3 API-Level Errors

These arise from interactions with external LLM providers.

Common API errors:

- 401 – Unauthorized (Invalid API key)
- 403 – Forbidden (Access denied)
- 429 – Too Many Requests (Rate limit exceeded)
- 500/503 – Server-side errors

Mitigation:

- Validate API keys
- Implement retry logic with exponential backoff
- Respect rate limits
- Handle server errors gracefully

### 3.4 Model Output Errors

LLMs may return unexpected or invalid outputs.

Examples:

- Hallucinated or factually incorrect responses
- Ignoring prompt instructions
- Invalid JSON or structured output
- Partial or truncated responses

Mitigation:

- Enforce strict prompt instructions
- Validate response format
- Apply post-processing checks
- Use fallback responses when validation fails

### 3.5 Network and Infrastructure Errors

These errors are caused by connectivity or infrastructure issues.

Examples:

- Network timeouts
- DNS resolution failures
- SSL certificate issues
- Proxy or firewall restrictions

Mitigation:

- Set request timeouts
- Retry failed requests selectively
- Monitor network health
- Implement fallback mechanisms

## **4. Retry and Recovery Strategies**

### **4.1 Retry Logic**

Retries should be applied only to recoverable errors.

Recoverable:

- Rate limit errors
- Temporary network failures
- Transient server issues

Non-recoverable:

- Invalid input
- Authentication failures

### **4.2 Exponential Backoff**

Gradually increase wait time between retries to avoid overwhelming APIs.

## **5. Graceful Degradation and Fallback Handling**

When errors persist:

- Return cached responses
- Switch to smaller or local models
- Provide user-friendly error messages
- Disable non-critical features temporarily

## **6. Logging and Monitoring Errors**

Proper logging is essential for diagnosing issues.

Log:

- Error type and code
- Timestamp
- Request identifiers
- Response latency

Avoid logging:

- API keys
- Personal user data
- Confidential prompts

## **7. Security Considerations in Error Handling**

- Never expose internal error details to users
- Mask sensitive information in logs
- Follow compliance and data protection guidelines

## **8. End-to-End Error Handling Flow**

1. Validate input
2. Check token limits
3. Make API call
4. Handle API and network errors
5. Validate model output
6. Apply fallback if needed
7. Log and monitor errors