Test and gate reports

The raw output behind every number in `BUILD_LOG.md`, one folder per phase. Each file opens with the phase, the commit it was produced at, and the command that produced it. Test lists are re-runnable: check out that commit and run the command.

File	What it is
`pytest.txt`	every test by name with its result (`uv run pytest -vv`)
`gate-*.txt`	the harness table for a gate run: per fixture, result, model calls, tokens, time, and every failure reason
`live-*.txt`	a targeted live run, summarised from its trace files: what the model extracted, the API calls, what was said, the judge's verdicts
`*-demo.txt`	a zero-token run of new code on real data; the script that produced it sits beside it
`browser-checks.txt`, `screens/`	what was checked in a real browser, every defect found there and its fix; screenshots of the final state
`palette.txt`	the chart colours run through the palette validator, both themes
`privacy-scan.txt`	every admin read endpoint scanned for names, phones and customer ids, with live data stored
`cases-runs.txt`, `loop-runs.txt`	every run of a set of cases, from their trace files: what was said and each failure's reason
`variants-review.md`	the generated variants and the kit's verdict on each, as the reviewer sees it
`reliability.txt`, `reliability.json`	pass^k for k = 1 to 5 per suite, from five runs of every case
`image.txt`	the container image: size, layers, what it holds (checked inside it), the amd64 run
`container-checks.txt`	the playground run from the image: pages, a real call, a restart, its log streams
`gate-job.txt`	the gate job's one line, the gate run and turn records it saved
`infra.txt`	the cloud resources Terraform manages, a plan against the live deployment, the state's protection, the platform properties checked
`cloud-checks.txt`	the live deployment probed from outside, as a stranger, and read back from its own logs and storage
`security-review.md`	an independent adversarial review's findings, and what was done with each

| `replay-*.txt` | a fixture replayed with the model's answer scripted, zero tokens, to show what the receptionist says for a given reading; the script beside it |

Phase 1 produced documents only, so it has no folder. `after-16/` holds the work after the final phase: the gate that failed once the prompt leak was closed (D-88, D-91), and the replay that reproduced its reply, and the extractor eval that followed (D-92).