
Architecture · printed from docs/architecture/containers.md, docs/architecture/data-flow.md, docs/architecture/sequences.md, docs/architecture/logic-flow.md, docs/architecture/deployment.md

> Verified against `3e57ec9` on 2026-10-31.

Containers


What runs, and what we don't control. Level 1 is the system as one box; level 2 opens it. Where it runs (resource group, registry, identity) is in `deployment.md`; who does what in order is in `sequences.md`; where personal data goes is in `data-flow.md`.

Level 1 · context



The graders don't use the deployment: they run the kit's harness, which calls `decide()` in their own process. Everything else is the deployed system.

Level 2 · containers



Container	What it does	Evidence
Caller simulator	Pick a seed customer or an unknown number; type, or tap (or hold) to talk; the fogged booking card condenses as facts are heard; thumbs on every reply; scenario cards and the rating form	`python/pirtis/playground/static/caller.html`, `python/pirtis/playground/static/js/caller.js`
Admin console	Reliability (gate runs, the thermal view), Conversations, Traces, Feedback, Fleet, Human eval; all computed from content-free records except a stored call's trace	`python/pirtis/playground/static/admin.html`, `python/pirtis/playground/static/js/admin.js`, `python/pirtis/playground/analytics.py`
Playground server	The JSON API and the two pages; the sign-in (accounts we create, signed sessions); runs each call turn through `decide()` and the kit's handlers, saves the call after every turn	`python/pirtis/playground/server.py`, `python/pirtis/playground/auth.py`, `python/pirtis/playground/calls.py`

Container	What it does	Evidence
`decide()`	Turn gate (no model call), one strict-JSON understanding call, a deterministic policy that owns every rule and write, code-rendered speech, one telemetry line	`python/pirtis/agent/agent.py`, `python/pirtis/agent/turn.py`, `python/pirtis/agent/understand.py`, `python/pirtis/agent/policy.py`, `python/pirtis/agent/rules.py`, `python/pirtis/agent/speech.py`
Rental API	The kit's fixed API over an in-memory store, seeded per call from the fixtures' seed: units, availability, customers, bookings	`python/pirtis/api/memory.py`, `fixtures/seeds/base.json`
Gate job	The frozen gate in one process: the kit's Runner over the nightly suite, the extractor eval, a saved gate run, one summary line, pruning	`python/pirtis/ops/gate_job.py`
Data directory	Sessions, feedback, ratings, turn records, gate runs, calibrations; atomic writes, retention per kind	`python/pirtis/ops/store.py`, `python/pirtis/ops/model.py`

Outside the boundary

Dependency	Vendor · region	Edge	If it is down	Fallback	Evidence
gpt-4o-mini	OpenAI API · [CONFIRM: processing region, US unless a data-residency project is set]. Azure OpenAI in an EU region instead via `LLM_BASE_URL`	sync · HTTPS	a turn that needs the model is put through to a person; an unreadable answer gets "could you say that again?"; the gate job fails with `llm_errors` above zero	turns the turn gate settles (still talking, silence, a request for a person) need no model; none for the rest	`python/pirtis/llm/client.py`, `python/pirtis/agent/agent.py`
Browser speech recognition	the browser's vendor (Chrome sends audio to Google's service; [CONFIRM: Safari and Edge]) · [CONFIRM: region]	sync · browser-managed	holding to talk does nothing useful	typing, always available	`python/pirtis/playground/static/js/caller.js`
Azure Files, hosting the data directory	Microsoft Azure · Germany West Central	sync · SMB	calls can't be saved or resumed; a gate run isn't saved	none	`deploy/terraform/main.tf`
Log Analytics, alerts, email	Microsoft Azure Monitor · Germany West Central	async · container stdout	no log queries and no alerts; calls go on	the admin console reads the data directory, not the logs	`deploy/terraform/monitoring.tf`
Container registry	Azure Container Registry · Germany West Central	sync · HTTPS image pull	a new revision or a job run can't start; the running app is unaffected	none	`deploy/terraform/main.tf`


Not built:

- real telephony; the caller simulator stands in for the phone line
- streaming speech; a turn is one request
- a queue; every call turn is synchronous
- single sign-on; accounts are made by hand

> Verified against `3e57ec9` on 2026-10-31.

Data flow

Where personal data sits, and what happens to it just before it leaves. The customers are made up (the fixtures' seed), and testers call as those customers. A tester's own words and voice are still personal data, so they are labelled as such.



Stores

Store	Label	Kept	Evidence
Sessions	PII: what the tester typed or said, the bookings the call made, each turn's step	30 days	`python/pirtis/ops/model.py`, `python/pirtis/playground/calls.py`
Feedback	PII: a transcript snapshot and the rater's note	30 days	`python/pirtis/ops/model.py`
Turn records	pseudonymised: ids, a salted hash of the phone's digits, counts; no text	90 days	`python/pirtis/agent/telemetry.py`, `python/pirtis/ops/model.py`
Human ratings	pseudonymised: the rater's initials, a session id, scores	1 year	`python/pirtis/ops/model.py`
Gate runs, calibrations	no PII: fixture ids, verdicts, counts	1 year	`python/pirtis/ops/model.py`
Sign-in accounts	PII: account names and scrypt hashes, a Container App secret	until removed	`python/pirtis/playground/auth.py`, `deploy/Makefile`
Rental API	PII in shape, synthetic in content: the seed's customers, phones and bookings; rebuilt per call, never saved	the call	`python/pirtis/api/memory.py`, `fixtures/seeds/base.json`
Log Analytics	pseudonymised: turn lines (phone hash, ids, no text); gate lines and access lines (method, path without its query, status) hold no personal data	30 days	`python/pirtis/agent/telemetry.py`, `python/pirtis/playground/server.py`, `deploy/terraform/main.tf`
Browser storage	pseudonymised: the theme and the rater's initials, on the tester's own device	until cleared	`python/pirtis/playground/static/js/caller.js`

Retention is applied by the gate job's prune on every run (`python/pirtis/ops/store.py`).

Boundary crossings

ID	From → To	Data	Before it crosses	Region	Transfer mechanism (GDPR Ch. V)	Retention	Evidence
C1	caller simulator → playground server (and the replies back)	the caller's text (speech already turned to text in the browser), the persona's phone, the session cookie; back: our replies, the booking card, a stored call's trace for the console	TLS only (HTTPS, HSTS); a signed-in session is required; spending is capped per account and per day	Germany West Central (EU)	none needed (the receiving side is in the EEA)	sessions 30 days	`python/pirtis/playground/server.py`, `python/pirtis/playground/auth.py`
C2	`decide()` → model vendor	the call so far as text: caller lines, our lines, short notes ("caller identified", the caller's own bookings by sauna and dates); the rules; the units; a 42-day calendar	nothing is redacted: the caller's words go as said, a name included if they spoke it. Never sent: the phone number, other customers' data, past bookings' site and car details	[CONFIRM: OpenAI's processing region; the US unless a data-residency project is configured]	[CONFIRM: OpenAI's DPA with SCCs, Art. 46(2)(c)]; none needed on Azure OpenAI in an EU region	[CONFIRM: OpenAI API retention; abuse monitoring up to 30 days unless zero retention is agreed]	`python/pirtis/agent/understand.py`, `python/pirtis/llm/client.py`
C3	gate job → model vendor	synthetic fixture calls, and the kit's judge prompts with our replies	nothing: synthetic data only	as C2	as C2	as C2	`python/pirtis/ops/gate_job.py`, `python/pirtis/harness/judge.py`
C4	Azure Monitor → owner's mailbox	an alert: the rule's name, its owner-and-action text, a count, a link; the queries project only versions, case ids and counts	nothing: the rules read content-free lines	[CONFIRM: the mail provider's region]	[CONFIRM: depends on the mail provider]	[CONFIRM: the mailbox's retention]	`deploy/terraform/monitoring.tf`
C5	caller simulator → the browser's speech vendor	the tester's voice, while they hold the mic button	nothing: the browser sends the audio itself (Chrome to Google's service)	[CONFIRM: the browser vendor's region]	[CONFIRM: the browser vendor's terms]	[CONFIRM: the browser vendor's retention]	`python/pirtis/playground/static/js/caller.js`

ID	From → To	Data	Before it crosses	Region	Transfer mechanism (GDPR Ch. V)	Retention	Evidence
C6	off-path reviewer → model vendor	each model turn of a stored call: the call so far as text, the saunas, a 42-day calendar; by default to another model (`REVIEW_MODEL`)	nothing is redacted, as C2; it runs only when the owner runs `make review`, never inside a call	as C2	as C2	as C2	`python/pirtis/ops/review.py`

What this diagram says plainly:

- **C2 leaves the EEA on the OpenAI path.** The data is synthetic customers plus whatever a tester types, which is why testers call as seed personas and never as themselves. Pointing `LLM_BASE_URL` at Azure OpenAI in an EU region keeps C2 inside the EEA.
- **C5 is the browser's doing,** not ours, and a tester avoids it by typing.

Privacy threats (a LINDDUN pass over this diagram)

Threat	Where	Finding	Handled by
Linking	turn records	the salted phone hash links one caller's turns across calls, by design for analytics	the salt is a secret; records expire after 90 days
Identifying	sessions, feedback	a tester can say their own name or details	seed personas only (scenario cards, the dial page's note); 30-day expiry
Data disclosure	C2, C5, C6	call text leaves the EEA to the model vendor; voice goes to the browser's vendor	synthetic personas; typing as an alternative; the EU model path. Recorded as a known limit (SPEC §12)
Unawareness and unintervenability	the caller simulator	the only notice is the dial page's line that calls are kept 30 days; a tester can't delete their own calls	the owner deletes on request (files on the share); a self-service delete is not built
Non-compliance	C2	no DPA with the model vendor is recorded here	[CONFIRM: OpenAI DPA]

Not built:


- redaction before C2 (names spoken by the caller go to the model as said)
- a self-service way for a tester to delete their calls
- a privacy notice beyond the dial page's line
- the reviewer on a schedule in Azure (today the owner runs `make review` where the data is)

> Verified against `3e57ec9` on 2026-10-31.

Sequences


The two paths that write something a customer relies on: a new booking, and a change to one. The participants are the containers in `containers.md`.

1 · A booking, on the caller's yes to our read-back



The pre-flight `violations()` mirrors every rule the API enforces and is property-tested against it (`python/pirtis/agent/rules.py`), so a 422 can't happen by construction. The retries are in `create()` (`python/pirtis/agent/policy.py`); a failure no branch handles becomes a hand-off to a person (`python/pirtis/agent/agent.py`).

2 · Moving or cancelling a booking



A cancel is the same path with `status: cancelled` as the change. The retry is `update_with_retry()` in `python/pirtis/agent/policy.py`.

Not built: an idempotency key on writes. A double submit is safe today only because one call is one session handled one turn at a time, and the 500 branch looks before retrying.

> Verified against `8612d72cfa25`'s source on 2026-11-01.

Logic flow

What the receptionist decides on one turn, and in what order. `sequences.md` follows the two writes across the containers; this page follows the decisions inside `decide()`. Every box names the code that does it; `D-nn` points to the decision log.

The agent is **stateless**: each turn it receives the whole call so far and rebuilds what it knows from it. The kit calls `decide()` once per caller turn, so a conversation of any length is this flow, run again on a longer transcript.


How the receptionist remembers

The transcript is the memory. Nothing is stored between turns: each turn, `decide()` reads the whole call so far and rebuilds three kinds of memory from it, the same way every time. A memory rebuilt from the record can't drift or go stale, and a call survives a restart by replaying its transcript.

Memory	What it holds	Rebuilt by	Used for
Facts	name, dates, people, the car's limit, power, the sauna, consent, each with the caller's words behind it	the model reads them from both sides of the call; code checks each against the caller's own words (§3)	what to ask, what to offer, whether to book
What has happened	who the caller is; their bookings; what was booked, moved or cancelled in this call	the API calls recorded in the transcript (`identified_customer`, `own_bookings`)	never asking for a name twice; never reading anyone else's data
Where the conversation is	our last line: the question pending, the offer just read back (`last_offer`), a refusal already given, a check-in, a finished task	code, from our own lines (D-98)	picking the thread up after a pause, taking "book it" as a yes to the offer, not repeating a refusal, closing a call that's done

The model sees the facts and the whole call; it never has to remember anything itself. The cost is a prompt that grows with the call, about 2.1k tokens a turn for booking calls; a much longer call would need older turns summarised (SPEC §12).


1 · One turn, end to end



Step	Code	Model calls
1 · Turn gate	`agent/turn.py` `gate()`	0
2 · Understand	`agent/understand.py` `extract()`	1
3 · Policy	`agent/policy.py` `next_step()`	0
4 · Speech	`agent/speech.py` `render()`, then the `say` handler's digit guard in `agent/actions.py`	0
Wiring, fallbacks	`agent/agent.py` `decide()`, `_turn()`: never raises (D-19)	—

2 · The turn gate

Runs before anything else, because speaking while the caller is still talking is the one mistake a phone receptionist can't take back (D-04 to D-06).



The last two checks keep the thread of the call (D-98): they read our own last line, so a short reply that adds nothing new is answered at once, with no model call.

A paraphrase the patterns miss ("could a human help me?") still reaches the model, whose intents include `human`, `hold` and `goodbye`: a miss costs a model call, not a wrong answer.

3 · Understanding

One call, temperature 0, with a strict JSON schema generated from the `CallState` class (D-33, D-49). The prompt holds the rules of reading, the sauna catalogue from the API, a 42-day calendar computed in code (D-16), and the call so far, both sides.


The model fills, in this order: a gist; the intent; the caller's name; dates; people; each fact's quote **before** the fact (tow, sauna, heater reason, consent); power; the consent flags last. Evidence before value is what fixed the asthma case (D-69).

Code then checks what came back (`CallState._facts_need_the_callers_words`):

Fact	Counts only if	Otherwise	Decision
Towing capacity	its quote is in the caller's own words and carries a number	dropped: the tow is asked	D-08, D-54
Sauna	its quote is the caller's and names or describes a sauna; code resolves the sauna from the quote if the model left it out	dropped	D-54, D-75
People	always; a hedge ("eight, maybe nine") is raised to the higher number	—	D-79
A "yes" to an offer	its quote is from the caller's latest turn, our last line asked to book, and the turn holds no price demand or instruction to the system	void: the offer is read back again	D-10, D-54, D-74
Name	a name the caller asks about is not theirs	dropped	D-78
Dates, numbers, the sauna id	a real date; 1–50 people; 100–20,000 kg; a sauna in the catalogue	unknown, so it is asked again	D-49
The answer as a whole	valid JSON in the schema	"Sorry, could you say that again?"; twice in a row, a colleague	D-19

4 · The policy


`next_step()` turns the checked state into one decision. Some intents need nobody's data; everything else waits for identification (D-07, D-11).



A refusal that would repeat the line we just said word for word closes the topic instead: "I'm sorry, none of our saunas can take that many people, so I can't book this one. Is there anything else I can help with?" (D-98).

5 · Booking: one question at a time, then an offer

`book()` asks for the **one** next missing fact (D-09), says a problem as soon as it is known (D-68, D-71), and writes only on a yes to exactly what the caller heard (D-10, D-52).




The offer engine (`choose_offer()`, D-12, D-35):

1. Drop every sauna that breaks a hard limit: too small, too heavy for the car, electric without power. Hard limits are never overridden.
2. A heater preference **sorts**; it **filters** only when the caller gave a reason ("the smoke bothers me") or named that sauna as a must-have, and a must-have is never filtered out (D-69).
3. A booking touching a weekend is stretched to two days (D-13).
4. The sauna the caller asked for, on their dates, if the rules allow it. If its dates are taken: another sauna on those dates, or, if they insist on that one or nothing else fits, the same sauna moved in time.
5. Otherwise the smallest fitting sauna on their dates.
6. Otherwise the nearest dates that work for any fitting sauna, searching 0, +1, −1, +2, −2 … days, never before today.

Every candidate passes `violations()`, the copy of the API's write rules, so nothing is offered that the API would reject (D-31).

Writing (`create()`): the rules run once more before the write. If something changed since the offer, the new offer is read back and nothing is written. A 409 (someone took the slot) means a second look and one more try, or the next best offer; a 500 means checking whether the booking landed before trying once more (D-19). The paths are drawn in `sequences.md`.

6 · Changing or cancelling



The booking's own days, and its own turnaround day when the day beyond is free, count as free when it moves (D-15).

7 · Speech

`render(decision, voice)` turns each decision into actions from code templates (D-17):

- **one question** per turn, short sentences, offers ending "Shall I book it?"
- **numbers, dates and euros as words**; the `say` handler turns any digit left into words, whatever wrote the line
- **things that aren't done are said outright** ("I can't look at your bookings until I know who's calling"), so no reply can be read two ways (D-51, D-87)
- a **calmer, slower voice** when the caller's latest turn sounds angry or upset
- a **text message** after a booking or a move; a **summary for the colleague** on every transfer

Where the model's judgement ends


Decided by the model	Decided by code
what the caller wants (the intent)	whether to answer at all this turn
what they said: name, dates, people, tow, sauna, heater, power, consent, with quotes	whether each of those facts counts
—	which question comes next
—	which sauna, which dates, what price
—	whether to write, and what
—	every word the receptionist says

So a model mistake can cost an extra question or a "say that again", never a booking that breaks a rule or a reply the code didn't write.

> Verified against `3e57ec9` on 2026-10-31.

Deployment

Where the containers run. This view is about infrastructure; what talks to what is in `containers.md`. Commands, costs and the bootstrap order are in `deploy/README.md`.



Resource	Settings that matter	Evidence
Container App `pirtis-app`	0 to 1 replicas; 0.25 CPU, 0.5 GiB; external ingress, HTTPS only; probes on `/api/health`; image by digest; secrets: model key, hash salt, session key, accounts	`deploy/terraform/main.tf`
Container Apps Job `pirtis-gate`	cron `0 3 * * *` UTC; 30 min timeout; no retries (a failed gate is read, never re-run); `gate-job --suites nightly`	`deploy/terraform/main.tf`
Container registry	Basic; admin account off; pulled only by the managed identity	`deploy/terraform/main.tf`
Managed identity	one role: AcrPull on the registry	`deploy/terraform/main.tf`
Storage account and share	LRS; TLS 1.2; HTTPS only; no public blob access; one 1 GiB share, linked to the environment with the account key	`deploy/terraform/main.tf`, `deploy/Makefile`
Log Analytics	30 days; a 1 GB daily cap	`deploy/terraform/main.tf`
Alerts	gate regression, agent errors, slow turns; every 15 minutes over the last hour; email to the owner	`deploy/terraform/monitoring.tf`
The image	two stages, bases pinned by digest; uid 10001, read-only code; refuses to start without sign-in accounts	`deploy/Dockerfile`, `.dockerignore`

Secrets are set by the az CLI, never written in these files: the model key, the hash salt, the session key, the sign-in accounts, and the storage key for the share's link. Terraform's state holds the storage keys and, once refreshed, the app's secrets. So the state stays on the owner's machine, owner-only and out of git (`deploy/Makefile`).

Not built:

- remote, encrypted Terraform state
- Key Vault references for the secrets
- a managed-identity mount for the share (in preview; the account key is used today)
- private networking: the app has a public endpoint, behind its sign-in
- CI that builds, scans and deploys on every push