То,
lad mamnali
Village :varkheda Taluka :mulshi District :pune
hfjfkfl
SUB: AUTHENTICATION OF CO-ORDINATES.AMSL.HEIGHTS AND AERIAL DISTANCE REGARDING
Survey No 58, Hissa No 58/1/1/1, 58/1/1/2, 58/2, 58/4/1, 58/11/7, 58/11/8,
Village- Kondhwa Khurd, Taluka - Haveli, District - Pune-411048
Sir, With reference to above Site, the Co-ordinates, Aerial Distance and AMSL, Heigths of site shown by you are given in Annexure - I which is enclosed herewith for purpose of Airport NOC.
For Monarch Surveyors & Engineering

Enclosure:

i) Annexure – IA & IB

ii) Toposheet for reference purpose only.

iii) Survey of India Receipt number_____ dated_____ has been enclosed for evidence of topo sheet purchase which is Annexure 02.

Consultants Ltd.

Director

Annexure - IA (Co-Ordinates Of Site/Plot)

		Co-ordinates (in WGS-84)					
Sr. No	Description of Pillars	Latitude	Longitude	AMSL, height of Co- ordinates given in column(C) in meters	Aerial Distance between Co-ordinates given in column (C) and ARP of NDA, Pune	Aerial Distance between Co-ordinates given in column (C) and ARP of ARP LOHEGAON, Pune	Remarks
(A)	(B)	(C		(D)	(E)	(F)	(G)
	Point No. P1:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'56.0487"	18°28'38.1182 "	660.36	11.43 KM	5.29 KM	
	Point No. P2:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.9878"	18°28'37.6230 "	660.558	11.43 KM	5.29 KM	
	Point No. P3:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'53.9743"	18°28'38.0644 "	661.461	11.37 KM	5.34 KM	
	Point No. P4:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'53.8471"	18°28'37.4073 "	660.661	11.36 KM	5.34 KM	
	Point No. P5 :- Differential GPS Observation taken	73°52'55.2163"	18°28'37.1005 "	659.656	11.40 KM	5.31 KM	

	on Ground IN STATIC mode					
6	Point No. P6:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.1270"	18°28'36.6868 "	659.608	11.40 KM	5.32 KM
7	Point No. P7:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.1497"	18°28'36.4557 "	658.949	11.46 KM	5.27 KM
8	Point No. P8:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.1953"	18°28'36.7073 "	658.973	11.47 KM	5.27 KM
9	Point No. P9:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.0811"	18°28'36.7296 "	658.76	11.46 KM	5.27 KM
	Point No. P10 :- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.2274"	18°28'37.4117 "	658.937	11.47 KM	5.26 KM
	Point No. P11:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'58.0278"	II			5.24 KM
12	Point No. P12:- Differential GPS Observation taken	73°52'58.1086"	18°28'37.8198 "	659.043	11.49 KM	5.24 KM

	T =	1	T	ī	T	Ţ Ţ
	on Ground IN STATIC mode					
13	Point No. B1:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.4721"	18°28'37.5746	659.466	11.41 KM	5.30 KM
14	Point No. B2:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'54.0978"	18°28'37.8790	660.98	11.37 KM	5.34 KM
15	Point No. B3:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'54.0068"	18°28'37.5124 "	660.789	11.37 KM	5.34 KM
16	Point No. B4:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.3832"	18°28'37.2073	659.497	11.41 KM	5.31 KM
17	Point No. B5:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.5736"	18°28'36.9295	659.547	11.42 KM	5.31 KM
18	Point No. B6:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.5438"	18°28'36.7432 "	659.182	11.41 KM	5.31 KM
19	Point No. B7:- Differential GPS Observation taken	73°52'55.7555"	18°28'36.7118 "	658.912	11.42 KM	5.30 KM

	on Ground IN STATIC mode						
	Point No. B8:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'55.7848"	18°28'36.8979	659.448	11.42 KM	5.30 KM	
	Point No. B9:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'56.3538"	18°28'37.8859	659.72	11.44 KM	5.28 KM	
	Point No. B10 :- Differential GPS Observation taken on Ground IN STATIC mode	73°52'56.1722"	18°28'36.7291	658.839	11.43 KM	5.29 KM	
	Point No. B11 :- Differential GPS Observation taken on Ground IN STATIC mode	73°52'56.7675"	18°28'36.6453	658.745	11.45 KM	5.28 KM	
	Point No. B12:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'56.9484"	18°28'37.8011 "	659.591	11.46 KM	5.27 KM	
25	Point No. B13:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.3617"	18°28'37.7928 "	659.148	11.47 KM	5.26 KM	
26	Point No. B14:- Differential GPS Observation taken	73°52'57.9993"	18°28'37.7009 "	658.736	11.49 KM	5.24 KM	

	on Ground IN STATIC mode						
27	Point No. B15:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.9525"	18°28'37.3989	659.05	11.49 KM	5.24 KM	
28	Point No. B16:- Differential GPS Observation taken on Ground IN STATIC mode	73°52'57.3134"	18°28'37.4896 "	659.172	11.47 KM	5.26 KM	

Note:

- i. The Co-ordinates given in column (C) of above table are of Points shown by Applicant in his site. These Co-ordinates are based on observations of Differential GPS instrument in STATIC mode and they are in WGS84 Co- ordinates system.
- ii. The heights given in column (D) are based on the Height of Reference station which is connected to SOI GTS BM using DT levelling.
- iii. Monarch Surveyors & Engineering Consultants Pvt. Ltd. is not responsible for
- iv. the correctness of the Survey Nos. / Gut Nos./ Hissa Nos, address and ownership of property.Responsibility of correctness of said details lies with the
- v. Applicant. This certificate is being issued on Applicants request vide Letter
- vi. under reference in covering letter only to enable him to apply for the clearance from the concerned authorities. This certificate to be used only for the purpose
- vii. for which it is indented and not to be used for any other purpose. No request
- viii. for any change in the above certificate will be entertained after issuance. Accuracy of Co-ordinates is ± 1 m and Aerial distnace rounded off up to first
- ix. decimal of Km.
- x. The distance between point P4 and IAF compound wall of NDA is calculated based on satellite image available on Google Earth and it may vary by ± 20 m

For Monarch Surveyors & Engineering Consultants Ltd.

Director

Enclosure: Relevant topo sheet has been enclosed for reference purpose only and centre of the plot, as elaborated in Annexure 01, with various point numbers have been circled with round stamp, with center of the stamp being centre of the plot (for easy identification purpose only)