NOTE TO USERS Improving Relay Life for NI Switches

Switch Software

Monitor Relay Usage

- Analyze the relay counts on your NI switch products to better manage the use of each relay.
 - Use the niSwitch Get Relay Count VI or the niSwitch_GetRelayCount function to track relay usage for most Switch modules. Refer to the Relay Count topic of the NI Switches Help for more information about supported modules.
 - Edit test sequences to reduce the number of switching cycles.
 - Change external connections on overused rows and columns in a matrix.

Switch Hardware

Prevent High Currents from Damaging Relays

High inrush current can damage relays when switching with capacitive loads. This is because the inrush current needed to charge the capacitive load may be substantially higher than the steady-state current through the system.

- Use series resistance when switching with capacitve loads to prevent high inrush currents from damaging relays.
 - Examples of capacitive loads include: DMMs, long cabling, and DUTs.
- Turn off power supplies or other voltage sources connected to the relay before switching to ensure that voltage levels are the same on both sides of the relay.

Limit Flyback Voltages

Flyback voltages are large counter electromotive forces that occur when relays open. This counter electromotive force can generate large voltage spikes across your relay contact because of the reactive energy stored in the load as the magnetic field in the inductor breaks down.

- Install a flyback diode for DC loads or a metal oxide varistor for AC loads when switching with inductive loads to prevent flyback voltages from damaging relays.
 - Examples of inductive loads include: motors, solenoids, transformers, and relay coils.



Note Ensure that implemented changes do not affect signal integrity or minimum signal requirements for your NI Switch product. Refer to the *General Switching Considerations* topic of the *NI Switches Help* for more information.



| LabVIEW, National Instruments, NI, ni.com, the National Instruments corporate logo, and the Eagle logo are trademarks of National Instruments Corporation. Refer to the Trademark Information at ni.com/trademarks for other National Instruments trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products/technology, refer to the appropriate location: Help-Patents in your software, the patents.txt file on your media, or the National Instruments Patents Notice at ni.com/patents. Refer to the Export Compliance Information at ni.com/legal/export-compliance for the National Instruments global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. | |
|--|-------|
| 373699A-01 | Oct12 |