

View



Feature

- 2HDD Bay (or 1 HDD Bay & 1 eSATA)
- Multi-Languages Supported
- Privacy Zone
- Covert Channel
- Watermarking
- Two-way Audio
- DDNS, DHCP, UPnP

Distinctive Features

- End of Line Resistor Sensor
- Dual 485 Port
- Coaxitron (960H only)
- Equalizer (960H only)
- Camera Tamper Alarm (960H only)
- POS/ATM
- iSCSI (Recording)

General

- OS: Embedded Linux
- Compression: H.264
- Power Supply: 12V/5A - Level 5
- Consumption: 60/40Watts
- Operating Temp: 5 ~ 40°C
- Humidity: 10 ~ 80%
- Net Weight (w/o HDD): 3Kg
- Certification: CE, FCC, RoHS Compliance

Network Software

- VMS, RMS

- Mac Viewer




- Smartphone Viewer



Dimensions

- Size - 340x59x300mm



Specifications

HD-SDI Universal

Model Name		SH3-16u	SH3-08u	SH3-04u
System	Time Sync.	NTP, GMT, DST		
	User	15 Users (Admin., User1 ~ User14)		
Video	Input	16 BNC	8 BNC	4 BNC
	Output	1 HDMI, 1 VGA, 1 BNC		
	Loop	N/A		
	Spot	1 BNC		
	Universal	Yes		
Audio	Input	16 RCA	8 RCA	4 RCA
	Output	1 HDMI, 1 RCA		
Video Recording	Speed	1920x1080p Realtime (max. 30fps/ch)		
	Resolution	1080p, 720p, 960H, D1, CIF		
	Quality	5 Levels		
	Bit Rate	Max 5Mbps/Ch		
Audio Rec	Compression	G.711u		
Network	Interface	Ethernet 10/100/1G		
	Compression	H.264, JPEG		
	Speed	Max. 720P 10fps/ch		
	Resolution	Max. 1280x720p		
Alarm	Pre / Post-Alarm	5sec / 5sec~5min		
	Motion Grid	32x24(NTSC/PAL)		
	Alarm Action	E-mail, Ch Popup, Buzzer, Relay, PTZ Preset, Spot, Remote VMS, Front LED		
	Input / Output	4/1 - NC/NO/EOL		
Display	HDMI, VGA	Full HD, XGA		
	TV	SDTV (720x480/576)		
External Interface	PTZ / Keyboard	2 RS485 - Terminal Block		
	ATM / POS	RS232C - Terminal Block / Ethernet POS		
Storage	Primary / External / ODD	2 HDD (or 1 HDD & 1 eSATA)		



SH3-16u



SH3-08u



SH3-04u