

KCE-SDTIT6530D

TVI x4 Zoom Motorized Vari-focal GIMBALL DOME CAMERA

KCE
Korea Communication Electronics

TURBO HD

FUNCTION

- 1/3" 2.1Megapixel Sony Exmor **TVI Technology**
- High-End Motorized Zoom/ Auto Focus
- FULL HD 1080P (1920x1080) video quality
- 2.8~12mm x4 Zoom Motorized Varifocal Lens (ICR)
- 3DNR (DIGITAL NOISE REDUCTION)
- UTC control via Turbo DigiGuard DVR
- Built-in 30pcs IR LEDs for Day & Night
- Gimbal Plastic Dome for indoor use
- Made in Korea



SPECIFICATION

DESCRIPTION	NTSC	PAL
IMAGE SENSOR	1/2.9" 2.1Megapixel Sony Exmor CMOS	
EFFECTIVE PIXEL	1920 (H) × 1080 (V) = 2.07M	
SCANNING SYSTEM	Progressive	
SYNCHRONIZATION	Internal	
HORIZONTAL RESOLUTION	Full HD 1080P	
VIDEO OUTPUT	TVI, CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	More than 52dB	
Min. ILLUMINATION	0.02Lux(Sens-UP X32)	
IRIS ADJUSTMENT	ALC / ELC	
LENS	2.8~12mm Motorized Varifocal Lens (ICR TYPE)	
ELECTRONIC SHUTTER	AUTO/(1/25~1/60,000)/FLK MANUAL	
OSD LANGUAGE	ENG/CHN/CHN[S]/JPN/KOR	
BACKLIGHT COMPENSATION	OFF /HLC/BLC/WDR	
Day & Night	COLOR/BW/EXTERN/AUTO	
D-WDR	OFF/LOW/MIDDLE/HIGH	
AUTO GAIN CONTROL	LEVEL(0~20)Adjustment	
WHITE BALANCE	AUTO/AUTODEXT/PRESET/MANUAL	
PRIVACY MASKING	On / Off (Programmable 16 zones)	
DNR	OFF/LOW/MIDDLE/HIGH	
SMART IR	ANTI-SET (0~20)Adjustment	
LSC	OFF/ON	
GAMMA	0.45/0.5/0.55/0.6/0.65	
DEFOG	OFF/LOW/MIDDLE/HIGH	
DIGITAL ZOOM	OFF/ON (x1 ~ x8.0)	
DAEAD PIXEL COMPENSATI	LIVE DPC/ DPC SET	
SENS-UP	OFF/ X2~X32	
MOTION	4 AREA	
DIGITAL EFFECT	OFF / V-FLIP / MIRROR / ROTATE	
COMMUNICATION	UTC / RS485 (OPTION)	
IR LED	30PCS	
INPUT VOLTAGE	DC 12V(±10%)	
POWER CONSUMPTION	DC IR OFF : 180mA(±10%) / IR ON : 500mA(MAX)	
OPERATING TEMP. / HUM.	-10℃ ~ +50℃ / MAX 90% RH	
STORAGE TEMP. / HUM.	-20℃ ~ +60℃ / MAX 90% RH	

DIMENSION Unit : mm (Inch)

