

H.264 HD Series

RHE-828-J

8CH HD-SDI 1080P standalone DVR

1080P

Main Features

- 8CH HD-SDI video inputs
- Max 120/100 fps@1080p
- 8CH non-realtime 1080P or realtime 720P playback
- RS-485 serial interface
- One SATA device, 2 USB, RJ45(10/100/1000)

P2P connection solution




With easy QR code settings, you can monitor with smart phones and tablets over the internet from anywhere, anytime.

Model		RHE-828-J
Camera Input		8CH HD-SDI
Housing		J
Video	Input	HD-SDI (1080i@60fps, 1080i@50fps, 1080p@30fps, 1080p@25fps, 720p@60fps, 720p@50fps)
	Output	Max. 1920x1080 2 independent output: 1 HDMI with Audio, 1 VGA 1BNC (NTSC/PAL) bindable to either HDMI or VGA
Audio	Input	8 HD-SDI , 4 RCA
	Output	2 RCA
System	Operating System	Embedded Linux OS
	SATA Devices	Max. 1 x SATA Devices (HDDx1)
	External HDD	N/A
	Sensor In (NO, NC) Relay Out	Sensor-in x 4 Relay-out x 1
	Serial Interface	RS-485
	USB 2.0 Ports	2 x USB2.0
	Dimension (mm)	280(w)x51(h)x203(d)
	Power Rating	12V 3A,36W
Display	Split screen	1, 4, 8, SEQ.
	Auto Channel Switching	Switching time : 1 ~ 99 sec
	Mode	Zoom (Digital x2~ x5), PIP, Auto SEQ.
Recording	Compression	H.264 Main Profile
	Main (Recording) Resolution	8 x 1080P30@15fps(1920x1080) 8 x 720P30@30fps(1280x720)
	Sub (Network) Resolution	640x360
	Picture Quality	10~100 levels for adjustment
	Mode	Manual, Motion, Sensor, Schedule
	Record Rate	NTSC 1080p 120 fps / 720p 240fps PAL 1080p 100 fps / 720p 200fps
	Pre-Alarm	1 ~ 10 SEC
	Post-Alarm	1 ~ 100 SEC
Playback	Search mode	Date/time, Event
	Zoom	*Digital (x2 ~ x5)
Network	Network Interface	10/100/1000 Ethernet
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS
	Application	Windows XP/VISTA/7, Mac OS X
	Remote Software	iWatch DVR, IE Browser, iCMS
	Account	1 Admin + 10 Users
	Mobile Device System	Windows Phone 7.8, iPhone, iPad, Android
Backup	Interface	USB 2.0 or SATA
	Audio Backup	Yes
	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc
Alarm	Motion Detection	Sensitivity : 100 levels for each channel Area : Programmable individually
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
OSD & DVR Control	Multi-Language	Supported
	Camera Title	Multi-Language
	USB Mouse	Yes
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
	Remote Controller	IR Remote Control
	System Upgrade	USB Flash Drive, iWatch DVR
	Pan/Tilt/Zoom Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)

All specifications are subject to change without notice.

H.264 HD Series

RHE-828-J



iCatch Inc. www.icatchinc.com

2F, No. 26, Lane 513, RuiGuang Road, NeiHu District Taipei, Taiwan 114

Tel: 886-2-5550-6660 Fax: 886-2-5550-6670