

# KCE-CVDTI6536D2

## HD-SDI VARIFOCAL LENS IR VANDAL DOME CAMERA



- 1/2.9" 2.1Megapixel Sony Exmor CMOS SENSOR
- 0.02Lux(Sens-UP X32)
- 2.8~12mm DC IRIS MEGAPIXEL LENS (ICR)
- BUILT IN OSD CONTROLLER & 2nd BNC CONNECTOR
- DIGITAL NOISE REDUCTION
- MULTI LANGUAGE
- IP68 (INTERNATIONAL PROTECTION RATING)
- ICR FILTER CHANGE FUNCTION
- 3-AXIS WALL MOUNT BRACKET
- VIDEO OUTPUT : HD\_SDI, CVBS : 1.0Vp-p, 75Ω composite
- HD\_SDI(1080P(30P)/ 720P(30P)/720 CROP(60P)



DESCRIPTION	NTSC	PAL
IMAGE SENSOR	1/2.9	
EFFECTIVE PIXEL	1920 (H) × 1080 (V) = 2.07M	1920 (H) × 1080 (V) = 2.07M
SCANNING SYSTEM	Progressive	
SYNCHRONIZATION	Internal	
HORIZONTAL RESOLUTION	Full HD	
VIDEO OUTPUT	HD_SDI, CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y SIGNAL)	More than 52dB	
MIN. ILLUMINATION	0.02Lux(Sens-UP X32)	
IRIS ADJUSTMENT	ALC	
LENS	2.8~12mm DC IRIS MEGAPIXEL LENS (ICR)	
ELECTRONIC SHUTTER	AUTO(1/30~1/60,000)	AUTO(1/25~1/60,000)FLK
OSD LANGUAGE	ENG/CHN/CHN[S]	
	JPN/KOR	
BACKLIGHT COMPENSATION	OFF/HLC/BLC/WDR	
DAY & NIGHT	COLOR/BW/EXTERN/AUTO	
D-WDR	OFF/LOW/MIDDLE/HIGH	
AUTO GAIN CONTROL	LEVEL(0~20)Adjustment	
WHITE BALANCE	AUTO/AUTODEXT/PRESET/MANUAL	
PRIVACY MASKING	On / Off (Programmable 16 zones)	
DNR	OFF/LOW/MIDDLE/HIGH	
SMART IR	ANTI-SET (0~20)Adjustment	
LSC	OFF/ON	
GAMMA	0.45/0.5/0.55/0.6/0.65	
DEFOG	OFF/ON	
DIGITAL ZOOM	OFF/ON (x1 ~ x8.0)	
DEAD PIXEL COMPENSATION	LIVE DPC/ DPC SET	
SENS-UP	OFF/ X2~X32	
MOTION	4 AREA	
DIGITAL EFFECT	OFF / V-FLIP / MIRROR / ROTATE	
COMMUNICATION	RS485 (OPTION)	
IR LED	36PCS	
INPUT VOLTAGE	Dual Voltage	
POWER CONSUMPTION	DC IR OFF :150mA (±10%)	
	DC IR ON : 400mA (MAX)	
OPERATING TEMP. / HUM.	-10℃~+50℃/MAX90%RH	
STORAGE TEMP. / HUM.	-20℃~+60℃/MAX90%RH	