Scan Report

October 16, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "Lab03 Authenticated Scan". The scan started at Fri Oct 16 12:22:03 2026 UTC and ended at Fri Oct 16 12:44:35 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

1.1 Host Authentications 2

2 Results per Host **2**

2.1 10.0.5.4 2

2.1.1 Log 22/tcp 2

2.1.2 Log general/tcp 3

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
10.0.5.4	0	0	0	0	2	0
Total: 1	0	0	0	0	2	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Critical" are not shown.
Issues with the threat level "Debug" are not shown.
Issues with the threat level "False Positive" are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 2 results selected by the filtering described above. Before filtering there were 68 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
10.0.5.4	SSH	Success	Protocol SSH, Port 22, User gvmscan

2 Results per Host

2.1 10.0.5.4

Host scan start Fri Oct 16 12:23:25 2026 UTC
Host scan end Fri Oct 16 12:44:30 2026 UTC

Service (Port)	Threat Level
22/tcp	Log
general/tcp	Log

2.1.1 Log 22/tcp

Log (CVSS: 0.0)

NVT: SSH Login Successful For Authenticated Checks

Summary
It was possible to login using the provided SSH credentials. Hence authenticated checks are enabled.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Solution:

. . . continues on next page . . .

... continued from previous page ...

Log Method
Details: SSH Login Successful For Authenticated Checks
OID:1.3.6.1.4.1.25623.1.0.108540
Version used: 2023-07-28T16:09:07Z

[return to 10.0.5.4]

2.1.2 Log general/tcp

Log (CVSS: 0.0)
NVT: Authenticated Scan / LSC Info Consolidation (Linux/Unix SSH Login)

Summary
Consolidation and reporting of various technical information about authenticated scans / local security checks (LSC) via SSH for Linux/Unix targets.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Description (Knowledge base entry)
↪                                                                    : Value/Content
------------------------------------------------------------------------------------
↪-----------------------------------------------------------------------------------
↪-----------------------------------------------------------------------------------
↪-------------------------------------------------------------
Also use 'find' command to search for Applications enabled within 'Options for L
↪ocal Security Checks' (ssh/lsc/enable_find)                         : yes
Amount of timeouts the 'find' command has reached (ssh/lsc/find_timeout)
↪                                                                    : None
CPU Vendor / Vendor ID (gathered via 'cat /proc/cpuinfo') (ssh/login/cpu_vendor_
↪id)                                                                 : GenuineIntel
Clear received buffer before sending a command (ssh/force/clear_buffer)
↪                                                                    : FALSE
Commands are send via a pseudoterminal/pty (ssh/force/pty)
↪                                                                    : FALSE
Debugging enabled within 'Global variable settings' (global_settings/ssh/debug)
↪                                                                    : FALSE
Descend directories on other filesystem enabled within 'Options for Local Securi
↪ty Checks' (ssh/lsc/descend_ofs)                                    : yes
Don't prepend '/bin/sh -c' to used commands (ssh/force/nosh)
↪                                                                    : FALSE
Don't prepend 'LANG=C; LC_ALL=C;' to the '/bin/sh -c' commands (ssh/force/nolang
↪_sh)                                                                : FALSE
Elevate Privileges Feature: Enabled
↪                                                                    : FALSE
Folder exclusion regex for file search on Unixoide targets (ssh/lsc/search_exclu
↪de_paths)                                                           : ^(/(proc|afs|dev
↪|media|mnt|net|run|sfs|sys|tmp|udev|var/(backups|cache|lib|local|lock|log|mail
↪|opt|run|spool|tmp)|etc/init\.d|usr/share/doc)|.*/lost\+found)
FreeBSD package management tool available (ssh/login/freebsdpkg/available)
↪                                                                    : Not applicable f
↪or target
FreeBSD patchlevel (ssh/login/freebsdpatchlevel)
↪                                                                    : Not applicable f
↪or target
FreeBSD release (ssh/login/freebsdrel)
↪                                                                    : Not applicable f
↪or target
Fully Qualified Domain Name (FQDN) (ssh/login/fqdn)
↪                                                                    : lab03-target
Hardware Product Serial Number (ssh/login/product_serial)
↪                                                                    : FALSE
Hardware Product UUID (ssh/login/product_uuid)
↪                                                                    : FALSE
Ignore packages of inactive Linux kernels (ssh/login/ignore_inactive_kernels/ena
```

... continues on next page ...

... continued from previous page ...

```
↪bled)                                                          : FALSE
Integer that sets the directory depth when using 'find' on unixoide systems (ssh
↪/lsc/find_maxdepth)                                            : 12
Login on a system with a restricted shell (ssh/restricted_shell)
↪                                                               : FALSE
Login on a system without common commands like 'cat' or 'find' (ssh/no_linux_she
↪ll)                                                            : FALSE
Login via SSH failed (login/SSH/failed)
↪                                                               : FALSE
Login via SSH successful (login/SSH/success)
↪                                                               : TRUE
Mac OS X build (ssh/login/osx_build)
↪                                                               : Not applicable f
↪or target
Mac OS X release name (ssh/login/osx_name)
↪                                                               : Not applicable f
↪or target
Mac OS X version (ssh/login/osx_version)
↪                                                               : Not applicable f
↪or target
Machine ID (ssh/login/machine_id)
↪                                                               : 42fc3691ea804ec8
↪a0d92b51411fe34c
Machine hardware name (gathered via 'uname -m') (ssh/login/arch)
↪                                                               : x86_64
Misconfigured CISCO device. No autocommand should be configured for the scanning
↪ user. (ssh/cisco/broken_autocommand)                          : FALSE
OpenBSD version (ssh/login/openbsdversion)
↪                                                               : Not applicable f
↪or target
Operating System Key (used for Notus based Local Security Checks) (ssh/login/rel
↪ease_notus)                                                    : FALSE
Operating System Key (used for e.g. classic Local Security Checks) (ssh/login/re
↪lease)                                                         : UBUNTU24.04 LTS
Port used for authenticated scans (kb_ssh_transport())
↪                                                               : 22/tcp
Report vulnerabilities of inactive Linux Kernel(s) separately (only for GOS 21.0
↪4 and older) (ssh/login/kernel_reporting_overwrite/enabled)    : FALSE
Response to 'uname -a' command (ssh/login/uname)
↪                                                               : Linux lab03-targ
↪et 6.8.0-146-generic #146-Ubuntu SMP PREEMPT_DYNAMIC Thu Sep  3 16:12:30 UTC 2
↪026 x86_64 x86_64 x86_64 GNU/Linux
Send an extra command (ssh/send_extra_cmd)
↪                                                               : FALSE
Solaris hardware type (ssh/login/solhardwaretype)
↪                                                               : Not applicable f
↪or target
Solaris version (ssh/login/solosversion)
↪                                                               : Not applicable f
↪or target
The SSH session/connection is re-opened before sending each command (ssh/force/r
↪econnect)                                                      : FALSE
Use 'su - USER' option on SSH commands (ssh/lsc/use_su)
↪                                                               : FALSE
Use this user for 'su - USER' option on SSH commands (ssh/lsc/su_user)
↪                                                               : FALSE
User used for authenticated scans (kb_ssh_login())
↪                                                               : gvmscan
locate: Command available (ssh/locate/available)
↪                                                               : FALSE
locate: Response to 'locate -S' command (ssh/locate/broken)
↪                                                               : /bin/sh: 1: loca
↪te: not found
rpm: Access to the RPM database failed (ssh/login/failed_rpm_db_access)
↪                                                               : FALSE
NOTE: The locate command seems to be unavailable for this user/account/system. T
↪his command is highly recommended for authenticated scans to improve the searc
↪h performance on the target system. Please see the output above for a possible
↪ hint / reason why this command is not available.
```

Solution:

... continues on next page ...

. . . continued from previous page . . .

Log Method
Details: Authenticated Scan / LSC Info Consolidation (Linux/Unix SSH Login)
OID:1.3.6.1.4.1.25623.1.0.108162
Version used: 2026-09-04T15:37:29Z

References
url: https://docs.greenbone.net/GSM-Manual/gos-25.0/en/scanning.html#requirements-on-target-systems-with-linux-unix
url: https://docs.greenbone.net/GSM-Manual/gos-24.10/en/scanning.html#requirements-on-target-systems-with-linux-unix

[return to 10.0.5.4]