

Creating Forms Using Formik



Nitin Singh

Full-stack Developer



Overview



Disadvantages of using vanilla React for creating forms

Understanding how Formik overcomes these problems

Components provided by Formik

Understanding how Formik maintains input and error states for fields


Helpers provided by Formik for common operations



Problems with Using Vanilla React for Forms



Very verbose



**Repetitive code for
maintaining state and
handling callbacks**



Error prone

Formik is a library that solves all the above problems with writing controlled React forms.




Salient Features of Formik




Automatically keeps track of values, errors and visited fields



Automatically hooks up appropriate callback functions on form elements



Provides helpers for sync and async validations and showing error messages



Provides sensible defaults for common functionalities while allowing maximum customization



Setting up Formik in Your App



To install formik run: `npm install formik --save`



You don't need to migrate all forms in your app at once



Replace the form and form-element tags in your components with respective Formik components



Key Formik Components

1

`<Formik>`

2

`<Form>`

3

`<Field>`

4


`<ErrorMessage>`




```
<Formik >
  <Form>
    <label htmlFor="firstName">First Name</label>
    <Field name="firstName" type="text" />
    <ErrorMessage name="firstName" />
    <button type="submit">Submit</button>
  </Form>
</Formik>
```

Anatomy of a Formik Form


<Formik> Component



This is the top-level component which controls all other components



Responsible for keeping track of state for the field components using their “name” attribute as key



Responsible for injecting and handling callbacks for field components



Provides properties to set initial values, validation function and handle callbacks like submit and reset




Allows rendering via children and custom components



How Formik Maintains State for Form Fields

Formik maintains three maps to automatically track the state of all the `<Field>` tags it contains.



K	V


values

Map of the `<Field>` tags' name to its user input value



errors

Map of the `<Field>` tags' name to the error string returned by validation functions



touched

Map of the `<Field>` tags' name to a boolean indicating whether it was ever focused or not




<Form> Component



Wrapper around HTML `<form>` tag



Automatically hooks parent Formik's on submit and reset callbacks into the HTML form



Extra props are passed to the DOM directly



<Field> Component



By default it renders a HTML `<input>` tag



Uses the name attribute on the `<Field>` to match up with the Formik state



`<Formik>` will automatically inject `onChange`, `onBlur` and `value` attributes for all `<Field>` tags



To render a non-input tag set the “as” attribute of the `<Field>` tag to `textarea`, `select` or any custom component



Allows for field level validation via the `validate` attribute




<ErrorMessage> Component



Represents error message for the <Field> tag whose “name” attribute matches with its own “name” attribute



The message to render is always expected to be a string



Fully custom rendering supported via children, component and render properties



```
<Formik
```

```
  initialValues={{ username: 'jared' }}
```

```
  validate={(values, props) => {
```

```
    // ..validation logic
```

```
  }}
```

```
  onSubmit={(values, actions) => {
```

```
    const uname = values.username
```

```
  }}>
```

```
{props => (
```

```
  <Form>
```

```
    <Field name="username" type="text" />
```

```
  </Form>
```

```
)}
```

```
</Formik>
```

- ◀ Set initial values for the Fields as a JSON object with <Field> tag's name as key
- ◀ Business logic to validate input and return an error JSON object with <Field> tag's name as key
- ◀ Handle form submission
- ◀ Use the props variable to access Formik's helper functions
- ◀ <Field> tag that maps to <input> tag of type text



Bugs, Bugs, Everywhere!

Even if your form is empty by default, you must initialize all fields with initial values. Otherwise React will throw an error saying that you have changed an input from uncontrolled to controlled.



Key <Formik> Helper Props

1

isSubmitting

Indicates if form is
under submission

2

setSubmitting(bool)

Set a form's
submission phase

3

isValid

Indicates if form input
is valid

4

isValidating

Indicates if form is
being validated


5

resetForm(values)

Reset form using
given values



Handling Form Submission



On form submission the `onSubmit` callback on the `<Formik>` tag is invoked with the field values and validations are run



The `onSubmit` can be sync or it can be async and return a Promise



In sync `onSubmit` call `setSubmitting(false)` to indicate end of submission



Demo



Invoice tracker application

Install Formik in the project

Rewrite Sign In form using Formik

Add validation for all fields as earlier

**Disable submit button post click using
Formik helpers and make API call**



Summary



Downsides of using vanilla React to create forms

Salient features of Formik that help write concise form components

Various components provided by Formik and their properties

How Formik maps fields to values, errors automatically

Most useful helpers provided by Formik for common form operations



Up Next:
Implementing Data Validation

