

Oracle® Retail POS Suite

Operations Guide

Release 13.4.1

E29184-01

March 2012

Copyright © 2012, Oracle and/or its affiliates. All rights reserved.

Primary Author: Graham Fredrickson

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as **Access Via**™ licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as **Adobe Flex**™ licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Send Us Your Comments	viii
Preface	x
Audience.....	x
Documentation Accessibility	x
Related Documents	xi
Customer Support	xi
Review Patch Documentation	xi
Oracle Retail Documentation on the Oracle Technology Network	xii
Conventions	xii
 1 Data Purge	
Invoking Stored Procedures.....	1-2
Stored Procedures on Oracle	1-2
Stored Procedures on DB2	1-3
Calls to Invoke Stored Procedures.....	1-3
Data Purge Scripts.....	1-4
Restricting Access To Data Purge Scripts	1-5
 2 Database Downtime in Central Office	

List of Examples

1-1	Invoking The Stored Procedures—SQL Plus Method 1	1-2
1-2	Invoking The Stored Procedures—SQL Plus Method 2	1-2
1-3	Invoking The Stored Procedures—SQL Plus Method 3	1-2
1-4	Invoking The Stored Procedures—DB2 Method	1-3

List of Tables

1-1	Stored Procedure Calls.....	1-3
-----	-----------------------------	-----

Send Us Your Comments

Oracle Retail POS Suite Operations Guide, Release 13.4.1

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the new Applications Release Online Documentation CD available on My Oracle Support and www.oracle.com. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address: retail-doc_us@oracle.com

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at www.oracle.com.

Preface

Oracle Retail Operations Guides are designed so that you can view and understand the application's behind-the-scenes processing, including such information as the following:

- Key system administration configuration settings
- Technical architecture
- Functional integration dataflow across the enterprise
- Batch processing

Audience

Anyone who has an interest in better understanding the inner workings of the Oracle Retail POS Suite system can find valuable information in this guide. There

are three audiences in general for whom this guide is written:

- Systems analysts and system operations personnel who need information about Oracle Retail POS Suite processes.
- Integrators and implementers who are responsible for implementing POS Suite.
- Business analysts who need information about Oracle Retail POS Suite processes and interfaces.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

Related Documents

For more information, see the following Release 13.4.1 documentation sets or Oracle Retail Returns Management Release 2.4.1 documentation set:

- Oracle Retail Back Office documentation set
- Oracle Retail Central Office documentation set
- Oracle Retail Labels and Tags documentation set
- Oracle Retail Point-of-Service documentation set
- Oracle Retail Returns Management documentation set

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.4) or a later patch release (for example, 13.4.1). If you are installing the base release, additional patch, and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation. Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

http://www.oracle.com/technology/documentation/oracle_retail.html

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Data Purge

Data purging is based upon logical sets of data. Logical sets of data can be contained in multiple tables. An example of a logical set of data is all the records associated to a particular Retail Transaction.

A purge of a logical set is not considered complete until all relevant rows of data are deleted.

Data purging is based upon a data-retention schedule whereupon all data existing prior to the computed date are purged. The data within this timeframe must meet constraints as required. For example, if a customer wants to retain the last 180 days worth of retail transaction data, then the integer 180 should be passed into the purge retail transaction routine and the system will purge COMPLETED transactions more than 180 days old.

The stored procedures reads the absolute value of a negative integer. For example, a value of **-30** passed into the stored procedures will be read as **30**, and the data will be retained for 30 days.

If no value is passed into the stored procedures, then the default value is used. The default value is 30.

The number of data retention days is passed into the stored procedures. The constraints are built into the stored procedures and are therefore not parameterized.

A logical set purge will succeed even if data is not found in an expected table.

The Financial History and Financial Summary data purge scripts do not address the issue of the weekly sum of daily totals that will no longer match weekly totals. For example, if the purge occurs on a Wednesday, the sum of the daily totals from Wednesday through Saturday will not match the weekly total that was based upon a Sunday through Saturday timeframe.

Caution: Passing in a **zero (0)** as a parameter to the purge transaction routines will result in the deletion of all completed transactional data. Oracle is not responsible for loss or damage of any sort that might incur from passing in zero as a parameter.

The customer is fully responsible for the database configuration. Oracle assumes the purge routines will operate within the confines of the database configuration, such as the size of the rollback segments and other such parameters that might affect the functioning of the purge routines.

Invoking Stored Procedures

The following are examples how to invoke stored procedures for both Oracle and DB2 databases:

Note: It is assumed that the user calling the stored procedures has the necessary privileges to invoke these procedures.

Stored Procedures on Oracle

The following examples show how to invoke the stored procedures on an Oracle database:

Example 1–1 Invoking The Stored Procedures—SQL Plus Method 1

```
SQL> EXECUTE <procedure name (parameters)>;
```

Example:

```
EXECUTE PURGE_FN_SMY(90);
```

Example 1–2 Invoking The Stored Procedures—SQL Plus Method 2

```
SQL> BEGIN
SQL> <procedure name (parameters)>;
SQL> END;
```

Example:

```
SQL> BEGIN
SQL> PURGE_FN_SMY(90);
SQL> END;
```

Example 1–3 Invoking The Stored Procedures—SQL Plus Method 3

```
SQL> CALL <procedure name (parameters)>;
```

Example:

```
CALL PURGE_FN_SMY(90);
```

You can choose to create a script file that contains these commands and have a scheduler execute the script on a nightly basis. To do this, you must be logged into the database.

The scheduler must be able to log in to the database to be able to run the scripts, or the log in must be the first line in the script.

Stored Procedures on DB2

The following example shows how to invoke the stored procedures on a DB2 database:

Example 1–4 Invoking The Stored Procedures—DB2 Method

```
DB2=> CALL <procedure name (parameters)>;
```

Example:

```
CALL PURGE_FN_SMY(90);
```

You can choose to create a script file that contains these commands and have a scheduler execute the script on a nightly basis. To do this, you must be logged into the database.

The scheduler must be able to log in to the database to be able to run the scripts, or the log in must be the first line in the script.

Calls to Invoke Stored Procedures

Table 1–1 contains the calls to use to invoke stored procedures.

Table 1–1 Stored Procedure Calls

Subject Area	Procedure Call	Description
Advanced Pricing Rules	PURGE_PRDV(<Number of Retention Days>)	Removes all advanced pricing rules older than the specified number of retention days.
Control Transactions	PURGE_CTL_TRN(<Number of Retention Days>)	Removes all Store Operation, Void, NoSale, and BankDeposit transactions older than the specified number of retention days.
Duplicate Price Changes	PURGE_DUP_PRC_CHN_EV()	Removes all duplicated price change events older than the current date.
eJournal	PURGE_EJRL(<Number of Retention Days>)	Removes all EJournal tape records older than the specified number of retention days.
Financial Histories	PURGE_FN_HST(<Number of Retention Days>)	Removes all financial totals from history tables older than the specified number of retention days.
Financial Summaries	PURGE_FN_SMY(<Number of Retention Days>)	Removes all aggregate financial totals from summary tables older than the specified number of retention days.
Financial Transaction	PURGE_FN_TRN(<Number of Retention Days>)	Removes all Financial transaction-related tables that are older than the number of retention days specified and meeting the identified constraints then executes the PURGE_TRN procedure.
Layaways	PURGE_LY(<Number of Retention Days>)	Removes all Layaways in the completed, deleted, suspended, and voided status older than the specified number of retention days.
Orders	PURGE_ORD(<Number of Retention Days>)	Removes all Orders in the complete, canceled, suspended, and voided status older than the specified number of retention days.
Price Changes	PURGE_PRC_CHN_EV(<Number of Retention Days>)	Removes all permanent price changes older than the specified number of retention days.

Table 1–1 (Cont.) Stored Procedure Calls

Subject Area	Procedure Call	Description
Promotions	PURGE_TMP_PRC_EV(<Number of Retention Days>)	Removes all expired temporary price changes (promotions) older than the specified number of retention days.
Retail Transactions	PURGE_RTL_TRN(<Number of Retention Days>)	Removes all Sale, Return, House Account Payment, Instant Credit Enrollment, and Redeem transaction types older than specified number of retention days.
Retail Transaction Common	PURGE_RTL_TRN_COMMON	Removes immediate RetailTransaction-related tables and also executes other purges common to all Retail Transactions that meet the passed in criteria. Note: This routine is only called by other purge routines and not directly executed.
Retail Transaction Line Item	PURGE_RTL_TRN_LTM	Removes all immediate RetailTransaction-related child tables that meet the passed in criteria. Note: This routine is only called by PURGE_RTL_TRN_COMMON and not directly executed.
Sale Return Line Item	PURGE_SLS_RTN_LTM	Removes all immediate SaleReturnLineItem-related child tables that are older than the number of retention days specified. Note: This routine is only called by PURGE_RTL_TRN_COMMON and not directly executed.
Tender Line Item	PURGE_TND_LTM	Removes tender line items from a specific transaction. In the script, a specific transaction ID has to be specified.
Training Mode Transactions	PURGE_TRG_TRN(<Number of Retention Days>)	Removes all transactions performed in training mode older than the specified number of retention days.
Transaction	PURGE_TRN	Removes all transaction header tables that meet the purge criteria.

Data Purge Scripts

The following data purge scripts are available for Back Office, Central Office, Point-of-Service, and Returns Management:

- CreateProcedurePurgeAdvancedPricing.sql
- CreateProcedurePurgeControlTransaction.sql
- CreateProcedurePurgeDuplicatePriceChangeEvent.sql
- CreateProcedurePurgeEJournal.sql
- CreateProcedurePurgeFinancialHistory.sql
- CreateProcedurePurgeFinancialSummary.sql
- CreateProcedurePurgeFinancialTransaction.sql
- CreateProcedurePurgeLayaway.sql
- CreateProcedurePurgeOrder.sql

- CreateProcedurePurgePriceChangeEvent.sql
- CreateProcedurePurgePromotionEvent.sql
- CreateProcedurePurgeRetailTransaction.sql
- CreateProcedurePurgeRetailTransactionCommon.sql
- CreateProcedurePurgeRetailTransactionLineItem.sql
- CreateProcedurePurgeSaleReturnLineItem.sql
- CreateProcedurePurgeTenderLineItem.sql
- CreateProcedurePurgeTrainingModeTransaction.sql
- CreateProcedurePurgeTransaction.sql

Restricting Access To Data Purge Scripts

For more information about restricting access to data purge scripts, see the *Oracle Retail POS Suite Security Guide*.

Database Downtime in Central Office

When the Central Office database is down for maintenance or backing up, the Central Office application should be brought down as well. See your application server documentation for information on stopping the application server container running Central Office.

While the Central Office database is down, Point-of-Service continues sending messages containing retail transaction information to Central Office. This information cannot be persisted in the Central Office database until the database is once again available. If the database remains down, and the number of messages, sends, and retries exceeds a specified number, Point-of-Service stops attempting to send the messages to Central Office and instead places the messages into an error queue. At that point, manual intervention is required to resend the messages from Point-of-Service or to retrieve the messages from the error queue.

