MSC ARTIFICIAL INTELLIGENCE DISSERTATION


Learning to Select Actions for Complex Hand Tasks

A comparative study of visuomotor policies and latent world models

Graham Pellegrini
Supervised by Prof. Alexiei Dingli
Department of Artificial Intelligence, Faculty of ICT, University of Malta


What is a policy?

A policy is a model that learns from demonstrations (human, robot or simulated) to turn the current scene into a chunk of future actions.




In this study, input: the current scene






In this study, output: an action chunk, the next 16 wrist poses for both hands (18 numbers per step)

The problem of selection in a policy



Different latent or noise samples give different candidates.
Candidate 0 is the policy's default output: z = 0 for ACT, the first sample for Diffusion Policy.




$$e_t = e_{t-1} + \delta_t = \delta_1 + \ldots + \delta_t$$

Suboptimal candidate → compounding error

→ unsuccessful or dangerous state


Why world models, not a VLA

A VLA maps the scene straight to an action, without predicting its consequences. A world model predicts those consequences first.




Screenshot from Welch Labs, Yann LeCun's $1B Bet Against LLMs (2026). Highlights added.

DIWA: THE PAPER WE BUILD ON



OUR APPROACH: EXTERNAL WORLD-MODEL SELECTION



Left: Chandra et al. (2025), evaluated on CALVIN. This study reproduces (c). Right: illustrative frames.


RESEARCH QUESTION

Can a frozen world model, used externally to select among a policy's sampled candidates, reduce error compared with a single policy output?

Tested offline, with the world model acting only as the final decision stage over candidates the policy already proposed.

- How much does it help, and for which policy and world-model pairings?
- When does selection fail, and why?
- How does selecting compare with finetuning the policy inside a world model (DiWA on CALVIN)?

Dataset: EgoDex



Recorded with Apple Vision Pro, both hands tracked at 30 frames per second

EgoDex full release

829 hours, 338k episodes, 194 tasks

Training parts

1 2 3

Our training: parts 1 to 3

63 tasks, 194,333 episodes, 430,962 windows

4 5

not used


Official test set

111 tasks
3,229 episodes
7,607 windows

never used in training

Windowing scheme and data representation





18 numbers per step


Per wrist: 3 position + 6 orientation (6-D rotation encoding)

12 DoF in total, 6 per wrist. Poses come from the headset's hand tracking.

430,962
TRAINING WINDOWS

7,607
TEST WINDOWS

THE METHOD



K = 5
CANDIDATES PER WINDOW

3 seeds
POOLED RESULTS

COMPUTE CONSTRAINTS


Understanding candidate selection

random, not tunable

Diffusion Policy
how it selects




ACT
how it selects



No selection

Candidate 0 = the policy run once.
The first sample or z = 0,
and it is kept.

World model
how it improves it




Selection

Candidate 3 has the highest plausibility score.

Never sees the real motion.
True error is measured afterwards.

Posterior collapse


Diffusion Policy



Five genuinely different motions

independent pool, clean measurement

ACT



Five copies of one motion

no diversity, so selection has nothing to choose between

Diffusion Policy denoises Gaussian noise into a motion over DDIM steps. 5 independent noise samples give 5 candidates.

ACT is a CVAE, where a latent z sampled at test time should vary the motion. Posterior collapse means the decoder learned to ignore z, so all 5 samples are the same motion.

ACT: four latent training configurations


RUN	RECIPE	WHAT IT IS MEANT TO DO
v1	KL weight 10, the standard recipe	Baseline: the decoder can ignore z
v2	KL weight 100	Penalise information in z ten times harder
v3	Cyclical KL annealing and 30% observation dropout	Ease the penalty in cycles and hide observations, so the decoder must lean on z
v4	Cyclical KL annealing and free bits, 0.5 nats per dimension	Let z carry a minimum amount of information for free

No diversity

- All five samples identical
- Differences below 10^{-6}
- Posterior collapse

CEMP: Cross-Entropy Method with Policy


Cross-entropy method, started from the policy's output (inspired by TD-MPC2).



The same world model builds the pool and then picks from it, so the pool already leans towards what that world model prefers.

ACT results therefore measure the world model and the planner as one unit.

CEMP only applied where needed




Only seed 42 needed CEMP, so seeds 43 and 44 were scored on ACT's own candidates. The pooled ACT result therefore mixes a world-model-plus-planner measurement with a plain scorer measurement. Read it as one result for this rule, not as a clean measurement of the scorer. This is why Diffusion Policy carries the main claim.

5 world models, 1 validated gain

MODEL	WHAT IT IS	GAIN	WHAT IT SHOWED
V-JEPA2-AC	Frozen video-pretrained encoder, our action head	-5.98%	Validated: its score tracks the true error
DexWM	Frozen DINOv2 encoder, second predictor and a hand-consistency head	+0.57%	No gain, single seed
LeWM	Small, compact, trained end to end, no pretrained encoder	-10.1%	Big gain, but its scores did not track the true error, so the gain is not from its predictions
V-JEPA2, no action	Control: same model, action input set to zero	0.00%	Every score ties: the motion is what matters
PointWorld proxy	Weakened motion input	+0.27%	No gain
DINO-WM, JEPA-WM	Official robot checkpoints, smoke-tested only	latent only	Interface mismatch: 18-D hand motion squeezed into 7-D robot actions


Translation error change, Diffusion Policy, Branch 2, matched training exposure. ACT with CEMP gave -0.58%, read as one unit (slides 12 to 14). LeWM detail: Backups B and C.

Ranking Diffusion Policy candidates with V-JEPA2-AC cuts translation error by 5.98%



The gain comes from reading each candidate's motion, not from the video backbone. Pooled across three seeds, 95% CI [5.43, 6.47], no retraining. Rotation error -0.96°. Win / tie / loss 49.9 / 23.2 / 27.0%. Branch 3: 5.37% of a 14.68% ceiling. The ceiling is what a perfect selector could remove from the same five candidates.

Secondary study on DiWA's own benchmark




4 tasks
CALVIN MANIPULATION SKILLS

~100 episodes
PER TASK, ABOUT 33 PER SEED

3 seeds
42, 43 AND 44


Success rate
% OF EPISODES COMPLETED

Finetuning > external selection



Task success rate (%), CALVIN. Selection (C2) is within noise of the policy alone (C1) on every task; finetuning (C3b) adds 14 to 40 points.

What a world model needs to help



Diverse pool

The candidates must be genuinely different motions, or there is nothing to choose between.

Action information


The score must depend on each candidate's motion. Without it, every score ties.

In-support candidates


Candidates must be close to the scorer's training data, so its predictions can be trusted.

Diffusion Policy + V-JEPA2-AC ● ● ●
DiWA, by design ● ● ●
ACT, collapsed ○ ● ●
No-action control ● ○ ●
7-D adapters ● ● ○

DIWA (ILLUSTRATIVE)



OUR SELECTION



Finetuning improves the policy. Selection improves the choice.

Conclusion, limitation and future work

1

CONCLUSION

External selection helps

A frozen world model picked better motions from the policy's own candidates: 5.98% lower error, no retraining, when the three conditions hold.

2

LIMITATION

Time and compute

K = 5, three seeds, EgoDex parts 1 to 3. Larger K, more seeds and more world models would firm up the result.

3

FUTURE WORK

Close the loop

Run it on a robot in M.AI.ESTRO and score task success, not just plausibility.

THANK YOU FOR LISTENING

Questions


Graham Pellegrini
graham.pellegrini@um.edu.mt

Which published work anchored each choice

Diffusion sampling	→	DDIM (Song et al.), DP-T (Chi et al.)	Implemented
ACT collapse fixes	→	KL annealing (Fu et al.), free bits (Kingma et al.)	Tried, failed
Candidate search for ACT (CEMP)	→	Cross-entropy method, inspired by TD-MPC2	Adapted
Action-conditioned scorer	→	V-JEPA2-AC (Assran et al.)	Head trained locally
Finetuning comparison	→	DiWA (Chandra et al.) on CALVIN	Reproduced
K = 5, 100,000-item exposure	→	No paper: compute budget	Compute choice

LeWM variants

Rollout scorer: predictor + selection




-10.09%

≈

Action-prior scorer: a typicality filter + selection

no world model, no frames





-10.24%

Almost the same gain, and only the rollout scorer uses LeWM's learned dynamics. So the gain comes from how typical the motion is, not from prediction.

Does the score order match the true order?

Spearman rank correlation: how well the world model's ranking of the candidates matches their true ranking. Gain says how much error drops; correlation says whether the ranking is right.






V-JEPA2-AC: per window, candidate scores against candidate errors (K = 5, pooled seeds). LeWM: across windows, score margin against true improvement (+0.54 on a 512-window check, -0.51 on all 7,607). The no-action control ties every score.

The result holds at every seed, and the controls behave as designed

	SEED 42	SEED 43	SEED 44
Baseline translation error	0.1142	0.1178	0.1191
V-JEPA2-AC, Branch 2	-6.41%	-6.09%	-5.46%
V-JEPA2 without action input	0.00%	0.00%	0.00%
PointWorld proxy	+0.50%	+0.23%	+0.07%
LeWM rollout (unvalidated)	-10.10%	-10.06%	-10.12%

Three seeds are a basic robustness check, not proof of stability. DexWM is single-seed by a cost decision of roughly 121 extra GPU-hours.


More candidates buy more headroom, not a better scorer



Capture	K = 2	K = 3	K = 4	K = 5	K = 6	K = 8	K = 10	K = 12	K = 16	K = 20
	40%	38%	38%	38%	38%	37%	38%	37%	37%	37%


Seed 42, Branch 2, nested pools. More candidates raise the ceiling, but they come from the same policy and capture stays about flat, so the scorer, not K, limits the gain.

On the easiest fifth of windows, selection makes things worse



Windows sorted by baseline error, K = 8, Branch 2. Translation error rises 5.81% in Q1. Confidence gating does not help, because the score gap has a correlation of -0.002 with baseline error. A state-change-targeted windowing removes most of the reversal.

How error is measured



16 future steps, both wrists

Translation error = average, over the 16 steps and both wrists, of the root-mean-square position error per axis (metres)

Gain = mean error of the chosen candidate ÷ mean error of candidate 0, minus 1


Rotation error is the same idea for orientation: the mean geodesic angle in degrees. Error is always measured against the recorded human motion, which the world model never sees.

Objective achievement

OBJ.	STATUS	BASIS
1	Fully	Three-branch benchmark implemented as designed and used for every family reported
2	Partly	Local exposure matched, externally pretrained backbones carry an advantage not equalised
3	Within tested configurations	Whether and when selection helps determined for every combination, one positive, a likely explanation for each other


Objectives 4 and 5 are in the Conclusion chapter's objective table. Every non-positive-route explanation is the study's own interpretation, not independently proven.

We reproduced DiWA's finetuning




Success rate (%), CALVIN, three seeds, the authors' released checkpoints. Within 5 points on every task; base policy within 7 (Q&A 3). The behaviour-cloning weight was set to the paper's values after a run at zero collapsed two tasks.

Where each pick ranks among the five



Seed 42, 7,607 windows, ranked by true translation error. Candidate 0 is spread evenly, like a random pick. The world model finds the best candidate about 1.8 times as often as chance.

How AI was used: a human-led workflow



References cited in this deck

- Assran et al. (2025). V-JEPA 2: Self-Supervised Video Models Enable Understanding, Prediction and Planning.
- Chandra et al. (2025). DiWA: Diffusion Policy Adaptation with World Models. CoRL.
- Chi et al. (2023). Diffusion Policy: Visuomotor Policy Learning via Action Diffusion. RSS.
- Fu et al. (2019). Cyclical Annealing Schedule: A Simple Approach to Mitigating KL Vanishing. NAACL.
- Goswami et al. (2025). World Models for Learning Dexterous Hand-Object Interactions from Human Videos.
- Hansen et al. (2024). TD-MPC2: Scalable, Robust World Models for Continuous Control. ICLR.
- Hoque et al. (2026). EgoDex: Learning Dexterous Manipulation from Large-Scale Egocentric Video. ICLR.
- Huang et al. (2026). PointWorld: Scaling 3D World Models for In-The-Wild Robotic Manipulation. CVPR.
- Kingma and Welling (2014). Auto-Encoding Variational Bayes. ICLR.
- LeCun (2022). A Path Towards Autonomous Machine Intelligence, v0.9.2.
- Maes et al. (2026). LeWorldModel: Stable End-to-End Joint-Embedding Predictive Architecture from Pixels.
- Mees et al. (2022). CALVIN: A Benchmark for Language-Conditioned Policy Learning for Long-Horizon Robot Manipulation. RA-L.
- Rubinstein and Kroese (2004). The Cross-Entropy Method.
- Song et al. (2021). Denoising Diffusion Implicit Models. ICLR.
- Terver et al. (2026). What Drives Success in Physical Planning with Joint-Embedding Predictive World Models?
- Welch Labs (2026). Yann LeCun's $1B Bet Against LLMs. Video essay.
- Zhao et al. (2023). Learning Fine-Grained Bimanual Manipulation with Low-Cost Hardware (ACT). RSS.
- Zhou et al. (2025). DINO-WM: World Models on Pre-Trained Visual Features Enable Zero-Shot Planning. ICML.