Graine

IN-APP AGENTS · DOCUMENTATION

Graine In-App Integration Guide

Your AI agent inside your app and on your website — chat, voice, WhatsApp-style calls both ways and scheduled calls. Every platform: iOS, Android, Kotlin Multiplatform, Flutter, React Native and the web. Release 0.10.1.

Online, always current: www.graine.ai/docs/in-app/integration-guide

Printed 15 October 2026

Integration guide: apps and website

The one page your team starts from — release 0.10.1, no meeting needed: the versions, a first success in 30 minutes, the dashboard set up from scratch, install and initialise on React Native, iOS, Android, Flutter, Kotlin Multiplatform and the web, every use case with its code, variables, calls both ways and their messages, booking with the SDK's sheet, data and privacy, error codes, the QA script and the go-live checklist.

This guide takes your team from nothing to a launched agent in your app and on your website — talking, chatting, seeing the screen, acting on it, remembering each user, booking calls and calling them like WhatsApp — with no meeting. It is written for release **0.10.1**, and every part links to the page that covers it in depth.

Start here — no meeting needed

Everything your engineers need is in this guide, the SDK references and the demo apps. Read in the order below; if anything blocks you, write to us (at the end of this section) and we answer by email.

What you receive

	What it is
This guide	Online at www.graine.ai/docs/in-app/integration-guide, and as a PDF in your integration pack: the setup, every use case with its code on every platform, variables, calls, the QA script and the go-live checklist
One SDK reference per platform	Every public function, property, event, error and type, with its signature, parameters, what it returns, the errors it raises and what to expect — grouped by use case, then A to Z: React Native, iOS, Android, Flutter, Kotlin Multiplatform, Website
The demo apps	Working apps for React Native, Flutter, iOS, Android, Kotlin Multiplatform and the web, each with two agents. **RUN-THE-DEMO.md** in the demo runs them with your own agents; **agent-setup/SETUP.md** recreates the demo's agents in your workspace

The versions

Platform	Package	Version	Install	R o
iOS (Swift; Objective-C too)	`GraineInApp`	**0.10.1**	Swift Package Manager: `https://github.com/GraineAI/inapp-ios`, from 0.10.1	iO 1 X 1
Android (Kotlin, Java)	`ai.graine:inapp-android`	**0.10.1**	`implementation("ai.graine:inapp-android:0.10.1")`	A 7 2
Flutter	`graine_inapp`	**0.10.1**	`graine_inapp: ^0.10.1`	F 3
React Native	`@graineai/inapp-react-native`, and `@graineai/inapp-react-native-calls` for calls	**0.44.1** and **0.5.1**	`npm install @graineai/inapp-react-native@0.44.1 @graineai/inapp-react-native-calls@0.5.1`	R N 0 (n b n E G
Kotlin Multiplatform	`ai.graine:inapp-kmp`, `ai.graine:inapp-kmp-compose`	**0.10.1**	`implementation("ai.graine:inapp-kmp:0.10.1")`	K 2 A 7 1
Website	The loader	Always current	`<script src="https://www.graine.ai/embed/v1.js"></script>`	A n b
Calls over WebRTC (optional)	iOS `GraineInAppRTC`, Android `ai.graine:inapp-`	The SDK's own	Calls over WebRTC	A S

Platform	Package	Version	Install	R o
	`android-rtc`; React Native and Flutter: a build switch			

The iOS pod (`pod 'GraineInApp', '~> 0.10'`) builds the same sources. The source of every native SDK is public: github.com/GraineAI.

The order to read

1. **This section**, then What you build and How it works.
2. Set up everything from scratch — the dashboard, in order, with screenshots.
3. Install and initialise on your platform.
4. The use cases you need — each with the exact code on every platform, the dashboard settings it needs and a troubleshooting table.
5. **Your platform's SDK reference**, as you code.
6. The QA script and the go-live checklist.

A first success in 30 minutes

1. **An agent.** Create one in the dashboard (or clone yours), and try it there.
2. **Its key and your app.** Agent → Embed & Widgets → **Set up embedding** → **Install**: copy the `pk_live_…` key, and add `app://` (and your website hosts) to **Allowed domains**.
3. **The SDK** — install and initialise: configure it once at launch with the key, and put the bar on screen.
4. **Open the bar.** The launcher appears in your design; tap it and the agent greets you. Nothing appears? `app://` is missing or the key is wrong — Troubleshooting.

WhatsApp-style calls end to end: a checklist

- ☐ iOS: Push Notifications, Background Modes **Audio** and **Voice over IP**, the microphone string; `enableVoIPPushes()` at every launch.
- ☐ Android: Firebase in the app — the SDK registers for pushes itself (an app with its own messaging service forwards the token and every message to the SDK); notifications asked for on Android 13+.
- ☐ Workspace settings → **In-app calling**: the APNs key and the Firebase service account, *Checked and working.* — create your credentials.
- ☐ Agent → **Calls & scheduling**: **Name on the incoming call**, who may book, the limits, quiet hours; the agent's **Calling Window**.
- ☐ `identify()` after sign-in, with the identifier **Who is the user?** names.
- ☐ The user calls the agent: `startCall(reason:)` — how.
- ☐ The agent calls the user: book one (the agent, the booking sheet, or your team), or test with **Ring now** — how.
- ☐ The prompt handles `who_called` (`customer`, `scheduled`, `agent`) and `call_reason`.
- ☐ Optional: calls over WebRTC — the module in the build (iOS, Android) or the build switch (React Native, Flutter); the agent's **In-app call audio** on **WebRTC (recommended)** — how.

What's new

0.10.1 (React Native 0.44.1, calls 0.5.1):

- **On Android the SDK registers for pushes itself.** Add Firebase to the app (`google-services.json`, its Gradle plugin and the messaging library) and the SDK's own messaging service rings every call push and receives every new token — no messaging service to write. An app that has its own `FirebaseMessagingService` keeps handing Graine's pushes and tokens over (`handlePush`, `onNewToken`). Changelog.

0.10.0 (React Native 0.44.0, calls 0.5.0):

- **The SDK asks for call permissions.** `requestCallPermissions()` asks for the microphone, notifications (Android 13+) and the full-screen ring (Android 14+); `callPermissions` reads each one and `openCallSettings()` opens the page to change it. Permissions.

- **A setup check.** `callSetupProblems` lists what is still missing for calls to ring — a capability, the microphone sentence, a push token, a permission, push credentials not uploaded — each with the exact fix.
- **React Native: an Expo plugin** adds the microphone sentence, the background modes and the push entitlement; `webrtc: true` turns on WebRTC calls.

0.9.0 (React Native 0.43.0, calls 0.4.0):

- **Calls over WebRTC, in both directions.** Add the SDK's WebRTC module — iOS `GraineInAppRTC`, Android `ai.graine:inapp-android-rtc`, a build switch in React Native and Flutter, each platform's module in Kotlin Multiplatform — and the calls the user places and the calls Graine rings carry their audio over WebRTC: steadier on a weak network, prepared while the ring shows. A call WebRTC cannot set up continues on the WebSocket inside the same call. `callTransport` chooses, `transport` says which one ran, and the agent's **In-app call audio** setting can keep every call on the WebSocket. Calls over WebRTC.
- **The same features on every SDK**: emptying the chat on screen (`clear`, `clearChat`), a chat that says it is reconnecting or gave up, the voice captions switch, the rows a chat window draws for a chat of your own, answering a component from your own UI, the brand's design tokens and the merged prompt variables in Kotlin Multiplatform. Changelog.
- **Variables over 1 KB are trimmed to fit**, the biggest left off first, instead of none travelling. Variables.

0.8.0:

- **The SDK's own booking sheet** on every platform: `presentBooking` (iOS, Android, Kotlin Multiplatform), `GraineBooking.show` (Flutter), `openBooking` and `<GraineBookingSheet>` (React Native), `GraineAgent.openBooking` (website), with `bookingAvailable` to show your own **Call me** button only when booking works — and **Book a call** in each SDK's chat window. Booking with the SDK's sheet.
- **Calls that cannot connect say so, quickly.** iOS: one 20-second deadline before the conversation opens, and a clear end when the phone never gives the call its audio; Android: a dead connection ends after 50 seconds of silence, and a slow network never freezes a call. A call starts at once on the agent's settings already on the device. The messages.
- **Variables travel only on the signed ticket** for chats and calls. Variables.

- **In-app call audio** — the dashboard setting for how calls' audio travels, ready for the WebRTC calls that 0.9.0 brings.

Questions


Email support@graine.ai with your workspace name, the platform and SDK version, what you did, what you expected and what happened — a screenshot or the error `code` helps. We answer by email. Never email keys or credential files: push credentials are uploaded in Workspace settings → In-app calling.

What you build

	What your users get	What you write
The agent in your app	A bar in your brand's design: voice or chat, components drawn on screen, the agent filling fields and moving them forward	The SDK, a few lines at launch, one hook or call per screen, one handler per action
The agent on your website	The same agent in a widget: voice or chat, components, actions on the page	Two script tags, plus the same identity, screen and action calls if you want them
Calls like WhatsApp	The user calls the agent from your app; the agent calls them back when they asked — ringing on the lock screen, going on with the screen off	One button, two lines that hand the SDK its push tokens, and your push credentials uploaded once
Booking a call	"Call me at..." — the day, the time, what it is about — drawn by the SDK in your design	One call: `presentBooking` / `openBooking` / `GraineBooking.show`
A user who is remembered	The agent knows them across conversations, devices and channels — app, website and phone; a chat picks up where it left off	One identifier passed with `identify()`

No server of yours is needed for any of it: your app and your site use a publishable key and the SDKs, and Graine rings, schedules and remembers.

How it works



Your app and your website talk to the same agent; Graine keeps one key per customer, remembers under it, and rings their phone for it.

The whole platform, in an engineer's terms — transports, admission, data, limits, failure modes: Architecture and guarantees.

Before you start

	What you need
Graine	A workspace, and an Admin for the steps that change workspace settings (push credentials)
Apps	React Native 0.71+ (calls: a native build, not Expo Go); iOS 15+ and Xcode 15+; Android 7 (API 24)+; Flutter 3.19+; Kotlin Multiplatform with Kotlin 2.1.20+ (Android 7+, iOS 15+)
Calls on iOS	An Apple Developer account, an **APNs auth key** (a `.p8` file, its Key ID, your Team ID), and a real iPhone — calls do not ring in the simulator
Calls on Android	A Firebase project with Cloud Messaging, its `google-services.json` in the app, and a **service account** that may send messages
Website	The domains the widget will run on, staging included
Phones to test on	At least one iPhone and two Android phones from different manufacturers

Set up everything from scratch

The dashboard, in the order that works: the agent; Embed & Widgets → the publishable key and **Allowed domains** (with `app://`); Agent → Memory → **Who is the user?**; **Calls & scheduling** — **Users, from your app**, the calling window, **In-app call audio**; Workspace settings → **In-app calling** — the APNs key and the Firebase service account; the design in the Garage; the demo's agent packs; a test with the demo apps. Step by step, with screenshots: Set up everything from scratch.

Install and initialise

REACT NATIVE

```
npm install @graineai/inapp-react-native@0.44.1 react-native-webview
@graineai/inapp-react-native-calls@0.5.1
npx expo install expo-font react-native-svg
cd ios && pod install
```

Declare the microphone (`RECORD_AUDIO`, `MODIFY_AUDIO_SETTINGS`; `NSMicrophoneUsageDescription`) and, for calls, the iOS capabilities — Permissions.

App.tsx

```
const [open, setOpen] = useState(false);

<GraineProvider baseUrl="https://www.graine.ai" publishableKey="pk_live_…"
navigationRef={navigationRef}
                autoConnect={false} loadFont={Font.loadAsync} svg={{ Svg,
Path }}>
  <NavigationContainer ref={navigationRef}><RootNavigator />
</NavigationContainer>
  <GraineVoiceLauncher webView={WebView} active={open} autoStart>
    {(api) => (open ? <GraineVoiceBar api={api} onClose={() =>
setOpen(false)} /> : null)}
  </GraineVoiceLauncher>
  {!open && <GraineLauncherButton onPress={() => setOpen(true)} style={{
position: "absolute", right: 16, bottom: 24 }} />}
  <CallsBridge />
</GraineProvider>
```

`CallsBridge` attaches the calls package to the in-app client — calls the user places.

Calls over WebRTC (optional). `ENV["GRAINE_WEBRTC"] = "1"` at the top of `ios/Podfile` and `graineWebRtc=true` in `android/gradle.properties` (or `GRAINE_WEBRTC=1` in the build's environment), then rebuild: calls in both directions carry their audio over WebRTC, steadier on a weak network — about 12 MB on an iPhone, 7.4 MB on a 64-bit Android phone. No code changes; the agent's **In-app call audio** setting can keep calls on the WebSocket — Calls over WebRTC.

IOS

Add the package — in Xcode, **File → Add Package Dependencies…** with `https://github.com/GraineAI/inapp-ios` from **0.10.1** and the `GraineInApp` library, or in `Package.swift`:

Package.swift

```
.package(url: "https://github.com/GraineAI/inapp-ios", from: "0.10.1"),
```

Then the microphone usage string, and for calls Push Notifications and Background Modes → Audio and Voice over IP.

```
final class AppDelegate: NSObject, UIApplicationDelegate {
    func application(_ application: UIApplication,
                     didFinishLaunchingWithOptions launchOptions:
[UIApplication.LaunchOptionsKey: Any]? = nil) -> Bool {
        let graine = GraineInApp.configure(GraineConfig(baseUrl:
"https://www.graine.ai", publishableKey: "pk_live_…"))
        graine.calls.configure(GraineCallsConfig(displayName: "Asha from
Acme"))
        graine.calls.enableVoIPPushes()   // every launch: registers the
device for rings
        return true
    }
}

// Your root view
RootView()
    .overlay(GraineAgentBar())
    .overlay(alignment: .bottom) { GraineWidgetView().padding(.horizontal,
12).padding(.bottom, 96) }
```

Calls over WebRTC (optional). Add `https://github.com/GraineAI/inapp-ios-rtc` at the same version, its `GraineInAppRTC` library in the same target (CocoaPods: `pod 'GraineInAppRTC'`): calls in both directions carry their audio over WebRTC, steadier on a weak network — about 12 MB more installed. No code, no capability; the agent's **In-app call audio** setting can keep calls on the WebSocket — Calls over WebRTC.

ANDROID

```
// app/build.gradle.kts
implementation("ai.graine:inapp-android:0.10.1")
implementation(platform("com.google.firebase:firebase-bom:<latest>"))
implementation("com.google.firebase:firebase-messaging")
```

```
class AcmeApp : Application() {
    override fun onCreate() {
        super.onCreate()
        val graine = GraineInApp.init(this, GraineConfig(baseUrl =
"https://www.graine.ai", publishableKey = "pk_live_…"))
        graine.calls.configure(GraineCallsConfig(displayName = "Asha from
Acme", smallIcon = R.drawable.ic_stat_call))
    }
}
```

```
class MainActivity : Activity() {
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.main)
        GraineInApp.get().voice.attach(this)   // the engine, idle
        findViewById<FrameLayout>
(R.id.root).addView(GraineAgentBarView(this),
            FrameLayout.LayoutParams(MATCH_PARENT, WRAP_CONTENT,
Gravity.BOTTOM))
    }

    override fun onRequestPermissionsResult(code: Int, permissions: Array<out
String>, results: IntArray) {
        if (!GraineInApp.get().voice.onRequestPermissionsResult(code,
results))
            super.onRequestPermissionsResult(code, permissions, results)
    }
}
```

The library's manifest brings every permission and component a call needs.

Calls over WebRTC (optional). Add `implementation("ai.graine:inapp-android-rtc:0.10.1")` beside the SDK, at the same version: calls in both directions carry their audio over WebRTC, steadier on a weak network — about 7.4 MB more on a 64-bit

phone; its manifest adds `ACCESS_NETWORK_STATE`. No code changes; the agent's **In-app call audio** setting can keep calls on the WebSocket — Calls over WebRTC.

FLUTTER

```
dependencies:
  graine_inapp: ^0.10.1
  permission_handler: ^11.0.0
```

Calls that ring on Android need Firebase Cloud Messaging in the Android app — `google-services.json` in `android/app`, the Google services Gradle plugin, and `com.google.firebase:firebase-messaging` in `android/app/build.gradle.kts` — and nothing in Dart: the SDK registers for pushes itself. An app that uses `firebase_messaging` hands its pushes to `GraineCalls.instance.handlePush` (In-app calling → Flutter).

```
Future<void> main() async {
  WidgetsFlutterBinding.ensureInitialized();
  GraineInApp.init(GraineConfig(
    baseUrl: 'https://www.graine.ai',
    publishableKey: 'pk_live_…',
    requestMicrophone: () async => (await
Permission.microphone.request()).isGranted,
  ));
  await GraineCalls.instance.configure(const
GraineCallsOptions(publishableKey: 'pk_live_…', displayName: 'Asha from
Acme'));
  GraineCalls.instance.attach();
  runApp(MaterialApp(
    builder: (context, child) => GraineEngine(child: Stack(children: [child!,
const GraineAgentBar()])),
    home: const HomeScreen(),
  ));
}
```

Calls over WebRTC (optional). `ENV['GRAINE_WEBRTC'] = '1'` at the top of `ios/Podfile` and `graineWebRtc=true` in `android/gradle.properties` (or `GRAINE_WEBRTC=1` in the build's environment), then rebuild: calls in both directions carry their audio over

WebRTC, steadier on a weak network — about 12 MB on an iPhone, 7.4 MB on a 64-bit Android phone. No code changes; the agent's **In-app call audio** setting can keep calls on the WebSocket — Calls over WebRTC.

KOTLIN MULTIPLATFORM

```
// shared/build.gradle.kts
kotlin {
    androidTarget()
    iosArm64(); iosSimulatorArm64(); iosX64()
    sourceSets {
        commonMain.dependencies {
            implementation("ai.graine:inapp-kmp:0.10.1")
            implementation("ai.graine:inapp-kmp-compose:0.10.1")   // the
chat, call screen and bar for Compose Multiplatform
        }
    }
}
```

On Android the Android SDK comes with it, manifest included. On iOS, add `https://github.com/GraineAI/inapp-ios` (the `GraineInApp` library) to the app target, from 0.10.1, and build the shared framework as a static framework (`isStatic = true`, the Compose Multiplatform default); then the microphone usage string, and for calls Push Notifications and Background Modes → Audio and Voice over IP.

```
// Once, at launch: Application.onCreate on Android, the app's init on iOS
Graine.configure(GraineConfig(baseUrl = "https://www.graine.ai",
publishableKey = "pk_live_…"))
Graine.calls.configure(GraineCallsConfig(displayName = "Asha from Acme"))
Graine.calls.enableVoIPPushes()   // iOS, every launch: registers the device
for rings

// Compose: the bar over your app, and the call screen while there is a call
Box(Modifier.fillMaxSize()) {
    AppContent()

GraineAgentBar(Modifier.align(Alignment.BottomCenter).fillMaxWidth().height(1
80.dp))
}
val call by Graine.calls.state.collectAsState()
if (call.showsCallScreen) GraineCallScreen(Modifier.fillMaxSize())
```

On Android, an activity that shows the bar or places calls forwards its permission answers: `if (Graine.onRequestPermissionsResult(requestCode, grantResults)) return`.

Calls over WebRTC (optional). Each platform's module, at the same version as its SDK: `ai.graine:inapp-android-rtc` in the Android app, and the `GraineInAppRTC` package (or pod) beside `GraineInApp` in the iOS app. Calls in both directions then carry their audio over WebRTC, steadier on a weak network; nothing in shared code changes — Calls over WebRTC.

WEBSITE

Paste before `</body>` on every page the agent should be on — Embed & Widgets → Install has it with your ids filled in:

```
<script src="https://www.graine.ai/embed/v1.js"></script>
<script>
  GraineAgent.load({
    agentId: "your-website-agent-id",
    publishableKey: "pk_live_…",
  });
</script>
```

The widget draws the design from the Garage, loads its own typeface, and needs no build step. Embed on your website

When it works: the launcher appears in your design; open it and the agent greets you. Nothing appears? `app://` or your domain is missing from Allowed domains, or the key is wrong — Troubleshooting.

Use cases by SDK

Every use case, with the exact code on every platform — the functions to call in order, what they read or set and what to expect at each step, from setting up to cleaning up — plus the dashboard settings it needs and a troubleshooting table:

Use case	The how-to
Install the SDK and get the first answer	Install
Identify the user: memory and conversations that continue	Identity and memory
Chat: the window, its sizes and the Garage's controls	Chat
The voice bar	The voice bar
Several agents in one app	Several agents
Screen context, actions and components	Screen, actions, components
WhatsApp-style calls: the user calls the agent	Calls from the app
Calls Graine rings: booked calls and Ring now	Rings
Calls over WebRTC: both directions, steadier on a weak network	Calls over WebRTC
Booking from your app with the SDK's sheet	The booking sheet
The scheduled-calls list	Scheduled calls
Design in the Garage	Design
Going live	Going live

The same rows against every platform, each cell opening that platform's code: Use cases by SDK.

Identity and memory

Pass the signed-in user with the identifier your **Who is the user?** setting names — `user_id` by default, or `email`, `phone`, or a field of your own such as `customer_id` — and whether they allow memory. Sign-out is `identify(null)`.

- The identifier is never a prompt variable. Graine stores the identifier your app sends so your team can see who each conversation was with — Call History shows **User ID · u_8812** — and the memory service only ever receives a one-way key derived from it. Every other trait (`name`) is masked on the device and becomes a prompt variable.
- With the **same field and value** on your app and your website, they are one user: memory and scheduled calls follow them. A phone caller is the same user only when the field is **Phone number**.
- No identifier, a placeholder such as `guest`, or a device past the user's limit means **no memory** for that conversation — never a shared one.
- **Conversations continue.** For an identified user with memory on, Graine keeps their last 50 messages with each agent, for 7 days after the latest. When they come back, the chat opens on the conversation — the earlier messages, a voice call as one row, a date line where the day changes — and the agent picks up where it left off; a new call still opens with a greeting, and the agent knows what was said. `newConversation()` — or **New conversation** in the chat's header — starts a fresh thread and keeps the memories; a successful `forgetMemory()` deletes both.

The code on every platform: Identify the user · the rules: Identity and users · Memory.


Variables

What your app can tell the agent — traits from `identify`, variables at start-up and while the app runs, a call's `reason` — reaches the prompt's placeholders (`{name}`, `{plan}`, `{call_reason}`). Chats and calls carry them in the signed ticket that opens the conversation: **12 variables, 200 characters each, about 1 KB in all** (on a call, `who_called` and `call_reason` first; past 1 KB the SDKs leave off the biggest values first); a call over WebRTC carries the same set; the voice bar's WebRTC audio allows 40 of 300 characters, then drops the biggest values first. Keys starting with `graine_` are Graine's own and never reach the agent from an app. In full, with what happens when a set is too big: Variables.


Chat, voice and components

What a user gets is the dashboard's **What visitors get**: the call, the chat, or both with a switch. One conversation runs at a time.

- **Voice** — the microphone is declared by your app and asked for when a call starts (the voice bar).
- **Chat** — typed, with the same screen context, actions and components, at the Garage's **Window size** — Compact, Large or Full screen — or the size your code asks for (chat).
- **Components** — lists, plans, slots and choices drawn in your design; a tap is the user's next turn (components).
- **Several agents** — a support agent in Help, a sales agent on Plans: each its own key, design, chat and actions; who the user is, shared (several agents).



iPhone
The demo app, mid-conversation, with a component




Android
The dashboard's Android preview: a new chat

Calls like WhatsApp

Two directions, one call engine in your app. **The user calls the agent** from a button — `startCall(reason:)`, and the agent hears `who_called` = `customer` (how). **The agent calls the user**: Graine rings their phone when a booked call is due, through your push credentials, and the agent hears `who_called` = `scheduled` with the booking's reason (how). Both directions carry their audio over WebRTC when your app includes the SDK's WebRTC module — steadier on a weak network — and over the WebSocket otherwise (how).

What your users see



Rings
Android, full screen: Answer or Decline

In the call
Your call screen while the app is open

Ended
Your ended words, then it closes

Missed
If your app shows it: Call back

Moment	iPhone	Android
Booked	Nothing rings yet. Your app can list it with `scheduledCalls()`	The same
Ringing — the booked time arrives	The system's incoming call, full screen when locked and a banner in use, with your call name and ringtone	A full-screen ring when locked (with the full-screen permission), a heads-up call notification otherwise — Answer and Decline
In the call	Your call screen while the app is open; the system's call screen on the lock screen	Your call screen, and an ongoing notification with **Hang up**
Ended	Your ended words for a moment, then the screen closes	The same
Missed	**Missed call** with **Close** and **Call back** on the call screen for 30 seconds; no notification is left. It rings once more after your re-ring delay, if you set one	A missed-call notification with **Call back**; a call screen that showed the ring stays on **Missed call** for 30 seconds. One more ring after your delay, if set
Declined	Nothing rings again for at least 6 hours	The same

When a call cannot connect

A call that cannot connect ends `failed`, with a message in its outcome and on the call screen:

Message	Platform	When
The call could not connect within 20 seconds.	iOS	Everything before the conversation opens — the agent's settings, the ticket and the connection — shares one 20-second deadline
The conversation did not open within 15 seconds.	iOS	The connection itself did not open — its own limit, which can end the call before the 20 seconds are up
The call's audio could not start.	iOS	The conversation opened but the phone never gave the call its audio: the SDK waits 3 seconds, starts it itself once, then waits 3 more
The call could not connect within 15 seconds.	Android	The connection did not open in time
Nothing arrived for 50 seconds: the connection was lost.	Android	Nothing at all arrived on a live call for 50 seconds; the call does not reconnect

With the WebRTC module, a call first has up to 12 seconds to connect over WebRTC; one that cannot does not end — it continues on the WebSocket inside the same call, and these messages are what is left when neither can connect.

A call starts at once on the agent's settings the SDK already has — this launch's, or the ones kept on the device — and refreshes them behind the call. On Android a slow network never freezes a call: at most 300 ms of the user's speech waits, the oldest dropped first, and hanging up lets go of the microphone at once.


The call screen's look, words and controls are the Garage's **Call** tab; the setup per platform is In-app calling and Permissions.

Scheduled calls and the booking sheet

A scheduled call is for a **user** — the one your **Who is the user?** field identifies — and rings that user's newest app device, in their time zone, within the agent's Calling Window and outside quiet hours.

Booked by	How
The agent	It books when the user asks to be called back (**The agent, during a conversation**)
Your app or website	The SDK's booking sheet, or `scheduleCall({ at, reason })` (**Users, from your app**)
Your team	Agent → Calls & scheduling → **Schedule a call**, by the user's identifier; **Ring now** to test

There is no repeating schedule: for a daily check-in, the agent offers and books the next call at the end of each conversation, or the user books from the sheet.



The booking sheet is the SDK's own "Call me at…": the day, the time, the phone's time zone, what it is about and **Book call**, in your agent's design, with every refusal in plain words. Offer it where `bookingAvailable` is true — Graine rings this phone, the agent lets users book, and the user is identified; on a website only the last two count, and the sheet says "We'll ring you in the app". It returns the booked call, or nothing when the user closed it. Booking with the SDK's sheet · the scheduled-calls list.

> ⚠ **A website cannot ring.** A call booked on your website — by the agent, the sheet or `scheduleCall` — rings the identified user's **app** on their phone. A user with no app device seen in the last 30 days is not rung: the call ends `no_device`. Identify the user before you offer booking on your website.

Design

One design, chosen in the Garage, drawn everywhere: the launcher, the bar, the chat window, components, the booking sheet and the call screen, on your website and in every SDK. A saved change reaches a website on its next page load and an app the next time it starts. Nothing in your code names a colour or a font. Design in the Garage.

Data and privacy

What leaves the phone or page	What you report — the screen, traits, variables — masked on the device for PAN, Aadhaar, card and account numbers, phones and emails; the user's voice only while a call is connected; typed messages; your actions' answers
The identifier	Never a prompt variable. Graine stores the identifier your app sends so your team can see who each conversation was with; the memory service only ever receives a one-way key derived from it
Memory	Short facts under that key, redacted before they are stored, kept for your retention, forgotten on request from the app or the dashboard. Deleting an agent does not delete them; they expire
Recent messages	With memory on, an identified user's last 50 messages with each agent, so a conversation continues; kept 7 days after the latest, and forgotten with the memories
A ring	The call's id, the call name and which agent is calling — no reason, no variables, nothing about the user
Push credentials and tokens	Encrypted with your workspace's own key, never shown again or logged; dead tokens deleted, and devices unseen for 90 days
The publishable key	Public by design; it selects the agent and cannot read your data or place a phone call

Privacy and security · Architecture and guarantees

Error codes

Each SDK raises these as a typed error with a `code` and a `message` — which method raises which is on your platform's SDK reference, and every code with its fix on Errors.

`code`	**Means**	**Fix**
`invalid_key`	The publishable key is not one, or belongs to no agent	Copy it again from Embed & Widgets → Install
`origin_refused`	The app or site is not allowed	Add `app://`, or the exact host, to Allowed domains
`identity_required`	Booking, ringing or forgetting needs the user's identifier	`identify()` with the identifier first
`device_limit`	This install is not one of the user's allowed devices	Sign out elsewhere, raise Devices per user, or reset their devices
`scheduling_off`	**Users, from your app** is off	Turn it on, or book from the dashboard
`too_soon`, `too_far`	Outside **With at least this much notice** / **Booked at most this far ahead**	Pick another time
`outside_window`	The user's time is outside the agent's Calling Window	Pick a time inside it
`too_many_pending`	The user has the maximum calls waiting	Cancel one first
`not_found`	The call is not this user's, or does not exist	Refresh the list
`invalid_request`	A field is missing or malformed — a time without its offset, a reason over 120 characters	Fix the request
`rate_limited`	Too many requests from this install, key or address	Back off, honouring `Retry-After`
`unavailable`, `network`	Graine could not complete it just now, or could not be reached	Retry with backoff

Troubleshooting

What you see	Where to look
Nothing appears	Allowed domains and the key — Install → Troubleshooting
Needs microphone	The declaration, or a refusal — Permissions
The agent does not know the screen	Screen context
The agent says it cannot do something	The action's declaration and handler — Actions
No component	Components → Is it actually on the agent?, and the dashboard's Playground
It does not remember	The identity field, memory for that user, the device limit — Memory → Troubleshooting
`bookingAvailable` is false	The booking sheet → Troubleshooting
A booked call never rings	Credentials, device registration, notifications — Hosted ringing → Troubleshooting
A call ends *could not connect*	When a call cannot connect
Calls never use WebRTC	The module or build switch, `callTransport`, the agent's In-app call audio — Calls over WebRTC → Troubleshooting
A call rang later than booked	The user's hours and quiet hours — Scheduled calls
The design did not change	Restart the app — The Garage

QA script

Run it on an iPhone, two Android phones and your website, signed in as a test user whose identifier you know.

#	Do this	Expect
1	Open the app and the bar	The launcher in your design; the agent greets you by name
2	Ask "what screen am I on?"	It names the screen and its fields
3	Ask it to do something you declared	It changes in the app, and it says so
4	Ask for something a component shows	The component appears; a tap continues the conversation
5	Switch to the chat, and back	One conversation at a time; the call ends when the chat opens
6	Tell it something to remember, end, start again	It remembers — on the website too, signed in as the same user
7	Turn memory off for the user, start again	It remembers nothing new
8	Sign out, start again	Anonymous: no name, no memory; your **Call me** button hides (`bookingAvailable` false)
9	Sign in again with memory on, chat a little, close the app completely, reopen it and open the chat	The earlier messages are there, under a date line; the agent carries on, with no second welcome. **New conversation** in the header starts over
10	If your app runs a second agent, open a screen that talks to it	Its own design and greeting; it knows who you are without signing in again; starting it ends the first agent's conversation
11	Tap your call button	The call screen; the agent knows you called
12	Turn on airplane mode, then tap your call button	It ends *could not connect* within 20 seconds (iPhone) or 15 (Android) — not stuck on Connecting
13	With WebRTC in the build, tap your call button, then answer a **Ring now**	Both connect as before, the greeting not clipped; the call's `transport` is `webrtc`

#	Do this	Expect
14	Set the agent's **In-app call audio** to **Standard**, restart the app, call	It connects; `transport` is `websocket`. Set it back
15	Ask the agent to call you back in 10 minutes	It confirms the time; **Scheduled calls** lists it
16	Open the booking sheet; pick a time too soon, then a good one	The refusal line under **Book call**; then *Booked — … will call you on …* and **Done**; the chat's card lists it
17	Book from the website with `openBooking`	It books; the sheet says *We'll ring you in the app*; the call rings the app
18	**Ring now** from the dashboard with the app closed and the phone locked	It rings on the lock screen; answer, and the agent knows why it called
19	Decline one, let one ring out	`declined`, then nothing for 6 hours; `missed` (a missed-call notification with Call back on Android), then one re-ring if set
20	Lock the phone mid-call, open another app	The call goes on
21	Deny the microphone, then notifications (Android 13+)	*Needs microphone*; a booked call does not ring with the app closed
22	Book for a user who has never used the app	The call ends `no_device`
23	Open each conversation in Call History	Transcript, the app's timeline, the actions, the call's outcome — and who it was with: **User ID · u_8812**, or your own field's name

Go-live checklist

Dashboard

- ☐ An agent per surface; keys in the builds; `app://` and every site, staging included, in Allowed domains

- ☐ The design saved on all three Garage surfaces; Setup saved
- ☐ Actions declared and saved; components ticked; friction tuned
- ☐ Memory → Settings: the same **Who is the user?** field on the app's and the website's agents
- ☐ Calls & scheduling: call name, quiet hours, who may book, limits; the agent's Calling Window
- ☐ In-app calling credentials *Checked and working.* on both platforms
- ☐ The prompt handles `who_called` and `call_reason`, and offers call-backs when it should

Apps

- ☐ The microphone declared on every platform; `requestCallPermissions()` at onboarding (the microphone, and notifications on Android 13+)
- ☐ iOS: Push Notifications, Background Modes Audio and Voice over IP; `enableVoIPPushes` at every launch
- ☐ Android: Firebase in the app — the SDK registers for pushes itself (an app with its own messaging service forwards the token and every message, `handlePush` first)
- ☐ `identify()` after sign-in and at every launch once your sign-in is restored; `identify(null)` on sign-out
- ☐ **Call me** buttons shown only where `bookingAvailable` is true
- ☐ Store submissions: Play's foreground-service and full-screen-intent declarations, App Store review notes, no development launcher (Expo: `expo-dev-client`) in the store build — Permissions → Store review
- ☐ Calls over WebRTC — the module or build switch in the release build, WebRTC in your open-source licences
- ☐ Debug logging off in release builds

Website

- ☐ The snippet on every page the agent belongs on; `identify()` on sign-in

Tested

- ☐ The QA script above, on every platform

The fuller list, with what each failure means: Going live.

‹ Previous
In-app agents

Next ›
Set up everything from scratch