

Contents

1 Basic	1	6.11 Factorial without prime factor*	14
1.1 Hash.sh	1	6.12 QuadraticResidue*	14
1.2 readchar	1	6.13 PiCount*	14
1.3 Black Magic	1	6.14 Discrete Log*	14
1.4 Pragma Optimization	1	6.15 Berlekamp Massey	14
1.5 Sanitize Fix	1	6.16 Primes	15
		6.17 Theorem	15
		6.18 Estimation	15
		6.19 Euclidean Algorithms	15
		6.20 General Purpose Numbers	16
		6.21 Tips for Generating Functions	16
2 Graph	1	7 Polynomial	16
2.1 EBCC*	1	7.1 Fast Fourier Transform	16
2.2 VBCC*	1	7.2 FFT Arbitrary Mod	16
2.3 SCC*	2	7.3 Number Theory Transform*	16
2.4 2SAT*	2	7.4 NTT Primes	16
2.5 MinimumMeanCycle*	2	7.5 Fast Walsh Transform*	17
2.6 Virtual Tree*	2	7.6 Polynomial Operation	17
2.7 Maximum Clique Dyn*	2	7.7 Linear Recursion	18
2.8 Minimum Steiner Tree*	3	7.8 Value Polynomial	18
2.9 Dominator Tree*	3	7.9 Newton's Method	18
2.10 Minimum Arborescence*	3		
2.11 Vizing's theorem*	4		
2.12 Minimum Clique Cover*	4		
2.13 NumberofMaximalClique*	4		
3 Data Structure	4	8 Geometry	18
3.1 Discrete Trick	4	8.1 Default Code	18
3.2 Mergeable Heap	5	8.2 PointSegDist*	19
3.3 BIT kth*	5	8.3 Heart	19
3.4 Centroid Decomposition*	5	8.4 point in circle	19
3.5 Treap*	5	8.5 Convex hull*	19
3.6 Link cut tree*	6	8.6 PointInConvex*	19
3.7 KDTree	6	8.7 TangentPointToHull*	19
		8.8 Intersection of line and convex	19
		8.9 minMaxEnclosingRectangle*	19
4 Flow/Matching	7	8.10 VectorInPoly*	20
4.1 Bipartite Matching*	7	8.11 PolyUnion*	20
4.2 Kuhn Munkres*	7	8.12 Half plane intersection*	20
4.3 MincostMaxflow*	7	8.13 HPI Alternative Form	20
4.4 Maximum Simple Graph Matching*	8	8.14 RotatingSweepLine	20
4.5 Maximum Weight Matching*	8	8.15 Minimum Enclosing Circle*	20
4.6 SW-mincut	9	8.16 Intersection of two circles*	21
4.7 BoundedFlow*(Dinic*)	9	8.17 Intersection of polygon and circle*	21
4.8 Gomory Hu tree*	9	8.18 Intersection of line and circle*	21
4.9 Minimum Cost Circulation*	10	8.19 Tangent line of two circles	21
4.10 Flow Models	10	8.20 CircleCover*	21
		8.21 3Dpoint*	21
		8.22 Convexhull3D*	22
		8.23 DelaunayTriangulation*	22
		8.24 Triangulation Voronoi*	22
		8.25 Minkowski Sum*	23
		8.26 Closest Pair	23
5 String	10	9 Else	23
5.1 KMP	10	9.1 Cyclic Ternary Search*	23
5.2 Z-value*	10	9.2 Mo's Algorithm(With modification)	23
5.3 Manacher*	10	9.3 Mo's Algorithm On Tree	23
5.4 Suffix Array*	11	9.4 Additional Mo's Algorithm Trick	23
5.5 SAIS C++20*	11	9.5 Hilbert Curve	23
5.6 Aho-Corasick Automatan*	11	9.6 DynamicConvexTrick*	23
5.7 Smallest Rotation*	11	9.7 All LCS*	24
5.8 De Bruijn sequence*	11	9.8 Matroid Intersection	24
5.9 Extended SAM*	12	9.9 Matroid Intersection	24
5.10 PalTree*	12	9.10 AdaptiveSimpson*	24
5.11 Main Lorentz	12	9.11 Simulated Annealing	24
		9.12 Tree Hash*	24
		9.13 Binary Search On Fraction*	25
		9.14 1D1D	25
		9.15 SMAWK	25
		9.16 Min Plus Convolution*	25
		9.17 Bitset LCS	25
		9.18 Python	25
6 Math	12		
6.1 ax+by=gcd(only exgcd*)	12		
6.2 Floor and Ceil	12		
6.3 Floor Enumeration	12		
6.4 Mod Min	13		
6.5 Gaussian integer gcd	13		
6.6 Miller Rabin*	13		
6.7 System of Linear Equations	13		
6.8 Pollard Rho*	13		
6.9 Simplex Algorithm	13		
6.9.1 Construction	14		
6.10 chineseRemainder	14		

1 Basic

1.1 Hash.sh

```
echo "Useful for verifying that there aren't mistypes."
cpp $1 -dD -P -fpreprocessed | tr -d '[:space:]' \
| md5sum | cut -c-6
```

1.2 readchar [7e1a14]

```
inline char readchar() {
    const int B = 1 << 16;
    static char buf[B], *p = buf, *end = buf;
    if (p == end)
        end = buf + fread_unlocked(p = buf, 1, B, stdin);
    return *p++;
}
```

1.3 Black Magic [15375c]

```
#include <ext/pb_ds/priority_queue.hpp>
#include <ext/pb_ds/assoc_container.hpp> // rb_tree
#include <ext/rope> // rope
using namespace __gnu_pbds;
using namespace __gnu_cxx; // rope
typedef __gnu_pbds::priority_queue<int> heap;
int main() {
```

```
heap h1, h2; // max heap
h1.push(1), h1.push(3), h2.push(2), h2.push(4);
h1.join(h2); // h1 = {1, 2, 3, 4}, h2 = {};
tree<ll, null_type, less<ll>, rb_tree_tag,
    tree_order_statistics_node_update> st;
tree<ll, ll, less<ll>, rb_tree_tag,
    tree_order_statistics_node_update> mp;
for (int x : {0, 3, 20, 50}) st.insert(x);
assert(st.order_of_key(3) == 1);
assert(st.order_of_key(4) == 2);
assert(*st.find_by_order(2) == 20);
assert(*st.lower_bound(4) == 20);
rope<char> *root[10]; // nsqrt(n)
root[0] = new rope<char>();
root[1] = new rope<char>(*root[0]);
// root[1]->insert(pos, 'a');
// root[1]->at(pos); 0-base
// root[1]->erase(pos, size);
}
// __int128_t, __float128_t
// bs._Find_first(), bs._Find_next(i): size() if none
```

1.4 Pragma Optimization [49e509]

```
#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,arch=skylake")
__builtin_ia32_ldmxcsr(__builtin_ia32_stmxcsr()|0x8040)
```

1.5 Sanitize Fix [6bec31]

```
#include <sys/personality.h>
#include <bits/stdc++.h>
int main(int argc, char** argv) {
    personality(ADDR_NO_RANDOMIZE);
    execv(argv[1], argv+1);
}
```

2 Graph

2.1 EBCC* [fe081b]

```
struct EBCC { // need adj
    int n, dfcnt = 0, bcnt = 0;
    vector<int> dfn, low, bcc, st;
    EBCC(int n) : n(n), dfn(n+1), low(dfn), bcc(dfn) {}
    void tarjan(int pos, int fa) {
        dfn[pos] = low[pos] = ++dfcnt;
        st.pb(pos);
        bool vs = 0;
        for (int np : adj[pos]) {
            if (np != fa || vs) {
                if (dfn[np] == 0) {
                    tarjan(np, pos);
                    low[pos] = min(low[pos], low[np]);
                    if (dfn[pos] < low[np]) {
                        bcnt++;
                        while (1) {
                            int x = st.back();
                            bcc[x] = bcnt;
                            st.pop_back();
                            if (x == np) break;
                        }
                    } else { low[pos] = min(low[pos], dfn[np]); }
                } else { vs = 1; }
            }
        }
        if (pos == fa) {
            bcnt++;
            while (st.size()) {
                bcc[st.back()] = bcnt;
                st.pop_back();
            }
        }
        void work() {
            FOR (i, 1, n) if (dfn[i] == 0) tarjan(i, i);
        }
    };
};
```

2.2 VBCC* [8fadbe]

```
struct VBCC { // need adj
    int n, dfcnt = 0, bcnt = 0;
    vector<int> dfn, low, st;
    vector<vector<int>> bcc;
    VBCC() {}
```

```

VBCC(int n) : n(n) {
    dfn = low = vector<int>(n + 1, 0);
    bcc = vector<vector<int>>(n + 1, vector<int>());
}
void tarjan(int pos, int fa) {
    dfn[pos] = low[pos] = ++dfcnt;
    st.pb(pos);
    for (int np : adj[pos]) {
        if (np != fa) {
            if (dfn[np] == 0) {
                tarjan(np, pos);
                low[pos] = min(low[pos], low[np]);
                if (dfn[pos] <= low[np]) {
                    bccnt++;
                    while (1) {
                        int x = st.back();
                        bcc[x].pb(bccnt);
                        st.pop_back();
                        if (x == np) break;
                    }
                    bcc[pos].pb(bccnt);
                }
            } else { low[pos] = min(low[pos], dfn[np]); }
        }
    }
    if (pos == fa) {
        st.pop_back();
        if (bcc[pos].size() == 0) bcc[pos].pb(++bccnt);
    }
}
void work() {
    FOR (i, 1, n) if (dfn[i] == 0) tarjan(i, i);
}
};

```

2.3 SCC* [7c6db3]

```

struct SCC { // need adj
    int n, dfcnt = 0, sccnt = 0;
    vector<int> dfn, scc, st;
    vector<vector<int>> scc_adj;
    SCC() {}
    SCC(int n)
        : n(n), dfn(n + 1), scc(n + 1), scc_adj(n + 1) {}
    void tarjan(int u) { // scc[] numbered sink first
        int lw = dfn[u] = ++dfcnt, x;
        st.pb(u);
        for (int v : adj[u]) if (!scc[v]) {
            if (!dfn[v]) tarjan(v);
            lw = min(lw, dfn[v]);
        }
        if (lw == dfn[u]) {
            sccnt++;
            do {
                x = st.back(), st.pop_back(), scc[x] = sccnt;
            } while (x != u);
        }
        dfn[u] = lw; // dfn[] now holds the low-link
    }
    void work() {
        FOR (i, 1, n) if (!dfn[i]) tarjan(i);
    }
    void build_adj() {
        FOR (i, 1, n) for (int j : adj[i])
            if (scc[i] != scc[j]) scc_adj[scc[i]].pb(scc[j]);
    }
};

```

2.4 2SAT* [11893d]

```

// 0-base, reuses SCC, so it needs the same adj.
// ~x is NOT x; literal a lives on node en(a) + 1
struct TwoSat {
    int n;
    vector<int> ans; // 0 / 1, set by solve()
    TwoSat(int n = 0) : n(n) {}
    int en(int a) { return max(a * 2, -1 - a * 2); }
    int add_var() { return n++; } // adj must have room
    void either(int a, int b) { // a or b
        int x = en(a), y = en(b);
        adj[(x ^ 1) + 1].pb(y + 1);
        adj[(y ^ 1) + 1].pb(x + 1);
    }
    void set_value(int x) { either(x, x); }
    void at_most_one(const vector<int> &v) {
        if (v.size() <= 1) return;
        int cur = ~v[0];
        FOR (i, 2, (int)v.size() - 1) {
            int nxt = add_var();

```

```

            either(cur, ~v[i]), either(cur, nxt);
            either(~v[i], nxt), cur = ~nxt;
        }
        either(cur, ~v[1]);
    }
    bool solve() { // scc[] is numbered sink first
        SCC scc(n * 2);
        scc.work();
        ans.assign(n, 0);
        FOR (i, 0, n - 1) {
            int a = i * 2 + 1, b = i * 2 + 2;
            if (scc.scc[a] == scc.scc[b]) return false;
            ans[i] = scc.scc[a] < scc.scc[b];
        }
        return true;
    }
};

```

2.5 MinimumMeanCycle* [e33105]

```

typedef pair<ll, ll> pll;
ll road[N][N]; // input here
struct MinimumMeanCycle { // needs every weight > 0
    ll dp[N + 5][N], n;
    pll solve() {
        ll a = -1, b = -1, L = n + 1;
        FOR (i, 2, L)
            FOR (k, 0, n - 1)
                FOR (j, 0, n - 1)
                    dp[i][j] =
                        min(dp[i - 1][k] + road[k][j], dp[i][j]);
        FOR (i, 0, n - 1) {
            if (dp[L][i] >= INF) continue;
            ll ta = 0, tb = 1;
            FOR (j, 1, n)
                if (dp[j][i] < INF &&
                    ta * (L - j) < (dp[L][i] - dp[j][i]) * tb)
                    ta = dp[L][i] - dp[j][i], tb = L - j;
            if (ta == 0) continue;
            if (a == -1 || a * tb > ta * b) a = ta, b = tb;
        }
        if (a != -1) {
            ll g = __gcd(a, b);
            return pll(a / g, b / g);
        }
        return pll(-1LL, -1LL);
    }
    void init(int _n) {
        n = _n;
        FOR (i, 0, n - 1)
            FOR (j, 0, n - 1) dp[i + 2][j] = INF;
    }
};

```

2.6 Virtual Tree* [0c5077]

```

vector<int> vG[N];
int top, st[N];
void insert(int u) {
    if (top == -1) return st[++top] = u, void();
    int p = LCA(st[top], u);
    if (p == st[top]) return st[++top] = u, void();
    while (top >= 1 && dep[st[top - 1]] >= dep[p])
        vG[st[top - 1]].pb(st[top]), --top;
    if (st[top] != p)
        vG[p].pb(st[top]), --top, st[++top] = p;
    st[++top] = u;
}
void reset(int u) {
    for (int i : vG[u]) reset(i);
    vG[u].clear();
}
void solve(vector<int> &v) {
    top = -1;
    sort(v.begin(), v.end(),
        [&](int a, int b) { return dfn[a] < dfn[b]; });
    for (int i : v) insert(i);
    while (top > 0) vG[st[top - 1]].pb(st[top]), --top;
    // do something
    reset(st[0]);
}

```

2.7 Maximum Clique Dyn* [3bcbd8]

```

struct MaxClique { // fast when N <= 100
    bitset<N> G[N], cs[N];
    int ans, sol[N], q, cur[N], d[N], n;
    void init(int _n) {
        n = _n;

```

```

FOR (i, 0, n - 1) G[i].reset();
}
void add_edge(int u, int v) {
    G[u][v] = G[v][u] = 1;
}
void pre_dfs(vector<int> &r, int l, bitset<N> mask) {
    if (l < 4) {
        for (int i : r) d[i] = (G[i] & mask).count();
        sort(r.begin(), r.end(),
            [&](int x, int y) { return d[x] > d[y]; });
    }
    vector<int> c((int)r.size());
    int lft = max(ans - q + 1, 1), rgt = 1, tp = 0;
    cs[1].reset(), cs[2].reset();
    for (int p : r) {
        int k = 1;
        while ((cs[k] & G[p]).any()) ++k;
        if (k > rgt) cs[++rgt].reset();
        cs[k][p] = 1;
        if (k < lft) r[tp++] = p;
    }
    FOR (k, lft, rgt)
        for (int p = cs[k]._Find_first(); p < N;
            p = cs[k]._Find_next(p))
            r[tp] = p, c[tp] = k, ++tp;
    dfs(r, c, l + 1, mask);
}
void dfs(vector<int> &r, vector<int> &c, int l,
    bitset<N> mask) {
    while (!r.empty()) {
        int p = r.back();
        r.pop_back(), mask[p] = 0;
        if (q + c.back() <= ans) return;
        cur[q++] = p;
        vector<int> nr;
        for (int i : r) if (G[p][i]) nr.pb(i);
        if (!nr.empty()) pre_dfs(nr, l, mask & G[p]);
        else if (q > ans) ans = q, copy_n(cur, q, sol);
        c.pop_back(), --q;
    }
}
int solve() {
    vector<int> r(n);
    ans = q = 0, iota(r.begin(), r.end(), 0);
    pre_dfs(r, 0, bitset<N>(string(n, '1')));
    return ans;
}
};

```

2.8 Minimum Steiner Tree* [ed9655]

```

struct SteinerTree { // 0-base, need INF
    int n, mid[N][N], eid[N][N], fr[1 << T][N];
    ll dst[N][N], dp[1 << T][N], vcst[N]; // vertex cost
    vector<int> ans; // edge ids, set by solve()
    void init(int _n) {
        n = _n;
        FOR (i, 0, n - 1) {
            fill_n(dst[i], n, INF), fill_n(mid[i], n, -1);
            dst[i][i] = vcst[i] = 0;
        }
    }
    void add_edge(int u, int v, ll w, int id = -1) {
        if (w < dst[u][v]) dst[u][v] = w, eid[u][v] = id;
    }
    void shortest_path() { // dst[i][j] ends up counting
        FOR (k, 0, n - 1) // every vcst on i -> j but i's
            FOR (i, 0, n - 1)
                FOR (j, 0, n - 1)
                    if (dst[i][k] + vcst[k] + dst[k][j] < dst[i][j])
                        dst[i][j] = dst[i][k] + vcst[k] + dst[k][j],
                            mid[i][j] = k;
        FOR (i, 0, n - 1) FOR (j, 0, n - 1)
            if (i != j) dst[i][j] += vcst[j];
    }
    void path(int i, int j) { // edges along i -> j
        if (i == j) return;
        int k = mid[i][j];
        if (k < 0) { ans.pb(eid[i][j]); return; }
        path(i, k), path(k, j);
    }
    void walk(int msk, int i) { // fr: 0 base case,
        int f = fr[msk][i]; // s > 0 split, -j - 1 from j
        if (!f) return;
        if (f > 0) walk(f, i), walk(msk ^ f, i);
        else path(-f - 1, i), walk(msk, -f - 1);
    }
    ll solve(const vector<int> &ter) {
        shortest_path();
    }
}

```

```

int t = (int)ter.size(), full = (1 << t) - 1;
FOR (i, 0, full)
    fill_n(dp[i], n, INF), fill_n(fr[i], n, 0);
copy_n(vcst, n, dp[0]);
FOR (msk, 1, full) {
    if (!(msk & (msk - 1))) {
        int w = ter[__lg(msk)];
        dp[msk][w] = vcst[w];
    }
    FOR (i, 0, n - 1)
        for (int s = (msk - 1) & msk; s; --s &= msk)
            if (ll v = dp[s][i] + dp[msk ^ s][i] - vcst[i];
                v < dp[msk][i])
                dp[msk][i] = v, fr[msk][i] = s;
    FOR (i, 0, n - 1) FOR (j, 0, n - 1) // in place is
        if (dp[msk][j] + dst[j][i] < dp[msk][i]) // fine
            dp[msk][i] = dp[msk][j] + dst[j][i],
                fr[msk][i] = -j - 1;
}
ll *d = dp[full]; int b = min_element(d, d + n) - d;
ans.clear(), walk(full, b);
sort(ans.begin(), ans.end());
ans.erase(unique(ans.begin(), ans.end()), ans.end());
return d[b];
}; // O(V 3^T + V^2 2^T)

```

2.9 Dominator Tree* [68d093]

```

struct dominator_tree { // 1-base
    vector<int> G[N], rG[N];
    int n, pa[N], dfn[N], id[N], Time;
    int semi[N], idom[N], best[N];
    vector<int> tree[N]; // dominator_tree
    void init(int _n) {
        n = _n;
        FOR (i, 1, n) G[i].clear(), rG[i].clear();
    }
    void add_edge(int u, int v) {
        G[u].pb(v), rG[v].pb(u);
    }
    void dfs(int u) {
        id[dfn[u] = ++Time] = u;
        for (auto v : G[u])
            if (!dfn[v]) dfs(v), pa[dfn[v]] = dfn[u];
    }
    int find(int y, int x) {
        if (y <= x) return y;
        int tmp = find(pa[y], x);
        if (semi[best[y]] > semi[best[pa[y]]])
            best[y] = best[pa[y]];
        return pa[y] = tmp;
    }
    void tarjan(int root) {
        Time = 0;
        FOR (i, 1, n) {
            dfn[i] = idom[i] = 0;
            tree[i].clear();
            best[i] = semi[i] = i;
        }
        dfs(root);
        for (int i = Time; i > 1; i--) {
            int u = id[i];
            for (auto v : rG[u])
                if (v = dfn[v]) {
                    find(v, i);
                    semi[i] = min(semi[i], semi[best[v]]);
                }
            tree[semi[i]].pb(i);
            for (auto v : tree[pa[i]]) {
                find(v, pa[i]);
                idom[v] =
                    semi[best[v]] == pa[i] ? pa[i] : best[v];
            }
            tree[pa[i]].clear();
        }
        FOR (i, 2, Time) {
            if (idom[i] != semi[i]) idom[i] = idom[idom[i]];
            tree[id[idom[i]]].pb(id[i]);
        }
    }
};

```

2.10 Minimum Arborescence* [bsfdd3]

```

/* TODO
DSU: disjoint set
- DSU(n), .boss(x), .Union(x, y)
min_heap<T, Info>: min heap of {T, Info}, lazy add on T

```

```

- .push({w, i}), .top(), .join(heap), .pop(), .empty(),
.add_lazy(v)
*/
struct E { int s, t; ll w; }; // 0-base
vector<int> dmst(const vector<E> &e, int n, int root) {
    vector<min_heap<ll, int>> h(n * 2);
    FOR (i, 0, (int)e.size() - 1)
        h[e[i].t].push({e[i].w, i});
    DSU dsu(n * 2);
    vector<int> v(n * 2, -1), pa(n * 2, -1), r(n * 2);
    v[root] = n + 1;
    int pc = n;
    FOR (i, 0, n - 1)
        if (v[i] == -1) {
            for (int p = i; v[p] == -1 || v[p] == i;
                p = dsu.boss(e[r[p]].s)) {
                if (v[p] == i) {
                    int q = p;
                    p = pc++;
                    do {
                        h[q].add_lazy(-h[q].top().F);
                        pa[q] = p, dsu.Union(p, q),
                        h[p].join(h[q]);
                    } while ((q = dsu.boss(e[r[q]].s)) != p);
                }
                v[p] = i;
                while (!h[p].empty() &&
                    dsu.boss(e[h[p].top().S].s) == p)
                    h[p].pop();
                if (h[p].empty()) return {}; // no solution
                r[p] = h[p].top().S;
            }
        }
    vector<int> ans;
    for (int i = pc - 1; i >= 0; i--) {
        if (i == root || v[i] == n) continue;
        for (int f = e[r[i]].t; ~f && v[f] != n; f = pa[f])
            v[f] = n;
        ans.pb(r[i]);
    }
    return ans; // default minimize, returns edgeid array
} // O(Ef(E)), f(E) from min_heap

```

2.11 Vizing's theorem* [4a6f64]

```

#define SZ(a) ((int)a.size())
namespace vizing { // 1-base, color of (u,v) in G[u][v]
    const int N = 105;
    int C[N][N], G[N][N], X[N], vst[N], n;
    void init(int _n) { n = _n;
        FOR (i, 0, n) FOR (j, 0, n) C[i][j] = G[i][j] = 0;
    }
    void solve(vector<pair<int, int>> &E) {
        auto update = [&](int u)
        { for (X[u] = 1; C[u][X[u]]; ++X[u]); };
        auto color = [&](int u, int v, int c) {
            int p = G[u][v];
            G[u][v] = G[v][u] = c;
            C[u][c] = v, C[v][c] = u;
            C[u][p] = C[v][p] = 0;
            if (p) X[u] = X[v] = p;
            else update(u), update(v);
            return p;
        };
        auto flip = [&](int u, int c1, int c2) {
            int p = C[u][c1];
            swap(C[u][c1], C[u][c2]);
            if (p) G[u][p] = G[p][u] = c2;
            if (!C[u][c1]) X[u] = c1;
            if (!C[u][c2]) X[u] = c2;
            return p;
        };
        fill_n(X + 1, n, 1);
        FOR (t, 0, SZ(E) - 1) {
            int u = E[t].F, v0 = E[t].S, v = v0, c0 = X[u],
                c = c0, d;
            vector<pair<int, int>> L;
            fill_n(vst + 1, n, 0);
            while (!G[u][v0]) {
                L.emplace_back(v, d = X[v]);
                if (!C[v][c])
                    for (int a = SZ(L) - 1; a >= 0; a--)
                        c = color(u, L[a].F, c);
                else if (!C[u][d])
                    for (int a = SZ(L) - 1; a >= 0; a--)
                        color(u, L[a].F, L[a].S);
                else if (vst[d]) break;
                else vst[d] = 1, v = C[u][d];
            }
        }
    }
}

```

```

if (!G[u][v0]) {
    for (; v; v = flip(v, c, d), swap(c, d));
    if (int a; C[u][c0]) {
        for (a = SZ(L) - 2; a >= 0 && L[a].S != c;
            --a);
        for (; a >= 0; a--) color(u, L[a].F, L[a].S);
    }
    else --t;
}
} // namespace vizing

```

2.12 Minimum Clique Cover* [76afac]

```

struct Clique_Cover { // 0-base, O(n2^n)
    int co[1 << N], n, E[N];
    unsigned dp[1 << N];
    void init(int _n) {
        n = _n, fill_n(dp, 1 << n, 0);
        fill_n(E, n, 0), fill_n(co, 1 << n, 0);
    }
    void add_edge(int u, int v) {
        E[u] |= 1 << v, E[v] |= 1 << u;
    }
    int solve() {
        FOR (i, 0, n - 1) co[1 << i] = E[i] | (1 << i);
        co[0] = (1 << n) - 1;
        dp[0] = (n & 1) * 2 - 1;
        FOR (i, 1, (1 << n) - 1) {
            int t = i & -i;
            dp[i] = -dp[i ^ t];
            co[i] = co[i ^ t] & co[t];
        }
        FOR (i, 0, (1 << n) - 1) co[i] = (co[i] & i) == i;
        fwt(co, 1 << n, 1);
        FOR (ans, 1, n - 1) {
            unsigned sum = 0; // probabilistic
            FOR (i, 0, (1 << n) - 1) sum += (dp[i] * co[i]);
            if (sum) return ans;
        }
        return n;
    }
};

```

2.13 NumberofMaximalClique* [785d70]

```

struct BronKerbosch { // 1-base
    int n, a[N], g[N][N];
    int cnt, all[N][N], some[N][N], none[N][N];
    void init(int _n) {
        n = _n;
        FOR (i, 1, n) FOR (j, 1, n) g[i][j] = 0;
    }
    void add_edge(int u, int v) {
        g[u][v] = g[v][u] = 1;
    }
    void dfs(int d, int an, int sn, int nn) {
        if (cnt > 1000) return; // pruning
        if (sn == 0 && nn == 0) ++cnt;
        int u = some[d][0];
        FOR (i, 0, sn - 1) {
            int v = some[d][i];
            if (g[u][v]) continue;
            int tsu = 0, tnn = 0;
            copy_n(all[d], an, all[d + 1]);
            all[d + 1][an] = v;
            FOR (j, 0, sn - 1)
                if (g[v][some[d][j]])
                    some[d + 1][tsu++] = some[d][j];
            FOR (j, 0, nn - 1)
                if (g[v][none[d][j]])
                    none[d + 1][tnn++] = none[d][j];
            dfs(d + 1, an + 1, tsu, tnn);
            some[d][i] = 0, none[d][nn++] = v;
        }
    }
    int solve() {
        iota(some[0], some[0] + n, 1);
        cnt = 0, dfs(0, 0, n, 0);
        return cnt;
    }
};

```

3 Data Structure

3.1 Discrete Trick

```

#define ALL(v) v.begin(), v.end()

```

```
vector<int> val;
// build
sort(ALL(val)), val.erase(unique(ALL(val)), val.end());
// index of x
upper_bound(ALL(val), x) - val.begin();
// max idx <= x
upper_bound(ALL(val), x) - val.begin();
// max idx < x
lower_bound(ALL(val), x) - val.begin();
```

3.2 Mergeable Heap [22fc92]

```
template <class T, class Info> // lazy add tag
struct min_heap { // mergeable
    using P = pair<T, Info>;
    priority_queue<P, vector<P>, greater<P>> pq;
    T lazy = 0;
    void push(P v) { pq.emplace(v.F - lazy, v.S); }
    P top() { return P(pq.top().F + lazy, pq.top().S); }
    void join(min_heap &rgt) {
        if ((int)pq.size() < (int)rgt.pq.size()) {
            swap(pq, rgt.pq);
            swap(lazy, rgt.lazy);
        }
        while (!rgt.pq.empty()) {
            push(rgt.top());
            rgt.pop();
        }
    }
    void pop() { pq.pop(); }
    bool empty() { return pq.empty(); }
    void add_lazy(T v) { lazy += v; }
};
```

3.3 BIT kth* [e39485]

```
int bit[N + 1]; // N = 2 ^ k
int query_kth(int k) {
    int res = 0;
    for (int i = N >> 1; i >= 1; i >>= 1)
        if (bit[res + i] < k) k -= bit[res + i];
    return res + 1;
}
```

3.4 Centroid Decomposition* [e94af0]

```
typedef pair<ll, ll> pll;
struct Cent_Dec { // 1-base
    vector<pll> G[N];
    pll info[N]; // store info. of itself
    pll upinfo[N]; // store info. of climbing up
    int n, pa[N], layer[N], sz[N], done[N];
    ll dis[__lg(N) + 1][N];
    void init(int _n) {
        n = _n, layer[0] = -1;
        fill_n(pa + 1, n, 0), fill_n(done + 1, n, 0);
        FOR (i, 1, n) G[i].clear();
    }
    void add_edge(int a, int b, int w) {
        G[a].pb(pll(b, w)), G[b].pb(pll(a, w));
    }
    void get_cent(
        int u, int f, int &mx, int &c, int num) {
        int mxsz = 0;
        sz[u] = 1;
        for (pll e : G[u])
            if (!done[e.F] && e.F != f) {
                get_cent(e.F, u, mx, c, num);
                sz[u] += sz[e.F], mxsz = max(mxsz, sz[e.F]);
            }
        if (mx > max(mxsz, num - sz[u]))
            mx = max(mxsz, num - sz[u]), c = u;
    }
    void dfs(int u, int f, ll d, int org) {
        // if required, add self info or climbing info
        dis[layer[org]][u] = d;
        for (pll e : G[u])
            if (!done[e.F] && e.F != f)
                dfs(e.F, u, d + e.S, org);
    }
    int cut(int u, int f, int num) {
        int mx = 1e9, c = 0, lc;
        get_cent(u, f, mx, c, num);
        done[c] = 1, pa[c] = f, layer[c] = layer[f] + 1;
        info[c] = upinfo[c] = pll(), dis[layer[c]][c] = 0;
        for (pll e : G[c])
            if (!done[e.F]) {
                if (sz[e.F] > sz[c])
                    lc = cut(e.F, c, num - sz[c]);
            }
    }
};
```

```
        else lc = cut(e.F, c, sz[e.F]);
        dfs(e.F, c, e.S, c);
    }
    return done[c] = 0, c;
}
void build() { cut(1, 0, n); }
void modify(int u) {
    for (int a = u, ly = layer[a]; a;
        a = pa[a], --ly) {
        info[a].F += dis[ly][u], ++info[a].S;
        if (pa[a])
            upinfo[a].F += dis[ly - 1][u], ++upinfo[a].S;
    }
}
ll query(int u) {
    ll rt = 0;
    for (int a = u, ly = layer[a]; a;
        a = pa[a], --ly) {
        rt += info[a].F + info[a].S * dis[ly][u];
        if (pa[a])
            rt -=
                upinfo[a].F + upinfo[a].S * dis[ly - 1][u];
    }
    return rt;
}
};
```

3.5 Treap* [5ab1a1]

```
struct node {
    int data, sz;
    node *l, *r;
    node(int k) : data(k), sz(1), l(0), r(0) {}
    void up() {
        sz = 1;
        if (l) sz += l->sz;
        if (r) sz += r->sz;
    }
    void down() {}
};
int sz(node *a) { return a ? a->sz : 0; }
node *merge(node *a, node *b) {
    if (!a || !b) return a ? a : b;
    if (rand() % (sz(a) + sz(b)) < sz(a))
        return a->down(), a->r = merge(a->r, b), a->up(), a;
    return b->down(), b->l = merge(a, b->l), b->up(), b;
}
void split(node *o, node *&a, node *&b, int k) {
    if (!o) return a = b = 0, void();
    o->down();
    if (o->data <= k)
        a = o, split(o->r, a->r, b, k), a->up();
    else b = o, split(o->l, a, b->l, k), b->up();
}
void split2(node *o, node *&a, node *&b, int k) {
    if (sz(o) <= k) return a = o, b = 0, void();
    o->down();
    if (sz(o->l) + 1 <= k)
        a = o, split2(o->r, a->r, b, k - sz(o->l) - 1);
    else b = o, split2(o->l, a, b->l, k);
    o->up();
}
node *kth(node *o, int k) {
    if (k <= sz(o->l)) return kth(o->l, k);
    if (k == sz(o->l) + 1) return o;
    return kth(o->r, k - sz(o->l) - 1);
}
int Rank(node *o, int key) {
    if (!o) return 0;
    if (o->data < key)
        return sz(o->l) + 1 + Rank(o->r, key);
    else return Rank(o->l, key);
}
bool erase(node *&o, int k) {
    if (!o) return 0;
    if (o->data == k) {
        node *t = o;
        o->down(), o = merge(o->l, o->r);
        delete t;
        return 1;
    }
    node *&t = k < o->data ? o->l : o->r;
    return erase(t, k) ? o->up(), 1 : 0;
}
void insert(node *&o, int k) {
    node *a, *b;
    split(o, a, b, k),
        o = merge(a, merge(new node(k), b));
}
```

```

void interval(node *&o, int l, int r) {
    node *a, *b, *c;
    split2(o, a, b, l - 1), split2(b, b, c, r);
    // operate
    o = merge(a, merge(b, c));
}

```

3.6 Link cut tree* [726922]

```

struct Splay { // path sum; swap + for ^ to get xor
    static Splay nil;
    Splay *ch[2], *f;
    int rev, size;
    ll val, sum;
    Splay(ll v = 0) : rev(0), size(1), val(v), sum(v) {
        f = ch[0] = ch[1] = &nil; }
    bool isr() {
        return f->ch[0] != this && f->ch[1] != this; }
    int dir() {
        return f->ch[0] == this ? 0 : 1; }
    void setCh(Splay *c, int d) {
        ch[d] = c;
        if (c != &nil) c->f = this;
        pull();
    }
    void give_tag(int r) {
        if (r) swap(ch[0], ch[1]), rev ^= 1;
    }
    void push() {
        if (ch[0] != &nil) ch[0]->give_tag(rev);
        if (ch[1] != &nil) ch[1]->give_tag(rev);
        rev = 0;
    }
    void pull() {
        // take care of the nil!
        size = ch[0]->size + ch[1]->size + 1;
        sum = ch[0]->sum + ch[1]->sum + val;
        if (ch[0] != &nil) ch[0]->f = this;
        if (ch[1] != &nil) ch[1]->f = this;
    }
} Splay::nil;
Splay *nil = &Splay::nil;
void rotate(Splay *x) {
    Splay *p = x->f;
    int d = x->dir();
    if (!p->isr()) p->f->setCh(x, p->dir());
    else x->f = p->f;
    p->setCh(x->ch[!d], d);
    x->setCh(p, !d);
    p->pull(), x->pull();
}
void splay(Splay *x) {
    vector<Splay*> splayVec;
    for (Splay *q = x;; q = q->f) {
        splayVec.pb(q);
        if (q->isr()) break;
    }
    reverse(splayVec.begin(), splayVec.end());
    for (auto it : splayVec) it->push();
    while (!x->isr()) {
        if (x->f->isr()) rotate(x);
        else if (x->dir() == x->f->dir())
            rotate(x->f), rotate(x);
        else rotate(x), rotate(x);
    }
}
Splay* access(Splay *x) {
    Splay *q = nil;
    for (; x != nil; x = x->f)
        splay(x), x->setCh(q, 1), q = x;
    return q;
}
void root_path(Splay *x) { access(x), splay(x); }
void chroot(Splay *x) {
    root_path(x), x->give_tag(1);
    x->push(), x->pull();
}
void split(Splay *x, Splay *y) {
    chroot(x), root_path(y);
}
void link(Splay *x, Splay *y) {
    root_path(x), chroot(y);
    x->setCh(y, 1);
}
void cut(Splay *x, Splay *y) {
    split(x, y);
    if (y->size != 5) return;
    y->push();
    y->ch[0] = y->ch[0]->f = nil;
}

```

```

}
Splay* get_root(Splay *x) {
    for (root_path(x); x->ch[0] != nil; x = x->ch[0])
        x->push();
    splay(x);
    return x;
}
bool conn(Splay *x, Splay *y) {
    return get_root(x) == get_root(y);
}
Splay* lca(Splay *x, Splay *y) {
    access(x), root_path(y);
    if (y->f == nil) return y;
    return y->f;
}
void change(Splay *x, ll val) {
    splay(x), x->val = val, x->pull();
}
ll query(Splay *x, Splay *y) {
    split(x, y);
    return y->sum;
}
}

```

3.7 KDTree [bbfd43]

```

namespace kdt {
    int root, lc[maxn], rc[maxn], xl[maxn], xr[maxn],
        yl[maxn], yr[maxn];
    point p[maxn];
    int build(int l, int r, int dep = 0) {
        if (l == r) return -1;
        function<bool(const point &, const point &)> f =
            [dep](const point &a, const point &b) {
                if (dep & 1) return a.x < b.x;
                else return a.y < b.y;
            };
        int m = (l + r) >> 1;
        nth_element(p + l, p + m, p + r, f);
        xl[m] = xr[m] = p[m].x;
        yl[m] = yr[m] = p[m].y;
        lc[m] = build(l, m, dep + 1);
        if (~lc[m]) {
            xl[m] = min(xl[m], xl[lc[m]]);
            xr[m] = max(xr[m], xr[lc[m]]);
            yl[m] = min(yl[m], yl[lc[m]]);
            yr[m] = max(yr[m], yr[lc[m]]);
        }
        rc[m] = build(m + 1, r, dep + 1);
        if (~rc[m]) {
            xl[m] = min(xl[m], xl[rc[m]]);
            xr[m] = max(xr[m], xr[rc[m]]);
            yl[m] = min(yl[m], yl[rc[m]]);
            yr[m] = max(yr[m], yr[rc[m]]);
        }
        return m;
    }
    bool bound(const point &q, int o, long long d) {
        double ds = sqrt(d + 1.0);
        if (q.x < xl[o] - ds || q.x > xr[o] + ds ||
            q.y < yl[o] - ds || q.y > yr[o] + ds)
            return false;
        return true;
    }
    long long dist(const point &a, const point &b) {
        return (a.x - b.x) * 1ll * (a.x - b.x) +
            (a.y - b.y) * 1ll * (a.y - b.y);
    }
    void dfs(
        const point &q, long long &d, int o, int dep = 0) {
        if (!bound(q, o, d)) return;
        long long cd = dist(p[o], q);
        if (cd != 0) d = min(d, cd);
        if ((dep & 1) && q.x < p[o].x ||
            !(dep & 1) && q.y < p[o].y) {
            if (~lc[o]) dfs(q, d, lc[o], dep + 1);
            if (~rc[o]) dfs(q, d, rc[o], dep + 1);
        } else {
            if (~rc[o]) dfs(q, d, rc[o], dep + 1);
            if (~lc[o]) dfs(q, d, lc[o], dep + 1);
        }
    }
    void init(const vector<point> &v) {
        FOR (i, 0, (int) v.size() - 1) p[i] = v[i];
        root = build(0, v.size());
    }
    long long nearest(const point &q) {
        long long res = LLONG_MAX;
        dfs(q, res, root);
        return res;
    }
}

```

```
}
} // namespace kdt
```

4 Flow/Matching

4.1 Bipartite Matching* [24c4a2]

```
struct Bipartite_Matching { // 0-base
    int mp[N], mq[N], dis[N + 1], cur[N], l, r;
    vector<int> G[N + 1];
    bool dfs(int u) {
        for (int &i = cur[u]; i < (int)G[u].size(); i++) {
            int e = G[u][i], v = mq[e];
            if (v == l || (dis[v] == dis[u] + 1 && dfs(v)))
                return mp[mq[e] = u] = e, 1;
        }
        return dis[u] = -1, 0;
    }
    bool bfs() {
        queue<int> q;
        fill_n(dis, l + 1, -1);
        FOR (i, 0, l - 1) if (!~mp[i]) q.push(i), dis[i] = 0;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int e : G[u])
                if (!~dis[mq[e]])
                    q.push(mq[e]), dis[mq[e]] = dis[u] + 1;
        }
        return dis[l] != -1;
    }
    int matching() {
        int res = 0;
        fill_n(mp, l, -1), fill_n(mq, r, l);
        while (bfs()) {
            fill_n(cur, l, 0);
            FOR (i, 0, l - 1) res += (!~mp[i] && dfs(i));
        }
        return res; // (i, mp[i] != -1)
    }
    vector<int> cover() { // Konig, call after matching()
        vector<int> vl(l), vr(r), q, res; // L: i, R: l + e
        FOR (i, 0, l - 1) if (!~mp[i]) vl[i] = 1, q.pb(i);
        for (int h = 0; h < (int)q.size(); h++)
            for (int e : G[q[h]]) if (!vr[e]) {
                vr[e] = 1;
                if (mq[e] != l && !vl[mq[e]])
                    vl[mq[e]] = 1, q.pb(mq[e]);
            }
        FOR (i, 0, l - 1) if (!vl[i]) res.pb(i);
        FOR (e, 0, r - 1) if (vr[e]) res.pb(l + e);
        return res; // complement = max independent set
    }
    void add_edge(int s, int t) { G[s].pb(t); }
    void init(int _l, int _r) {
        l = _l, r = _r;
        FOR (i, 0, l) G[i].clear();
    }
};
```

4.2 Kuhn Munkres* [181a95]

```
struct KM { // 0-base, maximum matching
    ll w[N][N], hl[N], hr[N], slk[N];
    int fl[N], fr[N], pre[N], qu[N], ql, qr, n, m; // n <= m
    bool vl[N], vr[N];
    void init(int _n, int _m) {
        n = _n, m = _m;
        FOR (i, 0, n - 1) fill_n(w[i], m, 0); // perfect: -INF
    }
    void add_edge(int a, int b, ll wei) {
        w[a][b] = max(w[a][b], wei);
    }
    bool Check(int y) {
        if (vr[y] = 1, ~fr[y])
            return vl[qu[qr++]] = fr[y] = 1;
        while (~y) swap(y, fl[fr[y] = pre[y]]);
        return 0;
    }
    void bfs(int s) {
        fill_n(slk, m, INF);
        fill_n(vl, n, 0), fill_n(vr, m, 0);
        ql = qr = 0, qu[qr++] = s, vl[s] = 1;
        for (ll d;;) {
            while (ql < qr)
                for (int y = 0, x = qu[ql++]; y < m; y++)
                    if (!vr[y] &&
                        slk[y] >= (d = hl[x] + hr[y] - w[x][y])) {
                        if (pre[y] = x, d) slk[y] = d;
                    }
            }
        }
```

```
        else if (!Check(y)) return;
    }
    d = INF;
    FOR (y, 0, m - 1)
        if (!vr[y] && d > slk[y]) d = slk[y];
    FOR (y, 0, m - 1) {
        if (vr[y]) hr[y] += d;
        else slk[y] -= d;
    }
    FOR (x, 0, n - 1) if (vl[x]) hl[x] -= d;
    FOR (y, 0, m - 1)
        if (!vr[y] && !slk[y] && !Check(y)) return;
    }
}
ll solve() {
    fill_n(fl, n, -1), fill_n(fr, m, -1);
    fill_n(hr, m, 0);
    FOR (i, 0, n - 1)
        hl[i] = *max_element(w[i], w[i] + m);
    FOR (i, 0, n - 1) bfs(i);
    ll res = 0;
    FOR (i, 0, n - 1) if (fl[i] != -1) res += w[i][fl[i]];
    return res;
}
};
```

4.3 MincostMaxflow* [cdf5a9]

```
#include <ext/pb_ds/priority_queue.hpp> // decrease-key
const ll INF = numeric_limits<ll>::max() / 4;
struct MinCostMaxFlow { // 0-base, need global N
    struct Edge {
        int from, to, rev;
        ll cap, cost, flow;
    } *par[N];
    vector<Edge> g[N];
    int n, vis[N];
    ll dis[N], pot[N];
    void init(int _n) {
        n = _n, fill_n(pot, n, 0);
        FOR (i, 0, n - 1) g[i].clear();
    }
    void add_edge(int a, int b, ll cap, ll cost) {
        if (a == b) return;
        g[a].pb(Edge{a, b, (int)g[b].size(), cap, cost, 0});
        g[b].pb(Edge{b, a, (int)g[a].size() - 1, 0, -cost, 0});
    }
    void path(int s) { // dijkstra on reduced costs
        fill_n(vis, n, 0), fill_n(dis, n, INF);
        dis[s] = 0;
        __gnu_pbds::priority_queue<pair<ll, int>> pq;
        vector<decltype(pq)::point_iterator> it(n);
        pq.push({0, s});
        while (!pq.empty()) {
            s = pq.top().S, pq.pop(), vis[s] = 1;
            ll d = dis[s] + pot[s];
            for (Edge &e : g[s])
                if (!vis[e.to]) {
                    ll v = d - pot[e.to] + e.cost;
                    if (e.cap - e.flow > 0 && v < dis[e.to]) {
                        dis[e.to] = v, par[e.to] = &e;
                        if (it[e.to] == pq.end())
                            it[e.to] = pq.push({-v, e.to});
                        else pq.modify(it[e.to], {-v, e.to});
                    }
                }
        }
        FOR (i, 0, n - 1) pot[i] = min(pot[i] + dis[i], INF);
    }
    pair<ll, ll> maxflow(int s, int t) {
        ll flow = 0, cost = 0;
        while (path(s), vis[t]) {
            ll f = INF;
            for (Edge *e = par[t]; e; e = par[e->from])
                f = min(f, e->cap - e->flow);
            flow += f;
            for (Edge *e = par[t]; e; e = par[e->from])
                e->flow += f, g[e->to][e->rev].flow -= f;
        }
        FOR (i, 0, n - 1)
            for (Edge &e : g[i]) cost += e.cost * e.flow;
        return {flow, cost / 2};
    }
    void setpi(int s) { // iff some cost is negative
        fill_n(pot, n, INF), pot[s] = 0;
        int it = n, ch = 1;
        ll v;
        while (ch-- && it--)
```

```

    FOR (i, 0, n - 1)
        if (pot[i] != INF)
            for (Edge &e : g[i])
                if (e.cap)
                    if ((v = pot[i] + e.cost) < pot[e.to])
                        pot[e.to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
};

```

4.4 Maximum Simple Graph Matching* [9af74d]

```

struct Matching { // 0-base
    queue<int> q; int n;
    vector<int> fa, s, vis, pre, match;
    vector<vector<int>> G;
    int Find(int u)
    { return u == fa[u] ? u : fa[u] = Find(fa[u]); }
    int LCA(int x, int y) {
        static int tk = 0; tk++; x = Find(x); y = Find(y);
        for (; swap(x, y)) tk++ (x != n) {
            if (vis[x] == tk) return x;
            vis[x] = tk;
            x = Find(pre[match[x]]);
        }
    }
    void Blossom(int x, int y, int l) {
        for (; Find(x) != l; x = pre[y]) {
            pre[x] = y, y = match[x];
            if (s[y] == 1) q.push(y), s[y] = 0;
            for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
        }
    }
    bool Bfs(int r) {
        iota(fa.begin(), fa.end(), 0);
        fill(s.begin(), s.end(), -1);
        q = queue<int>(); q.push(r); s[r] = 0;
        for (; !q.empty(); q.pop()) {
            for (int x = q.front(); int u : G[x])
                if (s[u] == -1) {
                    if (pre[u] = x, s[u] = 1, match[u] == n) {
                        for (int a = u, b = x, last;
                            b != n; a = last, b = pre[a])
                            last = match[b], match[b] = a, match[a] = b;
                        return true;
                    }
                    q.push(match[u]); s[match[u]] = 0;
                }
            else if (!s[u] && Find(u) != Find(x)) {
                int l = LCA(u, x);
                Blossom(x, u, l); Blossom(u, x, l);
            }
        }
        return false;
    }
    Matching(int _n) : n(_n), fa(n + 1), s(n + 1),
        vis(n + 1), pre(n + 1, n), match(n + 1, n), G(n) {}
    void add_edge(int u, int v)
    { G[u].pb(v), G[v].pb(u); }
    int solve() {
        int ans = 0;
        FOR (x, 0, n - 1) if (match[x] == n) ans += Bfs(x);
        return ans;
    } // match[x] == n means not matched
};

```

4.5 Maximum Weight Matching* [354226]

```

#define ALL(v) v.begin(), v.end()
struct WeightGraph { // 1-based
    struct edge { int u, v, w; }; int n, nx;
    vector<int> lab; vector<vector<edge>> g;
    vector<int> slk, match, st, pa, sl, vis;
    vector<vector<int>> flo, flo_from; queue<int> q;
    WeightGraph(int n_) : n(n_), nx(n * 2), lab(nx + 1),
        g(nx + 1, vector<edge>(nx + 1)), slk(nx + 1),
        flo(nx + 1, flo_from(nx + 1, vector(n + 1, 0))) {
        match = st = pa = sl = vis = slk;
        FOR (u, 1, n) FOR (v, 1, n) g[u][v] = {u, v, 0};
    }
    int E(edge e)
    { return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2; }
    void update_slk(int u, int x, int &s)
    { if (!s || E(g[u][x]) < E(g[s][x])) s = u; }
    void set_slk(int x) {
        slk[x] = 0;
        FOR (u, 1, n)
            if (g[u][x].w > 0 && st[u] != x &&
                sl[st[u]] == 0)
                update_slk(u, x, slk[x]);
    }
};

```

```

}
void q_push(int x) {
    if (x <= n) q.push(x);
    else for (int y : flo[x]) q_push(y);
}
void set_st(int x, int b) {
    st[x] = b;
    if (x > n) for (int y : flo[x]) set_st(y, b);
}
vector<int> split_flo(auto &f, int xr) {
    auto it = find(ALL(f), xr);
    if (auto pr = it - f.begin(); pr % 2 == 1)
        reverse(1 + ALL(f), it = f.end() - pr);
    auto res = vector(f.begin(), it);
    return f.erase(f.begin(), it), res;
}
void set_match(int u, int v) {
    match[u] = g[u][v].v;
    if (u <= n) return;
    int xr = flo_from[u][g[u][v].u];
    auto &f = flo[u], z = split_flo(f, xr);
    FOR (i, 0, (int)z.size() - 1)
        set_match(z[i], z[i ^ 1]);
    set_match(xr, v); f.insert(f.end(), ALL(z));
}
void augment(int u, int v) {
    for (;) {
        int xnv = st[match[u]]; set_match(u, v);
        if (!xnv) return;
        set_match(v = xnv, u = st[pa[xnv]]);
    }
}
int lca(int u, int v) {
    static int t = 0; ++t;
    for (++t; u || v; swap(u, v)) if (u) {
        if (vis[u] == t) return u;
        vis[u] = t, u = st[match[u]];
        if (u) u = st[pa[u]];
    }
    return 0;
}
void add_blossom(int u, int o, int v) {
    int b = find(n + 1 + ALL(st), 0) - begin(st);
    lab[b] = 0, sl[b] = 0, match[b] = match[o];
    vector<int> f = {o};
    for (int t : {u, v}) {
        reverse(1 + ALL(f));
        for (int x = t, y; x != o; x = st[pa[y]])
            f.pb(x), f.pb(y = st[match[x]]), q_push(y);
    }
    flo[b] = f; set_st(b, b);
    FOR (x, 1, nx) g[b][x].w = g[x][b].w = 0;
    fill(ALL(flo_from[b]), 0);
    for (int xs : flo[b]) {
        FOR (x, 1, nx)
            if (g[b][x].w == 0 || E(g[xs][x]) < E(g[b][x]))
                g[b][x] = g[xs][x], g[x][b] = g[x][xs];
        FOR (x, 1, n)
            if (flo_from[xs][x]) flo_from[b][x] = xs;
    }
    set_slk(b);
}
void expand_blossom(int b) {
    for (int x : flo[b]) set_st(x, x);
    int xr = flo_from[b][g[b][pa[b]].u], xs = -1;
    for (int x : split_flo(flo[b], xr)) {
        if (xs == -1) { xs = x; continue; }
        pa[xs] = g[x][xs].u, sl[xs] = 1, sl[x] = 0;
        slk[xs] = 0, set_slk(x), q_push(x), xs = -1;
    }
    for (int x : flo[b])
        if (x == xr) sl[x] = 1, pa[x] = pa[b];
        else sl[x] = -1, set_slk(x);
    st[b] = 0;
}
bool on_found_edge(const edge &e) {
    if (int u = st[e.u], v = st[e.v]; sl[v] == -1) {
        int nu = st[match[v]];
        pa[v] = e.u;
        sl[v] = 1;
        slk[v] = slk[nu] = sl[nu] = 0;
        q_push(nu);
    }
    else if (sl[v] == 0) {
        if (int o = lca(u, v)) add_blossom(u, o, v);
        else return augment(u, v), augment(v, u), true;
    }
    return false;
}
}

```

```

bool matching() {
    fill(ALL(sl), -1), fill(ALL(slk), 0);
    q = queue<int>();
    FOR (x, 1, nx)
        if (st[x] == x && !match[x])
            pa[x] = sl[x] = 0, q.push(x);
    if (q.empty()) return false;
    for (;;) {
        while ((int)q.size()) {
            int u = q.front(); q.pop();
            if (sl[st[u]] == 1) continue;
            FOR (v, 1, n)
                if (g[u][v].w > 0 && st[u] != st[v]) {
                    if (E(g[u][v]) != 0)
                        update_slk(u, st[v], slk[st[v]]);
                    else if (on_found_edge(g[u][v])) return true;
                }
        }
        int d = INF;
        FOR (b, n + 1, nx)
            if (st[b] == b && sl[b] == 1)
                d = min(d, lab[b] / 2);
        FOR (x, 1, nx)
            if (int s = slk[x];
                st[x] == x && s && sl[x] <= 0)
                d = min(d, E(g[s][x]) / (sl[x] + 2));
        FOR (u, 1, n) if (sl[st[u]] == 1) lab[u] += d;
        else if (sl[st[u]] == 0) {
            if (lab[u] <= d) return false;
            lab[u] -= d;
        }
        FOR (b, n + 1, nx)
            if (st[b] == b && sl[b] >= 0)
                lab[b] += d * (2 - 4 * sl[b]);
        FOR (x, 1, nx)
            if (int s = slk[x]; st[x] == x &&
                s && st[s] != x && E(g[s][x]) == 0)
                if (on_found_edge(g[s][x])) return true;
        FOR (b, n + 1, nx)
            if (st[b] == b && sl[b] == 1 && lab[b] == 0)
                expand_blossom(b);
    }
    return false;
}

pair<ll, int> solve() {
    fill(ALL(match), 0);
    FOR (u, 0, n) st[u] = u, flo[u].clear();
    int w_max = 0;
    FOR (u, 1, n)
        FOR (v, 1, n) {
            flo_from[u][v] = (u == v ? u : 0);
            w_max = max(w_max, g[u][v].w);
        }
    fill(ALL(lab), w_max);
    int n_matches = 0; ll tot_weight = 0;
    while (matching()) ++n_matches;
    FOR (u, 1, n)
        if (match[u] && match[u] < u)
            tot_weight += g[u][match[u]].w;
    return make_pair(tot_weight, n_matches);
}

void add_edge(int u, int v, int w)
{ g[u][v].w = g[v][u].w = w; }
};

```

4.6 SW-mincut [5ea7ab]

```

auto globalMinCut(vector<vector<int>> mat) {
    pair<int, vector<int>> best = {INT_MAX, {}};
    int n = mat.size();
    vector<vector<int>> co(n);
    FOR (i, 0, n - 1) co[i] = {i};
    FOR (ph, 1, n - 1) {
        vector<int> w = mat[0];
        int s = 0, t = 0;
        FOR (it, 0, n - ph - 1) {
            w[t] = INT_MIN, s = t;
            t = max_element(w.begin(), w.end()) - w.begin();
            FOR (i, 0, n - 1) w[i] += mat[t][i];
        }
        best = min(best, {w[t] - mat[t][t], co[t]});
        co[s].insert(co[s].end(), co[t].begin(), co[t].end());
        FOR (i, 0, n - 1) mat[s][i] += mat[t][i];
        FOR (i, 0, n - 1) mat[i][s] = mat[s][i];
        mat[0][t] = INT_MIN;
    }
    return best;
}
// O(V^3); O(VE log V) with a heap in the inner loop

```

4.7 BoundedFlow*(Dinic*) [c99952]

```

#define SZ(a) ((int)a.size())
struct BoundedFlow { // 0-base
    struct edge {
        int to, cap, flow, rev;
    };
    vector<edge> G[N];
    int n, s, t, dis[N], cur[N], cnt[N];
    void init(int _n) {
        n = _n;
        FOR (i, 0, n + 2) G[i].clear(), cnt[i] = 0;
    }
    void add_edge(int u, int v, int lcap, int rcap) {
        cnt[u] -= lcap, cnt[v] += lcap;
        G[u].pb(edge{v, rcap, lcap, SZ(G[v]}));
        G[v].pb(edge{u, 0, 0, SZ(G[u]} - 1});
    }
    void add_edge(int u, int v, int cap) {
        G[u].pb(edge{v, cap, 0, SZ(G[v]}));
        G[v].pb(edge{u, 0, 0, SZ(G[u]} - 1});
    }
    int dfs(int u, int cap) {
        if (u == t || !cap) return cap;
        for (int &i = cur[u]; i < SZ(G[u]); i++) {
            edge &e = G[u][i];
            if (dis[e.to] == dis[u] + 1 && e.cap != e.flow) {
                int df = dfs(e.to, min(e.cap - e.flow, cap));
                if (df) {
                    e.flow += df, G[e.to][e.rev].flow -= df;
                    return df;
                }
            }
        }
        dis[u] = -1;
        return 0;
    }
    bool bfs() {
        fill_n(dis, n + 3, -1);
        queue<int> q;
        q.push(s), dis[s] = 0;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (edge &e : G[u])
                if (!dis[e.to] && e.flow != e.cap)
                    q.push(e.to), dis[e.to] = dis[u] + 1;
        }
        return dis[t] != -1;
    }
    int maxflow(int _s, int _t) {
        s = _s, t = _t;
        int flow = 0, df;
        while (bfs()) {
            fill_n(cur, n + 3, 0);
            while ((df = dfs(s, INF))) flow += df;
        }
        return flow;
    }
    bool solve() {
        int sum = 0;
        FOR (i, 0, n - 1)
            if (cnt[i] > 0)
                add_edge(n + 1, i, cnt[i]), sum += cnt[i];
            else if (cnt[i] < 0) add_edge(i, n + 2, -cnt[i]);
        if (sum != maxflow(n + 1, n + 2)) sum = -1;
        FOR (i, 0, n - 1)
            if (cnt[i] > 0)
                G[n + 1].pop_back(), G[i].pop_back();
            else if (cnt[i] < 0)
                G[i].pop_back(), G[n + 2].pop_back();
        return sum != -1;
    }
    int solve(int _s, int _t) {
        add_edge(_t, _s, INF);
        if (!solve()) return -1; // invalid flow
        int x = G[_t].back().flow;
        return G[_t].pop_back(), G[_s].pop_back(), x;
    }
};

```

4.8 Gomory Hu tree* [143fe3]

```

MaxFlow Dinic;
int g[MAXN];
void GomoryHu(int n) { // 0-base
    fill_n(g, n, 0);
    FOR (i, 1, n - 1) {
        Dinic.reset();
    }
}

```

```

    add_edge(i, g[i], Dinic.maxflow(i, g[i]));
    FOR (j, i + 1, n - 1)
        if (g[j] == g[i] && ~Dinic.dis[j]) g[j] = i;
}
}

```

4.9 Minimum Cost Circulation* [b3f178]

```

struct MinCostCirculation { // 0-base
    struct Edge {
        ll from, to, cap, fcap, flow, cost, rev;
    } *past[N];
    vector<Edge> G[N];
    ll dis[N], inq[N], n;
    void BellmanFord(int s) {
        fill_n(dis, n, INF), fill_n(inq, n, 0);
        queue<int> q;
        auto relax = [&](int u, ll d, Edge *e) {
            if (dis[u] > d) {
                dis[u] = d, past[u] = e;
                if (!inq[u]) inq[u] = 1, q.push(u);
            }
        };
        relax(s, 0, 0);
        while (!q.empty()) {
            int u = q.front();
            q.pop(), inq[u] = 0;
            for (auto &e : G[u])
                if (e.cap > e.flow)
                    relax(e.to, dis[u] + e.cost, &e);
        }
        void try_edge(Edge &cur) {
            if (cur.cap > cur.flow) return ++cur.cap, void();
            BellmanFord(cur.to);
            if (dis[cur.from] + cur.cost < 0) {
                ++cur.flow, --G[cur.to][cur.rev].flow;
                for (int i = cur.from; past[i]; i = past[i]->from) {
                    auto &e = *past[i];
                    ++e.flow, --G[e.to][e.rev].flow;
                }
            }
            ++cur.cap;
        }
        void solve(int mxlg) {
            for (int b = mxlg; b >= 0; b--) {
                FOR (i, 0, n - 1)
                    for (auto &e : G[i]) e.cap *= 2, e.flow *= 2;
                FOR (i, 0, n - 1)
                    for (auto &e : G[i])
                        if (e.fcap >> b & 1) try_edge(e);
            }
        }
        void init(int _n) { n = _n;
            FOR (i, 0, n - 1) G[i].clear();
        }
        void add_edge(ll a, ll b, ll cap, ll cost) {
            G[a].pb(Edge{a, b, 0, cap, 0, cost,
                (int)G[b].size() + (a == b)});
            G[b].pb(Edge{
                b, a, 0, 0, 0, -cost, (int)G[a].size() - 1});
        }
    } mcmf; // O(VE * ElogC)
}

```

4.10 Flow Models

- Maximum/Minimum flow with lower bound / Circulation problem
 - Construct super source S and sink T .
 - For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity $u - l$.
 - For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
 - If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
 - The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.
- Construct minimum vertex cover from maximum matching M on bipartite graph (X, Y)
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - DFS from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited.
 - $y \in Y$ is chosen iff y is visited.
- Minimum cost cyclic flow

- Construct super source S and sink T
- For each edge (x, y, c) , connect $x \rightarrow y$ with $(cost, cap) = (c, 1)$ if $c > 0$, otherwise connect $y \rightarrow x$ with $(cost, cap) = (-c, 1)$
- For each edge with $c < 0$, sum these cost as K , then increase $d(y)$ by 1, decrease $d(x)$ by 1
- For each vertex v with $d(v) > 0$, connect $S \rightarrow v$ with $(cost, cap) = (0, d(v))$
- For each vertex v with $d(v) < 0$, connect $v \rightarrow T$ with $(cost, cap) = (0, -d(v))$
- Flow from S to T , the answer is the cost of the flow $C + K$
- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T
 - Construct a max flow model, let K be the sum of all weights
 - Connect source $s \rightarrow v, v \in G$ with capacity K
 - For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
 - For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
 - T is a valid answer if the maximum flow $f < K|V|$
- Minimum weight edge cover
 - For each $v \in V$ create a copy v' , and connect $u' \rightarrow v'$ with weight $w(u, v)$.
 - Connect $v \rightarrow v'$ with weight $2\mu(v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
 - Find the minimum weight perfect matching on G' .
- Project selection problem
 - If $p_v > 0$, create edge (s, v) with capacity p_v ; otherwise, create edge (v, t) with capacity $-p_v$.
 - Create edge (u, v) with capacity w with w being the cost of choosing u without choosing v .
 - The mincut is equivalent to the maximum profit of a subset of projects.
- Dual of minimum cost maximum flow
 - Capacity c_{uv} , Flow f_{uv} , Cost w_{uv} , Required Flow difference for vertex b_u .
 - If all w_{uv} are integers, then optimal solution can happen when all p_u are integers.

$$\begin{aligned}
 \min \sum_{uv} w_{uv} f_{uv} \quad & \min \sum_u b_u p_u + \sum_{uv} c_{uv} \max(0, p_v - p_u - w_{uv}) \\
 -f_{uv} \geq -c_{uv} \Leftrightarrow \quad & \sum_v f_{vu} - \sum_v f_{uv} = -b_u \quad p_u \geq 0
 \end{aligned}$$

5 String

5.1 KMP [c665d9]

```

int fail[MXN];
vector<int> match(string A, string B) {
    vector<int> ans;
    fail[0] = -1, fail[1] = 0;
    for (int i = 1, j = 0; i < (int)B.size();
        fail[++i] = ++j) {
        if (B[i] == B[j]) fail[i] = fail[j]; // optimize
        while (j != -1 && B[i] != B[j]) j = fail[j];
    }
    for (int i = 0, j = 0; i < (int)A.size(); i++) {
        while (j != -1 && A[i] != B[j]) j = fail[j];
        if (++j == (int)B.size())
            ans.pb(i + 1 - j), j = fail[j];
    }
    return ans;
}

```

5.2 Z-value* [3dd732]

```

int z[SIZE];
void make_z(const string &s) {
    int l = 0, r = 0, n = s.size();
    FOR (i, 1, n - 1) {
        for (z[i] = max(0, min(r - i + 1, z[i - l]));
            i + z[i] < n && s[i + z[i]] == s[z[i]]; ++z[i]);
        if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
    }
}

```

5.3 Manacher* [29eb4f]

```

int z[SIZE]; // 0-base
/* center i: radius z[i * 2 + 1] / 2
   center i, i + 1: radius z[i * 2 + 2] / 2
   both aba, abba have radius 2 */
void Manacher(string tmp) {
    string s = "";
    int l = 0, r = 0, n;
    for (char c : tmp) s.push_back(c), s.push_back('%');
    n = s.size();
    FOR (i, 0, n - 1) {
        z[i] = r > i ? min(z[2 * l - i], r - i) : 1;
        while (i - z[i] >= 0 && i + z[i] < s.size()
            && s[i + z[i]] == s[i - z[i]]) ++z[i];
        if (z[i] + i > r) r = z[i] + i, l = i;
    }
}

```

5.4 Suffix Array* [df6e92]

```
vector<int> suffix_array(string s) {
    int n = s.size();
    if (n == 1) return {0};
    s += '\0';
    vector<int> sa(n + 1), rnk(n + 1), cnt(n + 1);
    array<int, 256> alp{};
    FOR (i, 0, n) alp[s[i]]++;
    FOR (i, 1, 255) alp[i] += alp[i - 1];
    FOR (i, 0, n) sa[--alp[s[i]]] = i;
    for (int i = 1, cur = 0; i <= n; i++) {
        if (s[sa[i]] != s[sa[i - 1]]) cur++;
        rnk[sa[i]] = cur;
    }
    for (int len = 1; len <= n; len <= 1) {
        vector<int> lp(n + 1), nrnk(n + 1);
        fill(cnt.begin(), cnt.end(), 0);
        FOR (i, 0, n) {
            lp[i] = sa[i] - len;
            if (lp[i] < 0) lp[i] += n + 1;
            cnt[rnk[i]]++;
        }
        FOR (i, 1, n) cnt[i] += cnt[i - 1];
        for (int i = n; i >= 0; i--)
            sa[--cnt[rnk[lp[i]]]] = lp[i];
        nrnk[sa[0]] = 0;
        for (int i = 1, cur = 0; i <= n; i++) {
            int np1 = sa[i] + len, np2 = sa[i - 1] + len;
            if (np1 >= n + 1) np1 -= n + 1;
            if (np2 >= n + 1) np2 -= n + 1;
            if (rnk[sa[i]] != rnk[sa[i - 1]]) ||
                rnk[np1] != rnk[np2])
                cur++;
            nrnk[sa[i]] = cur;
        }
        rnk = nrnk;
    }
    sa.erase(sa.begin());
    return sa;
}

vector<int> lcp_array(string s, vector<int> sa = {}) {
    int n = s.size(), len = 0;
    if (sa.size() == 0) sa = suffix_array(s);
    vector<int> rnk(n), lcp(n - 1);
    FOR (i, 0, n - 1) rnk[sa[i]] = i;
    FOR (i, 0, n - 1) {
        if (rnk[i] == n - 1) {
            len = 0;
            continue;
        }
        int j = sa[rnk[i] + 1];
        while (i + len < n && j + len < n &&
            s[i + len] == s[j + len])
            len++;
        lcp[rnk[i]] = len;
        len = max(0, len - 1);
    }
    return lcp;
}
```

5.5 SAIS C++20* [954bda]

```
auto sais(const auto &s) {
    const int n = (int)s.size(), z = ranges::max(s) + 1;
    if (n == 1) return vector{0};
    vector<int> c(z); for (int x : s) ++c[x];
    partial_sum(c.begin(), c.end(), begin(c));
    vector<int> sa(n); auto I = views::iota(0, n);
    vector<bool> t(n, true);
    for (int i = n - 2; i >= 0; i--)
        t[i] = s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1];
    auto is_lms = views::filter([&t](int x) {
        return x && t[x] && !t[x - 1];
    });
    auto induce = [&] {
        for (auto x = c; int y : sa)
            if (y-- && (!t[y])) sa[x[s[y] - 1]++] = y;
        for (auto x = c; int y : sa | views::reverse)
            if (y-- && t[y]) sa[--x[s[y]]] = y;
    };
    vector<int> lms, q(n); lms.reserve(n);
    for (auto x = c; int i : I | is_lms)
        q[i] = (int)lms.size(), lms.pb(sa[--x[s[i]]] = i);
    induce();
    vector<int> ns((int)lms.size());
    for (int j = -1, nz = 0; int i : sa | is_lms) {
        if (j >= 0) {
            int len = min({n - i, n - j, lms[q[i] + 1] - i});
            ns[q[i]] = nz += lexicographical_compare(
                begin(s) + j, begin(s) + j + len,
                begin(s) + i, begin(s) + i + len);
        }
        j = i;
    }
    fill(sa.begin(), sa.end(), 0);
    auto nsa = sais(ns);
    for (auto x = c; int y : nsa | views::reverse)
        y = lms[y], sa[--x[s[y]]] = y;
    return induce(), sa;
} // return with one leading padding
```

5.6 Aho-Corasick Automatan* [dbd87e]

```
struct AC_Automatan {
    int nx[len][sigma], fl[len], cnt[len], ord[len], top;
    int rnx[len][sigma]; // node actually be reached
    int newnode() {
        fill_n(nx[top], sigma, -1);
        return top++;
    }
    void init() { top = 1, newnode(); }
    int input(string &s) {
        int X = 1;
        for (char c : s) {
            if (!nx[X][c - 'A']) nx[X][c - 'A'] = newnode();
            X = nx[X][c - 'A'];
        }
        return X; // return the end node of string
    }
    void make_fl() {
        queue<int> q;
        q.push(1), fl[1] = 0;
        for (int t = 0; !q.empty(); ) {
            int R = q.front();
            q.pop(), ord[t++] = R;
            FOR (i, 0, sigma - 1)
                if (~nx[R][i]) {
                    int X = rnx[R][i] = nx[R][i], Z = fl[R];
                    for (; Z && !~nx[Z][i]; ) Z = fl[Z];
                    fl[X] = Z ? nx[Z][i] : 1, q.push(X);
                }
                else rnx[R][i] = R > 1 ? rnx[fl[R]][i] : 1;
            }
        }
        // count every pattern in t: walk t along rnx, ++cnt
        // at each node, then solve() pushes cnt up fail links
        void solve() {
            for (int i = top - 2; i > 0; i--)
                cnt[fl[ord[i]]] += cnt[ord[i]];
        }
    } ac;
```

5.7 Smallest Rotation* [5323de]

```
string mcp(string s) {
    int n = (int)s.size(), i = 0, j = 1;
    s += s;
    while (i < n && j < n) {
        int k = 0;
        while (k < n && s[i + k] == s[j + k]) ++k;
        if (s[i + k] < s[j + k]) j += k + 1;
        else i += k + 1;
        if (i == j) ++j;
    }
    int ans = i < n ? i : j;
    return s.substr(ans, n);
}
```

5.8 De Bruijn sequence* [18d8a1]

```
constexpr int MAXC = 10, MAXN = 1e5 + 10;
struct DBSeq {
    int C, N, K, L, buf[MAXC * MAXN]; // K <= C^N
    void dfs(int *out, int t, int p, int &ptr) {
        if (ptr >= L) return;
        if (t > N) {
            if (N % p) return;
            for (int i = 1; i <= p && ptr < L; i++)
                out[ptr++] = buf[i];
        } else {
            buf[t] = buf[t - p], dfs(out, t + 1, p, ptr);
            FOR (j, buf[t - p] + 1, C - 1)
                buf[t] = j, dfs(out, t + 1, t, ptr);
        }
    }
    void solve(int _c, int _n, int _k, int *out) {
        int p = 0;
    }
}
```

```

    C = _c, N = _n, K = _k, L = N + K - 1;
    dfs(out, 1, 1, p);
    if (p < L) fill(out + p, out + L, 0);
}
} dbs;

```

5.9 Extended SAM* [d31fc3]

```

struct exSAM {
    int len[N * 2], link[N * 2]; // maxlength, suflink
    int next[N * 2][CNUM], tot; // [0, tot), root = 0
    int lenSorted[N * 2]; // topo. order
    int cnt[N * 2]; // occurence
    int newnode() {
        fill_n(next[tot], CNUM, 0);
        len[tot] = cnt[tot] = link[tot] = 0;
        return tot++;
    }
    void init() { tot = 0, newnode(), link[0] = -1; }
    int insertSAM(int last, int c) {
        int cur = next[last][c];
        len[cur] = len[last] + 1;
        int p = link[last];
        while (p != -1 && !next[p][c])
            next[p][c] = cur, p = link[p];
        if (p == -1) return link[cur] = 0, cur;
        int q = next[p][c];
        if (len[p] + 1 == len[q]) return link[cur] = q, cur;
        int clone = newnode();
        FOR (i, 0, CNUM - 1)
            next[clone][i] = len[next[q][i]] ? next[q][i] : 0;
        len[clone] = len[p] + 1;
        while (p != -1 && next[p][c] == q)
            next[p][c] = clone, p = link[p];
        link[link[cur] = clone] = link[q];
        link[q] = clone;
        return cur;
    }
    void insert(const string &s) {
        int cur = 0;
        for (auto ch : s) {
            int &nxt = next[cur][int(ch - 'a')];
            if (!nxt) nxt = newnode();
            cnt[cur = nxt] += 1;
        }
    }
    void build() {
        queue<int> q;
        q.push(0);
        while (!q.empty()) {
            int cur = q.front();
            q.pop();
            FOR (i, 0, CNUM - 1)
                if (next[cur][i]) q.push(insertSAM(cur, i));
        }
        vector<int> lc(tot);
        FOR (i, 1, tot - 1) ++lc[len[i]];
        partial_sum(lc.begin(), lc.end(), lc.begin());
        FOR (i, 1, tot - 1) lenSorted[--lc[len[i]]] = i;
    }
    void solve() {
        for (int i = tot - 2; i >= 0; i--)
            cnt[link[lenSorted[i]]] += cnt[lenSorted[i]];
    }
};

```

5.10 PalTree* [189708]

```

struct palindromic_tree {
    struct node {
        int next[26], fail, len;
        int cnt, num; // cnt: appear times, num: number of
                      // pal. suf.
        node(int l = 0) : fail(0), len(l), cnt(0), num(0) {
            FOR (i, 0, 25) next[i] = 0;
        }
    };
    vector<node> St;
    vector<char> s;
    int last, n;
    palindromic_tree() : St(2), last(1), n(0) {
        St[0].fail = 1, St[1].len = -1, s.pb(-1);
    }
    inline void clear() {
        St.clear(), s.clear(), last = 1, n = 0;
        St.pb(0), St.pb(-1);
        St[0].fail = 1, s.pb(-1);
    }
    inline int get_fail(int x) {

```

```

        while (s[n - St[x].len - 1] != s[n]) x = St[x].fail;
        return x;
    }
    inline void add(int c) {
        s.pb(c == 'a'), ++n;
        int cur = get_fail(last);
        if (!St[cur].next[c]) {
            int now = (int)St.size();
            St.pb(St[cur].len + 2);
            St[now].fail =
                St[get_fail(St[cur].fail)].next[c];
            St[cur].next[c] = now;
            St[now].num = St[St[now].fail].num + 1;
        }
        last = St[cur].next[c], ++St[last].cnt;
    }
    inline void count() { // counting cnt
        auto i = St.rbegin();
        for (; i != St.rend(); ++i) {
            St[i->fail].cnt += i->cnt;
        }
    }
    inline int size() { // The number of diff. pal.
        return (int)St.size() - 2;
    }
};

```

5.11 Main Lorentz [bc347f]

```

vector<pair<int, int>> rep[kN]; // 0-base [l, r]
void main_lorentz(const string &s, int sft = 0) {
    const int n = s.size();
    if (n == 1) return;
    const int nu = n / 2, nv = n - nu;
    const string u = s.substr(0, nu), v = s.substr(nu);
    ru(u.rbegin(), u.rend()), rv(v.rbegin(), v.rend());
    main_lorentz(u, sft), main_lorentz(v, sft + nu);
    const auto z1 = Zalgo(ru), z2 = Zalgo(v + '#' + u),
              z3 = Zalgo(ru + '#' + rv), z4 = Zalgo(v);
    auto get_z = [](const vector<int> &z, int i) {
        return (0 <= i && i < (int)z.size()) ? z[i] : 0;
    };
    auto add = [&](bool lf, int c, int l, int k1, int k2) {
        const int L = max(1, l - k2), R = min(l - lf, k1);
        if (L > R) return;
        const int o = sft + c - (lf ? 0 : l - 1);
        rep[l].pb(o - R, o - L);
    };
    FOR (cntr, 0, n - 1) {
        int l, k1, k2;
        if (cntr < nu) {
            l = nu - cntr;
            k1 = get_z(z1, nu - cntr);
            k2 = get_z(z2, nv + 1 + cntr);
        } else {
            l = cntr - nu + 1;
            k1 = get_z(z3, nu + 1 + nv - 1 - (cntr - nu));
            k2 = get_z(z4, (cntr - nu) + 1);
        }
        if (k1 + k2 >= l) add(cntr < nu, cntr, l, k1, k2);
    }
} // p \in [l, r] => s[p, p + i] = s[p + i, p + 2i]

```

6 Math

6.1 ax+by=gcd(only exgcd *) [42ad36]

```

typedef pair<ll, ll> pll;
pll exgcd(ll a, ll b) {
    if (b == 0) return pll(1, 0);
    ll p = a / b;
    pll q = exgcd(b, a % b);
    return pll(q.S, q.F - q.S * p);
}
/* ax+by=res, let x be minimum non-negative
g, p = gcd(a, b), exgcd(a, b) * res / g
if p.F < 0: t = (abs(p.F) + b / g - 1) / (b / g)
else: t = -(p.F / (b / g))
p += (b / g, -a / g) * t *

```

6.2 Floor and Ceil [692c04]

```

int floor(int a, int b)
{ return a / b - (a % b && (a < 0) ^ (b < 0)); }
int ceil(int a, int b)
{ return a / b + (a % b && (a < 0) ^ (b > 0)); }

```

6.3 Floor Enumeration [7cbcdf]

```

// enumerating x = floor(n / i), [l, r]

```

```
for (int l = 1, r; l <= n; l = r + 1) {
    int x = n / l;
    r = n / x;
}
```

6.4 Mod Min [59ba59]

```
// min{k | l <= ((ak) mod m) <= r}, no solution -> -1
ll mod_min(ll a, ll m, ll l, ll r) {
    if (a == 0) return l ? -1 : 0;
    if (ll k = (l + a - 1) / a; k * a <= r) return k;
    ll b = m / a, c = m % a;
    if (ll y = mod_min(c, a, a - r % a, a - l % a); ~y)
        return (l + y * c + a - 1) / a + y * b;
    return -1;
}
```

6.5 Gaussian integer gcd [9e648b]

```
cpx gaussian_gcd(cpx a, cpx b) {
#define rnd(a, b) ((2 * a + (a < 0 ? -b : b)) / (2 * b))
    ll c = a.real() * b.real() + a.imag() * b.imag();
    ll d = a.imag() * b.real() - a.real() * b.imag();
    ll r = b.real() * b.real() + b.imag() * b.imag();
    if (c % r == 0 && d % r == 0) return b;
    return gaussian_gcd(b,
        a - cpx(rnd(c, r), rnd(d, r)) * b);
}
```

6.6 Miller Rabin* [0498b2]

```
// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : primes <= 13
// n < 2^64              7 :
// 2, 325, 9375, 28178, 450775, 9780504, 1795265022
bool Miller_Rabin(ll a, ll n) {
    if ((a = a % n) == 0) return 1;
    if (n % 2 == 0) return n == 2;
    ll tmp = (n - 1) / ((n - 1) & (1 - n));
    ll t = __lg(((n - 1) & (1 - n))), x = 1;
    for (; tmp; tmp >>= 1, a = ((__int128)a * a % n)
        if (tmp & 1) x = ((__int128)x * a % n);
    if (x == 1 || x == n - 1) return 1;
    while (--t)
        if ((x = ((__int128)x * x % n) == n - 1) return 1;
    return 0;
}
```

6.7 System of Linear Equations [98560f]

```
template <typename T> // T: + - * / and == T()
struct matrix { // m variables, n equations
    int n, m, rank, pv[MAXN];
    bool fixed[MAXN];
    T M[MAXN][MAXN + 1], sol[MAXN + 1],
      basis[MAXN][MAXN + 1];
    int solve() { // -1: inconsistent, else dim of
        rank = m; // the solution space
        FOR (i, 0, n - 1) {
            int &p = pv[i] = 0;
            while (p < m && M[i][p] == T()) p++;
            if (p == m) continue;
            FOR (j, 0, n - 1) if (i != j) {
                T t = -M[j][p] / M[i][p];
                FOR (k, 0, m) M[j][k] = t * M[i][k] + M[j][k];
            }
        }
        FOR (i, 0, n - 1) {
            int p = pv[i];
            if (p == m) {
                if (!(M[i][m] == T())) return rank = -1;
                continue;
            }
            rank--;
            for (int j = m; j >= p; j--)
                M[i][j] = M[i][j] / M[i][p];
            sol[p] = M[i][m], fixed[p] = 1;
        }
        FOR (i, 0, n - 1)
            for (int j = 0, k = 0; j < m; j++)
                if (!fixed[j]) basis[k++][pv[i]] = -M[i][j];
        for (int j = 0, k = 0; j < m; j++)
            if (!fixed[j]) basis[k++][j] = 1;
        return rank;
    }
};
```

6.8 Pollard Rho* [e90c91]

```
map<ll, int> cnt;
void PollardRho(ll n) {
    if (n == 1) return;
    if (prime(n)) return ++cnt[n], void();
    if (n % 2 == 0) return ++cnt[2], PollardRho(n / 2);
    ll x = 2, y = 2, d = 1, p = 1;
#define f(x, n, p) (((__int128)x * x + p) % n)
    while (true) {
        if (d != n && d != 1) {
            PollardRho(n / d);
            PollardRho(d);
            return;
        }
        if (d == n) ++p;
        x = f(x, n, p), y = f(f(y, n, p), n, p);
        d = gcd(abs(x - y), n);
    }
}
```

6.9 Simplex Algorithm [76b226]

```
const int MAXN = 11000, MAXM = 405;
const double eps = 1E-10;
double a[MAXN][MAXM], b[MAXN], c[MAXN];
double d[MAXN][MAXM], x[MAXN];
int ix[MAXN + MAXM]; // !!! array all indexed from 0
// max{cx} subject to {Ax<=b, x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
// usage :
// value = simplex(a, b, c, N, M);
double simplex(int n, int m) {
    ++m;
    fill_n(d[n], m + 1, 0);
    fill_n(d[n + 1], m + 1, 0);
    iota(ix, ix + n + m, 0);
    int r = n, s = m - 1;
    FOR (i, 0, n - 1) {
        FOR (j, 0, m - 2) d[i][j] = -a[i][j];
        d[i][m - 1] = 1;
        d[i][m] = b[i];
        if (d[r][m] > d[i][m]) r = i;
    }
    copy_n(c, m - 1, d[n]);
    d[n + 1][m - 1] = -1;
    for (double dd;; ) {
        if (r < n) {
            swap(ix[s], ix[r + m]);
            d[r][s] = 1.0 / d[r][s];
            FOR (j, 0, m) if (j != s) d[r][j] *= -d[r][s];
            FOR (i, 0, n + 1)
                if (i != r) {
                    FOR (j, 0, m)
                        if (j != s) d[i][j] += d[r][j] * d[i][s];
                    d[i][s] *= d[r][s];
                }
        }
        r = s = -1;
        FOR (j, 0, m - 1)
            if (s < 0 || ix[s] > ix[j]) {
                if (d[n + 1][j] > eps ||
                    (d[n + 1][j] > -eps && d[n][j] > eps))
                    s = j;
            }
        if (s < 0) break;
        FOR (i, 0, n - 1)
            if (d[i][s] < -eps) {
                if (r < 0 ||
                    (dd = d[r][m] / d[r][s] -
                     d[i][m] / d[i][s]) < -eps ||
                    (dd < eps && ix[r + m] > ix[i + m]))
                    r = i;
            }
        if (r < 0) return -1; // not bounded
    }
    if (d[n + 1][m] < -eps) return -1; // not executable
    double ans = 0;
    fill_n(x, m, 0);
    FOR (i, m,
        n + m - 1) { // the missing enumerated x[i] = 0
        if (ix[i] < m - 1) {
            ans += d[i - m][m] * c[ix[i]];
            x[ix[i]] = d[i - m][m];
        }
    }
    return ans;
}
```

6.9.1 Construction

Primal	Dual
Maximize $c^T x$ s.t. $Ax \leq b, x \geq 0$	Minimize $b^T y$ s.t. $A^T y \geq c, y \geq 0$
Maximize $c^T x$ s.t. $Ax \leq b$	Minimize $b^T y$ s.t. $A^T y = c, y \geq 0$
Maximize $c^T x$ s.t. $Ax = b, x \geq 0$	Minimize $b^T y$ s.t. $A^T y \geq c$

$\bar{x}$ and $\bar{y}$ are optimal if and only if for all $i \in [1, n]$, either $\bar{x}_i = 0$ or $\sum_{j=1}^m A_{ji} \bar{y}_j = c_i$ holds and for all $i \in [1, m]$ either $\bar{y}_i = 0$ or $\sum_{j=1}^n A_{ij} \bar{x}_j = b_j$ holds.

1. In case of minimization, let $c'_i = -c_i$
2. $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3. $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
4. If x_i has no lower bound, replace x_i with $x_i - x'_i$

6.10 chineseRemainder [99ca0c]

```
ll solve(ll x1, ll m1, ll x2, ll m2) { // lcm < 4e18
    ll g = gcd(m1, m2);
    if ((x2 - x1) % g) return -1; // no sol
    m1 /= g; m2 /= g;
    pair<ll, ll> p = exgcd(m1, m2);
    ll lcm = m1 * m2 * g;
    ll k = (__int128)p.F * ((x2 - x1) / g) % m2;
    ll res = k * m1 * g + x1;
    return (res % lcm + lcm) % lcm;
}
```

6.11 Factorial without prime factor* [8d24f6]

```
// O(p^k + log^2 n), pk = p^k
ll prod[MAXP];
ll fac_no_p(ll n, ll p, ll pk) {
    prod[0] = 1;
    FOR (i, 1, pk)
        if (i % p) prod[i] = prod[i - 1] * i % pk;
        else prod[i] = prod[i - 1];
    ll rt = 1;
    for (; n; n /= p) {
        rt = rt * mpow(prod[pk], n / pk, pk) % pk;
        rt = rt * prod[n % pk] % pk;
    }
    return rt;
} // (n! without factor p) % p^k
```

6.12 QuadraticResidue* [a09dba]

```
int Jacobi(int a, int m) {
    int s = 1;
    for (; m > 1; ) {
        a %= m;
        if (a == 0) return 0;
        const int r = __builtin_ctz(a);
        if ((r & 1) && ((m + 2) & 4)) s = -s;
        a >>= r;
        if (a & m & 2) s = -s;
        swap(a, m);
    }
    return s;
}

int QuadraticResidue(int a, int p) {
    if (p == 2) return a & 1;
    const int jc = Jacobi(a, p);
    if (jc == 0) return 0;
    if (jc == -1) return -1;
    int b, d;
    for (; ; ) {
        b = rand() % p;
        d = (1LL * b * b + p - a) % p;
        if (Jacobi(d, p) == -1) break;
    }
    ll f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
    for (int e = (1LL + p) >> 1; e; e >>= 1) {
        if (e & 1) {
            tmp = (g0 * f0 + d * (g1 * f1 % p)) % p;
            g1 = (g0 * f1 + g1 * f0) % p;
            g0 = tmp;
        }
        tmp = (f0 * f0 + d * (f1 * f1 % p)) % p;
        f1 = 2 * f0 * f1 % p;
        f0 = tmp;
    }
    return g0;
}
```

6.13 PiCount* [f3d2ec]

```
ll PrimeCount(ll n) { // n ~ 10^13 => < 2s
    if (n <= 1) return 0;
    int v = sqrt(n), s = (v + 1) / 2, pc = 0;
    vector<int> smalls(v + 1), skip(v + 1), roughs(s);
    vector<ll> larges(s);
    FOR (i, 2, v) smalls[i] = (i + 1) / 2;
    FOR (i, 0, s - 1) {
        roughs[i] = 2 * i + 1;
        larges[i] = (n / (2 * i + 1) + 1) / 2;
    }
    FOR (p, 3, v) {
        if (smalls[p] > smalls[p - 1]) {
            int q = p * p;
            ++pc;
            if (1LL * q * q > n) break;
            skip[p] = 1;
            for (int i = q; i <= v; i += 2 * p) skip[i] = 1;
            int ns = 0;
            FOR (k, 0, s - 1) {
                int i = roughs[k];
                if (skip[i]) continue;
                ll d = 1LL * i * p;
                larges[ns] = larges[k] + pc - (d <= v ? larges[smalls[d] - pc] : smalls[n / d]);
                roughs[ns++] = i;
            }
            s = ns;
            for (int j = v / p; j >= p; j--) {
                int c = smalls[j] - pc, e = min(j * p + p, v + 1);
                FOR (i, j * p, e - 1) smalls[i] -= c;
            }
        }
    }
    FOR (k, 1, s - 1) {
        const ll m = n / roughs[k];
        ll t = larges[k] - (pc + k - 1);
        FOR (l, 1, k - 1) {
            int p = roughs[l];
            if (1LL * p * p > m) break;
            t -= smalls[m / p] - (pc + l - 1);
        }
        larges[0] -= t;
    }
    return larges[0];
}
```

6.14 Discrete Log* [7dde1b]

```
int DiscreteLog(int s, int x, int y, int m) {
    int kStep = sqrt(m) + 1;
    unordered_map<int, int> p;
    int b = 1;
    FOR (i, 0, kStep - 1) {
        p[y] = i;
        y = 1LL * y * x % m;
        b = 1LL * b * x % m;
    }
    for (ll i = 0; i <= m; i += kStep) {
        s = 1LL * s * b % m;
        if (p.find(s) != p.end()) return i + kStep - p[s];
    }
    return -1;
}

int DiscreteLog(int x, int y, int m) {
    if (m == 1) return 0;
    int s = 1;
    FOR (i, 0, 99) {
        if (s == y) return i;
        s = 1LL * s * x % m;
    }
    if (s == y) return 100;
    int p = 100 + DiscreteLog(s, x, y, m);
    if (fpow(x, p, m) != y) return -1;
    return p;
} // find minimum k such that x^k == y (mod m)
```

6.15 Berlekamp Massey [d0dd49]

```
#define SZ(a) ((int)a.size())
// a_i = \sum_{j=1}^i a_{i-j}; returns c 1-based,
// c[0] unused, k = SZ(c) - 1. Feeds LinearRecursion.
template <typename T>
vector<T> BerlekampMassey(const vector<T> &output) {
    vector<T> d(SZ(output) + 1), me, he;
    for (int f = 0, i = 1; i <= SZ(output); i++) {
        FOR (j, 0, SZ(me) - 1)
            d[i] += output[i - j - 2] * me[j];
        if ((d[i] - output[i - 1]) == 0) continue;
        if (me.empty()) {
```

```

    me.resize(f = i);
    continue;
}
vector<T> o(i - f - 1);
T k = -d[i] / d[f]; o.pb(-k);
for (T x : he) o.pb(x * k);
o.resize(max(SZ(o), SZ(me)));
FOR (j, 0, SZ(me) - 1) o[j] += me[j];
if (i - f + SZ(he) >= SZ(me)) he = me, f = i;
me = o;
}
me.insert(me.begin(), T()); // me[j] was c_(j+1)
return me;
}

```

6.16 Primes

```

/* 12721 13331 14341 75577 123457 222557 556679 999983
* 1097774749 1076767633 100102021 999997771 1001010013
* 1000512343 987654361 999991231 999888733 98789101
* 987777733 999991921 1010101333 1010102101
* 1000000000039 100000000000037 2305843009213693951
* 4611686018427387847 9223372036854775783
* 18446744073709551557 */

```

6.17 Theorem

- Cramer's rule

$$\begin{aligned} ax+by &= e & x &= \frac{ed-bf}{ad-bc} \\ cx+dy &= f & y &= \frac{af-ec}{ad-bc} \end{aligned}$$

- Vandermonde's Identity

$$C(n+m, k) = \sum_{i=0}^k C(n, i) C(m, k-i)$$

- Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$ (in-degree for directed case), $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

- Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .

- Cayley's Formula

- Given a degree sequence $d_1, d_2, \dots, d_n$ for each *labeled* vertices, there are $\frac{(d_1-1)!(d_2-1)!\dots(d_n-1)!}{(n-2)!}$ spanning trees.
- Let $T_{n,k}$ be the number of *labeled* forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

- Erdős-Gallai theorem

A sequence of nonnegative integers $d_1 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + \dots + d_n$

is even and $\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$ holds for every $1 \leq k \leq n$.

- Gale-Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and $b_1, \dots, b_n$ is

bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Fulkerson-Chen-Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs

with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and

$\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Pick's theorem

For simple polygon, when points are all integer, we have $A = \#\{\text{lattice points in the interior}\} + \frac{\#\{\text{lattice points on the boundary}\}}{2} - 1$.

- Möbius inversion formula

- $f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f(\frac{n}{d})$
- $f(n) = \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu(\frac{d}{n}) f(d)$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume $= \pi h^2(3r-h)/3 = \pi h(3a^2+h^2)/6 = \pi r^3(2+\cos\theta)(1-\cos\theta)^2/3$.
- Area $= 2\pi rh = \pi(a^2+h^2) = 2\pi r^2(1-\cos\theta)$.

- Lagrange multiplier

- Optimize $f(x_1, \dots, x_n)$ when k constraints $g_i(x_1, \dots, x_n) = 0$.
- Lagrangian function $\mathcal{L}(x_1, \dots, x_n, \lambda_1, \dots, \lambda_k) = f(x_1, \dots, x_n) - \sum_{i=1}^k \lambda_i g_i(x_1, \dots, x_n)$.
- The solution corresponding to the original constrained optimization is always a saddle point of the Lagrangian function.

- Nearest points of two skew lines

- Line 1: $v_1 = p_1 + t_1 d_1$
- Line 2: $v_2 = p_2 + t_2 d_2$
- $n = d_1 \times d_2$
- $n_1 = d_1 \times n$
- $n_2 = d_2 \times n$
- $c_1 = p_1 + \frac{(p_2 - p_1) \cdot n_2}{d_1 \cdot n_2} d_1$
- $c_2 = p_2 + \frac{(p_1 - p_2) \cdot n_1}{d_2 \cdot n_1} d_2$

- Derivatives/Integrals

Integration by parts: $\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$

$$\left| \begin{aligned} \frac{d}{dx} \sin^{-1} x &= \frac{1}{\sqrt{1-x^2}} & \frac{d}{dx} \cos^{-1} x &= -\frac{1}{\sqrt{1-x^2}} & \frac{d}{dx} \tan^{-1} x &= \frac{1}{1+x^2} \\ \frac{d}{dx} \tan x &= 1 + \tan^2 x & \int \tan x &= -\frac{\ln|\cos x|}{a} \\ \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \text{erf}(x) & \int x e^{ax} dx &= \frac{e^{ax}}{a^2} (ax-1) \\ \int \sqrt{a^2+x^2} &= \frac{1}{2} \left(x\sqrt{a^2+x^2} + a^2 \sinh(x/a) \right) \end{aligned} \right|$$

- Spherical Coordinate

$$(x, y, z) = (r \sin \theta \cos \phi, r \sin \theta \sin \phi, r \cos \theta)$$

$$(r, \theta, \phi) = (\sqrt{x^2 + y^2 + z^2}, \arccos(z/\sqrt{x^2 + y^2 + z^2}), \text{atan2}(y, x))$$

- Rotation Matrix

$$M(\theta) = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix}, R_x(\theta_x) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \theta_x & -\sin \theta_x \\ 0 & \sin \theta & \cos \theta \end{bmatrix}$$

- Min-Max Inclusion Exclusion Principle

(Works in expect values version, i.e., $E[\min]$, too)

$$\text{kthmax}_{i \in S} x_i = \sum_{T \subseteq S} (-1)^{|T|-k} \binom{|T|-1}{k-1} \min_{j \in T} x_j$$

$$\text{kthmin}_{i \in S} x_i = \sum_{T \subseteq S} (-1)^{|T|-k} \binom{|T|-1}{k-1} \max_{j \in T} x_j$$

6.18 Estimation

$\frac{n}{p(n)}$	2	3	4	5	6	7	8	9	20	30	40	50	100
$\frac{n}{d(i)}$	2	3	5	7	11	15	22	30	627	5604	4e4	2e5	2e8
$\frac{n}{d(n)}$	12	32	240	1344	6720	26880	103680						
$\frac{n}{B_n}$	2	5	15	52	203	877	4140	21147	115975	7e5	4e6	3e7	

6.19 Euclidean Algorithms

- $m = \lfloor \frac{a+b}{c} \rfloor$
- Time complexity: $O(\log n)$

$$f(a, b, c, n) = \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor$$

$$= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)}{2} + \lfloor \frac{b}{c} \rfloor \cdot (n+1) \\ + f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm - f(c, c-b-1, a, m-1), & \text{otherwise} \end{cases}$$

$$g(a, b, c, n) = \sum_{i=0}^n i \lfloor \frac{ai+b}{c} \rfloor$$

$$= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot \frac{n(n+1)}{2} \\ + g(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1) \\ - h(c, c-b-1, a, m-1)), & \text{otherwise} \end{cases}$$

$$h(a, b, c, n) = \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor^2$$

$$= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + 2 \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) \\ + h(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{a}{c} \rfloor \cdot g(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{b}{c} \rfloor \cdot f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm(m+1) - 2g(c, c-b-1, a, m-1) \\ - 2f(c, c-b-1, a, m-1) - f(a, b, c, n), & \text{otherwise} \end{cases}$$

6.20 General Purpose Numbers

- Bernoulli numbers

$$B_0=1, B_1^{\pm}=\pm\frac{1}{2}, B_2=\frac{1}{6}, B_3=0$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0, \text{EGF is } B(x) = \frac{x}{e^x - 1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}.$$

$$S_m(n) = \sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

- Stirling numbers of the second kind Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k), S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$$

$$x^n = \sum_{i=0}^n S(n, i) (x)_i$$

- Pentagonal number theorem

$$\prod_{n=1}^{\infty} (1-x^n) = 1 + \sum_{k=1}^{\infty} (-1)^k \left(x^{k(3k+1)/2} + x^{k(3k-1)/2} \right)$$

- Catalan numbers

$$C_n^{(k)} = \frac{1}{(k-1)n+1} \binom{kn}{n}$$

$$C^{(k)}(x) = 1 + x[C^{(k)}(x)]^k$$

- Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k, j :s s.t. $\pi(j) > \pi(j+1)$, $k+1, j$:s s.t. $\pi(j) \geq j$, k, j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.21 Tips for Generating Functions

- Ordinary Generating Function $A(x) = \sum_{i \geq 0} a_i x^i$

$$A(rx) \Rightarrow r^n a_n$$

$$A(x) + B(x) \Rightarrow a_n + b_n$$

$$A(x)B(x) \Rightarrow \sum_{i=0}^n a_i b_{n-i}$$

$$A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} a_{i_1} a_{i_2} \dots a_{i_k}$$

$$xA(x) \Rightarrow na_n$$

$$\frac{A(x)}{1-x} \Rightarrow \sum_{i=0}^n a_i$$

- Exponential Generating Function $A(x) = \sum_{i \geq 0} \frac{a_i}{i!} x^i$

$$A(x) + B(x) \Rightarrow a_n + b_n$$

$$A^{(k)}(x) \Rightarrow a_{n+k}$$

$$A(x)B(x) \Rightarrow \sum_{i=0}^n \binom{n}{i} a_i b_{n-i}$$

$$A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} \binom{n}{i_1, i_2, \dots, i_k} a_{i_1} a_{i_2} \dots a_{i_k}$$

$$xA(x) \Rightarrow na_n$$

- Special Generating Function

$$(1+x)^n = \sum_{i \geq 0} \binom{n}{i} x^i$$

$$\frac{1}{(1-x)^n} = \sum_{i \geq 0} \binom{n-1}{i} x^i$$

7 Polynomial

7.1 Fast Fourier Transform [a07ad9]

```
typedef complex<double> cplx;
// safe if (sum a_i^2 + sum b_i^2) log2(n) < 9e14
void fft(vector<cplx> &a) {
    int n = a.size(), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<cplx> rt(2, 1);
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n), rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        FOR (i, k, 2 * k - 1)
            rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
    }
    vector<int> rev(n);
    FOR (i, 0, n - 1)
        rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    FOR (i, 0, n - 1) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k)
            FOR (j, 0, k - 1) {
                cplx z = rt[j + k] * a[i + j + k];
                a[i + j + k] = a[i + j] - z;
                a[i + j] += z;
            }
}

vector<double> conv(
    const vector<double> &a, const vector<double> &b) {
    if (a.empty() || b.empty()) return {};
    int m = a.size() + b.size() - 1;
    int L = 32 - __builtin_clz(m), n = 1 << L;
    vector<double> res(m);
    vector<cplx> in(n), out(n);
    copy(a.begin(), a.end(), in.begin());
    FOR (i, 0, (int)b.size() - 1) in[i].imag(b[i]);
    fft(in);
    for (cplx &x : in) x *= x;
```

```
    FOR (i, 0, n - 1)
        out[i] = in[-i & (n - 1)] - conj(in[i]);
    fft(out);
    FOR (i, 0, m - 1) res[i] = imag(out[i]) / (4 * n);
    return res;
}
```

7.2 FFT Arbitrary Mod [5776da]

```
// needs FFT; ok while n log2(n) * M < 8.6e14
// inputs must already be in [0, M)
template <int M>
vector<ll> conv_mod(
    const vector<ll> &a, const vector<ll> &b) {
    if (a.empty() || b.empty()) return {};
    int m = a.size() + b.size() - 1;
    int B = 32 - __builtin_clz(m), n = 1 << B;
    int cut = (int)sqrt(M);
    vector<ll> res(m);
    vector<cplx> L(n), R(n), os(n), ol(n);
    FOR (i, 0, (int)a.size() - 1)
        L[i] = cplx((int)a[i] / cut, (int)a[i] % cut);
    FOR (i, 0, (int)b.size() - 1)
        R[i] = cplx((int)b[i] / cut, (int)b[i] % cut);
    fft(L), fft(R);
    FOR (i, 0, n - 1) {
        int j = -i & (n - 1);
        ol[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        os[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(ol), fft(os);
    FOR (i, 0, m - 1) {
        ll av = (ll)(real(ol[i]) + .5);
        ll cv = (ll)(imag(os[i]) + .5);
        ll bv = (ll)(imag(ol[i]) + .5) + (ll)(real(os[i]) + .5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

7.3 Number Theory Transform* [cbc898]

```
#define SZ(a) ((int)a.size())
#define ALL(v) v.begin(), v.end()
// needs mod, G (a primitive root), N = 2^k, and
// add, sub, mul, Pow -- Pow's exponent must be ll,
// PolyPow passes k. Operation wants fac[], ifac[] too
struct NTT {
    int w[N];
    NTT() {
        int dw = Pow(G, (mod - 1) / N);
        w[0] = 1;
        FOR (i, 1, N - 1) w[i] = mul(w[i - 1], dw);
    } // 0 <= a[i] < P
    void operator()(vector<int> &a, bool inv = false) {
        int n = SZ(a);
        for (int j = 1, x = 0; j < n - 1; j++) {
            for (int k = n >> 1; (x ^= k) < k; k >= 1);
            if (j < x) swap(a[x], a[j]);
        }
        for (int L = 2; L <= n; L <= 1) {
            int dx = N / L, dl = L >> 1;
            for (int i = 0; i < n; i += L) {
                for (int j = i, x = 0; j < i + dl; j++, x += dx) {
                    int tmp = mul(a[j + dl], w[x]);
                    a[j + dl] = sub(a[j], tmp);
                    a[j] = add(a[j], tmp);
                }
            }
        }
        if (inv) {
            reverse(a.begin() + 1, a.end());
            int invn = Pow(n, mod - 2);
            FOR (i, 0, n - 1) a[i] = mul(a[i], invn);
        }
    }
} ntt;
```

7.4 NTT Primes

$P = c \cdot 2^k + 1$ with primitive root g ; 2^k bounds the transform length.

P	g	2^k	P	g	2^k
7681	17	2^9	104857601	3	2^{22}
12289	11	2^{12}	985661441	3	2^{22}
40961	3	2^{13}	998244353	3	2^{23}
65537	3	2^{16}	2810183681	11	2^{23}
786433	10	2^{18}	167772161	3	2^{25}
5767169	3	2^{19}	1107296257	10	2^{25}
7340033	3	2^{20}	469762049	3	2^{26}
605028353	3	2^{20}	2885681153	3	2^{26}
23068673	3	2^{21}	2013265921	31	2^{27}

2061584302081	7	2^{37}
2748779069441	3	2^{39}
9223372036737335297	3	2^{24}
1945555039024054273	5	2^{56}

7.5 Fast Walsh Transform* [86cae0]

```

/* x: a[j], y: a[j + (L >> 1)]
or: (y += x * op), and: (x += y * op)
xor: (x, y = (x + y) * op, (x - y) * op)
invop: or, and, xor = -1, -1, 1/2 */
void fwt(int *a, int n, int op) { //or
    for (int L = 2; L <= n; L <= 1)
        for (int i = 0; i < n; i += L)
            FOR (j, i, j + (L >> 1) - 1)
                a[j + (L >> 1)] += a[j] * op;
}

const int N = 18; // L <= N, 3 (N + 1) 2^N ints
int f[N + 1][1 << N], g[N + 1][1 << N],
    h[N + 1][1 << N], ct[1 << N];
void subset_convolution(int *a, int *b, int *c, int L) {
    // c_k = \sum_{i | j = k, i & j = 0} a_i * b_j
    int n = 1 << L;
    FOR (i, 1, n - 1) ct[i] = ct[i & (i - 1)] + 1;
    FOR (i, 0, L) fill_n(f[i], n, 0),
        fill_n(g[i], n, 0), fill_n(h[i], n, 0);
    FOR (i, 0, n - 1)
        f[ct[i]][i] = a[i], g[ct[i]][i] = b[i];
    FOR (i, 0, L) fwt(f[i], n, 1), fwt(g[i], n, 1);
    FOR (i, 0, L) FOR (j, 0, i) FOR (x, 0, n - 1)
        h[i][x] += f[j][x] * g[i - j][x];
    FOR (i, 0, L) fwt(h[i], n, -1);
    FOR (i, 0, n - 1) c[i] = h[ct[i]][i];
}

```

7.6 Polynomial Operation [cb93d8]

```

typedef vector<int> Poly;
Poly Mul(Poly a, Poly b, int bound = N) {
    int m = SZ(a) + SZ(b) - 1, n = 1;
    while (n < m) n <= 1;
    a.resize(n), b.resize(n);
    ntt(a), ntt(b);
    FOR (i, 0, n - 1) a[i] = mul(a[i], b[i]);
    ntt(a, true), a.resize(min(m, bound));
    return a;
} // 8e2e8b
Poly Inverse(Poly a) {
    // O(NlogN), a[0] != 0
    int n = SZ(a);
    Poly res(1, Pow(a[0], mod - 2));
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        Poly v1(a.begin(), a.begin() + m * 2), v2 = res;
        v1.resize(m * 4), v2.resize(m * 4);
        ntt(v1), ntt(v2);
        FOR (i, 0, m * 4 - 1)
            v1[i] = mul(mul(v1[i], v2[i]), v2[i]);
        ntt(v1, true);
        res.resize(m * 2);
        FOR (i, 0, m - 1) res[i] = add(res[i], res[i]);
        FOR (i, 0, m * 2 - 1) res[i] = sub(res[i], v1[i]);
    }
    res.resize(n);
    return res;
} // 4d79c8
pair<Poly, Poly> Divide(Poly a, Poly b) {
    // a = bQ + R, O(NlogN), b.back() != 0
    int n = SZ(a), m = SZ(b), k = n - m + 1;
    if (n < m) return {{0}, a};
    Poly ra = a, rb = b;
    reverse(ra.begin(), ra.end()), ra.resize(k);
    reverse(rb.begin(), rb.end()), rb.resize(k);
    Poly Q = Mul(ra, Inverse(rb), k);
    reverse(Q.begin(), Q.end());
    Poly res = Mul(b, Q), R(m - 1);
    FOR (i, 0, m - 2) R[i] = sub(a[i], res[i]);
    return {Q, R};
} // 7d15e3

```

```

Poly SqrtImpl(Poly a) {
    if (a.empty()) return {0};
    int z = QuadraticResidue(a[0], mod), n = SZ(a);
    if (z == -1) return {-1};
    Poly q(1, z);
    const int inv2 = (mod + 1) / 2;
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        q.resize(m * 2);
        Poly f2 = Mul(q, q, m * 2);
        FOR (i, 0, m * 2 - 1) f2[i] = sub(f2[i], a[i]);
        f2 = Mul(f2, Inverse(q), m * 2);
        FOR (i, 0, m * 2 - 1)
            q[i] = sub(q[i], mul(f2[i], inv2));
    }
    q.resize(n);
    return q;
} // 984549
Poly Sqrt(Poly a) {
    // O(NlogN), return {-1} if not exists
    int n = SZ(a), m = 0;
    while (m < n && a[m] == 0) m++;
    if (m == n) return Poly(n);
    if (m & 1) return {-1};
    Poly s = SqrtImpl(Poly(a.begin() + m, a.end()));
    if (s[0] == -1) return {-1};
    Poly res(n);
    FOR (i, 0, SZ(s) - 1) res[i + m / 2] = s[i];
    return res;
} // d1acd7
Poly Derivative(Poly a) {
    int n = SZ(a);
    Poly res(n - 1);
    FOR (i, 0, n - 2) res[i] = mul(a[i + 1], i + 1);
    return res;
} // 001be0
Poly Integral(Poly a) {
    int n = SZ(a);
    Poly res(n + 1);
    FOR (i, 0, n - 1)
        res[i + 1] = mul(a[i], Pow(i + 1, mod - 2));
    return res;
} // 6fc53d
Poly Ln(Poly a) {
    // O(NlogN), a[0] = 1
    int n = SZ(a);
    if (n == 1) return {0};
    Poly d = Derivative(a);
    a.pop_back();
    return Integral(Mul(d, Inverse(a), n - 1));
} // 377d20
Poly Exp(Poly a) {
    // O(NlogN), a[0] = 0
    int n = SZ(a);
    Poly q(1, 1);
    a[0] = add(a[0], 1);
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        Poly g(a.begin(), a.begin() + m * 2), h(ALL(q));
        h.resize(m * 2), h = Ln(h);
        FOR (i, 0, m * 2 - 1) g[i] = sub(g[i], h[i]);
        q = Mul(g, q, m * 2);
    }
    q.resize(n);
    return q;
} // 525e8f
Poly PolyPow(Poly a, ll k) {
    int n = SZ(a), m = 0;
    Poly ans(n, 0);
    while (m < n && a[m] == 0) m++;
    if (k && m && (k >= n || k * m >= n)) return ans;
    if (m == n) return ans[0] = 1, ans;
    int lead = m * k;
    Poly b(a.begin() + m, a.end());
    int base = Pow(b[0], k), inv = Pow(b[0], mod - 2);
    FOR (i, 0, n - m - 1) b[i] = mul(b[i], inv);
    b = Ln(b);
    FOR (i, 0, n - m - 1) b[i] = mul(b[i], k % mod);
    b = Exp(b);
    FOR (i, lead, n - 1) ans[i] = mul(b[i - lead], base);
    return ans;
} // 7d695a
vector<int> Evaluate(Poly a, vector<int> x) {
    if (x.empty()) return {};
    int n = SZ(x);
    vector<Poly> up(n * 2);
    FOR (i, 0, n - 1) up[i + n] = {sub(0, x[i]), 1};
    for (int i = n - 1; i > 0; i--)

```

```

    up[i] = Mul(up[i * 2], up[i * 2 + 1]);
    vector<Poly> down(n * 2);
    down[1] = Divide(a, up[1]).second;
    FOR (i, 2, n * 2 - 1)
        down[i] = Divide(down[i >> 1], up[i]).second;
    Poly y(n);
    FOR (i, 0, n - 1) y[i] = down[i + n][0];
    return y;
} // bff354
Poly Interpolate(vector<int> x, vector<int> y) {
    int n = SZ(x);
    vector<Poly> up(n * 2);
    FOR (i, 0, n - 1) up[i + n] = {sub(0, x[i]), 1};
    for (int i = n - 1; i > 0; i--)
        up[i] = Mul(up[i * 2], up[i * 2 + 1]);
    Poly a = Evaluate(Derivative(up[1]), x);
    FOR (i, 0, n - 1) a[i] = mul(y[i], Pow(a[i], mod - 2));
    vector<Poly> down(n * 2);
    FOR (i, 0, n - 1) down[i + n] = {a[i]};
    for (int i = n - 1; i > 0; i--) {
        Poly lhs = Mul(down[i * 2], up[i * 2 + 1]);
        Poly rhs = Mul(down[i * 2 + 1], up[i * 2]);
        down[i].resize(SZ(lhs));
        FOR (j, 0, SZ(lhs) - 1)
            down[i][j] = add(lhs[j], rhs[j]);
    }
    return down[1];
} // af80e7
Poly TaylorShift(Poly a, int c) {
    // return sum a_i(x + c)^i;
    // fac[i] = i!, ifac[i] = inv(i!)
    int n = SZ(a);
    FOR (i, 0, n - 1) a[i] = mul(a[i], fac[i]);
    reverse(a.begin(), a.end());
    Poly b(n);
    int w = 1;
    FOR (i, 0, n - 1) b[i] = mul(ifac[i], w), w = mul(w, c);
    a = Mul(a, b, n), reverse(a.begin(), a.end());
    FOR (i, 0, n - 1) a[i] = mul(a[i], ifac[i]);
    return a;
} // 3a3763
vector<int> SamplingShift(vector<int> a, int c, int m) {
    // given f(0), f(1), ..., f(n - 1)
    // return f(c), f(c + 1), ..., f(c + m - 1)
    int n = SZ(a); // 4d649d
    FOR (i, 0, n - 1) a[i] = mul(a[i], ifac[i]);
    Poly b(n);
    FOR (i, 0, n - 1) {
        b[i] = ifac[i];
        if (i & 1) b[i] = sub(0, b[i]);
    }
    a = Mul(a, b, n);
    FOR (i, 0, n - 1) a[i] = mul(a[i], fac[i]);
    reverse(a.begin(), a.end());
    int w = 1;
    FOR (i, 0, n - 1)
        b[i] = mul(ifac[i], w), w = mul(w, sub(c, i));
    a = Mul(a, b, n);
    reverse(a.begin(), a.end());
    FOR (i, 0, n - 1) a[i] = mul(a[i], ifac[i]);
    a.resize(m), b.resize(m);
    FOR (i, 0, m - 1) b[i] = ifac[i];
    a = Mul(a, b, m);
    FOR (i, 0, m - 1) a[i] = mul(a[i], fac[i]);
    return a;
} // 2e52c1
Poly power_proj(vector<int> w, Poly f, int m) {
    // return sum_j w_j[x^j]f^i for i=0,1,...,m
    int n = 1;
    while (n < SZ(f)) n <= 1;
    f.resize(n), w.resize(n), reverse(w.begin(), w.end());
    int k = 1, n2 = 2 * n, n4 = 4 * n;
    Poly _P(n2), _Q(n2);
    FOR (i, 0, n - 1) _P[i] = w[i], _Q[i] = sub(0, f[i]);
    while (n > 1) {
        Poly R(n2);
        FOR (i, 0, n2 - 1)
            R[i] = (i & 1 ? sub(0, _Q[i]) : _Q[i]);
        Poly PQ = Mul(_P, R), QQ = Mul(_Q, R);
        PQ.resize(n4), QQ.resize(n4);
        for (int i = 0, j = n2; i < n2; i++, j++) {
            PQ[j] = add(PQ[j], _P[i]);
            QQ[j] = add(QQ[j], add(_Q[i], R[i]));
        }
        fill(ALL(_P), 0), fill(ALL(_Q), 0);
        FOR (j, 0, 2 * k - 1)
            FOR (i, 0, n / 2 - 1) {
                _P[n * j + i] = PQ[2 * n * j + 2 * i + 1];

```

```

                _Q[n * j + i] = QQ[2 * n * j + 2 * i + 0];
            }
            n /= 2, k *= 2;
        }
        Poly p(k);
        FOR (i, 0, k - 1) p[i] = _P[2 * i];
        reverse(p.begin(), p.end()), p.resize(m + 1);
        return p;
    } // 1409fd

```

7.7 Linear Recursion [6287ff]

```

int FastLinearRecursion(vector<int> a, vector<int> c,
    ll k) {
    // a_n = sigma c_j * a_{n - j - 1}, 0-based
    // O(NlogNlogK), |a| = |c|
    int n = SZ(a);
    if (k < n) return a[k];
    vector<int> base(n + 1, 1);
    FOR (i, 0, n - 1) base[i] = sub(0, c[n - i - 1]);
    vector<int> poly(n);
    (n == 1 ? poly[0] = c[n - 1] : poly[1] = 1);
    auto calc = [&](vector<int> p1, vector<int> p2) {
        // O(n^2) brute force or O(nlogn) NTT
        return Divide(Mul(p1, p2), base).second;
    };
    vector<int> res(n, 0); res[0] = 1;
    for (; k >= 1, poly = calc(poly, poly)) {
        if (k & 1) res = calc(res, poly);
    }
    int ans = 0;
    FOR (i, 0, n - 1) ans = add(ans, mul(res[i], a[i]));
    return ans;
}

```

7.8 Value Polynomial [521fc2]

```

#define SZ(a) ((int)a.size())
struct Poly {
    mint base; // f(x) = poly[x - base]
    vector<mint> poly;
    Poly(mint b = 0, mint x = 0): base(b), poly(1, x) {}
    mint get_val(const mint &x) {
        if (x >= base && x < base + SZ(poly))
            return poly[x - base];
        mint rt = 0;
        vector<mint> lmul(SZ(poly), 1), rmul(SZ(poly), 1);
        FOR (i, 1, SZ(poly) - 1)
            lmul[i] = lmul[i - 1] * (x - (base + i - 1));
        for (int i = SZ(poly) - 2; i >= 0; i--)
            rmul[i] = rmul[i + 1] * (x - (base + i + 1));
        FOR (i, 0, SZ(poly) - 1)
            rt += poly[i] * ifac[i] * inegfac[SZ(poly) - 1 - i]
                * lmul[i] * rmul[i];
        return rt;
    }
    void raise() { // g(x) = sigma{base:x} f(x)
        if (SZ(poly) == 1 && poly[0] == 0) return;
        mint nw = get_val(base + SZ(poly));
        poly.pb(nw);
        FOR (i, 1, SZ(poly) - 1) poly[i] += poly[i - 1];
    }
};

```

7.9 Newton's Method

Given $F(x)$ where

$$F(x) = \sum_{i=0}^{\infty} \alpha_i (x - \beta)^i$$

for β being some constant. Polynomial P such that $F(P) = 0$ can be found iteratively. Denote by Q_k the polynomial such that $F(Q_k) = 0 \pmod{x^{2^k}}$, then

$$Q_{k+1} = Q_k - \frac{F(Q_k)}{F'(Q_k)} \pmod{x^{2^{k+1}}}$$

8 Geometry

8.1 Default Code [ffec37]

```

#define X first
#define Y second
#define SZ(a) ((int)a.size())
#define ALL(v) v.begin(), v.end()
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef pair<double, double> pdd;
typedef pair<pdd, pdd> Line;
struct Cir { pdd O; double R; };
const double eps = 1e-8;

```

```

pdd operator+(pdd a, pdd b)
{ return pdd(a.X + b.X, a.Y + b.Y); }
pdd operator-(pdd a, pdd b)
{ return pdd(a.X - b.X, a.Y - b.Y); }
pdd operator*(pdd a, double b)
{ return pdd(a.X * b, a.Y * b); }
pdd operator/(pdd a, double b)
{ return pdd(a.X / b, a.Y / b); }
double dot(pdd a, pdd b)
{ return a.X * b.X + a.Y * b.Y; }
double cross(pdd a, pdd b)
{ return a.X * b.Y - a.Y * b.X; }
double abs2(pdd a)
{ return dot(a, a); }
double abs(pdd a)
{ return sqrt(dot(a, a)); }
int sign(double a)
{ return fabs(a) < eps ? 0 : a > 0 ? 1 : -1; }
int ori(pdd a, pdd b, pdd c)
{ return sign(cross(b - a, c - a)); }
bool collinearity(pdd p1, pdd p2, pdd p3)
{ return sign(cross(p1 - p3, p2 - p3)) == 0; }
bool btw(pdd p1, pdd p2, pdd p3) {
    if (!collinearity(p1, p2, p3)) return 0;
    return sign(dot(p1 - p3, p2 - p3)) <= 0;
}
bool seg_intersect(pdd p1, pdd p2, pdd p3, pdd p4) {
    int a123 = ori(p1, p2, p3);
    int a124 = ori(p1, p2, p4);
    int a341 = ori(p3, p4, p1);
    int a342 = ori(p3, p4, p2);
    if (a123 == 0 && a124 == 0)
        return btw(p1, p2, p3) || btw(p1, p2, p4) ||
            btw(p3, p4, p1) || btw(p3, p4, p2);
    return a123 * a124 <= 0 && a341 * a342 <= 0;
}
pdd intersect(pdd p1, pdd p2, pdd p3, pdd p4) { // C^3/C^2
    double a123 = cross(p2 - p1, p3 - p1);
    double a124 = cross(p2 - p1, p4 - p1);
    return (p4 * a123 - p3 * a124) / (a123 - a124);
}
pdd perp(pdd p1)
{ return pdd(-p1.Y, p1.X); }
pdd projection(pdd p1, pdd p2, pdd p3) { // p3 onto p1p2
    pdd d = p2 - p1;
    return p1 + d * dot(p3 - p1, d) / abs2(d);
}
pdd reflection(pdd p1, pdd p2, pdd p3)
{ return projection(p1, p2, p3) * 2 - p3; }
pdd linearTransformation(pdd p0, pdd p1, pdd q0,
    pdd q1, pdd r) { // map line p0p1 onto q0q1, apply to r
    pdd dp = p1 - p0, dq = q1 - q0, r0 = r - p0;
    pdd n(cross(dp, dq), dot(dp, dq));
    return q0 + pdd(cross(r0, n), dot(r0, n)) / abs2(dp);
}

```

8.2 PointSegDist* [57b6de]

```

double PointSegDist(pdd q0, pdd q1, pdd p) {
    if (sign(abs(q0 - q1)) == 0) return abs(q0 - p);
    if (sign(dot(q1 - q0, p - q0)) >= 0 &&
        sign(dot(q0 - q1, p - q1)) >= 0)
        return fabs(cross(q1 - q0, p - q0) / abs(q0 - q1));
    return min(abs(p - q0), abs(p - q1));
}

```

8.3 Heart [a5ce98]

```

pdd circenter(pdd a, pdd b, pdd c) { // r = abs(a - ret)
    b = b - a, c = c - a;
    return a + perp(b * abs2(c) - c * abs2(b))
        / cross(b, c) / 2;
}
pdd incenter(pdd p1, pdd p2, pdd p3) { // r = area*2/s
    double a = abs(p2 - p3), b = abs(p1 - p3),
        c = abs(p1 - p2), s = a + b + c;
    return (p1 * a + p2 * b + p3 * c) / s;
}
pdd masscenter(pdd p1, pdd p2, pdd p3)
{ return (p1 + p2 + p3) / 3; }
pdd orthcenter(pdd p1, pdd p2, pdd p3)
{ return p1 + p2 + p3 - circenter(p1, p2, p3) * 2; }

```

8.4 point in circle [a0508f]

```

// q vs circumcircle of tri(p[0],p[1],p[2]), p is ccw
bool in_cc(const array<pll, 3> &p, pll q) {
    __int128 det = 0;
    FOR (i, 0, 2)

```

```

        det += __int128(abs2(p[i]) - abs2(q)) *
            cross(p[(i + 1) % 3] - q, p[(i + 2) % 3] - q);
    return det > 0; // in: >0, on: =0, out: <0
}

```

8.5 Convex hull* [a44105]

```

void hull(vector<pll> &p) { // n=1 => p = {}
    sort(p.begin(), p.end());
    vector<pll> h(1, p[0]);
    for (int ct = 0; ct < 2; ct++, reverse(ALL(p)))
        for (int i = 1, t = SZ(h); i < SZ(p); h.pb(p[i++]))
            while (SZ(h) > t &&
                ori(h[SZ(h) - 2], h.back(), p[i]) <= 0)
                h.pop_back();
    h.pop_back(), h.swap(p);
}

```

8.6 PointInConvex* [f86640]

```

bool PointInConvex(const vector<pll> &C, pll p,
    bool strict = true) { // C: no 3 collinear vertices
    int a = 1, b = SZ(C) - 1, r = !strict;
    if (SZ(C) == 0) return false;
    if (SZ(C) < 3) return r && btw(C[0], C.back(), p);
    if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
    if (ori(C[0], C[a], p) >= r || ori(C[0], C[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (ori(C[0], C[c], p) > 0 ? b : a) = c;
    }
    return ori(C[a], C[b], p) < r;
}

```

8.7 TangentPointToHull* [523bc1]

```

/* The point should be strictly out of hull
   return arbitrary point on the tangent line */
pii get_tangent(vector<pll> &C, pll p) {
    auto gao = [&](int s) {
        return cyc_tsearch(SZ(C), [&](int x, int y)
            { return ori(p, C[x], C[y]) == s; });
    };
    return pii(gao(1), gao(-1));
} // return (a, b), ori(p, C[a], C[b]) >= 0

```

8.8 Intersection of line and convex [157258]

```

int TangentDir(vector<pll> &C, pll dir) {
    return cyc_tsearch(SZ(C), [&](int a, int b) {
        return cross(dir, C[a]) > cross(dir, C[b]);
    });
}
#define cmpl(i) sign(cross(C[i] - a, b - a))
pii lineHull(pll a, pll b, vector<pll> &C) {
    int A = TangentDir(C, a - b);
    int B = TangentDir(C, b - a);
    int n = SZ(C);
    if (cmpl(A) < 0 || cmpl(B) > 0)
        return pii(-1, -1); // no collision
    auto gao = [&](int l, int r) {
        for (int t = l; (l + 1) % n != r; ) {
            int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
            (cmpl(m) == cmpl(t) ? l : r) = m;
        }
        return (l + !cmpl(r)) % n;
    };
    pii res = pii(gao(B, A), gao(A, B)); // (i, j)
    if (res.X == res.Y) // touching the corner i
        return pii(res.X, -1);
    if (!cmpl(res.X) && !cmpl(res.Y)) // along side i, i+1
        switch ((res.X - res.Y + n + 1) % n) {
            case 0: return pii(res.X, res.X);
            case 2: return pii(res.Y, res.Y);
        }
    /* crossing sides (i, i+1) and (j, j+1)
       crossing corner i is treated as side (i, i+1)
       in the order the line hits the convex */
    return res;
} // convex cut: {r, l}

```

8.9 minMaxEnclosingRectangle* [2f07f5]

```

const double INF = 1e18;
pdd solve(vector<pll> &dots) {
    #define diff(u, v) (dots[u] - dots[v])
    #define vec(v) (dots[v] - dots[i])
    hull(dots);
    double Max = 0, Min = INF;

```



```
    return c;
} // expected O(n)
```

8.16 Intersection of two circles* [a9c33e]

```
bool CCinter(Cir &a, Cir &b, pdd &p1, pdd &p2) {
    pdd o1 = a.O, o2 = b.O;
    double r1 = a.R, r2 = b.R, d2 = abs2(o1 - o2);
    double d = sqrt(d2);
    if (d < fabs(r1 - r2) || d > r1 + r2) return 0;
    pdd u = (o1 + o2) * 0.5 +
        (o1 - o2) * ((r2 * r2 - r1 * r1) / (2 * d2));
    double A = sqrt((r1 + r2 + d) * (r1 - r2 + d) *
        (r1 + r2 - d) * (-r1 + r2 + d));
    pdd v = perp(o2 - o1) * A / (2 * d2);
    p1 = u + v, p2 = u - v;
    return 1;
}
```

8.17 Intersection of polygon and circle* [5be77f]

```
// Divides into multiple triangle, and sum up
const double PI = acos(-1);
double _area(pdd pa, pdd pb, double r) {
    if (abs(pa) < abs(pb)) swap(pa, pb);
    if (abs(pb) < eps) return 0;
    double ar, h, theta;
    double a = abs(pb), b = abs(pa), c = abs(pb - pa);
    double k = fabs(cross(pa, pb)); // acos may give NaN
    double B = atan2(k, dot(pb, pb - pa));
    double C = atan2(k, dot(pa, pb));
    if (a > r) {
        ar = (C / 2) * r * r;
        h = a * b * sin(C) / c;
        if (h < r && B < PI / 2)
            ar -= (acos(h / r) * r * r -
                h * sqrt(r * r - h * h));
    } else if (b > r) {
        theta = PI - B - asin(sin(B) / r * a);
        ar = .5 * a * r * sin(theta) +
            (C - theta) / 2 * r * r;
    } else ar = .5 * sin(C) * a * b;
    return ar;
}
double area_poly_circle(const vector<pdd> poly,
    const pdd &o, const double r) {
    double ar = 0;
    FOR (i, 0, SZ(poly) - 1)
        ar += _area(poly[i] - o,
            poly[(i + 1) % SZ(poly)] - o, r) *
            ori(0, poly[i], poly[(i + 1) % SZ(poly)]);
    return fabs(ar);
}
```

8.18 Intersection of line and circle* [3a1dbb]

```
vector<pdd> circleLine(pdd c, double r, pdd a, pdd b) {
    pdd d = b - a, p = projection(a, b, c);
    double s = cross(d, c - a);
    double h2 = r * r - s * s / abs2(d);
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    pdd h = d / abs(d) * sqrt(h2);
    return {p - h, p + h};
}
```

8.19 Tangent line of two circles [2f476e]

```
vector<Line> go(
    const Cir &c1, const Cir &c2, int sign1) {
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;
    double d_sq = abs2(c1.O - c2.O);
    if (sign(d_sq) == 0) return ret;
    double d = sqrt(d_sq);
    pdd v = (c2.O - c1.O) / d;
    double c = (c1.R - sign1 * c2.R) / d;
    if (c * c > 1) return ret;
    double h = sqrt(max(0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
        pdd n = pdd(v.X * c - sign2 * h * v.Y,
            v.Y * c + sign2 * h * v.X);
        pdd p1 = c1.O + n * c1.R;
        pdd p2 = c2.O + n * (c2.R * sign1);
        if (sign(p1.X - p2.X) == 0 and
            sign(p1.Y - p2.Y) == 0)
            p2 = p1 + perp(c2.O - c1.O);
        ret.pb(Line(p1, p2));
    }
    return ret;
}
```

8.20 CircleCover* [2e5df3]

```
const int N = 1021;
struct CircleCover {
    int C;
    Cir c[N];
    bool g[N][N], overlap[N][N];
    // Area[i] : area covered by at least i circles
    double Area[N];
    void init(int _C) { C = _C; }
    struct Teve {
        pdd p; double ang; int add;
        bool operator<(const Teve &a) const
        { return ang < a.ang; }
    } eve[N * 2];
    // strict: x = 0, otherwise x = -1
    bool disjunct(Cir &a, Cir &b, int x)
    { return sign(abs(a.O - b.O) - a.R - b.R) > x; }
    bool contain(Cir &a, Cir &b, int x)
    { return sign(a.R - b.R - abs(a.O - b.O)) > x; }
    bool contain(int i, int j) {
        /* c[j] is non-strictly in c[i]. */
        int s = sign(c[i].R - c[j].R);
        return (s > 0 || (s == 0 && i < j)) &&
            contain(c[i], c[j], -1);
    }
    void solve() {
        fill_n(Area, C + 2, 0);
        FOR (i, 0, C - 1)
            FOR (j, 0, C - 1) overlap[i][j] = contain(i, j);
        FOR (i, 0, C - 1)
            FOR (j, 0, C - 1)
                g[i][j] = !(overlap[i][j] || overlap[j][i] ||
                    disjunct(c[i], c[j], -1));
        FOR (i, 0, C - 1) {
            int E = 0, cnt = 1;
            pdd o = c[i].O; double R = c[i].R;
            FOR (j, 0, C - 1) cnt += j != i && overlap[j][i];
            FOR (j, 0, C - 1)
                if (i != j && g[i][j]) {
                    pdd aa, bb;
                    CCinter(c[i], c[j], aa, bb);
                    double A = atan2(aa.Y - o.Y, aa.X - o.X);
                    double B = atan2(bb.Y - o.Y, bb.X - o.X);
                    eve[E++] = {bb, B, 1}, eve[E++] = {aa, A, -1};
                    if (B > A) ++cnt;
                }
            if (E == 0) Area[cnt] += acos(-1) * R * R;
            else {
                sort(eve, eve + E);
                eve[E] = eve[0];
                FOR (j, 0, E - 1) {
                    cnt += eve[j].add;
                    Area[cnt] += cross(eve[j].p, eve[j + 1].p) * .5;
                    double th = eve[j + 1].ang - eve[j].ang;
                    if (th < 0) th += 2 * acos(-1);
                    Area[cnt] += (th - sin(th)) * R * R * .5;
                }
            }
        }
    }
};
```

8.21 3Dpoint* [ccd7b]

```
struct Point {
    double x, y, z;
    Point(double x = 0, double y = 0, double z = 0)
        : x(x), y(y), z(z) {}
    Point(pdd p) { x = p.X, y = p.Y, z = abs2(p); }
};
Point operator-(Point p1, Point p2)
{ return Point(p1.x - p2.x, p1.y - p2.y, p1.z - p2.z); }
Point operator+(Point p1, Point p2)
{ return Point(p1.x + p2.x, p1.y + p2.y, p1.z + p2.z); }
Point operator*(Point p1, double v)
{ return Point(p1.x * v, p1.y * v, p1.z * v); }
Point operator/(Point p1, double v)
{ return Point(p1.x / v, p1.y / v, p1.z / v); }
Point cross(Point a, Point b) {
    return Point(a.y * b.z - a.z * b.y,
        a.z * b.x - a.x * b.z, a.x * b.y - a.y * b.x);
}
double dot(Point p1, Point p2)
{ return p1.x * p2.x + p1.y * p2.y + p1.z * p2.z; }
double abs(Point a)
{ return sqrt(dot(a, a)); }
Point cross3(Point a, Point b, Point c)
{ return cross(b - a, c - a); }
```

```
double area(Point a, Point b, Point c)
{ return abs(cross3(a, b, c)); }
double volume(Point a, Point b, Point c, Point d)
{ return dot(cross3(a, b, c), d - a); }
// azimuth (longitude) from the x-axis, in [-pi, pi]
double phi(Point p) { return atan2(p.y, p.x); }
// zenith angle (latitude) from the z-axis, in [0, pi]
double theta(Point p)
{ return atan2(sqrt(p.x * p.x + p.y * p.y), p.z); }
Point masscenter(Point a, Point b, Point c, Point d)
{ return (a + b + c + d) / 4; }
pdd proj(Point a, Point b, Point c, Point u) {
// proj. u to the plane of a, b, and c
Point e1 = b - a;
Point e2 = c - a;
e1 = e1 / abs(e1);
e2 = e2 - e1 * dot(e2, e1);
e2 = e2 / abs(e2);
Point p = u - a;
return pdd(dot(p, e1), dot(p, e2));
}
Point rotate_around(Point p, double angle, Point axis) {
double s = sin(angle), c = cos(angle);
Point u = axis / abs(axis);
return u * dot(u, p) * (1 - c) + p * c +
    cross(u, p) * s;
}
```

8.22 Convexhull3D* [02414a]

```
struct convex_hull_3D {
struct Face {
int a, b, c;
Face(int ta, int tb, int tc) : a(ta), b(tb), c(tc) {}
}; // return the faces with pt indexes
vector<Face> res;
vector<Point> P;
convex_hull_3D(const vector<Point> &P) : res(), P(P) {
// all points coplanar case will WA, O(n^2)
int n = SZ(P);
if (n <= 2) return; // be careful about edge case
// ensure first 4 points are not coplanar
swap(P[1], *find_if(ALL(P), [&](auto p)
{ return sign(abs(P[0] - p)) != 0; }));
swap(P[2], *find_if(ALL(P), [&](auto p)
{ return sign(abs(cross3(p, P[0], P[1]))) != 0; }));
swap(P[3], *find_if(ALL(P), [&](auto p)
{ return sign(volume(P[0], P[1], P[2], p)) != 0; }));
vector<vector<int>> flag(n, vector<int>(n));
res.emplace_back(0, 1, 2); res.emplace_back(2, 1, 0);
FOR (i, 3, n - 1) {
vector<Face> next;
for (auto [a, b, c] : res) {
int d = sign(volume(P[a], P[b], P[c], P[i]));
if (d <= 0) next.pb(a, b, c);
flag[a][b] = flag[b][c] = flag[c][a] = d;
}
for (auto f : res) {
auto add = [&](int x, int y) {
if (flag[x][y] > 0 && flag[y][x] <= 0)
next.emplace_back(x, y, i);
};
add(f.a, f.b);
add(f.b, f.c);
add(f.c, f.a);
}
res = next;
}
}
bool same(Face s, Face t) {
for (int x : {t.a, t.b, t.c})
if (sign(volume(P[s.a], P[s.b], P[s.c], P[x])))
return 0;
return 1;
}
int polygon_face_num() {
int ans = 0;
FOR (i, 0, SZ(res) - 1)
ans += none_of(res.begin(), res.begin() + i,
[&](Face g) { return same(res[i], g); });
return ans;
}
double get_volume() {
double ans = 0;
for (auto f : res)
ans += volume(Point(0, 0, 0), P[f.a], P[f.b], P[f.c]);
return fabs(ans / 6);
}
double get_dis(Point p, Face f) {
```

```
Point a = P[f.a], b = P[f.b], c = P[f.c];
return fabs(volume(a, b, c, p)) / area(a, b, c);
};
// n^2 delaunay: facets with negative z normal of
// convexhull of (x, y, x^2 + y^2), use a pseudo-point
// (0, 0, inf) to avoid degenerate case
```

8.23 DelaunayTriangulation* [e5bda0]

```
/* Delaunay Triangulation:
Given a sets of points on 2D plane, find a
triangulation such that no points will strictly
inside circumcircle of any triangle. */
struct Edge {
int id; // oidx[id]
list<Edge>::iterator twin;
Edge(int _id = 0) : id(_id) {}
};
struct Delaunay { // 0-base
int n, oidx[N];
list<Edge> head[N]; // result udir. graph
pll p[N];
void init(int _n, pll _p[]) {
n = _n, iota(oidx, oidx + n, 0);
FOR (i, 0, n - 1) head[i].clear();
sort(oidx, oidx + n, [&](int a, int b)
{ return _p[a] < _p[b]; });
FOR (i, 0, n - 1) p[i] = _p[oidx[i]];
divide(0, n - 1);
}
void addEdge(int u, int v) {
head[u].push_front(Edge(v));
head[v].push_front(Edge(u));
head[u].begin()->twin = head[v].begin();
head[v].begin()->twin = head[u].begin();
}
void divide(int l, int r) {
if (l == r) return;
if (l + 1 == r) return addEdge(l, l + 1);
int mid = (l + r) >> 1, nw[2] = {l, r};
divide(l, mid), divide(mid + 1, r);
auto gao = [&](int t) {
pll pt[2] = {p[nw[0]], p[nw[1]]};
for (auto it : head[nw[t]]) {
int v = ori(pt[1], pt[0], p[it.id]);
if (v > 0 || (v == 0 && abs2(pt[t ^ 1] - p[it.id])
< abs2(pt[1] - pt[0])))
return nw[t] = it.id, true;
}
return false;
};
while (gao(0) || gao(1));
addEdge(nw[0], nw[1]); // add tangent
while (true) {
pll pt[2] = {p[nw[0]], p[nw[1]]};
int ch = -1, sd = 0;
FOR (t, 0, 1)
for (auto it : head[nw[t]])
if (ori(pt[0], pt[1], p[it.id]) > 0 &&
(ch == -1 ||
in_cc({pt[0], pt[1], p[ch]}, p[it.id])))
ch = it.id, sd = t;
if (ch == -1) break; // upper common tangent
auto &hd = head[nw[sd]];
for (auto it = hd.begin(); it != hd.end(); )
if (seg_strict_intersect(pt[sd], p[it->id],
pt[sd ^ 1], p[ch]))
head[it->id].erase(it->twin), hd.erase(it++);
else ++it;
nw[sd] = ch, addEdge(nw[0], nw[1]);
}
}
} tool;
```

8.24 Triangulation Voronoi* [6ddd07]

```
// all coord. must be even; then halfPlaneInter(vec[i])
vector<vector<Line>> vec;
void build_voronoi_line(int n, pll *arr) {
tool.init(n, arr); // Delaunay
vec.clear(), vec.resize(n);
FOR (i, 0, n - 1)
for (auto e : tool.head[i]) {
int u = tool.oidx[i], v = tool.oidx[e.id];
pll m = (arr[v] + arr[u]) / 2LL,
d = perp(arr[v] - arr[u]);
vec[u].pb(Line(m, m + d));
}
}
```

}

8.25 Minkowski Sum* [e7102c]

```
vector<pll> Minkowski(vector<pll> A, vector<pll> B) {
    hull(A), hull(B); // neither hull may be degenerate
    int n = SZ(A), m = SZ(B);
    vector<pll> C(1, A[0] + B[0]), s1, s2;
    FOR (i, 0, n - 1) s1.pb(A[(i + 1) % n] - A[i]);
    FOR (i, 0, m - 1) s2.pb(B[(i + 1) % m] - B[i]);
    for (int i = 0, j = 0; i < n || j < m; )
        if (j >= m || (i < n && cross(s1[i], s2[j]) >= 0))
            C.pb(B[j % m] + A[i++]);
        else C.pb(A[i % n] + B[j++]);
    return hull(C), C;
}
```

8.26 Closest Pair [6f81f1]

```
// closest pair; only needs pll + X/Y
pair<pll, pll> closest_pair(vector<pll> v) {
    sort(ALL(v), [](pll a, pll b) { return a.Y < b.Y; });
    pair<ll, pair<pll, pll>> r{LLONG_MAX, {}};
    set<pll> s;
    int j = 0;
    for (pll p : v) {
        ll d = 1 + (ll)sqrt(r.F);
        while (v[j].Y <= p.Y - d) s.erase(v[j++]);
        auto lo = s.lower_bound(pll(p.X - d, p.Y));
        auto hi = s.upper_bound(pll(p.X + d, p.Y));
        for (; lo != hi; lo++) {
            ll dx = lo->X - p.X, dy = lo->Y - p.Y;
            r = min(r, {dx * dx + dy * dy, {lo, p}});
        }
        s.insert(p);
    }
    return r.S; // r.F is the squared distance
}
```

9 Else

9.1 Cyclic Ternary Search* [9017cc]

```
/* bool pred(int a, int b);
f(0) ~ f(n - 1) is a cyclic-shift U-function
return idx s.t. pred(x, idx) is false forall x*/
int cyc_tsearch(int n, auto pred) {
    if (n == 1) return 0;
    int l = 0, r = n; bool rv = pred(1, 0);
    while (r - l > 1) {
        int m = (l + r) / 2;
        if (pred(0, m) ? rv : pred(m, (m + 1) % n)) r = m;
        else l = m;
    }
    return pred(l, r % n) ? l : r % n;
}
```

9.2 Mo's Algorithm(With modification) [0e4113]

```
/*
Mo's Algorithm With modification
Block: N^{2/3}, Complexity: N^{5/3}
*/
struct Query {
    int L, R, LBid, RBid, T;
    Query(int l, int r, int t):
        L(l), R(r), LBid(l / blk), RBid(r / blk), T(t) {}
    bool operator<(const Query &q) const {
        if (LBid != q.LBid) return LBid < q.LBid;
        if (RBid != q.RBid) return RBid < q.RBid;
        return T < q.T;
    }
};
void solve(vector<Query> query) {
    sort(query.begin(), query.end());
    int L = 0, R = -1, T = -1;
    for (auto q : query) {
        while (T < q.T) addTime(L, R, ++T); // TODO
        while (T > q.T) subTime(L, R, T--); // TODO
        while (R < q.R) add(arr[++R]); // TODO
        while (L > q.L) add(arr[--L]); // TODO
        while (R > q.R) sub(arr[R--]); // TODO
        while (L < q.L) sub(arr[L++]); // TODO
        // answer query
    }
}
```

9.3 Mo's Algorithm On Tree [e05b1a]

```
/*
Mo's Algorithm On Tree
Preprocess:
1) LCA
2) dfs with in[u] = dft++, out[u] = dft++
3) ord[in[u]] = ord[out[u]] = u
4) bitset<MAXN> inset
*/
struct Query {
    int L, R, LBid, lca;
    Query(int u, int v) {
        int c = LCA(u, v);
        if (c == u || c == v)
            lca = -1, L = out[c ^ u ^ v], R = out[c];
        else if (out[u] < in[v])
            lca = c, L = out[u], R = in[v];
        else lca = c, L = out[v], R = in[u];
        LBid = L / blk;
    }
};
bool operator<(const Query &q) const {
    if (LBid != q.LBid) return LBid < q.LBid;
    return R < q.R;
}
void flip(int x) {
    if (inset[x]) sub(arr[x]); // TODO
    else add(arr[x]); // TODO
    inset.flip(x);
}
void solve(vector<Query> query) {
    sort(query.begin(), query.end());
    int L = 0, R = -1;
    for (auto q : query) {
        while (R < q.R) flip(ord[++R]);
        while (L > q.L) flip(ord[--L]);
        while (R > q.R) flip(ord[R--]);
        while (L < q.L) flip(ord[L++]);
        if (~q.lca) add(arr[q.lca]);
        // answer query
        if (~q.lca) sub(arr[q.lca]);
    }
}
```

9.4 Additional Mo's Algorithm Trick

- Mo's Algorithm With Addition Only
 - Sort queries same as the normal Mo's algorithm.
 - For each query $[l, r]$:
 - If $l/blk = r/blk$, brute-force.
 - If $l/blk \neq curL/blk$, initialize $curL := (l/blk + 1) \cdot blk$, $curR := curL - 1$
 - If $r > curR$, increase $curR$
 - decrease $curL$ to fit l , and then undo after answering
- Mo's Algorithm With Offline Second Time
 - Require: Changing answer $\equiv$ adding $f([l, r], r+1)$.
 - Require: $f([l, r], r+1) = f([1, r], r+1) - f([1, l], r+1)$.
 - Part1: Answer all $f([1, r], r+1)$ first.
 - Part2: Store $curR \rightarrow R$ for $curL$ (reduce the space to $O(N)$), and then answer them by the second offline algorithm.
 - Note: You must do the above symmetrically for the left boundaries.

9.5 Hilbert Curve [1274a3]

```
ll hilbert(int n, int x, int y) {
    ll res = 0;
    for (int s = n / 2; s; s >= 1) {
        int rx = (x & s) > 0;
        int ry = (y & s) > 0;
        res += s * 1ll * s * ((3 * rx) ^ ry);
        if (ry == 0) {
            if (rx == 1) x = s - 1 - x, y = s - 1 - y;
            swap(x, y);
        }
    }
    return res;
} // n = 2^k
```

9.6 DynamicConvexTrick* [193e69]

```
// only works for integer coordinates!! maintain max
struct Line {
    mutable ll a, b, p;
    bool operator<(const Line &o) const { return a < o.a; }
    bool operator<(ll x) const { return p < x; }
};
struct DynamicHull : multiset<Line, less<>> {
    static const ll kInf = 1e18;
    ll Div(ll a, ll b)
        return a / b - ((a ^ b) < 0 && a % b);
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = kInf; return 0; }
    }
```

```

    if (x->a == y->a) x->p = x->b > y->b ? kInf : -kInf;
    else x->p = Div(y->b - x->b, x->a - y->a);
    return x->p >= y->p;
}
void addline(ll a, ll b) {
    auto z = insert({a, b, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y))
        isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
        isect(x, erase(y));
}
ll query(ll x) {
    auto l = *lower_bound(x);
    return l.a * x + l.b;
}
};

```

9.7 All LCS* [84c2d5]

```

struct AllLCS { // 0-base
    string t;
    vector<int> h;
    AllLCS(const string &t) : t(t), h(t.size()) {
        iota(h.begin(), h.end(), 0);
    }
    void push(char c) { // append c to the other string
        int v = -1;
        FOR (i, 0, (int)t.size() - 1)
            if (t[i] == c || h[i] < v) swap(h[i], v);
    }
    // after pushing s[0, a], for every b <= c:
    // LCS(s[0, a], t[b, c]) =
    // c - b + 1 - #{i <= c : h[i] >= b}
    // h[i] might become -1 !!
};

```

9.8 Matroid Intersection

Start from $S = \emptyset$. In each iteration, let

- $Y_1 = \{x \notin S \mid S \cup \{x\} \in I_1\}$
- $Y_2 = \{x \notin S \mid S \cup \{x\} \in I_2\}$

If there exists $x \in Y_1 \cap Y_2$, insert x into S . Otherwise for each $x \in S, y \notin S$, create edges

- $x \rightarrow y$ if $S - \{x\} \cup \{y\} \in I_1$.
- $y \rightarrow x$ if $S - \{x\} \cup \{y\} \in I_2$.

Find a *shortest* path (with BFS) starting from a vertex in Y_1 and ending at a vertex in Y_2 which doesn't pass through any other vertices in Y_2 , and alternate the path. The size of S will be incremented by 1 in each iteration. For the weighted case, assign weight $w(x)$ to vertex x if $x \in S$ and $-w(x)$ if $x \notin S$. Find the path with the minimum number of edges among all minimum length paths and alternate it.

9.9 Matroid Intersection [63f9dd]

```

// max common independent set of two matroids on
// {0..n-1}. Each matroid provides
// void build(const vector<int> &s) // s[i]: i in S?
// bool ind(int x, int y) // S - x + y independent?
// // // x = -1 means just S + y
// O(r) rounds, each O(n^2) oracle calls. Weighted ver:
// replace the BFS with Bellman-Ford minimising
// (sum of w(x), x in S / -w(y), y not in S; #edges).
template <class M1, class M2>
vector<int> matroid_isect(int n, M1 &m1, M2 &m2) {
    vector<int> sel(n, 0);
    while (1) {
        m1.build(sel), m2.build(sel);
        vector<int> pre(n, -2), q;
        FOR (y, 0, n - 1)
            if (!sel[y] && m1.ind(-1, y)) pre[y] = -1, q.pb(y);
        int t = -1;
        for (int h = 0; h < (int)q.size(); h++) {
            int u = q[h];
            if (!sel[u] && m2.ind(-1, u)) {
                t = u;
                break;
            }
            FOR (v, 0, n - 1)
                if (pre[v] == -2)
                    if (sel[u] ? !sel[v] && m1.ind(u, v)
                        : sel[v] && m2.ind(v, u))
                        pre[v] = u, q.pb(v);
        }
        if (t < 0) return sel;
        for (int v = t; v != -1; v = pre[v]) sel[v] ^= 1;
    }
}
struct ColorMat { // <= cap[c] chosen of colour c
    vector<int> col, cap, cnt;
    ColorMat(vector<int> col, vector<int> cap)
        : col(col), cap(cap) {}
};

```

```

void build(const vector<int> &s) {
    cnt.assign(cap.size(), 0);
    FOR (i, 0, (int)s.size() - 1) if (s[i]) cnt[col[i]]++;
}
bool ind(int x, int y) {
    int c = cnt[col[y]];
    if (x >= 0 && col[x] == col[y]) c--;
    return c < cap[col[y]];
}
};
struct GraphMat { // chosen edges form a forest
    int n;
    vector<pair<int, int>> e;
    vector<int> sel, f;
    GraphMat(int n, vector<pair<int, int>> e)
        : n(n), e(e), f(n) {}
    void build(const vector<int> &s) { sel = s; }
    int fd(int a) {
        while (f[a] != a) a = f[a] = f[f[a]];
        return a;
    }
    bool ind(int x, int y) {
        iota(f.begin(), f.end(), 0);
        FOR (i, 0, (int)e.size() - 1)
            if (sel[i] && i != x) f[fd(e[i].F)] = fd(e[i].S);
        return fd(e[y].F) != fd(e[y].S);
    }
};

```

9.10 AdaptiveSimpson* [b98c97]

```

template <typename Func, typename d = double>
struct Simpson {
    using pdd = pair<d, d>;
    Func f;
    pdd mix(pdd l, pdd r, optional<d> fm = {}) {
        d h = (r.F - l.F) / 2, v = fm.value_or(f(l.F + h));
        return {v, h / 3 * (l.S + 4 * v + r.S)};
    }
    d eval(pdd l, pdd r, d fm, d eps) {
        pdd m((l.F + r.F) / 2, fm);
        d s = mix(l, r, fm).S;
        auto [flm, sl] = mix(l, m);
        auto [fmr, sr] = mix(m, r);
        d delta = sl + sr - s;
        if (abs(delta) <= 15 * eps)
            return sl + sr + delta / 15;
        return eval(l, m, flm, eps / 2) +
            eval(m, r, fmr, eps / 2);
    }
    d eval(d l, d r, d eps) {
        return eval(
            {l, f(l)}, {r, f(r)}, f((l + r) / 2), eps);
    }
    d eval2(d l, d r, d eps, int k = 997) {
        d h = (r - l) / k, s = 0;
        for (int i = 0; i < k; i++, l += h)
            s += eval(l, l + h, eps / k);
        return s;
    }
};
template <typename Func>
Simpson<Func> make_simpson(Func f) {
    return {f};
}

```

9.11 Simulated Annealing [a6e293]

```

double factor = 100000;
const int base = 1e9; // remember to run ~ 10 times
FOR (it, 1, 1000000) {
    // ans: answer, nw: current value, rnd(): mt19937
    // rnd()
    if (exp(-(nw - ans) / factor) >=
        (double)rnd() % base / base)
        ans = nw;
    factor *= 0.99995;
}

```

9.12 Tree Hash* [6e1149]

```

typedef unsigned long long ull; // need G, seed
ull seed, h[N]; // h[u]: hash of u's subtree
ull shift(ull x) {
    x ^= x << 13;
    x ^= x >> 7;
    x ^= x << 17;
    return x;
}

```

```
ull dfs(int u, int f) {
    ull sum = seed;
    for (int i : G[u]) if (i != f) sum += shift(dfs(i, u));
    return h[u] = sum;
}
```

9.13 Binary Search On Fraction* [765c5a]

```
struct Q {
    ll p, q;
    Q go(Q b, ll d) { return {p + b.p*d, q + b.q*d}; }
};
bool pred(Q);
// returns smallest p/q in [lo, hi] such that
// pred(p/q) is true, and 0 <= p,q <= N
Q frac_bs(ll N) {
    Q lo{0, 1}, hi{1, 0};
    if (pred(lo)) return lo;
    assert(pred(hi));
    bool dir = 1, L = 1, H = 1;
    for (; L || H; dir = !dir) {
        ll len = 0, step = 1;
        for (int t = 0; t < 2 && (t ? step/=2 : step*=2);)
            if (Q mid = hi.go(lo, len + step);
                mid.p > N || mid.q > N || dir ^ pred(mid))
                t++;
            else len += step;
        swap(lo, hi = hi.go(lo, len));
        (dir ? L : H) = !len;
    }
    return dir ? hi : lo;
}
```

9.14 1D1D [770b85]

```
typedef pair<int, int> pii;
// cost(i, j): cost of transit from i to j
// search(i, j): last point when i is better in row i,
// j, need to check whether cost(i, i) is defined
int cost(int i, int j);
int search(int i, int j, int L, int R = N);
void concave1D1D() {
    vector<int> dp(N + 1, 0);
    vector<pii> st; // (idx, right end h_idx)
    st.emplace_back(pii(0, N + 1));
    FOR (j, 1, N) {
        while (st.back().S < j) st.pop_back();
        int i = st.back().F;
        dp[j] = dp[i] + cost(i, j);
        while (
            !st.empty() && search(j, i, j) >= st.back().S) {
            st.pop_back();
            i = st.back().F;
        }
        st.emplace_back(pii(j, search(j, i, j)));
    }
}
void convex1D1D() {
    vector<int> dp(N + 1, 0);
    deque<pii> dq; // (idx, right end)
    dq.emplace_back(pii(0, N + 1));
    FOR (j, 1, N) {
        while (dq.front().S < j) dq.pop_front();
        int i = dq.front().F;
        dp[j] = dp[i] + cost(i, j);
        i = dq.back().F;
        while (dq.size() >= 2 &&
            search(i, j, j) <= dq.end()[-2].S) {
            dq.pop_back();
            i = dq.back().F;
        }
        dq.back().S = search(i, j, j);
        dq.emplace_back(pii(j, N + 1));
    }
}
```

9.15 SMAWK [4f281d]

```
long long query(int l, int r);
struct SMAWK {
    // Condition:
    // If M[1][0] < M[1][1] then M[0][0] < M[0][1]
    // If M[1][0] == M[1][1] then M[0][0] <= M[0][1]
    // For all i, find r_i s.t. M[i][r_i] is maximum //
    // minimum.
    int ans[N], tmp[N];
    void interpolate(vector<int> l, vector<int> r) {
        int n = l.size(), m = r.size();
        vector<int> nl;
```

```
for (int i = 1; i < n; i += 2) { nl.pb(l[i]); }
run(nl, r);
for (int i = 1, j = 0; i < n; i += 2) {
    while (j < m && r[j] < ans[l[i]]) j++;
    assert(j < m && ans[l[i]] == r[j]);
    tmp[l[i]] = j;
}
for (int i = 0; i < n; i += 2) {
    int curl = 0, curr = m - 1;
    if (i) curl = tmp[l[i - 1]];
    if (i + 1 < n) curr = tmp[l[i + 1]];
    long long res = query(l[i], r[curl]);
    ans[l[i]] = r[curl];
    FOR (j, curl + 1, curr) {
        ll nxt = query(l[i], r[j]);
        if (res < nxt) res = nxt, ans[l[i]] = r[j];
    }
}
}
void reduce(vector<int> l, vector<int> r) {
    int n = l.size(), m = r.size();
    vector<int> nr;
    for (int j : r) {
        while (!nr.empty()) {
            int i = nr.size() - 1;
            if (query(l[i], nr.back()) <= query(l[i], j))
                nr.pop_back();
            else break;
        }
        if (nr.size() < n) nr.pb(j);
    }
    run(l, nr);
}
void run(vector<int> l, vector<int> r) {
    int n = l.size(), m = r.size();
    if (max(n, m) <= 2) {
        for (int i : l) {
            ans[i] = r[0];
            if (m > 1) {
                if (query(i, r[0]) < query(i, r[1]))
                    ans[i] = r[1];
            }
        }
    } else if (n >= m) {
        interpolate(l, r);
    } else {
        reduce(l, r);
    }
}
};
```

9.16 Min Plus Convolution* [5d8ac1]

```
// a is convex a[i+1]-a[i] <= a[i+2]-a[i+1]
vector<int> min_plus_convolution(
    vector<int> &a, vector<int> &b) {
    int n = (int)a.size(), m = (int)b.size();
    vector<int> c(n + m - 1, INF);
    auto dc = [&](auto Y, int l, int r, int jl, int jr) {
        if (l > r) return;
        int mid = (l + r) / 2, from = -1, &best = c[mid];
        FOR (j, jl, jr)
            if (int i = mid - j; i >= 0 && i < n)
                if (best > a[i] + b[j])
                    best = a[i] + b[j], from = j;
        Y(Y, l, mid - 1, jl, from),
        Y(Y, mid + 1, r, from, jr);
    };
    return dc(dc, 0, n - 1 + m - 1, 0, m - 1), c;
}
```

9.17 Bitset LCS [83b00e]

```
cin >> n >> m;
for (int i = 1, x; i <= n; i++) cin >> x, p[x].set(i);
for (int i = 1, x; i <= m; i++) {
    cin >> x, (g = f) |= p[x];
    f.shiftLeftByOne(), f.set(0);
    ((f = g - f) ^= g) &= g;
}
cout << f.count() << '\n';
```

9.18 Python

```
from decimal import *
setcontext(Context(prec=MAX_PREC, Emax=MAX_EMAX,
                    rounding=ROUND_HALF_UP))
print(Decimal(input()) * Decimal(input()))
from fractions import Fraction
Fraction('3.14159').limit_denominator(10).numerator # 22
```