## Profilight o

## **JASON LED PLUS**



1059				1059
90*				90*
100	1		V	1
60°	$\times (\!\!\!/ \!\!\!\!/ \!\!\!\!/ \!\!\!\!\!/ \!\!\!\!\!\!\!\!\!\!\!\!\!$	<b>&gt; 310</b>	$\times$	60*
		300	2	) e
	$\rightarrow$	500	+	
30*	159	00	15*	30*

Vlastnosti svietidla							
Označenie:	JASON-P						
Popis:	Interiérové minimalis- tické zapustené LED svietidlo.						
Montáž:	SUR, REC						
Optika:	Opálový PMMA difúzor						
Materiál:	PC, hliník						
Krytie IP:	44						
Krytie IK:	08						
Trieda ochrany:	II						
Index podania farieb:	> 80						
Tolerancia sv. toku:	+-10						
Pracovná teplota:	Od -15 do +35						
Životnosť:	L70B50 35 000						
Možnosti:	DALI; Rozšírenie na SUR montáž						

## Dostupné varianty

Kód	Výkon	Intenzita sv. toku	CCT	Výška	Priemer
[-]	[W]	[lm]	[K]	[mm]	[mm]
JASON-P-20-4	20	2700	4000	70	222
JASON-P-25-4	25	3450	4000	70	222

ProfiLIGHT Corporations, s.r.o
Obrancov mieru 346/4
018 41 Dubnica nad Váhom

Kontakt: +421 903 817 266

Tel.: + 421 424 440 208

E-mail: obchod@profilight.sk

