



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 1/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

1 Identification

Product identifier

Trade name: 836LFNC

Other Means of Identification: Flux Pen: Lead Free, No Clean

Related Part Number: 836LFNC-Pen, 836LFNC-P

Application of the substance / the mixture Flux

Uses advised against Not available

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office)

1210 Corporate Drive

Burlington, Ontario L7L 5R6

CANADA

+(1) 800-340-0772

+(1) 905-331-1396

info@mgchemicals.com

Distributor:

Masline

511 Clinton Ave S

Rochester, New York 14620

United States

+(1) 586-546-5373

Information department: sds@mgchemicals.com

Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)

USA or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service

CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

2 Hazard identification

Classification of the substance or mixture

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) – Category 3

H336 May cause drowsiness or dizziness.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 2/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

ethanol
Propan-2-ol

· Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapors.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

· Other hazards Repeated exposure may cause skin dryness or cracking.

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

64-17-5	ethanol	65-85% w/w *
67-63-0	Propan-2-ol	10-30% w/w *

(Contd. on page 3)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 3/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 2)

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

· After inhalation:

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

· After skin contact:

Take off immediately all contaminated clothing.

Wash with plenty of soap and water.

· After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

· After swallowing:

Rinse mouth.

Do NOT induce vomiting.

If symptoms persist consult doctor.

· Information for doctor: Treat symptomatically

· Most important symptoms and effects, both acute and delayed

See section 11 for additional information.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use water spray to cool containers.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture

Prevent fire-fighting wash from entering waterway or sewer system.

· Hazardous combustion products: Carbon Oxides (CO_x)

· Advice for firefighters

· Protective equipment: Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

— CA —

(Contd. on page 4)



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 4/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Remove or keep away all sources of extreme heat or open flames.
Avoid breathing mist, spray, or vapors.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Avoid breathing mist, spray, or vapors.
Use only outdoors or in a well-ventilated area.
Keep out of reach of children.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
Ground and bond container and receiving equipment.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store in a well-ventilated place. Keep cool.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Store locked up.
- **Specific end use(s)** See section 1.2

— CA —
(Contd. on page 5)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 5/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 4)

8 Exposure controls/ Personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

64-17-5 ethanol	
EL (Canada)	STEL: 1000 ppm
EV (Canada)	TWA: 1,900 mg/m ³ , 1,000 ppm
PEL (USA)	TWA: 1900 mg/m ³ , 1000 ppm
REL (USA)	TWA: 1900 mg/m ³ , 1000 ppm
TLV (USA)	STEL: 1880 mg/m ³ , 1000 ppm A3
67-63-0 Propan-2-ol	
EL (Canada)	STEL: 400 ppm TWA: 200 ppm
EV (Canada)	STEL: 400 ppm TWA: 200 ppm
PEL (USA)	TWA: 980 mg/m ³ , 400 ppm
REL (USA)	STEL: 1225 mg/m ³ , 500 ppm TWA: 980 mg/m ³ , 400 ppm
TLV (USA)	STEL: 984 mg/m ³ , 400 ppm TWA: 491 mg/m ³ , 200 ppm BEI, A4
· Ingredients with biological limit values:	
67-63-0 Propan-2-ol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

· Additional information:

The lists that were valid during the creation were used as basis.
Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· Exposure controls

· **Appropriate engineering controls** Keep airborne concentrations below exposure limits.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Advice should be sought from respiratory protection specialists.
If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

(Contd. on page 6)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 6/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 5)

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses or tightly sealed goggles: EN 166

* 9 Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Form:	Low viscosity
Color:	Colorless
Odor:	Alcohol-like
Odor threshold:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C (172.4 °F)
Flammability:	Highly flammable.
Explosion limits:	
Lower:	2 Vol %
Upper:	15 Vol %
Flash point:	12 °C (53.6 °F)
Auto igniting:	365 °C (689 °F)
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	
Kinematic at 20 °C (68 °F):	<3 mm ² /s
Dynamic:	Not determined.

(Contd. on page 7)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 7/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 6)

· Solubility in / Miscibility with · Water: · Partition coefficient (n-octanol/water): · Vapor pressure at 20 °C (68 °F): · Relative density at 25 °C (77 °F): · Vapor density (air=1): · Particle characteristics	Not miscible or difficult to mix. Not determined. 59 hPa (44.3 mm Hg) 0.81 ≥1.6 Not applicable.
· Other information · Important information on protection of health and environment, and on safety. · Ignition temperature: · Danger of explosion: · Solvent content: · Organic solvents: · Solids content: · Evaporation rate	Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapor mixtures are possible. 75–115 % 0.0 % Not determined.

10 Stability and reactivity

- **Reactivity** At elevated temperatures, may react with aluminum and generate hydrogen gas.
- **Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.
- **Incompatible materials:**

Strong acids

Strong bases

Halogenated compounds

Strong oxidizing agents

Aluminum at temperatures ≥49 °C
- **Hazardous decomposition products:**

No dangerous decomposition products known.

Hazardous combustion products: see section 5.

— CA —
(Contd. on page 8)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 8/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 7)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

64-17-5 ethanol		
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/L (rat)
67-63-0 Propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/L (rat)

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: Irritating effect.

· Sensitization: No sensitizing effects known.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

· Specific target organ toxicity - repeated exposure

Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

· Summary of effects and symptoms by route of exposure

· Eyes:

pain
tearing of the eyes
redness, serious irritation

· Skin: may cause redness, mild irritation, and dry skin

· Inhalation:

dizziness or drowsiness
irritation of the respiratory tract

· Swallowed:

irritation
burning sensation
see inhalation symptoms

· Delayed and immediate effects as well as chronic effects from short and long-term exposure

Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 9)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 9/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 8)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
64-17-5	ethanol	1
67-63-0	Propan-2-ol	3
· NTP (National Toxicology Program)		
None of the ingredients is listed.		

12 Ecological information

· Toxicity

· Aquatic toxicity:	
64-17-5 ethanol	
LC50	>1,000 mg/L (fish) Biodegradable
67-63-0 Propan-2-ol	
EC50/ 24 h	5,102 mg/L (daphnia)
EC50/ 72 h	>2,000 mg/L (algae)
LC50 96h	9,640 mg/L (minnow)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- **Recommendation:** This material and its container must be disposed of as hazardous waste.

· Uncleaned packagings:

· Recommendation:

Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.

(Contd. on page 10)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 10/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 9)
Where possible retain label warnings and SDS and observe all notices pertaining to the product.

*14 Transport information

· UN-Number	
· DOT/TDG, IMDG, IATA	UN1987
· UN proper shipping name	
· DOT/TDG, IATA	Alcohols, n.o.s. (ethanol, Propan-2-ol)
· IMDG	ALCOHOLS, N.O.S. (ethanol, Propan-2-ol)
· Transport hazard class(es)	
· DOT/TDG (Transport dangerous goods):	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT/TDG, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
	Limited Quantity
836LFNC-P	

(Contd. on page 11)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 11/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 10)

· DOT/TDG	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Special precautions for user	
· Hazard identification number (Kemler code):	Not applicable. 33
· EMS Number:	F-E,S-D
· Stowage Category	B
· UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S. (ETHANOL, PROPAN-2-OL), 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· OSHA Hazard Communication Standard (29 CFR Part 1900)

The safety data sheet and label comply with HCS 2024.

· Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

· Sara

· Section 355 (extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
67-63-0 Propan-2-ol
· TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
· Hazardous Air Pollutants
None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.

(Contd. on page 12)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 12/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 11)

· Chemicals known to cause developmental toxicity:	
64-17-5	ethanol

· **Note:**

While ethanol is present in this product, the Proposition 65 warning does NOT apply since this product is not an alcoholic beverage.

· **Carcinogenic categories**

· TLV (Threshold Limit Value)	
64-17-5	ethanol
67-63-0	Propan-2-ol

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· **Canadian substance listings:**

· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	

· Canadian Non-Domestic Substances List (NDSL)	
None of the ingredients is listed.	

· Canadian Ingredient Disclosure list (limit 0.1%)	
64-17-5	ethanol

· Canadian Ingredient Disclosure list (limit 1%)	
67-63-0	Propan-2-ol

· **HMIS-ratings (scale 0 - 4)**

Health = * 2

Fire = 3

Reactivity = 0

· **Europe**

· **RoHS (Restriction of Hazardous Substances Directive)**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· **WEEE (Waste Electrical and Electronic Equipment Directive)**

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

· Per- and polyfluoroalkyl substances (PFAS)	
None of the ingredients is listed.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Regulatory department

(Contd. on page 13)

— CA —



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 13/13

Date of issue 06/17/2025

Version number 1.00

Revision: 06/17/2025

Trade name: 836LFNC

(Contd. of page 12)

- **Contact:** sds@mgchemicals.com
- **Date of previous version** 05/28/2025
- **Date of preparation** 06/17/2025
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
- *** Data compared to the previous version altered.**

—CA—