

# CSC 211: Computer Programming

## Arrays, Vectors

Michael Conti


Department of Computer Science and Statistics  
University of Rhode Island

Fall 2022



## Administrative Notes

### ▸ A02 Due Sunday 10/16



### ▸ MC#03 due 10/20

2

## Question

- Write a program that reads in **3** values and outputs the same values in reverse order
- Write a program that reads in **n** values and outputs the same values in reverse order

3

# Arrays


# Arrays

- An array is a **contiguous** sequence of elements of the **same type**

- Each element (data in array) can be accessed using its **index**

array name: A

array length: n



5

# Declaration

```
// array declaration by specifying size
int myarray1[100];
```

```
// can also declare an array of
// user specified size
int n = 8;
int myarray2[n];
```

```
// can declare and initialize elements
double arr[] = { 10.0, 20.0, 30.0, 40.0 };
// compiler figures the right size
```

```
// a different way
int arr[5] = { 1, 2, 3 };
// compiler creates an array of length 5 and
// initializes first 3 elements
```

6

# Initialization and indexing

- Elements in an array **must be initialized** before use
  - ✓ otherwise, their initial values are **undetermined**
  - ✓ can use a loop to initialize values or `std::fill()`
- Individual elements can be accessed by using the **subscription operator [ ]**


```
int array[4];
array[0] = 5;
array[1] = array[0] + 10;
array[2] = array[1] + 20;
array[3] = array[2] + 30;
```

0	1	2	3
5	15	35	65

7

# Trace the code

```
C++ (gcc 4.8, C++11)
EXPERIMENTAL! known bugs/limitations
1 int main() {
2   int val = 0;
3   int array[10];
4
5   for (int i = 0 ; i < 10 ; i++) {
6     val += 50;
7     array[i] = val;
8   }
9
10  return 0;
11 }
```



8

## Out of bounds?

- There is no **out of bounds** checking at compile time

✓ **unexpected output**

A[9] ?

	0	1	2	3	4	5	6	7				
?	?	?	10	20	50	100	70	50	30	5	?	?



9


## What is the output?

```
#include <iostream>

int main() {
    int myarray[5];
    for (int i = 0 ; i < 5 ; i++) {
        myarray[i] = i;
    }
    for (int i = -10 ; i < 10 ; i++) {
        std::cout << myarray[i] << ' ';
    }
    std::cout << '\n';
    return 0;
}
```

10

## Computer memory



- A **memory address** is a reference to a specific memory location
- Memory addresses are **fixed-length** sequences of digits (hexadecimal codes)
- Word**-oriented memory organization (word size 32-bit in this illustration)

0x00000000	
0x00000004	
0x00000008	
0x0000000C	
0x00000010	
0x00000014	
0x00000018	
...	
...	
...	
0xFFFFFEC	
0xFFFFF0	
0xFFFFF4	
0xFFFFF8	
0xFFFFFC	

address content

11

## Computer memory (example)

Assuming 32-bit words

```
int main() {
    int a = 4;
    int i = 0;
    double b = 10;
    int arr[5];

    for (; i < 5 ; i++) {
        arr[i] = i * 100;
    }

    return 0;
}
```

...	
0x91340A04	
0x91340A08	4
0x91340A0C	5
0x91340A10	10
0x91340A14	
0x91340A18	0
0x91340A1C	100
0x91340A20	200
0x91340A24	300
0x91340A28	400
0x91340A2C	
0x91340A30	
0x91340A34	
...	

12

# Passing arrays to functions

- When specifying the parameter, use **empty brackets**
- When providing the argument, use the **array name**
  - need to pass the **array length** separately

```
void zeros(int a[], int n) {
    for (int i = 0 ; i < n ; i++) {
        a[i] = 0;
    }
}

int main() {
    int array[5];
    zeros(array, 5);
    // do stuff
}
```

13

# Base address

- Base address** is the memory location of the first element in an array
  - base address of **arr** is **0x91340A18** (previous example)

- When passing arrays to functions, the base address of the array is passed to the formal parameter

...	
0x91340A04	
0x91340A08	4
0x91340A0C	5
0x91340A10	
0x91340A14	10
0x91340A18	0
0x91340A1C	100
0x91340A20	200
0x91340A24	300
0x91340A28	400
0x91340A2C	
0x91340A30	
0x91340A34	
...	

14

# Base address

Users > michaelconti > Desktop > arr.cpp

```
2
3 int main(){
4
5     int array[4];
6     array[0] = 5;
7     array[1] = array[0] + 10;
8     array[2] = array[1] + 20;
9     array[3] = array[2] + 30;
10
11     std::cout << array;
12
13     return 0;
14 }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL


```
michaelconti@Michaels-MacBook-Pro-2 Desktop % ./temp
0x16ef638a8
michaelconti@Michaels-MacBook-Pro-2 Desktop %
```

15

# Passing arrays to functions

C++ (gcc 4.8, C++11)  
**EXPERIMENTAL!** [known bugs/limitations](#)

```
1 void zeros(int a[], int n) {
2     for (int i = 0 ; i < n ; i++) {
3         a[i] = 0;
4     }
5 }
6
7 int main() {
8     int array[5];
9     zeros(array, 5);
10    // do stuff
11 }
```



<http://pythontutor.com/cpp.html>

16

# Vectors

## Vectors

- Data structure for organizing elements

- **#include <vector>**

```
// declare
std::vector<int> myVector;
```

```
// initializer list (c++17)
std::vector<int> vector1 = {1, 2, 3, 4, 5};
```

18

## Declaration

```
// declare
std::vector<int> myVector;
```

```
// initializer list (c++17)
std::vector<int> vector1 = {1, 2, 3, 4, 5};
```

19

## Important Methods

```
//declare vector without size
std::vector<int> myVector;
```

```
//declare vector with size
std::vector<int> myVector(20);
```

```
//add element into vector
myVector.push_back(5);
```

```
//add element into vector
myVector[0] = 5;
```

```
//access vector (with bound checking)
myVector.at(0);
```

```
//access vector (without bound checking)
myVector[0];
```

```
//change vector element
myVector[0] = 10;
```

```
//remove element into vector
myVector.pop_back();
```

20

## Question

---

- Write a function that receives an array of integers and reverses the contents of the array

21

## Question

---

- Write a function that receives an array and returns the smallest element in that array.

22