

Data Manipulation with dplyr (basics)



Outline

The dplyr package

Outline

The dplyr package

Tidy data

Outline

The dplyr package

Tidy data

The basic functions

Outline

The dplyr package

Tidy data

The basic functions

Manipulating rows: `filter()`, `arrange()`, `slice()`

Outline

The dplyr package

Tidy data

The basic functions

Manipulating rows: `filter()`, `arrange()`, `slice()`

Manipulating columns: `mutate()`, `select()`, `summarize()`

Outline

The dplyr package

Tidy data

The basic functions

Manipulating rows: `filter()`, `arrange()`, `slice()`

Manipulating columns: `mutate()`, `select()`, `summarize()`

Others: `group_by()`

dplyr

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr expects that the data will be the tidy format!

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr expects that the data will be the tidy format!

If you know the querying language SQL, the verbs (functions) are going to sound very similar

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr expects that the data will be the tidy format!

If you know the querying language SQL, the verbs (functions) are going to sound very similar

dplyr functions all have similar form:

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr expects that the data will be the tidy format!

If you know the querying language SQL, the verbs (functions) are going to sound very similar

dplyr functions all have similar form:

First argument is the data (data frame/tibble)

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr expects that the data will be the tidy format!

If you know the querying language SQL, the verbs (functions) are going to sound very similar

dplyr functions all have similar form:

- First argument is the data (data frame/tibble)

- Subsequent arguments describe your proposed actions

dplyr

The *dplyr* package is a part of the *tidyverse* and is the main package for data manipulation (grammar for data manipulation)

dplyr expects that the data will be the tidy format!

If you know the querying language SQL, the verbs (functions) are going to sound very similar

dplyr functions all have similar form:

- First argument is the data (data frame/tibble)

- Subsequent arguments describe your proposed actions

- Result is a data frame / tibble

Tidy Data

Tidy Data

Tidy data is the mantra of the *tidyverse*!

Tidy Data

Tidy data is the mantra of the *tidyverse*!

Basic principles of tidy data:

Tidy Data

Tidy data is the mantra of the *tidyverse*!

Basic principles of tidy data:

- Every row is a case (person/place/thing being observed)

Tidy Data

Tidy data is the mantra of the *tidyverse*!

Basic principles of tidy data:

- Every row is a case (person/place/thing being observed)

- Every column is a variable

Tidy Data

Tidy data is the mantra of the *tidyverse*!

Basic principles of tidy data:

- Every row is a case (person/place/thing being observed)

- Every column is a variable

Hadley Wickham (creator of *tidyverse*) wrote a paper building up the theory of tidy data: You can find it [here](#)

Tidy Data

Tidy data is the mantra of the *tidyverse*!

Basic principles of tidy data:

- Every row is a case (person/place/thing being observed)

- Every column is a variable

Hadley Wickham (creator of *tidyverse*) wrote a paper building up the theory of tidy data: You can find it [here](#)

We will spend a large amount of time on tidying data (*tidyr*)!

Data Transformation with dplyr :: CHEAT SHEET



dplyr functions work with pipes and expect **tidy data**. In tidy data:



Each **variable** is in its own **column**

&



Each **observation**, or **case**, is in its own **row**



x %>% f(y)
becomes **f(x, y)**

Summarise Cases

These apply **summary functions** to columns to create a new table of summary statistics. Summary functions take vectors as input and return one value (see back).

summary function



summarise(.data, ...)
Compute table of summaries.
summarise(mtcars, avg = mean(mpg))



count(x, ..., wt = NULL, sort = FALSE)
Count number of rows in each group defined by the variables in ... Also **tally()**.
count(iris, Species)

VARIATIONS

summarise_all() - Apply funs to every column.
summarise_at() - Apply funs to specific columns.
summarise_if() - Apply funs to all cols of one type.

Group Cases

Use **group_by()** to create a "grouped" copy of a table. dplyr functions will manipulate each "group" separately and then combine the results.



*mtcars %>%
group_by(cyl) %>%
summarise(avg = mean(mpg))*


group_by(.data, ..., add = FALSE)
Returns copy of table grouped by ...
g_iris <- group_by(iris, Species)

ungroup(x, ...)
Returns ungrouped copy of table.
ungroup(g_iris)


Manipulate Cases

EXTRACT CASES


Row functions return a subset of rows as a new table.




filter(.data, ...) Extract rows that meet logical criteria. *filter(iris, Sepal.Length > 7)*



distinct(.data, ..., .keep_all = FALSE) Remove rows with duplicate values.
distinct(iris, Species)



sample_frac(tbl, size = 1, replace = FALSE, weight = NULL, .env = parent.frame()) Randomly select fraction of rows.
sample_frac(iris, 0.5, replace = TRUE)



sample_n(tbl, size, replace = FALSE, weight = NULL, .env = parent.frame()) Randomly select size rows. *sample_n(iris, 10, replace = TRUE)*

slice(.data, ...) Select rows by position.
slice(iris, 10:15)

top_n(x, n, wt) Select and order top n entries (by group if grouped data). *top_n(iris, 5, Sepal.Width)*

Logical and boolean operators to use with filter()

<	<=	is.na()	%in%		xor()
>	>=	!is.na()	!	&	


See **?base::Logic** and **?Comparison** for help.

ARRANGE CASES



arrange(.data, ...) Order rows by values of a column or columns (low to high), use with **desc()** to order from high to low.
arrange(mtcars, mpg)
arrange(mtcars, desc(mpg))

ADD CASES



add_row(.data, ..., .before = NULL, .after = NULL)
Add one or more rows to a table.
add_row(faithful, eruptions = 1, waiting = 1)

Manipulate Variables

EXTRACT VARIABLES

Column functions return a set of columns as a new vector or table.



pull(.data, var = -1) Extract column values as a vector. Choose by name or index.
pull(iris, Sepal.Length)



select(.data, ...)
Extract columns as a table. Also **select_if()**.
select(iris, Sepal.Length, Species)


Use these helpers with **select()**,
e.g. *select(iris, starts_with("Sepal"))*

contains(match)	num_range(prefix, range)	: e.g. mpg:cyl
ends_with(match)	one_of(...)	-, e.g. -Species
matches(match)	starts_with(match)	

MAKE NEW VARIABLES

These apply **vectorized functions** to columns. Vectorized funs take vectors as input and return vectors of the same length as output (see back).


vectorized function




mutate(.data, ...)
Compute new column(s).
mutate(mtcars, gpm = 1/mpg)




transmute(.data, ...)
Compute new column(s), drop others.
transmute(mtcars, gpm = 1/mpg)




mutate_all(.tbl, .funs, ...) Apply funs to every column. Use with **funs()**. Also **mutate_if()**.
mutate_all(faithful, funs(log(.), log2(.)))
mutate_if(iris, is.numeric, funs(log(.)))



mutate_at(.tbl, .cols, .funs, ...) Apply funs to specific columns. Use with **funs()**, **vars()** and the helper functions for **select()**.
mutate_at(iris, vars(-Species), funs(log(.)))



add_column(.data, ..., .before = NULL, .after = NULL) Add new column(s). Also **add_count()**, **add_tally()**. *add_column(mtcars, new = 1:32)*



rename(.data, ...) Rename columns.
rename(iris, Length = Sepal.Length)

filter()

filter() manipulates rows by keeping qualifying rows

filter()

filter() manipulates rows by keeping qualifying rows

data: The data to be manipulated

filter()

filter() manipulates rows by keeping qualifying rows

data: The data to be manipulated

... : One or more logical tests to match

filter()

filter() manipulates rows by keeping qualifying rows

```
filter(data, ...)
```

`data`: The data to be manipulated

`...` : One or more logical tests to match

filter()

filter() manipulates rows by keeping qualifying rows

`filter(data, ...)`

`data`: The data to be manipulated

`...` : One or more logical tests to match

A tibble: 5 x 3

x	y	c
<int>	<int>	<chr>
1	1	a
2	2	b
3	2	a
4	3	b
5	1	a

filter()

filter() manipulates rows by keeping qualifying rows

`filter(data, ...)`

`data`: The data to be manipulated

`...` : One or more logical tests to match

```
# A tibble: 5 x 3
```

```
tb %>% filter(x == 1)
```

x	y	c
<int>	<int>	<chr>
1	1	a
2	2	b
3	2	a
4	3	b
5	1	a

filter()

filter() manipulates rows by keeping qualifying rows

`filter(data, ...)`

`data`: The data to be manipulated

`...` : One or more logical tests to match

```
# A tibble: 5 x 3
```

x	y	c
<int>	<int>	<chr>
1	1	a
2	2	b
3	2	a
4	3	b
5	1	a

```
tb %>% filter(x == 1)
```

```
# A tibble: 1 x 3
```

x	y	c
<int>	<int>	<chr>
1	1	a

filter()

What logical test can we use inside of filter?

Logical and boolean operators to use with filter()

<	<=	is.na()	%in%		xor()
>	>=	!is.na()	!	&	

See **?base::Logic** and **?Comparison** for help.

<code>x < y</code>	Less than
<code>x > y</code>	Greater than
<code>x == y</code>	Equal to
<code>x <= y</code>	Less than or equal to
<code>x >= y</code>	Greater than or equal to
<code>x != y</code>	Not equal to
<code>x %in% y</code>	Group membership
<code>is.na(x)</code>	Is NA
<code>!is.na(x)</code>	Is not NA

filter()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```


filter()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

```
tb %>% filter(x = 1)
```

filter()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

```
tb %>% filter(x = 1)
```

```
tb %>% filter(c == a)
```

filter()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

```
tb %>% filter(x = 1)
```



```
tb %>% filter(c == a)
```

filter()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

```
tb %>% filter(x = 1)
```



```
tb %>% filter(c == a)
```

What's wrong with these function calls?

filter()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

```
tb %>% filter(x = 1)
```



```
tb %>% filter(c == a)
```

What's wrong with these function calls?

```
tb %>% filter(x == 1)
```



```
tb %>% filter(c == "a")
```

filter()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

Filter can take in multiple logical tests!

filter()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

Filter can take in multiple logical tests!

If you supply them with the comma, they will be combined with “and”

filter()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

Filter can take in multiple logical tests!

If you supply them with the comma, they will be combined with “and”

The same operation can be done with boolean operators!

filter()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

Filter can take in multiple logical tests!

If you supply them with the comma, they will be combined with “and”

The same operation can be done with boolean operators!

```
tb %>% filter(y == 2, c == "a")    =    tb %>% filter(y == 2 & c == "a")
```

filter()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

Filter can take in multiple logical tests!

If you supply them with the comma, they will be combined with “and”







The same operation can be done with boolean operators!

```
tb %>% filter(y == 2, c == "a")    =    tb %>% filter(y == 2 & c == "a")
```

?base::Logic

a & b	and
a b	or
xor(a, b)	exactly or
!a	not

filter()



arrange()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     3     2     a  
4     4     3     b  
5     5     1     a
```

arrange() arranges rows! By default, in ascending order

arrange()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

arrange() arranges rows! By default, in ascending order

```
tb %>% arrange(y)
```

arrange()

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
1     1  1  a
2     2  2  b
3     3  2  a
4     4  3  b
5     5  1  a
```

arrange() arranges rows! By default, in ascending order

```
tb %>% arrange(y)
```

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
1     1  1  a
5     5  1  a
2     2  2  b
3     3  2  a
4     4  3  b
```

arrange()

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
1     1     1 a
2     2     2 b
3     3     2 a
4     4     3 b
5     5     1 a
```

arrange() arranges rows! By default, in ascending order

```
tb %>% arrange(y)
```

```
tb %>% arrange(desc(y))
```

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
1     1     1 a
5     5     1 a
2     2     2 b
3     3     2 a
4     4     3 b
```

arrange()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

arrange() arranges rows! By default, in ascending order

```
tb %>% arrange(y)
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
2     2     2     b
3     3     2     a
4     4     3     b
```

```
tb %>% arrange(desc(y))
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
4     4     3     b
2     2     2     b
3     3     2     a
1     1     1     a
5     5     1     a
```


arrange()

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
1     1  1  a
2     2  2  b
3     3  2  a
4     4  3  b
5     5  1  a
```

arrange() arranges rows! By default, in ascending order

```
tb %>% arrange(y)
```

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
1     1  1  a
5     5  1  a
2     2  2  b
3     3  2  a
4     4  3  b
```

```
tb %>% arrange(desc(y))
```

```
# A tibble: 5 x 3
  x     y c
<int> <int> <chr>
4     3  3  b
2     2  2  b
3     2  2  a
1     1  1  a
5     1  1  a
```

desc() will sort by descending order

arrange()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

arrange() arranges rows! By default, in ascending order

```
tb %>% arrange(y)
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
2     2     2     b
3     3     2     a
4     4     3     b
```

```
tb %>% arrange(desc(y))
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
4     4     3     b
2     2     2     b
3     3     2     a
1     1     1     a
5     5     1     a
```

desc() will sort by descending order

You can also arrange based on multiple variables

arrange()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     3     2     a  
4     4     3     b  
5     5     1     a
```

arrange()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

You can also arrange based on multiple variables!

arrange()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     3     2     a  
4     4     3     b  
5     5     1     a
```

You can also arrange based on multiple variables!

```
tb %>% arrange(y, c)
```

arrange()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

You can also arrange based on multiple variables!

```
tb %>% arrange(y, c)
```

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
3     3     2     a
2     2     2     b
4     4     3     b
```

arrange()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

You can also arrange based on multiple variables!

```
tb %>% arrange(y, c)
```

```
tb %>% arrange(y, desc(c))
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
3     3     2     a
2     2     2     b
4     4     3     b
```

arrange()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

You can also arrange based on multiple variables!

```
tb %>% arrange(y, c)
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
3     3     2     a
2     2     2     b
4     4     3     b
```

```
tb %>% arrange(y, desc(c))
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
2     2     2     b
3     3     2     a
4     4     3     b
```


arrange()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

You can also arrange based on multiple variables!

```
tb %>% arrange(y, c)
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
3     3     2     a
2     2     2     b
4     4     3     b
```

```
tb %>% arrange(y, desc(c))
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
5     5     1     a
2     2     2     b
3     3     2     a
4     4     3     b
```

Ties are broken from left to right with multiple variables

slice()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     3     2     a  
4     4     3     b  
5     5     1     a
```

slice() allows you to select certain rows from the data

slice()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

slice() allows you to select certain rows from the data

```
tb %>% slice(1)
```

slice()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

slice() allows you to select certain rows from the data

```
tb %>% slice(1)
```

```
# A tibble: 1 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
```

slice()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

slice() allows you to select certain rows from the data

```
tb %>% slice(1)
```

```
# A tibble: 1 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
```

```
tb %>% slice(1:3)
```

slice()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

slice() allows you to select certain rows from the data

```
tb %>% slice(1)
```

```
# A tibble: 1 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
```

```
tb %>% slice(1:3)
```

```
# A tibble: 3 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
```

slice()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

slice() allows you to select certain rows from the data

```
tb %>% slice(1)
```

```
# A tibble: 1 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
```

```
tb %>% slice(1:3)
```

```
# A tibble: 3 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
```

```
tb %>% slice(-c(2,4))
```

slice()

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

slice() allows you to select certain rows from the data

```
tb %>% slice(1)
```

```
# A tibble: 1 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
```

```
tb %>% slice(1:3)
```

```
# A tibble: 3 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
```

```
tb %>% slice(-c(2,4))
```

```
# A tibble: 3 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
3     3     2     a
5     5     1     a
```


mutate()

mutate() allows you to create and/or modify columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

mutate()

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y)
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

mutate()

mutate() allows you to create and/or modify columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

```
tb %>% mutate(z = x+y)
```

```
# A tibble: 5 x 4
```

x	y	c	z
<int>	<int>	<chr>	<int>
1	1	a	2
2	2	b	4
3	2	a	5
4	3	b	7
5	1	a	6

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y)
```

```
tb %>% mutate(z = x+y, w = x*y)
```

```
# A tibble: 5 x 4
```

x	y	c	z
<int>	<int>	<chr>	<int>
1	1	a	2
2	2	b	4
3	2	a	5
4	3	b	7
5	1	a	6

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y)
```

```
# A tibble: 5 x 4
```

x	y	c	z
<int>	<int>	<chr>	<int>
1	1	a	2
2	2	b	4
3	2	a	5
4	3	b	7
5	1	a	6

```
tb %>% mutate(z = x+y, w = x*y)
```

```
# A tibble: 5 x 5
```

x	y	c	z	w
<int>	<int>	<chr>	<int>	<int>
1	1	a	2	1
2	2	b	4	4
3	2	a	5	6
4	3	b	7	12
5	1	a	6	5

mutate()

mutate() allows you to create and/or modify columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

mutate()

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
# A tibble: 5 x 3
      x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
# A tibble: 5 x 5
```

x	y	c	z	z2
<int>	<int>	<chr>	<int>	<dbl>
1	1	a	2	4
2	2	b	4	16
3	2	a	5	25
4	3	b	7	49
5	1	a	6	36

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
# A tibble: 5 x 5
```

x	y	c	z	z2
<int>	<int>	<chr>	<int>	<dbl>
1	1	a	2	4
2	2	b	4	16
3	2	a	5	25
4	3	b	7	49
5	1	a	6	36

Rolls the computations over

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
tb %>% mutate(y = x+y)
```

```
# A tibble: 5 x 5
```

x	y	c	z	z2
<int>	<int>	<chr>	<int>	<dbl>
1	1	a	2	4
2	2	b	4	16
3	2	a	5	25
4	3	b	7	49
5	1	a	6	36

Rolls the computations over

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
# A tibble: 5 x 5
```

x	y	c	z	z2
<int>	<int>	<chr>	<int>	<dbl>
1	1	a	2	4
2	2	b	4	16
3	2	a	5	25
4	3	b	7	49
5	1	a	6	36

```
tb %>% mutate(y = x+y)
```

```
# A tibble: 5 x 3
```

x	y	c
<int>	<int>	<chr>
1	2	a
2	4	b
3	5	a
4	7	b
5	6	a

Rolls the computations over

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
# A tibble: 5 x 5
```

x	y	c	z	z2
<int>	<int>	<chr>	<int>	<dbl>
1	1	a	2	4
2	2	b	4	16
3	2	a	5	25
4	3	b	7	49
5	1	a	6	36

Rolls the computations over

```
tb %>% mutate(y = x+y)
```

```
# A tibble: 5 x 3
```

x	y	c
<int>	<int>	<chr>
1	2	a
2	4	b
3	5	a
4	7	b
5	6	a

Replaces variables as well

mutate()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

mutate() allows you to create and/or modify columns

```
tb %>% mutate(z = x+y, z2 = z^2)
```

```
# A tibble: 5 x 5
```

x	y	c	z	z2
<int>	<int>	<chr>	<int>	<dbl>
1	1	a	2	4
2	2	b	4	16
3	2	a	5	25
4	3	b	7	49
5	1	a	6	36

Rolls the computations over

```
tb %>% mutate(y = x+y)
```

```
# A tibble: 5 x 3
```

x	y	c
<int>	<int>	<chr>
1	2	a
2	4	b
3	5	a
4	7	b
5	6	a

Replaces variables as well

There are many mutate() variants!

select()

select() allows you select/deselect certain columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

select()

select() allows you select/deselect certain columns

```
tb %>% select(x,y)
```

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

select()

select() allows you select/deselect certain columns

```
tb %>% select(x,y)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
# A tibble: 5 x 3
```

x	y	c
<int>	<int>	<chr>
1	1	a
2	2	b
3	2	a
4	3	b
5	1	a

select()

select() allows you select/deselect certain columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

```
tb %>% select(x,y)    tb %>% select(1,2)
```

```
# A tibble: 5 x 2
```

```
      x     y
<int> <int>
1     1     1
2     2     2
3     3     2
4     4     3
5     5     1
```

select()

select() allows you select/deselect certain columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

```
tb %>% select(x,y)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1,2)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

select()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

select() allows you select/deselect certain columns

```
tb %>% select(x,y)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1,2)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1:2)
```

select()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

select() allows you select/deselect certain columns

```
tb %>% select(x,y)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1,2)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1:2)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

select()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

select() allows you select/deselect certain columns

```
tb %>% select(x,y)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1,2)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(1:2)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

Names are preferred if possible for more readable code

select()

select() allows you select/deselect certain columns

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

```
tb %>% select(-3)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

```
tb %>% select(-c)
```

```
# A tibble: 5 x 2
```

x	y
<int>	<int>
1	1
2	2
3	2
4	3
5	1

select()

There are different helper functions that can make selecting variables easier!

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

select()

There are different helper functions that can make selecting variables easier!

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

```
tb %>% select(one_of(c("x", "y")))
```


select()

There are different helper functions that can make selecting variables easier!

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     2     2     a
4     3     3     b
5     1     1     a
```

```
tb %>% select(one_of(c("x", "y")))
```

```
# A tibble: 5 x 2
  x     y
<int> <int>
1     1     1
2     2     2
3     2     2
4     3     3
5     1     1
```

select()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1   a
2     2     2   b
3     3     2   a
4     4     3   b
5     5     1   a
```

There are different helper functions that can make selecting variables easier!

Helper functions

starts_with("x")

ends_with("x")

contains("x")

one_of(c("x", "y", "z"))

```
tb %>% select(one_of(c("x", "y")))
```

```
# A tibble: 5 x 2
```

```
      x     y
<int> <int>
1     1     1
2     2     2
3     3     2
4     4     3
5     5     1
```

select()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

There are different helper functions that can make selecting variables easier!

Helper functions

starts_with("x")

ends_with("x")

contains("x")

one_of(c("x", "y", "z"))

```
tb %>% select(one_of(c("x", "y")))
```

```
# A tibble: 5 x 2
```

```
      x     y
<int> <int>
1     1     1
2     2     2
3     3     2
4     4     3
5     5     1
```

These functions have to do with regular expressions.
We will talk about these later!

summarize()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

summarize()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

summarize() applies a summary function that creates a real-valued statistic

summarize()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

summarize() applies a summary function that creates a real-valued statistic

There are lots of variants of summarize as well!

summarize()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

summarize() applies a summary function that creates a real-valued statistic

There are lots of variants of summarize as well!

We will usually see summarize() used in conjunction with group_by()

summarize()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

summarize() applies a summary function that creates a real-valued statistic

```
tb %>% summarize(xbar = mean(x))
```

There are lots of variants of summarize as well!

We will usually see summarize() used in conjunction with group_by()

summarize()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

summarize() applies a summary function that creates a real-valued statistic

```
tb %>% summarize(xbar = mean(x))
```

```
# A tibble: 1 x 1
  xbar
<dbl>
1     3
```

There are lots of variants of summarize as well!

We will usually see summarize() used in conjunction with group_by()

group_by()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

group_by() groups certain variables together to enable conditional computation. We will usually use group_by() in conjunction with summarize() to create statistics for each group

group_by()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

group_by() groups certain variables together to enable conditional computation. We will usually use group_by() in conjunction with summarize() to create statistics for each group

There are lots of variants of summarize as well!

group_by()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

group_by() groups certain variables together to enable conditional computation. We will usually use group_by() in conjunction with summarize() to create statistics for each group

There are lots of variants of summarize as well!

We will usually see summarize() used in conjunction with group_by()

group_by()

```
# A tibble: 5 x 3  
  x     y     c  
<int> <int> <chr>  
1     1     1     a  
2     2     2     b  
3     2     2     a  
4     3     3     b  
5     1     1     a
```

group_by() groups certain variables together to enable conditional computation. We will usually use group_by() in conjunction with summarize() to create statistics for each group

There are lots of variants of summarize as well!

We will usually see summarize() used in conjunction with group_by()

```
diamonds %>%  
  group_by(cut) %>%  
  summarize(mean = mean(price))
```

group_by()

```
# A tibble: 5 x 3
  x     y     c
<int> <int> <chr>
1     1     1     a
2     2     2     b
3     3     2     a
4     4     3     b
5     5     1     a
```

group_by() groups certain variables together to enable conditional computation. We will usually use group_by() in conjunction with summarize() to create statistics for each group

There are lots of variants of summarize as well!

We will usually see summarize() used in conjunction with group_by()

```
diamonds %>%
  group_by(cut) %>%
  summarize(mean = mean(price))
```

```
# A tibble: 5 x 2
  cut      mean
<ord>   <dbl>
1 Fair    4359.
2 Good    3929.
3 Very Good 3982.
4 Premium 4584.
5 Ideal   3458.
```