

LAGraph table test



GRAPHBLAS

Test site

Table

operation/method	description	notation
<code>mxm</code>	matrix-matrix multiplication	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \mathbf{A} \oplus.\otimes \mathbf{B}$
<code>vxm</code>	vector-matrix multiplication	$\mathbf{w}^T\langle\mathbf{m}^T\rangle \odot = \mathbf{u}^T \oplus.\otimes \mathbf{A}$
<code>mxv</code>	matrix-vector multiplication	$\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{A} \oplus.\otimes \mathbf{u}$
<code>eWiseAdd</code>	element-wise addition using operator op	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \mathbf{A} \cup[\text{op}] \mathbf{B}$
	on elements in the set union of structures of \mathbf{A}/\mathbf{B} and \mathbf{u}/\mathbf{v}	$\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{u} \cup[\text{op}] \mathbf{v}$
<code>eWiseMult</code>	element-wise multiplication using operator op	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \mathbf{A} \cap[\text{op}] \mathbf{B}$
	on elements in the set intersection of structures of \mathbf{A}/\mathbf{B} and \mathbf{u}/\mathbf{v}	$\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{u} \cap[\text{op}] \mathbf{v}$
<code>extract</code>	extract submatrix from matrix \mathbf{A} using indices \mathbf{i} and indices \mathbf{j}	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \mathbf{A}(\mathbf{i},\mathbf{j})$
	extract the i th row vector from matrix \mathbf{A}	$\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{A}(i,:)$
	extract the j th column vector from matrix \mathbf{A}	$\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{A}(:,j)$
	extract subvector from \mathbf{u} using indices \mathbf{i}	$\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{u}(\mathbf{i})$
<code>assign</code>	assign matrix to submatrix with mask for \mathbf{C}	$\mathbf{C}\langle\mathbf{M}\rangle(\mathbf{i},\mathbf{j}) \odot = \mathbf{A}$
	assign scalar to submatrix with mask for \mathbf{C}	$\mathbf{C}\langle\mathbf{M}\rangle(\mathbf{i},\mathbf{j}) \odot = s$
	assign vector to subvector with mask for \mathbf{w}	$\mathbf{w}\langle\mathbf{m}\rangle(\mathbf{i}) \odot = \mathbf{u}$
	assign scalar to subvector with mask for \mathbf{w}	$\mathbf{w}\langle\mathbf{m}\rangle(\mathbf{i}) \odot = s$

operation/method	description	notation
<code>apply</code>	apply unary operator f with optional thunk k	$\mathbf{C}\langle\mathbf{M}\rangle \odot = f(\mathbf{A}, k)$ $\mathbf{w}\langle\mathbf{m}\rangle \odot = f(\mathbf{u}, k)$
<code>select</code>	apply select operator f with optional thunk k	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \mathbf{A}\langle f(\mathbf{A}, k) \rangle$ $\mathbf{w}\langle\mathbf{m}\rangle \odot = \mathbf{u}\langle f(\mathbf{u}, k) \rangle$
<code>reduce</code>	row-wise reduce matrix to column vector	$\mathbf{w}\langle\mathbf{m}\rangle \odot = [\oplus_j \mathbf{A}(:, j)]$
	reduce matrix to scalar	$s \odot = [\oplus_{i,j} \mathbf{A}(i, j)]$
	reduce vector to scalar	$s \odot = [\oplus_i \mathbf{u}(i)]$
<code>transpose</code>	transpose	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \mathbf{A}^\top$
<code>kron</code>	Kronecker multiplication using operator op	$\mathbf{C}\langle\mathbf{M}\rangle \odot = \text{kron}(\mathbf{A}, \text{op}, \mathbf{B})$

GraphBLAS operations and methods. Notation: Matrices and vectors are typeset in bold, starting with uppercase (\mathbf{A}) and lowercase (\mathbf{u}) letters, respectively. Scalars including indices are lowercase italic (k, i, j) while arrays are lowercase bold italic ($\mathbf{x}, \mathbf{i}, \mathbf{j}$). \oplus and \otimes are the addition and multiplication operators forming a semiring and default to conventional arithmetic $+$ and \times operators. \odot is the accumulator operator. Operations can be modified via a descriptor; matrices can be transposed (\mathbf{B}^\top), the mask can be complemented ($\mathbf{C}\langle\neg\mathbf{M}\rangle$), and the mask can be valued (shown above) or structural ($\mathbf{C}\langle s(\mathbf{M}) \rangle$). A structural mask can also be complemented ($\mathbf{C}\langle\neg s(\mathbf{M}) \rangle$). The result can be cleared (replaced) after using it as input to the mask/accumulator step ($\mathbf{C}\langle\mathbf{M}, \mathbf{r}\rangle$). Not all methods are listed (creating new operators, monoids, and semirings, clearing a matrix/vector, etc.).