



API Version 3.19.4

29/06/2021

Contents

1	Overview	3
1.1	Submission Process	3
1.2	API Authentication	3
1.3	Headers.....	3
1.4	URL	3
2	Methods.....	4
2.1	Submit application	4
	Response	5
2.2	Update.....	6
2.2.1	Update applicants.....	6
	Response	6
2.2.2	Update application status	6
	Response	6
2.2.3	Update business details.....	7
	Response	7
2.2.4	Update business address	7
	Response	7
2.3	Notes.....	8
2.3.1	Create note.....	8
	Response	8
2.3.2	Retrieve a specific note	8
	Response	8
2.3.3	Retrieve all notes for an application	9
	Response	9
2.4	Vehicles.....	10
2.5	Custom fields.....	11
2.6	Bank details.....	12
2.7	Affordability.....	13
	POST – Create & Update: Body should contain the affordability object outlined in 0.....	13
2.8	Settlement lender	15
2.9	Statuses	16
2.9.1	Sub-statuses	16
2.10	Potential values	17
2.10.1	Occupation types.....	17
2.10.2	Industries.....	17

2.11	Application Tasks	18
2.11.1	Create tasks	18
2.11.2	Task Actions	18
2.12	Finance details	19
2.13	Products	20
Object Types		22
2.14	Applicant.....	22
2.15	Address	24
2.16	Application Task	24
2.17	Employment.....	25
2.18	Vehicle.....	26
2.19	BankDetails	28
2.20	BusinessDetails	29
2.21	BusinessAddress.....	29
2.22	FinanceDetails.....	31
2.23	Product	32
2.24	Affordability.....	33
2.25	Consent.....	33
2.26	CustomField	33
2.27	ApplicationNote	33
2.28	FinanceDetails.....	34
3	Example Requests.....	35
3.1	Example submit request 1	35
3.2	Example submit request 2	39
3.3	Example submit request 3	41
3.4	Example update request 1	42
3.5	Example update request 2	43
3.6	Example update vehicles request	44
3.7	Example update vehicle request.....	45
3.8	Example update custom fields request	46
3.9	Example update custom field request	47
3.10	Example update business details.....	48
3.11	Example update business address	49
4	Appendices.....	50
4.1	Appendix 1 – Nationality alpha codes	50
4.2	Appendix 2 – Country alpha codes	0

1 Overview

We provide an HTTP POST based interface allowing third parties to submit car finance applications into the AutoConvert system with the interface being a server to server relationship. The post body is in JSON format and should have an application/json content-type header.

1.1 Submission Process

This section outlines the process your submission will take detailing the specifications and requirements of the HTTP POST. The response from the service is returned in JSON format containing the result of the application, including a reference.

1.2 API Authentication

You should obtain an API key that should be sent along with every request to the service.

1.3 Headers

The application must be correctly formatted using the input parameters in JSON format. You will be allocated an **API key**, (contact us if you do not yet have this) and this must be added as an HTTP header as follows:

Header name	Value
X-APIKey	[Your API key]

All your posts to our service must include this or you cannot be credited for the traffic. Some fields are completely free-format; others MUST be passed as one of a range of predefined values.

Please note that not all fields are required, however by providing as much as possible will improve the chances of the application converting.

1.4 URL

The base URL to use is **https://api.autoconvert.co.uk**

2 Methods

2.1 Submit application

This method will accept a full car finance application and submit it into our system and return a reference to the application.

POST /application/submit

Field name	Required	Data type	Notes
AmountToBorrow	N	Decimal	
Term	N	Int	If the finance type is PCP, the months will be represented in x + 1 format (+ 1 being the balloon payment) e.g., 60 will be shown as 59 + 1.
VehicleType	N	String	"Car", "Van", "Motorbike", "Caravan" "MotorHome", "HGV", "Static Caravan", "Other" Will default to Car
Applicants	Y	Array (applicant)	Must have at least one applicant
Vehicles	N	Array (Vehicle)	This is a child of application
BankDetails	N	BankDetails	This is a child of Application
FinanceDetails	N	Finance	This is a child of Application
BusinessDetails	N	BusinessDetails	Enquiry type must be set to 'Business' for data to be captured
BusinessAddress	N	BusinessAddress	Enquiry type must be set to 'Business' for data to be captured
Affordability	N	Affordability	This is a child of Application
Consent	N	Array (Consent)	
CustomFields	N	Array (CustomField)	
ApplicationNotes	N	Array (ApplicationNote)	[{ "Text": "Example note 1" }, { "Text": "Example note 2", "VisibleToIntroducer": false }]
SourceReference	N	String	Max 64 Characters
CampaignCode1	N	String	Max 32 Characters
CampaignCode2	N	String	Max 32 Characters

Field name	Required	Data type	Notes
CampaignCode3	N	String	Max 32 Characters
CampaignCode4	N	String	Max 32 Characters
CampaignCode5	N	String	Max 32 Characters
CreditScore	N	Int	
The following fields are obsolete			
Products	N	Array (Product)	
LoanAmount	N	Decimal	This is the cash price of the vehicle and should include the deposit amount.
LoanTerm	N	Int	Months
CreditSearchConsent	N	Bool	True / False – Please use the consent Object instead
FirstPartyMarketingConsent	N	Bool	True / False – Please use the consent Object instead
SmsConsent	N	Bool	True / False – Please use the consent Object instead
EmailConsent	N	Bool	True / False – Please use the consent Object instead
PostConsent	N	Bool	True / False – Please use the consent Object instead
CallConsent	N	Bool	True / False – Please use the consent Object instead

Response

The response is returned in JSON format.

Accepted Response:

```
{"Accepted":true, "Reference" : "6988a142-0eb7-48d1-a42d-db8d83cf3e7b"}
```

The reference returned in this response should be kept to allow for updates.

In the event of an unsuccessful submission, the response will contain a detailing of the incorrect fields.

2.2 Update

This resource allows you to update an application that has been previously submitted via 2.1.

2.2.1 Update applicants

This method allows you to update the main and joint applicants' information using the reference returned by 2.1 Response

PUT	/application/update/{applicationReference}/applicants
-----	---

Field name	Required	Data type	Notes
MainApplicant	N	Applicant	Either Main Applicant or Joint applicant[s] should be updated
JointApplicants	N	Array (Applicant)	

Response

A successful application update request will return a JSON response:

```
{
  "Success": true
}
```

In the event of an unsuccessful submission, contact an AutoConvert representative with your JSON request to receive guidance.

2.2.2 Update application status

This method allows you to update the sub-status of an enquiry, using the application reference returned by 2.1 Response and the reference of a sub-status.

POST	/application/update/{applicationReference}/subStatus/{subStatusReference}
------	---

Field name	Required	Data type	Notes
SubStatusReference	Y	GUID	The reference of the sub-status that the enquiry's sub-status should be updated to. These can be found in the admin status settings area.

Response

A successful application update request will return a status of 200 OK

2.2.3 Update business details

This method allows you to create or update the business details of an application using the reference returned by 2.1 Response

PUT	/application/update/{applicationReference}/businessdetails
-----	--

Field name	Required	Data type	Notes
BusinessDetails	N	BusinessDetails	This is a flat JSON object with no name in the update. Example provided in section 4.

Response

A successful application update request will return a JSON response:

```
{
  "Success": true
}
```

2.2.4 Update business address

This method allows you to create or update the business address of an application using the reference returned by 2.1 Response

PUT	/application/update/{applicationReference}/businessaddress
-----	--

Field name	Required	Data type	Notes
BusinessAddress	N	BusinessAddress	This is a flat JSON object with no name in the update. Example provided in section 4.

Response

A successful application update request will return a JSON response:

```
{
  "Success": true
}
```

In the event of an unsuccessful submission, contact an AutoConvert representative with your JSON request to receive guidance.

2.3 Notes

2.3.1 Create note

This resource allows you to add notes to an application using the reference returned by 2.1 Response

POST	/application/{applicationReference}/notes
------	---

Field name	Required	Data type	Notes
CreateWarningFromNote	N	Boolean	If set to true, will display the note when viewing the relevant Application/Enquiry. Defaults to false if not specified.
Text	Y	String	Free text
VisibleToIntroducer	N	Boolean	Defaults to true if not specified.
VisibleToLender	N	Boolean	Defaults to false if not specified.

Response

A successful note submission request will return a JSON response with a 201 status:

```
{
  "Reference": "F8E61236-425C-4E9F-87FA-FA4B04424FA5"
}
```

2.3.2 Retrieve a specific note

NB. Currently only applicable if VisibleToIntroducer is true.

GET	/application/{applicationReference}/notes/{noteReference}
-----	---

Response

A successful request will return a JSON response with a 200 status and the specified note.

```
{
  "Reference": "F8E61236-425C-4E9F-87FA-FA4B04424FA5",
  "Text": "this is a test",
  "VisibleToIntroducer": true,
  "VisibleToLender": false,
  "Created": "2020-01-22T10:41:39Z"
}
```

2.3.3 Retrieve all notes for an application

NB. Currently only applies to notes where VisibleToIntroducer is true.

GET	/application/{applicationReference}/notes
-----	---

Response

A successful request will return a JSON response with a 200 status and an array of notes.

```
[
  {
    "Reference": "7f033f7c-5acb-40e2-b5b7-12035280b603",
    "Text": "this is another test",
    "VisibleToIntroducer": true,
    "VisibleToLender": false,
    "Created": "2020-01-22T10:46:34Z"
  },
  {
    "Reference": "50823259-f5b3-4aae-b6fe-0b3428916cd5",
    "Text": "this is a test",
    "VisibleToIntroducer": true,
    "VisibleToLender": false,
    "Created": "2020-01-22T10:41:39Z"
  }
]
```

2.4 Vehicles

The vehicles API has a fully implemented set of CRUD operations. You will need the application reference returned upon successful submission (2.1 Response) and the API key given to you to interact with this API. Only applications created using your API key can be updated with your API key.

Create HTTP POST Endpoint:

POST	/application/{applicationReference}/vehicle
------	---

In the body should be an array of “vehicles” **or** a single “vehicle” object as defined in 2.18 Vehicle. See section 3.6 Example update vehicles request for an example body.

Retrieve all vehicles

GET	/application/{applicationReference}/vehicle
-----	---

Retrieve a specific vehicle

GET	/application/{applicationReference}/vehicle/{vehicleReference}
-----	--

Update application vehicles

PUT	/application/{applicationReference}/vehicle
-----	---

The body should be an array of vehicles defined in section 2.18 Vehicle. See section 3.6 Example update vehicles request for an example body. The body must contain all vehicle details as they will be overwritten.

Update a specific vehicle

PUT	/application/{applicationReference}/vehicle/{vehicleReference}
-----	--

In the body should be a single vehicle. See section 3.7 Example update vehicle request for an example body

Delete all vehicles

DELETE	/application/{applicationReference}/vehicle
--------	---

Delete a specific vehicle

DELETE	/application/{applicationReference}/vehicle/{vehicleReference}
--------	--

This deletes a specific vehicle, by vehicle reference. A GET call can be made to see which vehicle references are available on an application.

2.5 Custom fields

The custom fields API also has a fully implemented set of CRUD operations. You will need the application reference returned upon successful submission (2.1 Response) and the API key given to you to interact with this API. Only applications created using your API key can be updated with your API key.

Create HTTP POST Endpoint:

POST	/application/{applicationReference}/customfield
------	---

In the body should be an array of custom fields defined in 2.26 CustomField. See 3.8 Example update custom fields request for an example body

Retrieve all custom fields

GET	/application/{applicationReference}/customfield
-----	---

Retrieve specific custom field

GET	/application/{applicationReference}/customfield/{key}
-----	---

Update custom field

PUT	/application/{applicationReference}/customfield
-----	---

In the body should be an array of custom fields defined in section 2.26 CustomField. See section 3.8 Example update custom fields request for an example body

Update specific custom field

PUT	/application/{applicationReference}/customfield/{key}
-----	---

In the body should be a single custom field. See 3.9 Example update custom field request for an example body

Delete custom fields

DELETE	/application/{applicationReference}/customfield
--------	---

Delete a specific custom field

DELETE	/application/{applicationReference}/customfield/{key}
--------	---

This deletes all custom fields for the application whose reference is supplied

This deletes a specific custom field, by custom field key. A GET call can be made to see which custom field keys are available on an application.

2.6 Bank details

The bank details API has a set of CRUD methods available. You will need the application reference returned upon successful submission of an application (2.1 Response) and the API key given to you to interact with these methods. Only applications created using your API key can be updated with your API key.

POST - Create: Body should contain bank details object outlined in 2.19 BankDetails. Header of content-type: application/json is also required.

POST	/application/{applicationReference}/bankdetails
------	---

GET – retrieve: You will be returned in JSON the bank details on AutoConvert in the same object format as the bank details object outlined in 2.19 BankDetails.

GET	/application/{applicationReference}/bankdetails
-----	---

PUT – update: Body should contain bank details object outlined in 2.19 BankDetails. Header of content-type: application/json is also required. Update uses ignores non-set values, for example passing: { "BankName": "test bank name" } will only update the bank name and no other fields.

PUT	/application/{applicationReference}/bankdetails
-----	---

DELETE – delete: Call the endpoint using HttpDelete to remove the bank details from the application.

DELETE	/application/{applicationReference}/bankdetails
--------	---

2.7 Affordability

The affordability details of an application can be created or updated by making a POST request to the endpoint below. You will need the application reference returned upon successful submission of an application (2.1 Response) and the API key given to you to interact with these methods. Only applications created using your API key can be updated with your API key.

POST – Create & Update: Body should contain the affordability object outlined in 0

Affordability

Header of content-type: application/json is also required.

Note: that the all the Affordability fields will need to be passed through on update, as it will override them with default values.

POST	/application/{applicationReference}/affordability
-------------	---

2.8 Settlement lender

The settlement lender API allows for the retrieval of the available settlement lenders, this can be used in the submission of an application if a settlement exists (3.6 FinanceDetails). To interact with these methods, you will need to use the API key provided to you.

GET – retrieve: You will be returned, in JSON a list of SettlementLenders in the format of a reference and name, the reference can then be used in the application submission as the SettlementLenderReference (3.6 FinanceDetails).

Retrieve list of available settlement lenders:

GET	/settlementlender
-----	-------------------

Retrieve settlement lender by reference:

GET	/settlementlender/{settlementLenderReference}
-----	---

2.9 Statuses

This resource provides access to company-specific status information, such as the references for each sub-status in an account.

2.9.1 Sub-statuses

This resource permits access to company sub-statuses, which allow an application's status to be finely tuned.

Retrieve list of all available sub-statuses:

GET	/statuses/substatuses
-----	-----------------------

2.10 Potential values

These endpoints allow you to GET potential values to be passed in for other submission methods.

2.10.1 Occupation types

Retrieve a JSON object that contains a list of occupation type strings:

GET	/list/occupationtypes
-----	-----------------------

2.10.2 Industries

Retrieve a JSON object that contains a list of industry strings:

GET	/list/industries
-----	------------------

2.11 Application Tasks

The ApplicationTask route enables the creation of tasks against applications assigned to the same company as the ApiKey.

2.11.1 Create tasks

POST - Create: Creates a new Task. Body should contain application task object outlined in (2.14 Application task). Header of content-type: application/json is also required.

POST	/applicationTask
------	------------------

2.11.2 Task Actions

GET – retrieve a list of company task actions in the format of a reference and a name. The reference can be used to populate the TaskActionReference field of the (ApplicationTask object 2.14)

GET	/applicationTask/taskactions
-----	------------------------------

2.12 Finance details

The finance details API has a set of CRUD methods available. You will need the application reference returned upon successful submission of an application (2.1 Response) and the API key given to you to interact with these methods. Only applications created using your API key can be updated with your API key.

POST - Create: Creating a new finance details object is not currently supported. If you require this feature please contact support.

GET – retrieve: You will be returned in JSON the finance details on AutoConvert in the same object format as the bank details object outlined in 2.21 BankDetails.

GET	/application/{ applicationReference }/financedetails
-----	---

PUT – update: Body should contain the finance details object outlined in 2.1921 BankDetails. Header of content-type: application/json is also required. All values must be passed in so you may want to call GET first if you don't have all the values available to you.

PUT	/application/{ applicationReference }/financedetails
-----	---

2.13 Products

These endpoints provide methods to view products configured for your company or add/update a product to an application.

GET – Retrieve all products: You will be returned JSON containing products and variants configured for your account, taking into account product set configuration. The variant references returned can be used in the POST to create an application product.

GET	/products/retrieve
-----	--------------------

GET – Retrieve products on application: You will be returned JSON containing the products that have been added to an application, the reference returned is the “ProductReference” used in the PUT method below, please note the POST method requires the product variant reference NOT the product reference.

GET	/products/application/retrieve/{applicationReference}
-----	---

POST – Create application product using product variant: The body should contain the object provided below, will create an application product using provided product variant reference. You can only add products to an application that are configured for your company, if you would like to learn more about configuring products please check the knowledge base area for the detailed guide on products.

POST	/products/application/create/{applicationReference}
------	---

Field name	Required	Data type	Notes
VariantReference	Y	Guid	You can acquire the variant references using the GET – Retrieve all products method.
PaymentType	N	String	Default – Include in figures “Financed” = Include in figures “MonthlyDD” = Monthly direct debit “Cash” = Cash “FreeOfCharge” = Free of charge

PUT – Update premium on application product: The body should contain the object provided below, this method will update the premium of a product on an application, the premium cannot be higher than the max cost of the product and if this fails an error will be returned describing this. The product reference required can be retrieved using the “GET – Retrieve products on application” method.

PUT	/products/application/update/{applicationReference}
-----	---

Field name	Required	Data type	Notes
ProductReference	Y	Guid	You can acquire the product references using the GET – Retrieve products on application method.
Premium	N	Decimal	Default – Current premium of product Please note premium cannot be higher than the max cost for the variant.

Object Types

2.14 Applicant

Field name	Required	Data type	Notes
Title	N	String	One of the following "Mr", "Mrs", "Miss", "Ms", "Dr", "Other"
Forename	Y	String	
MiddleName	N	String	
Surname	Y	String	
MaidenName	N	String	
MainApplicant.Gender	N	String	"Male", "Female"
Email	Y	String	
Mobile	N	String	
Landline	N	String	
DateOfBirth	N	Date	Format: YYYY-MM-DD
MaritalStatus	N	String	"Single", "Cohabiting", "Married", "Separated", "Divorced", "Widowed", "Civil Partnership", "Dissolved Civil Partnership", "Engaged"
Addresses	N	Array (Address)	This is a child element of applicant
Employments	N	Array (Employment)	This is a child element of applicant
ValidUkPassport	N	Bool	True / False
DrivingLicenceType	N	String	"Full UK", "Provisional UK", "CBT", "A2", "Full A Class", "European", "International", "None"
DrivingLicenceNumber	N	String	
Endorsements	N	Int	Number of endorsements on driving licence
Nationality	N	String	See Appendix 1 – Will default to British if value is incorrect or not provided
NationalityAlphaCode	N	String	See Appendix 1– Will default to GBR if value is incorrect or not provided

Field name	Required	Data type	Notes
CountryOfBirth	N	String	See Appendix 2 – Will default to United Kingdom if value is incorrect or not provided
CountryOfBirthAlphaCode	N	String	See Appendix 2 – Will default to GBR if value is incorrect or not provided
HouseValuation	N	Decimal	
MortgageBalance	N	Decimal	
NumberOfDependants	N	Int	
OtherIncome	N	Int	
PositionWithinBusiness	N	String	
LicenceAtCurrentAddress	N	Bool	True / False
DebtManagement	N	Bool	True / False
Iva	N	Bool	True / False
Bankrupt	N	Bool	True / False

2.15 Address

Field name	Required	Data type	Notes
BuildingName	N	String	Eg; "The Granary"
BuildingNumber	N	String	Eg; "50"
SubBuildingName	N	String	Eg; "Office 1" or "Flat 1"
Street	N	String	
County	N	String	
Town	N	String	
Postcode	Y	String	
TimeAtAddressMonths	Y	Int	
TimeAtAddressYears	Y	Int	
ResidentialStatus	Y	String	"Homeowner", "Joint owner", "Tenant - Private", "Tenant - Private (unfurnished)", "Tenant - Housing Association", "Tenant - Council", "Living With Family", "Military Accommodation", "Work Accommodation", "Student Accommodation", "Other"
CountryAlphaCode	N	String	See Appendix 2 – If value is provided but does not match Appendix then will default to United Kingdom

2.16 Application Task

Field name	Required	Data type	Notes
PackagedApplicationReference	Y	Guid	
Description	N	String	Eg; "Call applicant, request documents"
Due	Y	DateTime	UTC
TaskActionReference	Y	Guid	

2.17 Employment

Field name	Required	Data type	Notes
Employer	N	String	
JobTitle	N	String	
EmploymentStatus	Y	String	"Full-Time Employment", "Part-Time Employment", "Temporary/Contract", "Self-Employed", "Benefits", "Education", "Retired", "Other", "Homemaker", "Carer", "Armed Services" "Self-Employed" can be used for sole traders
MonthlyIncome	N	Int	Monthly income before tax
OccupationType	N	String	Call list occupation types endpoint to retrieve potential values. See 2.11.1
Industry	N	String	Call list industries endpoint to retrieve potential values. See 2.10.2
CountryOfOperationAlphaCode	N	String	See Appendix 2 for values. This will only populate if employment status is "Self-Employed" or OccupationType is "Director / Board member". If value is not provided it will default to GBR
NetMonthlyIncome	N	Int	Monthly income after tax
TimeAtEmployerMonths	N	Int	
TimeAtEmployerYears	Y	Int	
PhoneNumber	N	String	Work phone
BuildingName	N	String	Eg; "The Granary"
BuildingNumber	N	String	Eg; "50"
SubBuildingName	N	String	Eg; "Office 1" or "Flat 1"
Street	N	String	
Town	N	String	
County	N	String	
PostCode	N	String	
CountryAlphaCode	N	String	See Appendix 2 – If value is provided but does not match Appendix then will default to null . If value is not provided it will default to GBR
SickLeave	N	Bool	True / False
MaternityLeave	N	Bool	True / False
ZeroHourContract	N	Bool	True / False
OnProbation	N	Bool	True / False

2.18 Vehicle

Field name	Required	Data type	Notes
VehicleType	N	String	"Car", "Van", "Motorbike", "Caravan", "MotorHome", "HGV", (Heavy Goods Vehicle) "StaticCaravan", "Horsebox", "Other" Will default to Car
Registration	N	String	
Make	N	String	
Model	N	String	
Derivative	N	String	
CostWhenNew	N	decimal	
CapId	N	Int	
CapCode	N	String	
Doors	N	Int	Number of doors on vehicle
NumberOfPreviousKeepers	N	Int	
BodyStyle	N	String	
Colour	N	String	
DateRegistered	N	DateTime	UTC
DriveType	N	String	
EngineNumber	N	String	
EngineSize	N	Decimal	
FuelType	N	String	
GearboxType	N	String	
GlassesCode	N	String	
ModelRange	N	String	
ModelYear	N	String	
New	N	Bool	If PartExchange is true this will default to false
RetailValue	N	Decimal	
SalesType	N	String	"Retail", "Fleet", "Motability", "Trade", "Commerical" if not passed will default to Retail
StockNumber	N	String	
Transmission	N	String	
Usage	N	String	"Business", "Driving school", "Social",

Field name	Required	Data type	Notes
			"Taxi" if not passed will default to Social
VatRate	N	Decimal	"0.0", "20.0" if New is false or PartExchange is true will default to 0.0
VehicleDescription	N	String	
Vin	N	String	
PartExchange	N	Bool	Send this as false to specify a purchase vehicle
Mileage	N	Int	
MarginScheme	N	Bool	If the vehicle is new OR the VAT rate is not equal to 0 OR the vehicle is part exchange, this will be overridden to false

2.19 BankDetails

Field name	Required	Data type	Notes
AccountNumber	N	String	
SortCode	N	String	
TimeAtBankMonths	N	int	
TimeAtBankYears	N	int	
AccountName	N	String	
BankName	N	String	
BranchName	N	String	
BankAddress	N	String	
AcceptBACS	N	Bool	
AcceptDirectCreditTransactions	N	Bool	
AcceptDirectDebitInstruction	N	Bool	
AcceptDirectDebitTransactions	N	Bool	
AcceptFasterPayment	N	Bool	

2.20 BusinessDetails

Field name	Required	Data type	Notes
BusinessType	N	String	"PrivateLimitedCompany", "PublicLimitedCompany", "Partnership", "LimitedLiabilityPartnership", "SoleTrader" Will default to PrivateLimitedCompany
BusinessName	Y	String	Required if enquiry type is business
MainTelephone	N	String	
DateOfIncorporation	N	DateTime	
IndustryType	Y	String	Agriculture Retail Wholesale Construction Chemicals Engineering Manufacturing FinancialServices OtherServices ServiceIndustry Professions Communications Energy Technology Transport TaxiVehicleHire
RegistrationNumber	N	String	
VatNumber	N	String	
PreviousBusinessName	N	String	
BusinessDescription	N	String	
CountryOfOperationAlphaCode	N	String	See Appendix 2 – If value is provided but does not match Appendix then will default to United Kingdom

2.21 BusinessAddress

Field name	Required	Data type	Notes
PremisesType	N	String	"Leased", "Licensed", "Mortgaged", "Owned" Will default to Leased
Building	N	String	

Field name	Required	Data type	Notes
Street	N	String	
Town	N	String	
DependentLocality	N	String	
County	N	String	
Postcode	N	String	
TimeAtAddressMonths	N	Int	
TimeAtAddressYears	N	Int	
UkAddress	N	Bool	Confirms the above address is in the UK
RegisteredAddress	N	Bool	Confirms the above address is the registered address
RegisteredPremisesType	N	String	The same options shown in this object by field PremisesType
RegisteredBuilding	N	String	
RegisteredStreet	N	String	
RegisteredTown	N	String	
RegisteredCounty	N	String	
RegisteredPostcode	N	String	
RegisteredTimeAtAddressMonths	N	Int	
RegisteredTimeAtAddressYears	N	Int	
RegisteredAddressUk	N	Bool	Confirms the registered address is in the UK

2.22 FinanceDetails

Field name	Required	Data type	Notes
FinanceTypeId	N	Int	1 = HP, 2 = PCP, 3 = Motor Loan, 4 = Motor Loan Balloon, 5 = Contract Hire, 6 = Cash Purchase
EnquiryType	N	String	"Private", "Business" Will default to Private
Deposit	N	Decimal	
PartExchangeValue	N	Decimal	
FDA	N	Decimal	This is dealer deposit
EstimatedAnnualMileage	N	Int	
Settlement	N	Decimal	
DistanceSale	N	Bool	
SettlementLenderReference	N	String	Settlement lender retrieved in section 2.8
InterestRate	N	Decimal	
InterestRateType	N	String	"APR", "FlatRate" Will default to FlatRate

2.23 Product

Field name	Required	Data type	Notes
Name	Y	String	
VAT	N	Decimal	0.0, 5.0, 20.0
NetValue	N	Decimal	
CategoryId	N	Int	0 = NotSet 1 = FactoryFitted 2 = DealerFitted 3 = RoadFundLicence 4 = DeliveryCharge 5 = RegistrationFee 6 = Warranty 7 = GAPorRTI 8 = Insurance 9 = NonInsurance 10 = TyreInsurance 11 = BreakdownAssistance 12 = ServicePlan 13 = CosmeticProtection 14 = FindersFees 15 = Guarantee 16 = Paint 17 = Charity 18 = DealerFee 19 = FreeHoliday 20 = CashBack 21 = Other 22 = Discount 23 = WheelsPainted 24 = SiteTransfer 25 = Fuel 26 = AdminFee
PaymentType	N	String	“Financed”, “Monthly Direct Debit”, “Cash”, “Free of Charge”
Name	Y	String	
NetValue	N	Decimal	

2.24 Affordability

Field name	Required	Data type	Notes
ChildcareCosts	N	Int	
CircumstanceChangesExpected	N	Bool	
ReplacingExistingLoan	N	Bool	
TotalMonthlyRentOrMortgage	N	Int	

2.25 Consent

Field name	Required	Data type	Notes
ConsentTypeId	Y	Int	1 = Credit search 2 = First party marketing 3 = SMS 4 = Call 5 = Email 7 = Post 8 = Privacy policy 9 = Terms and conditions

2.26 CustomField

Field name	Required	Data type	Notes
Key	Y	String	
Value	Y	String	

2.27 ApplicationNote

Field name	Required	Data type	Notes
CreateWarningFromNote	N	Boolean	If set to true, will display the note when viewing the relevant Application/Enquiry. Defaults to false if not specified.
Text	Y	String	Free text
VisibleToIntroducer	N	Boolean	Defaults to true if not specified.
VisibleToLender	N	Boolean	Defaults to false if not specified.

2.28 FinanceDetails

Field name	Required	Data type	Notes
FinanceTypeId	Y	Int	1 = HP, 2 = PCP, 3 = Motor Loan, 4 = Motor Loan Balloon, 5 = Contract Hire, 6 = Cash Purchase
EnquiryType	Y	String	"Private", "Business" Will default to Private
Deposit	Y	Decimal	
PartExchangeValue	Y	Decimal	
FDA	Y	Decimal	This is dealer deposit
EstimatedAnnualMileage	Y	Int	
Settlement	Y	Decimal	
DistanceSale	Y	Bool	
SettlementLenderReference	Y	String	Settlement lender retrieved in section 2.8
InterestRate	Y	Decimal	
InterestRateType	Y	String	"APR", "FlatRate" Will default to FlatRate
LoanAmount	Y	Decimal	This is the cash price of the vehicle and should include the deposit amount.
LoanTerm	Y	Int	The duration in months of the loan

3 Example Requests

The following shows example JSON formatted requests to our system. The service should respond with an application reference if it is correctly formatted (this request does not contain all possible fields, refer to the field list for a complete listing).

A postman collection can be found at:

<https://www.getpostman.com/collections/a25b5327fd023e663b47>

3.1 Example submit request 1

```
{
  "VehicleType": "Car",
  "CampaignCode1": "campaignCode1",
  "CampaignCode2": "campaignCode2",
  "CreditScore": 500,
  "SourceReference": "sourceReference",
  "AmountToBorrow": 20000,
  "Term": 20,
  "Products": [
    {
      "Name": "test product",
      "VAT": 20.0,
      "NetValue": 80.0,
      "CategoryId": 6,
      "PaymentType": "Financed"
    },
    {
      "Name": "test product two",
      "VAT": 0.0,
      "NetValue": 90,
      "CategoryId": 4,
      "PaymentType": "Financed"
    }
  ],
  "Consent": [
    {
      "ConsentTypeId": "2"
    },
    {
      "ConsentTypeId": "5"
    }
  ],
  "FinanceDetails": {
    "Deposit": 2000,
    "PartExchangeValue": null,
    "FDA": null,
    "EstimatedAnnualMileage": "8000",
    "Settlement": null,
    "DistanceSale": false,
    "EnquiryType": "Private",
    "FinanceTypeId": "4"
  },
  "Affordability": {
    "TotalMonthlyRentOrMortgage": 1000,
    "ChildcareCosts": 0,
    "CircumstanceChangesExpected": false,
    "ReplacingExistingLoan": false
  },
  "CustomFields": [
    {
      "Key": "Clean",
      "Value": "5000"
    }
  ]
}
```

```

    },
    {
        "Key": "Average",
        "Value": "4500"
    },
    {
        "Key": "BelowAverage",
        "Value": "4000"
    }
},
"BankDetails": {
    "SortCode": "000000",
    "AccountNumber": "00000000",
    "AccountName": "AccountName",
    "TimeAtBankYears": "2",
    "TimeAtBankMonths": "2",
    "BranchName": "Branch name",
    "BankName": "Bank name",
    "BankAddress": "Bank address 2",
    "AcceptBACS": true,
    "AcceptDirectCreditTransactions": true,
    "AcceptFasterPayment": true
},
"Vehicles": [
    {
        "Make": "Make",
        "Model": "Model",
        "Derivative": "Derivative",
        "Registration": "R010ERS",
        "Mileage": "0",
        "PartExchange": false,
        "VehicleType": "Car",
        "EngineNumber": "EngineNumber",
        "EngineSize": 15,
        "Colour": "Frozen ocean",
        "Doors": 4,
        "RetailValue": 4000,
        "New": true,
        "VatRate": 20
    },
    {
        "Make": "Fiat",
        "Model": "Model",
        "Derivative": "DerivativeTwo",
        "Registration": "F024IAT",
        "Mileage": "1000",
        "PartExchange": true,
        "EngineNumber": "20Big",
        "RetailValue": 20000,
        "Colour": "White",
        "EngineSize": 52,
        "Transmission": "Manual",
        "Vin": "testtest",
        "CapCode": " testtest ",
        "GlassesCode": "GlassesCode",
        "DateRegistered": "2018-03-01",
        "StockNumber": "10",
        "Doors": "4",
        "ModelYear": "2017"
    }
],
"Applicants": [
    {
        "Title": "Mr",
        "DateOfBirth": "1975-05-19",
        "MaritalStatus": "Divorced",

```

```

"DrivingLicenceType": "Full UK",
"Email": "APITESTING@test.co.uk",
"Forename": "ForenameNine",
"Surname": "Surname",
"Mobile": "+447777777777",
"Nationality": "British",
"Addresses": [
  {
    "Building": "The Granary",
    "BuildingNumber": "2",
    "SubBuildingName": "Flat 1",
    "Postcode": "FA11 0UT",
    "Street": "Street",
    "Town": "Megaton",
    "County": "Maryland",
    "TimeAtAddressYears": "13",
    "TimeAtAddressMonths": "10",
    "ResidentialStatus": "Living With Family"
  },
  {
    "Building": "101",
    "Postcode": "FA11 0UT",
    "Street": "Vault lane",
    "Town": "town",
    "County": "Maryland",
    "TimeAtAddressYears": "5",
    "TimeAtAddressMonths": null,
    "ResidentialStatus": "Tenant - Private"
  }
],
"Employments": [
  {
    "Employer": "Vault-tec",
    "Building": "1",
    "Street": "Lane",
    "Town": "town",
    "Postcode": "FA11 0UT",
    "JobTitle": "Job",
    "EmploymentStatus": "Full-Time Employment",
    "TimeAtEmployerYears": "4",
    "TimeAtEmployerMonths": "3",
    "NetMonthlyIncome": "2000",
    "ZeroHourContract": "False",
    "PhoneNumber": "07777777777"
  },
  {
    "Employer": "Megaton office",
    "Building": "1",
    "Street": "street",
    "Town": "Megaton",
    "Postcode": "FA11 0UT",
    "JobTitle": "Sheriff",
    "EmploymentStatus": "Full-Time Employment",
    "TimeAtEmployerYears": "3",
    "TimeAtEmployerMonths": null,
    "NetMonthlyIncome": "1860",
    "ZeroHourContract": "False",
    "PhoneNumber": "07777777777"
  }
]
}

```

Note that in this request the product premium (gross cost) is calculated. A net of £80 is sent through at 20% Vat resulting in a gross cost of £96.

3.2 Example submit request 2

```
{
  "VehicleType": "Car",
  "AmountToBorrow": 5000,
  "LoanTerm": 12,
  "Applicants": [
    {
      "DateOfBirth": "1984-9-28",
      "DrivingLicenceType": "International",
      "Email": "bob@test.co.uk",
      "Forename": "Andrew",
      "Surname": "Test",
      "MiddleName": "James",
      "MaidenName": "Test",
      "Mobile": "07712345678",
      "Title": "Mr",
      "MaritalStatus": "Married",
      "Landline": "07712345678",
      "ValidUkPassport": true,
      "NumberOfDependants": 1,
      "OtherIncome": 0,
      "MortgageBalance": 100000,
      "HouseValuation": 300000,
      "Addresses": [
        {
          "Building": "1",
          "Street": "test",
          "County": "test",
          "Postcode": "BT11BT",
          "TimeAtAddressMonths": 10,
          "TimeAtAddressYears": 10,
          "Town": "Lisburn",
          "ResidentialStatus": "Homeowner"
        }
      ],
      "Employments": [
        {
          "Company": "test",
          "Building": "test",
          "Street": "test",
          "Town": "test",
          "County": "test",
          "Postcode": "TE11ST",
          "EmploymentStatus": "Full- Time Employment",
          "JobTitle": "tester",
          "MonthlyIncome": 1000,
          "TimeAtEmployerMonths": 10,
          "TimeAtEmployerYears": 10
        }
      ]
    }
  ],
  "ApplicationNotes": [
    {
      "CreateWarningFromNote": true,
      "Text": "This is test note 1",
      "VisibleToIntroducer": false
    },
    {
      "Text": "This is test note 2",
      "VisibleToLender": true
    },
    {
      "CreateWarningFromNote": true,
      "Text": "This is test note 3",
    }
  ]
}
```



```
    "VisibleToIntroducer": false
    "VisibleToLender": true
  }
}
```

3.3 Example submit request 3

```
{
  "VehicleType": "Car",
  "LoanAmount": 20,
  "LoanTerm": 20,
  "Products": [
    {
      "Name": "Cannot be null",
      "VAT": null,
      "NetValue": null,
      "CategoryId": null,
      "PaymentType": null
    }
  ],
  "FinanceDetails": {
    "Deposit": null,
    "PartExchangeValue": null,
    "FDA": null,
    "EstimatedAnnualMileage": null,
    "Settlement": null,
    "EnquiryType": null,
    "FinanceTypeId": null
  },
  "BankDetails": {
    "SortCode": null,
    "AccountNumber": null,
    "AccountName": null,
    "TimeAtBankYears": null,
    "TimeAtBankMonths": null,
    "BranchName": null,
    "BankName": null,
    "BankAddress": null
  },
  "Vehicles": [
    {
      "Registration": null
    }
  ],
  "Applicants": [
    {
      "Email": "APITESTING@test.co.uk",
      "Forename": "Barebones",
      "Surname": "Example"
    }
  ]
}
```

Note that if you send through product details as null, you will not be able to edit this later.

3.4 Example update request 1

Endpoint: <https://api.autoconvert.co.uk/application/update/00000000-0000-00000000-0000>

```
{
  "MainApplicant": {
    "Forename": "test",
    "Surname": "test",
    "Email": "test@com"
  }
}
```

3.5 Example update request 2

```
{
  "MainApplicant": {
    "Forename": "updated",
    "Surname": "applicationThroughApi",
    "email": "updatedemail@com",
    "Addresses": [
      {
        "Building": "1",
        "Street": "test",
        "County": "test",
        "Postcode": "BT11BT",
        "TimeAtAddressMonths": 10,
        "TimeAtAddressYears": 10,
        "Town": "Lisburn",
        "ResidentialStatus": "Homeowner"
      }
    ]
  }
}
```

Note that if you send through an address, the entirety of the applicant's address history will be replaced with the address history you provided in the update.

3.6 Example update vehicles request

```
{
  "Vehicles": [
    {
      "Registration": "TE31 REG",
      "Make": "Test car make",
      "Model": "Test car model",
      "Derivative": "Test car derivative",
      "Doors": 4,
      "Colour": "Azzurro",
      "New": true,
      "VehicleType": "Car"
    },
    {
      "Registration": "TE32 REG",
      "Make": "Second car",
      "Model": "Second car",
      "VehicleType": "Car",
      "New": false,
      "PartExchange": true
    }
  ]
}
```

3.7 Example update vehicle request

```
{
  "Registration": "TE31 REG",
  "Make": "Test car make 2",
  "Model": "Test car model 2",
  "Derivative": "Test car derivative 2",
  "Doors": 3,
  "Colour": "Nero",
  "New": true,
  "VehicleType": "Car"
}
```

3.8 Example update custom fields request

```
{
  "CustomFields": [
    {
      "Key": "NavigateFrom",
      "Value": "Facebook"
    },
    {
      "Key": "CreditScore",
      "Value": "300"
    }
  ]
}
```

3.9 Example update custom field request

```
{  
  "Key": "NavigatedFrom",  
  "Value": "Facebook"  
}
```


3.10 Example update business details

```
{  
  "BusinessType": "Partnership",  
  "BusinessName": "Example business",  
  "MainTelephone": "07460222221",  
  "DateOfIncorporation": "2001-05-19",  
  "IndustryType": "Manufacturing",  
  "RegistrationNumber": "T3ST",  
  "VatNumber": "T3ST",  
  "PreviousBusinessName": "Older business name",  
  "CountryOfOperationAlphaCode": "GBR",  
  "BusinessDescription": "A brief description of your business"  
}
```

3.11 Example update business address

```
{
  "PremisesType": "Licensed",
  "Building": "BusinessBuilding",
  "Street": "BusinessStreet",
  "Town": "BusinessStreet",
  "County": "BusinessCounty",
  "Postcode": "T334ST",
  "UkAddress": true,
  "RegisteredAddress": false,
  "RegisteredPremisesType": "Licensed",
  "RegisteredBuilding": "RegisteredBuilding",
  "RegisteredStreet": "RegisteredStreet",
  "RegisteredTown": "RegisteredTown",
  "RegisteredCounty": "RegisteredCounty",
  "RegisteredPostcode": "RegisteredPostcode",
  "RegisteredAddressUk": true
}
```

4 Appendices

4.1 Appendix 1 – Nationality alpha codes

A

AFG - Afghan
 ALB - Albanian
 DZA - Algerian
 USA - American
 ASM - American Samoan
 AND - Andorran
 AGO - Angolan
 ATA - Anguillian
 ATA - Antarctic
 ARG - Argentine
 ARM - Armenian
 ABW - Aruban
 AUS - Australian
 AUT - Austrian
 AZE - Azerbaijani

B

BHS - Bahamian
 BHR - Bahraini
 BGD - Bangladeshi
 BRB - Barbadian
 BLM - Barthelemois
 LSO - Basotho
 BLR - Belarusian
 BEL - Belgian
 BLZ - Belizean
 BEN - Beninese,
 Beninois
 BMU - Bermudian,
 Bermudan
 BTN - Bhutanese
 IOT - BIOT
 GNB - Bissau-Guinean
 BOL - Bolivian
 BES - Bonaire
 BWA - Botswanan
 BVT - Bouvet Island
 BRA - Brazilian
 GBR - British
 VGB - British Virgin
 Island
 BRN - Bruneian
 BGR - Bulgarian
 BFA - Burkinan
 MMR - Burmese
 BDI - Burundian

C

CPV - Cabo Verdean
 KHM - Cambodian
 CMR - Cameroonian
 CAN - Canadian
 CYM - Caymanian
 CAF - Central African
 TCD - Chadian
 CHL - Chilean
 CHN - Chinese
 CXR - Christmas Island
 ATG - Citizen of Antigua
 and Barbuda
 BIH - Citizen of Bosnia
 and Herzegovina
 DOM - Citizen of the
 Dominican Republic
 CCK - Cocos Island
 COL - Colombian
 COM - Comoran, Comorian
 COG - Congolese
 COD - Congolese
 COK - Cook Island
 CRI - Costa Rican
 HRV - Croatian
 CUB - Cuban
 CUW - Curacaoan
 CYP - Cypriot

CZE - Czech

D

DNK - Danish
 DJI - Djiboutian
 DMA - Dominican
 NLD - Dutch

E

TLS - East Timorese
 ECU - Ecuadorean
 EGY - Egyptian
 ARE - Emirati
 GNQ - Equatorial
 ERI - Eritrean
 EST - Estonian
 ETH - Ethiopian

F

FLK - Falkland Island
 FRO - Faroese
 FJI - Fijian
 FIN - Finnish
 FRA - French

G

GAB - Gabonese
 GMB - Gambian
 GEO - Georgian
 DEU - German
 GHA - Ghanaian
 GIB - Gibraltarian
 GRC - Greek
 GRL - Greenlandic
 GRD - Grenadian
 GLP - Guadeloupe
 GUM - Guamanian
 GTM - Guatemalan
 GGY - Guernsey Channel
 Island
 GIN - Guinean
 GUY - Guyanese

H

HTI - Haitian
 HND - Honduran
 HKG - Hong Konger
 HUN - Hungarian

I

KIR - I-Kiribati
 ISL - Icelandic
 IND - Indian
 IDN - Indonesian
 IRN - Iranian
 IRQ - Iraqi
 IRL - Irish
 ISR - Israeli
 ITA - Italian
 CIV - Ivorian

J

JAM - Jamaican
 JPN - Japanese
 JEY - Jersey Channel
 Island
 JOR - Jordanian

K

KAZ - Kazakh
 KEN - Kenyan
 KNA - Kittitian
 KWT - Kuwaiti
 KGZ - Kyrgyzstani

L

LAO - Laotian
 LVA - Latvian
 LBN - Lebanese
 LBR - Liberian
 LBY - Libyan
 LIE - Liechtenstein
 citizen
 LTU - Lithuanian
 LUX - Luxembourger

M

MAC - Macanese
 MKD - Macedonian
 MYT - Mahoran
 MDG - Malagasy
 MWI - Malawian
 MYS - Malaysian
 MDV - Maldivian
 MLI - Malian
 MLT - Maltese
 IMN - Manx
 MHL - Marshallese
 MTQ - Martiniquais
 MRT - Mauritanian
 MUS - Mauritian
 MEX - Mexican
 FSM - Micronesian
 MDA - Moldovan
 MCO - Monegasque
 MNG - Mongolian
 MNE - Montenegrin
 MSR - Montserratian
 MAR - Moroccan
 MOZ - Mozambican

N

NAM - Namibian
 NRU - Nauruan
 NPL - Nepalese
 NCL - New Caledonian
 NZL - New Zealand
 NIC - Nicaraguan
 NGA - Nigerian
 NER - Nigerien
 NIU - Niuean
 NFK - Norfolk Island
 PRK - North Korean
 MNP - Northern Marianan
 NOR - Norwegian

O

OMN - Omani

P

PAK - Pakistani
 PLW - Palauan
 PSE - Palestinian
 PAN - Panamanian
 PNG - Papua New Guinean
 PRY - Paraguayan
 PER - Peruvian
 PHL - Philippine
 PCN - Pitcairn Island
 POL - Polish
 PRT - Portuguese
 PRI - Puerto Rican

Q

QAT - Qatari

R

ROU - Romanian
 RUS - Russian

RWA - Rwandan

S

SHN - Saint Helenian
 LCA - Saint Lucian
 VCT - Saint Vincentian
 MAF - Saint-Martinoise
 SPM - Saint-Pierrais or
 Miquelonnais
 SLV - Salvadoran
 SMR - Sammarinese
 WSM - Samoan
 SAU - Saudi
 SEN - Senegalese
 SRB - Serbian
 SYC - Seychellois
 SLE - Sierra Leonean
 SGP - Singaporean
 SXM - Sint Maarten
 SVK - Slovak
 SVN - Slovenian
 SLB - Solomon Island
 SOM - Somali
 ZAF - South African
 KOR - South Korean
 SSD - South Sudanese
 ESP - Spanish
 LKA - Sri Lankan
 SDN - Sudanese
 SUR - Surinamese
 SJM - Svalbard
 SWZ - Swazi
 SWE - Swedish
 CHE - Swiss
 SYR - Syrian

T

TWN - Taiwanese
 TJK - Tajik
 TZA - Tanzanian
 THA - Thai
 TGO - Togolese
 TKL - Tokelauan
 TON - Tongan
 TTO - Trinidadian or
 Tobagonian
 TUN - Tunisian
 TUR - Turkish
 TKM - Turkmen
 TCA - Turks and Caicos
 Island
 TUV - Tuvaluan

U

VIR - U.S. Virgin Island
 UGA - Ugandan
 UKR - Ukrainian
 URY - Uruguayan
 UZB - Uzbek

V

VUT - Vanuatuan
 VAT - Vatican
 VEN - Venezuelan
 VNM - Vietnamese

W

WLF - Wallisian

Y

YEM - Yemeni

Z

ZMB - Zambian
 ZWE - Zimbabwean

4.2 Appendix 2 – Country alpha codes

A

ABW - Aruba
AFG- Afghanistan
AGO- Angola
AIA- Anguilla
ALB- Albania
AND- Andorra
ARE- United Arab Emirates
ARG- Argentina
ARM- Armenia
ASM- American Samoa
ATA- Antartica
ATG- Antigua and Barbuda
AUS- Australia
AUT- Austria
AZE- Azerbaijan

B

BDI- Burundi
BEL- Belgium
BEN- Benin
BES- Bonair, Sint Eustatius and Saba
BFA- Burkina Faso
BGD- Bangladesh
BGR- Bulgaria
BHR- Bahrain
BHS- Bahamas
BIH- Bosnia and Herzegovina
BLM- Saint Barthélemy
BLR- Belarus
BLZ- Belize
BMU- Bermuda
BOL- Bolivia
BRA- Brazil
BRB- Barbados
BRN- Brunei Darissalam
BTN- Bhutan
BVT- Barbados
BWA- Botswana

C

CAF- Central African Republic
CAN- Canada
CKK- Cocos (Keeling) Islands
CHE- Switzerland
CHL- Chile
CHN- China
CIV- Côte d'Ivoire
CMR- Cameroon
COD- Congo (Democratic Republic of the)
COG- Congo (Republic of the)
COK- Cook Islands
COL- Colombia
COM- Comoros
CPV- Cabo Verde
CRI- Costa Rica
CUB- Cuba
CUW- Curaçao
CXR- Christmas Island
CYM- Cayman Islands
CYP- Cyprus
CZE- Czech Republic

D

DEU- Germany
DJI- Djibouti
DMA- Dominica
DNK- Denmark
DOM- Dominican Republic
DZA- Algeria

E

ECU- Ecuador
EGY- Egypt
ERI- Eritrea
ESP- Spain
EST- Estonia
ETH- Ethiopia

F

FIN- Finland
FJI- Fiji
FLK- Falkland Islands (Malvinas)
FRA- France
FRO- Faroe Islands
FSM- Micronesia (Federated States of)

G

GAB- Gabon
GBR- United Kingdom
GEO- Georgia
GGY- Guernsey
GHA- Ghana
GIB- Gibraltar
GIN- Guinea
GLP- Guadeloupe
GMB- Gambia
GNB- Guinea-Bissau
GNQ- Equatorial Guinea
GRC- Greece
GRD- Grenada
GRL- Greenland
GTM- Guatemala
GUM- Guam
GUY- Guyana

H

HKG- Hong Kong
HND- Honduras
HRV- Groatia
HTI- Haiti
HUN- Hungary

I

IDN- Indonesia
IMN- Isle of Man
IND- India
IOT- British Indian Ocean Territory
IRL- Ireland
IRN- Iran
IRQ- Iraq
ISL- Iceland
ISR- Israel
ITA- Italy

J

JAM- Jamaica
JEY- Jersey
JOR- Jordan
JPN- Japan

K

KAZ- Kazakhstan
KEN- Kenya
KGZ- Kyrgyzstan
KHM- Cambodia
KIR- Kiribatti
KNA- Saint Kitts and Nevis
KOR- Korea (Republic of)
KWT- Kuwait

L

LAO- Lao People's Democratic Republic
LBN- Lebanon
LBR- Liberia
LBY- Libya
LCA- Saint Lucia
LIE- Liechtenstein
LKA- Sri Lanka
LSO- Lesotho
LTU- Lithuania
LUX- Luxembourg
LVA- Latvia

M

MAC- Macao
MAF- Saint Martin
MAR- Morocco
MCO- Monaco
MDA- Moldova (Republic of)
MDG- Madagascar
MDV- Maldives
MEX- Mexico
MHL- Marshal Islands
MKD- Macedonia
MLI- Mali
MLT- Malta
MMR- Myanmar
MNE- Montenegro
MNG- Mongolia
MNP- Northern Mariana Islands
MOZ- Mozambique
MRT- Mauritania
MSR- Montserrat
MTQ- Martinique
MUS- Mauritius
MWI- Malawi
MYS- Malaysia
MYT- Mayotte

N

NAM- Namibia
NCL- New Caledonia
NER- Niger
NFK- Norfolk Island
NGA- Nigeria
NIC- Nicaragua
NIU- Niue
NLD- Netherlands
NOR- Norway
NPL- Nepal
NRU- Nauru
NZL- New Zealand

O

OMN- Oman

P

PAK- Pakistan
PAN- Panama
PCN- Pitcairn
PER- Peru
PHL- Philippines
PLW- Palau
PNG- Papua New Guinea
POL- Poland
PRI- Puerto Rico
PRK- Korea (Democratic People's Republic of)
PRT- Portugal
PRY- Paraguay
PSE- Palestine, State of

Q

QAT- Qatar

R

ROU- Romania
RUS- Russian Federation
RWA- Rwanda

S

SAU- Saudi Arabia
SDN- Sudan
SEN- Senegal
SGP- Singapore
SHN- Saint Helena
SJM- Svalbard and Jan Mayen
SLB- Solomon Islands
SLE- Sierra Leone
SLV- El Salvador
SMR- San Marino
SOM- Somalia
SPM- Saint Pierre Miquelon
SRB- Serbia
SSD- South Sudan
SUR- Suriname
SVK- Slovakia
SVN- Slovenia
SWE- Sweden
SWZ- Swaziland
SXM- Sint Maarten (Dutch Part)
SYC- Seychelles
SYR- Syrian Arab Republic

T

TCA- Turks and Caicos Islands
TCD- Chad
TGO- Togo
THA- Thailand
TJK- Tajikistan
TKL- Tokelau
TKM- Turkmenistan
TLS- Timor-Leste
TON- Tonga
TTO- Trinidad and Tobago
TUN- Tunisia
TUR- Turkey
TUV- Tuvalu
TWN- Taiwan
TZA- Tanzania, United Republic of

U

UGA- Uganda
UKR- Ukraine
URY- Uruguay
USA- United States of America
UZB- Uzbekistan

V

VAT- Vatican City State
VCT- Saint Vincent and the Grenadines
VEN- Venezuela (Bolivarian Republic of)
VGB- Virgin Islands (British)
VIR- Virgin Islands (U.S.)
VNM- Vietnam
VUT- Vanuatu

W

WLF- Wallis and Futuna
WSM- Samoa

Y

YEM- *Yemen*

Z

ZAF- *South Africa*

ZMB - *Zambia*

ZWE- *Zimbabwe*