NEURAL CODEC LATENT DISTILLATION FOR CORPUS RETRIEVAL SYNTHESIS ON THE ELK STOMP

Trent Eriksen, Jazz Segovia, Dennison Blackett
Independent Researchers
stardustst ereo@gmail.com, jazzcallshome@gmail.com
dennison.blackett@gmail.com

ABSTRACT

Latent granular resynthesis encodes a corpus and an input with a neural audio codec and replaces each input frame with a similar corpus frame. The Elk Stomp Dev Kit, a device without a neural processing unit, cannot run codecs like music2latent that are often utilized for this type of synthesis. We ask whether a small query encoder, distilled from music2latent selects grains as that encoder would, and what limits real-time operation. A distilled multilayer perceptron of 103k parameters is compared offline on input with four other query encoders with each analysis stage timed on the Elk. Results indicate it preserves the encoder's similarity ordering better than a linear map and MFCCs (Spearman ρ .83 against .80 and .58), with selections on average in the encoder's top 4–7 %. On the Elk it takes about 1 % of the 93 ms analysis period, and only the search grows with corpus size.

1. INTRODUCTION

The Elk Stomp Dev Kit runs the low latency Elk Audio OS [1] on an STM32MP157 with two Cortex-A7 cores at 800 MHz without NPU. Latent granular resynthesis [2] encodes an input and a corpus of recordings with a neural audio codec and replaces each input frame with a similar corpus frame. Here the codec is music2latent [3], a consistency autoencoder which turns each ≈93 ms of audio into a latent which is then decoded into audio. With 58 M parameters and no 32-bit armv7 LibTorch build, neither can run on the Elk. This study originates from a latent granular instrument that was originally built on an M1 Max Macbook for the Music Hackspace × MUTEK Montréal hackathon and presented at its winners' showcase. [1] The corpus can be encoded offline so only the live input, needs encoding on the Elk. We ask whether a small query encoder distilled from the music2latent encoder (the teacher) selects grains as the teacher would, and what limits real-time operation.

[1] https://forum.mutek.org/en/shows/2026/music-hackspace-x-mutek-hackathon-winners-showcase

© T. Eriksen, J. Segovia, and D. Blackett. Licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0). **Attribution:** T. Eriksen, J. Segovia, and D. Blackett, "Neural Codec Latent Distillation for Corpus Retrieval Synthesis on the Elk Stomp", in *Extended Abstracts for the Late-Breaking Demo Session of the 27th Int. Society for Music Information Retrieval Conf.,* Abu Dhabi, UAE, 2026.




Figure 1. (A) Offline, a student network is distilled from the music2latent encoder, which encodes the author's recordings. (B) On the Elk Stomp, the student replaces the encoder for the live input, and stored grains replace the decoder. (C) The Elk Stomp Dev Kit. Image: Elk Audio.

The student is a multilayer perceptron trained to reproduce the teacher's latents. We hypothesize that the student preserves the teacher's ordering of all grains by similarity better than a linear map and MFCCs (H1). We additionally hypothesize that on the Elk it costs a small fraction of the time between analyses while the search over all grains becomes the largest cost for large corpora (H2). Experiments 1 and 2 test H1 offline on four corpora and H2 on the Elk.

2. RELATED WORK

Neural audio instruments select grains by similarity in a codec's latent space [2], morph sounds via codec tokens [4] or navigate an autoencoder's latent [5]. All three decode through the model and have no embedded hardware. Instruments with embedded processing [1] need no laptop during performance. Elk Audio OS lists support for ML applications, including real-time music information retrieval, among its requirements [1]. It runs models on the Raspberry Pi 4 [6,7]. RTNeural [8] has run real time neural audio effects on a mobile phone with four Cortex-A7 cores [9], the Elk Stomp's core type. Knowledge distillation trains a small student to reproduce a larger teacher's outputs [10]. For embeddings the student regresses the frozen teacher's vectors under a squared error [11, 12] or cosine loss [13]. The distilled audio encoders of [11–14] are evaluated by word error rate or classification, not by whether they keep the teacher's similarity ordering, which

H1 tests.

3. METHOD

The initial desktop based instrument replaces each input latent with a grain's latent, sampled from a softmax over cosine similarities with temperature τ. On the Elk (Fig. 1) the student replaces the encoder for live input and stored audio grains joined with 10 ms crossfades replace the decoder. The Elk then concatenates recorded audio, as concatenative synthesis does [15], while ceasing the interpolation between grains that Tokui and Baker attribute to decoding [2]. A pack holds a corpus's 16-bit audio and teacher latents. [2] [3]

The student takes a frame's 80 band log-mel spectrum as the Elk computes it with one 4096-point FFT and a filterbank. It has two 256-unit hidden layers and runs through RTNeural [8]. It was trained on 45,983 mel-latent pairs from the author's recordings and MUSDB18 previews under MSE $+ 0.3\,(1 -$ mean-centered cosine$)$.

Real-time operation. The audio callback every 64 samples at 48 kHz (1.33 ms), only mixes scheduled grains. A worker thread runs the analysis every 4,480 samples. Each analysis runs the front end consisting of resampling, mel frames, the student and the search (grain cosine similarity and selection). Real time here means that each callback and each analysis finishes within its period.

4. EXPERIMENTS

Experiment 1 compares five query encoders small enough for the Elk; a linear ridge map from log-mel bands and spectral descriptors, the student and a 128-unit GRU to test temporal context. Two are references as the teacher itself sampled with a second seed and query MFCCs matched against corpus MFCCs. The 12 queries are held out at file level from all corpora and training. Each is matched against four corpora (percussive, tonal, textural, field) from the author recordings .

Metrics. The first criterion is Spearman's ρ between the encoder's and the teacher's similarity orderings of all grains. The second is the selected grain's percentile rank in the teacher's ordering (.95: more similar than 95 % of grains). Selection agreement is the share of frames where an encoder selects the teacher's grain. Hub share, the share of selections on the five most selected grains measures repetition related to hubness [16]. Both are reported but not used to rank as sampling at $\tau = 0.05$ keeps agreement low even for the teacher's second seed. Experiment 2 timed each analysis stage on the Elk for three corpus sizes (Fig. 2) and 32- or 8-bit latent tables.

5. RESULTS

Retrieval fidelity (H1). The student and the GRU keep the teacher's ordering well (Table 1, ρ .829 and .826). The student leads the ridge map by .032, while in every query MFCCs lag behind (.575). Its selections rank near the teacher's (.945 against .981) showing H1 is supported.

Query encoder	Parameters	ρ	Pct.	Agr.	Hub
Teacher, second seed	—	—	.981	.026	.17
MFCC cosine, no map	—	.575	.835	.007	.12
Ridge map	5.7 k	.797	.933	.039	.20
GRU-128	0.09 M	.826	.945	.045	.21
Student (MLP)	0.10 M	.829	.945	.047	.22

Table 1. Parameters, Spearman ρ, percentile rank (Pct.), agreement (Agr.) and hub share (Hub) over 48 query–corpus pairs at $\tau = 0.05$.




Figure 2. Median time per analysis on the Elk Stomp. The search grows with the corpus and runs 2.6 to 3.1 times faster with the 8-bit table.

On device cost (H2). Every analysis finished within its period and no run lost input. The callback is not the limit as granular synthesis averaged 1.95–2.39 % of it (at most 10.9 %), against 0.093 % on an M1 Max laptop. The student took about 1 % of the period while the search grew with the corpus (Fig. 2), costing most from 5,115 grains on (32-bit table) while the 8-bit table kept the student's ordering. H2 is supported as for the utilized corpora the search limits how short the period can be.

6. DISCUSSION

A student of 0.10M parameters keeps most of the teacher's 58 M parameter ordering and enables granular synthesis the Elk. The study is limited by four corpora of the author's recordings, the Elk's onboard compute and the metrics measure agreement with the teacher's ordering. Onsets are the student's weakest frames with cosine distance .295 against .262 for sustained frames. Future work could add an ordering term to the per frame loss, such as relational or similarity preserving losses [17, 18] or top-K ranking distillation [19]. The inclusion of expanded audio and music corpora along with variable onboard compute are promising directions for further experimentation in latent synthesis for embedded systems.

7. AI USAGE STATEMENT

Anthropic Claude aided initial literature review and drafting.

[2] Code, Elk logs and notebooks: `https://github.com/Grashopr-888/ISMIR_LBD_2026_submission`

[3] Demo video: `https://youtu.be/gLobf3o0Qg0?si=mHY-RTp-Ta_0zCg6`

8. REFERENCES

[1] L. Turchet and C. Fischione, "Elk Audio OS: An open source operating system for the internet of musical things," *ACM Transactions on Internet of Things*, vol. 2, no. 2, pp. 1–18, 2021.

[2] N. Tokui and T. Baker, "Latent granular resynthesis using neural audio codecs," in *Extended Abstracts for the Late-Breaking Demo Session of the 26th International Society for Music Information Retrieval Conference (ISMIR)*, 2025.

[3] M. Pasini, S. Lattner, and G. Fazekas, "Music2Latent: Consistency autoencoders for latent audio compression," in *Proceedings of the 25th International Society for Music Information Retrieval Conference (ISMIR)*, 2024, pp. 111–119.

[4] E. Karystinaios, "Neural Morphing: Sequence-optimized token-level morphing in neural audio codecs," in *Proceedings of the 29th International Conference on Digital Audio Effects (DAFx26)*, 2026.

[5] S. J. Zheng, K. Yoshida, N. García-Peguinho, J. Liu, D. Hearn, A. Xambó Sedó, and N. Bryan-Kinns, "Latent Terrain: Adapting neural audio autoencoders as design materials in NIME," in *Proceedings of the International Conference on New Interfaces for Musical Expression (NIME)*, 2026.

[6] D. Stefani and L. Turchet, "Real-time embedded deep learning on Elk Audio OS," in *2023 4th International Symposium on the Internet of Sounds (IS2)*, 2023.

[7] D. Stefani, S. Peroni, and L. Turchet, "A comparison of deep learning inference engines for embedded real-time audio classification," in *Proceedings of the 25th International Conference on Digital Audio Effects (DAFx20in22)*, 2022.

[8] J. Chowdhury, "RTNeural: Fast neural inferencing for real-time systems," 2021, arXiv:2106.03037.

[9] J. Hoopes, B. Chalmers, and V. Zappi, "Neural audio processing on Android phones," in *Proceedings of the 27th International Conference on Digital Audio Effects (DAFx24)*, 2024, pp. 33–40.

[10] J. Gou, B. Yu, S. J. Maybank, and D. Tao, "Knowledge distillation: A survey," *International Journal of Computer Vision*, vol. 129, no. 6, pp. 1789–1819, 2021.

[11] H. Lee and A. Saeed, "Distilled non-semantic speech embeddings with binary neural networks for low-resource devices," *Pattern Recognition Letters*, 2023.

[12] P. Yadla, M. Samragh Razlighi, D. Hwang, M. Xu, Y. Zhang, C.-C. Chiu, Y. Wang, Y. Liu, Z. Huang, and X. Zhuang, "Compressing streaming neural audio encoders via latent-space distillation," 2026, arXiv:2609.04102 (Apple). Posted 3 Sep 2026.

[13] M. A. El Adlouni, A. Quelennec, P. Chouteau, G. Peeters, and S. Essid, "S-SONDO: Self-supervised knowledge distillation for general audio foundation models," 2026, arXiv:2604.24933.

[14] F. Paissan and E. Farella, "tinyCLAP: Distilling contrastive language-audio pretrained models," in *Proceedings of Interspeech 2024*, 2024.

[15] D. Schwarz, G. Beller, B. Verbrugghe, and S. Britton, "Real-time corpus-based concatenative synthesis with CataRT," in *Proceedings of the 9th International Conference on Digital Audio Effects (DAFx-06)*, 2006, pp. 279–282.

[16] M. Radovanović, A. Nanopoulos, and M. Ivanović, "Hubs in space: Popular nearest neighbors in high-dimensional data," *Journal of Machine Learning Research*, vol. 11, pp. 2487–2531, 2010.

[17] W. Park, D. Kim, Y. Lu, and M. Cho, "Relational knowledge distillation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 3967–3976.

[18] F. Tung and G. Mori, "Similarity-preserving knowledge distillation," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2019, pp. 1365–1374.

[19] J. Tang and K. Wang, "Ranking distillation: Learning compact ranking models with high performance for recommender system," in *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2018.