

Python modules and packages

Structuring large(r) projects


Giuseppe Averta

Carlo Masone

Francesca Pistilli

Davide Buoso

Gaetano Falco



<https://realpython.com/python-modules-packages/>



Goal

- Split a large program in multiple files
- Make re-usable library of classes
- Import and use additional libraries

Modules

- Modules are collections of classes, functions, variables, and declarations
- The `import` statement runs the module source and makes the definitions available
- The defined names are created in a separated *namespace* to avoid confusion

Standard library modules

- random, math, csv, operator, os, dataclasses, datetime, ... 200 more
- <https://docs.python.org/3/library/index.html>

User-defined modules

- My python sources
- Files and directories in my project
- Files and directories in the Python search path

Downloaded modules

- From <https://pypi.org/> - over 500k projects
- Install using pip

Creating a Python module

- Just create a `.py` file
 - In the *same directory* of your main file
 - Should contain *declarations, only*
- The *name of the file* is the name of the module
 - The argument of `import`
- All names defined *at the top-level* become visible properties of the module
 - Constants
 - Functions
 - Classes
 - Variables (bad idea)

voto.py

```
MAX_VOTO = 30

class Voto:
    def __init__(self, esame, cfu, punteggio, lode, data):
        ...
    def __str__(self):
        ...
    def __repr__(self):
        ...

class Libretto:
    def __init__(self):
        ...
    def append(self, voto):
        ...
    def media(self):
        ...

def voto_casuale():
    ...
```

main.py

```
import voto
```

The `import` statement

- `import module_name`
 - Imports the definitions from `module_name`. They will be accessible as `module_name.definition`
 - Example: `import math` ; use `math.sin(math.pi)`
- `import module_name as alt_name`
 - Imports the definitions from `module_name`. They will be accessible as `alt_name.definition`
 - Example: `import cmath as c` ; use `c.sqrt(-1)`

The `from...import` statement

- `from module_name import name(s)`
 - Import one or more `name(s)` from `module_name`, and make them available in the current namespace
 - Example: `from math import pi, sin, cos` ; use `sin(pi)`
- `from module_name import name as alt_name`
 - Import one name from `module_name`, and make it available in the current namespace as `alt_name`
 - Example: `from cmath import sqrt as csqrt` ; use `csqrt(-1)`
- `from module_name import *`
 - Import all available names from `module_name`, and make them available in the current namespace
 - Except names starting with `'_'` (underscore)... they are ignored
 - Somewhat dangerous... may have conflicts with local names or other module's names

Querying available names: `dir()`

- The `dir()` function shows the list of names defined in a module
 - `dir()`: names defined (at the top level) of the **current** file
 - `dir(module_name)`: names defined in the **imported** module
- Several *dunder* methods, plus user-defined names

```
import voti

print(dir(voti))
# ['Libretto', 'MAX_VOTO', 'Voto', 'random', 'voto_casuale', ...]

print(dir())
# ['voti', ...]
```

```
from voti import Voto, Libretto

print(dir(voti))
# NameError: name 'voti' is not defined.

print(dir())
# ['Libretto', 'Voto', ...]
```

A module should not contain executable statements

- The `import` statement runs the module file to create the definitions of the various names
- If there are any instructions outside the defined classes/functions, they will be executed, too...
- If `voti.py` contains

```
v = voto_casuale()
print(repr(v))
```
- Then, the `import voti` statement in `main.py` will cause
 - Defining a new top-level name (`v`)
 - Calling `voto_casuale()`
 - Printing the random vote
- All this should **not** happen!

Solving the problem

- It is useful to have some code *inside the module*
 - Usually, **test code** to verify that the module works correctly
 - Sometimes, a **whole program** (with its top-level code) may be **used as a module** for a larger problem
- We **want** to **allow** in-module code, but we **don't want** it to **run**, when imported

- The solution is to check if the file is the top-level one, or an imported one: `__name__`


```
if __name__ == "__main__":  
    v = voto_casuale()  
    print(repr(v))
```

- Or, better:


```
def _main():  
    v = voto_casuale()  
    print(repr(v))  
  
if __name__ == "__main__":  
    _main()
```

Packages

- When an application grows, it is no longer viable to have all the Python file in a **single** directory
- We can split groups of files in separate directories, called **packages**
 - Each **directory** is a **package**
 - The **files** of the directory are **modules**
 - They can be imported with the syntax **package_name.module_name**



(and sub-packages)



Importing from packages

- The traditional syntax still applies
 - `import pkg.mod`
 - `from pkg.mod import name`
 - `from pkg.mod import name as alt_name`
- Additionally, you may import modules from a package
 - `from pkg import mod`
 - `from pkg import mod as alt_mod_name`

The `__init__.py` file

- Traditionally, the directory containing a package will also contain a special file
 - `__init__.py`
 - It was mandatory until Python 3.3, now it's optional
- Can contain initialization statements, that are run when importing any module from the package

Working with external modules

- To access a module from pypi.org, we must first install the module in our local Python interpreter
- Packages can be installed using the `pip` program
 - Search a project on <https://pypi.org/>
 - Install with `pip install project_name`
 - `pip install flet`
 - `pip install mariadb`
- Only installed packages can be imported

Installing packages with PyCharm

The screenshot shows the PyCharm interface with the **Python Packages** tool window open. The search bar contains **mariadb**. The left pane shows the search results under **PyPI (9 found)**, with **mariadb** selected and an **Install** button next to it. The right pane displays the **mariadb** package details, including a seal logo and the text **MariaDB**. A callout labeled **Search Package** points to the search bar. A callout labeled **Currently installed** points to the **Python Packages** tab. A callout labeled **Install** points to the **Install package** button. A callout labeled **Info** points to the package details pane.

Python Packages

Search Package

Currently installed

Python Packages

Install

Info

mariadb

Documentation

latest

Install package

mariadb

mariadb-dyncol

mariadb-kernel

MariaDB-SQLBuilder

MariadbAbcLog

cloud2mariadb

dictum-backend-mariadb

infra2mariadb

tencentcloud-sdk-python-r


MariaDB

Virtual Environments


- Different projects may require different packages
- ⚠️ Your local Python library will contain all sorts of packages, that are used by some project
- ⚠️ When shipping a project, it's not clear which packages are needed to run it
- Python has a mechanism for separating the packages needed by each project
- 💡 Virtual environments
- It's a local “copy” of the Python interpreter, alongside with the packages needed for that project
- Stored in the `.venv` directory

Virtual Environments in PyCharm

For existing project



For new project



Where does Python find packages?


- The import statement searches packages
 - In the current project directories
 - In the current virtual environment's library
 - In a set of directories defined by the Python installation

```
import sys  
print(sys.path)
```

```
[ 'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\PyCharm  
Professional\\plugins\\python\\helpers\\pydev',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\PyCharm  
Professional\\plugins\\python\\helpers\\third_party\\thri  
ftpy',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\PyCharm  
Professional\\plugins\\python\\helpers\\pydev',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\PyCharm  
Professional\\plugins\\python\\helpers\\pycharm_display',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\Python\\Pyt  
hon312\\python312.zip',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\Python\\Pyt  
hon312\\DLLs',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\Python\\Pyt  
hon312\\Lib',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\Python\\Pyt  
hon312', 'D:\\teaching\\TdP-2024\\libretto_voti\\.venv',  
'D:\\teaching\\TdP-2024\\libretto_voti\\.venv\\Lib\\site-  
packages',  
'C:\\Users\\Fulvio\\AppData\\Local\\Programs\\PyCharm  
Professional\\plugins\\python\\helpers\\pycharm_matplotli  
b_backend', 'D:\\teaching\\TdP-2024\\libretto_voti']
```

requirements.txt

- A project may require several external packages
 - Installed with pip
 - Stored in the virtual environment
- How can we **declare** the information about the **required packages**?
 - So that **other people** may install them in their system
 - So that we can control which **version numbers** are installed
- Add a file **requirements.txt** to your project
 - Contains one line per package
 - May optionally specify the version number
 - PyCharm helps us synchronizing the file with the import statements



```
requirements.txt x
1 pip==22.3.1
2 wheel==0.38.4
3 Pillow==9.5.0
4 setuptools==65.5.1
5 packaging==23.1
6 numpy==1.26.0
```

Don't specify version
Strong equality (==x.y.z)
Greater or equal (>=x.y.z)
Compatible version (~=x.y.z)

License



- These slides are distributed under a Creative Commons license “**Attribution-NonCommercial-ShareAlike 4.0 International (CC BY-NC-SA 4.0)**”
- **You are free to:**
 - **Share** — copy and redistribute the material in any medium or format
 - **Adapt** — remix, transform, and build upon the material
 - The licensor cannot revoke these freedoms as long as you follow the license terms.
- **Under the following terms:**
 - **Attribution** — You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
 - **NonCommercial** — You may not use the material for commercial purposes.
 - **ShareAlike** — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.
 - **No additional restrictions** — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.
- <https://creativecommons.org/licenses/by-nc-sa/4.0/>

