



[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

Quickref

Nvim `:help` pages, [generated](#) from [source](#) using the [tree-sitter-vimdoc](#) parser.

Quick reference guide

Contents

tag	subject
tag	subject
Q_ct	list of help files
Q_re	Repeating commands
Q_lr	motion: Left-right
Q_km	Key mapping
Q_ud	motion: Up-down
Q_ab	Abbreviations
Q_tm	motion: Text object
Q_op	Options
Q_pa	motion: Pattern searches
Q_ur	Undo/Redo commands
Q_ma	motion: Marks
Q_et	External commands
Q_vm	motion: Various
Q_qf	Quickfix commands
Q_ta	motion: Using tags
Q_vc	Various commands
Q_sc	Scrolling
Q_ce	Ex: Command-line editing
Q_in	insert: Inserting text
Q_ra	Ex: Ranges
Q_ai	insert: Keys
Q_ex	Ex: Special characters
Q_ss	insert: Special keys
Q_st	Starting Vim
Q_di	insert: Digraphs
Q_ed	Editing a file

Main

[Commands index](#)

[Quick reference](#)

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

[Q_si](#) insert: Special inserts
[Q_fl](#) Using the argument list
[Q_de](#) change: Deleting text
[Q_wq](#) Writing and quitting
[Q_cm](#) change: Copying and moving
[Q_ac](#) Automatic commands
[Q_ch](#) change: Changing text
[Q_wi](#) Multi-window commands
[Q_co](#) change: Complex
[Q_bu](#) Buffer list commands
[Q_vi](#) Visual mode
[Q_sy](#) Syntax highlighting
[Q_to](#) Text objects
[Q_gu](#) GUI commands

[Q_fo](#) Folding

[Q_lr](#) **Left-right motions**

N is used to indicate an optional count that can be given before the command.

h	N h	left (also: CTRL-H , <BS> , or <Left> key)
l	N l	right (also: <Space> or <Right> key)
0	0	to first character in the line (also: <Home> key)
^	^	to first non-blank character in the line
\$	N \$	to the next EOL (end of line) position
g0	g0	(also: <End> key) to first character in screen line (differs from "0" when lines wrap)
g^	g^	to first non-blank character in screen line (differs from "^" when lines

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

wrap)
`g$` `N g$` to last character in
screen line (differs from "\$"
 when lines wrap)
`gm` `gm` to middle of the screen
line
`gM` `gM` to middle of the line
`bar` `N |` to column N (default:
1)
`f` `N f{char}` to the Nth occurrence
of `{char}` to the right
`F` `N F{char}` to the Nth occurrence
of `{char}` to the left
`t` `N t{char}` till before the Nth
occurrence of `{char}` to the right
`I` `N T{char}` till before the Nth
occurrence of `{char}` to the left
`;` `N ;` repeat the last "f",
"F", "t", or "T" N times
`+` `N ,` repeat the last "f",
"F", "t", or "T" N times in
 opposite direction

Q_ud

Up-down motions

`k` `N k` up N lines (also: `CTRL-`
`P` and `<Up>`)
`j` `N j` down N lines (also:
`CTRL-J`, `CTRL-N`, `<NL>`, and `<Down>`)
`=` `N =` up N lines, on the
first non-blank character
`+` `N +` down N lines, on the
first non-blank character (also:
 `CTRL-M` and `<CR>`)
`_` `N _` down N-1 lines, on the
first non-blank character
`G` `N G` goto line N (default:
last line), on the first
 non-blank character
`gg` `N gg` goto line N (default:

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

`gg` `N` `gg` goto line `N` (default: first line), on the first non-blank character

`N%` `N` `%` goto line `N` percentage down in the file; `N` must be given, otherwise it is the `%` command

`gk` `N` `gk` up `N` screen lines (differs from `"k"` when line wraps)

`gj` `N` `gj` down `N` screen lines (differs from `"j"` when line wraps)

Q_tm**Text object motions**

<code>w</code>	<code>N</code>	<code>w</code>	<code>N</code> words forward
<code>W</code>	<code>N</code>	<code>W</code>	<code>N</code> blank-separated <u>WORDS</u> forward
<code>e</code>	<code>N</code>	<code>e</code>	forward to the end of the <code>N</code> th word
<code>E</code>	<code>N</code>	<code>E</code>	forward to the end of the <code>N</code> th blank-separated <u>WORD</u>
<code>b</code>	<code>N</code>	<code>b</code>	<code>N</code> words backward
<code>B</code>	<code>N</code>	<code>B</code>	<code>N</code> blank-separated <u>WORDS</u> backward
<code>ge</code>	<code>N</code>	<code>ge</code>	backward to the end of the <code>N</code> th word
<code>gE</code>	<code>N</code>	<code>gE</code>	backward to the end of the <code>N</code> th blank-separated <u>WORD</u>
<code>)</code>	<code>N</code>	<code>)</code>	<code>N</code> sentences forward
<code>(</code>	<code>N</code>	<code>(</code>	<code>N</code> sentences backward
<code>}</code>	<code>N</code>	<code>}</code>	<code>N</code> paragraphs forward
<code>{</code>	<code>N</code>	<code>{</code>	<code>N</code> paragraphs backward
<code>]]</code>	<code>N</code>	<code>]]</code>	<code>N</code> sections forward, at start of section
<code>[[</code>	<code>N</code>	<code>[[</code>	<code>N</code> sections backward, at start of section
<code>]]</code>	<code>N</code>	<code>]]</code>	<code>N</code> sections forward, at end of section
<code>[[</code>	<code>N</code>	<code>[[</code>	<code>N</code> sections backward, at

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

end of section

`[(` `N` `[(` `N` times back to unclosed '('

`[{` `N` `[{` `N` times back to unclosed '{'

`[m` `N` `[m` `N` times back to start of method (for Java)

`[M` `N` `[M` `N` times back to end of method (for Java)

`)]` `N` `)]` `N` times forward to unclosed ')'

`}]` `N` `}]` `N` times forward to unclosed '}'

`]m` `N` `]m` `N` times forward to start of method (for Java)

`]M` `N` `]M` `N` times forward to end of method (for Java)

`[#` `N` `[#` `N` times back to unclosed "#if" or "#else"

`]#` `N` `]#` `N` times forward to unclosed "#else" or "#endif"

`[star` `N` `[*` `N` times back to start of comment "/*"

`]star` `N` `]*` `N` times forward to end of comment "*/"

Q_pa

Pattern searches

`/` `N` `/ {pattern} [/ [offset]] <CR>`
 search forward for the
 Nth occurrence of `{pattern}`

`?` `N` `? {pattern} [? [offset]] <CR>`
 search backward for the
 Nth occurrence of `{pattern}`

`/<CR>` `N` `/<CR>` repeat last search, in
 the forward direction

`?<CR>` `N` `?<CR>` repeat last search, in
 the backward direction

`n` `N` `n` repeat last search

Main

[Commands index](#)

[Quick reference](#)

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

[N](#) [N](#) [N](#) repeat last search, in
opposite direction

[star](#) [N](#) [*](#) search forward for the
identifier under the cursor

<#> [N](#) <#> search backward for the
identifier under the cursor

[gstar](#) [N](#) [g*](#) like "[*](#)", but also find
partial matches

[g#](#) [N](#) [g#](#) like "<#>", but also find
partial matches

[gd](#) [gd](#) goto local declaration
of identifier under the cursor

[gD](#) [gD](#) goto global declaration
of identifier under the cursor

[pattern](#) Special characters in
search patterns

meaning		magic	nomagic
		matches any single	
character	.	\.	
		matches start of	
line	^	^	
		matches	
<EOL>	\$	\$	
		matches start of	
word	\<	\<	
		matches end of	
word	\>	\>	
	matches a single char from the		
range	[a-z]	\[a-z]	
	matches a single char not in the		
range	[^a-z]	\[^\a-z]	
	matches an identifier		
char	\i	\i	
	idem but excluding		
digits	\I	\I	
	matches a keyword		
character	\k	\k	
	idem but excluding		

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

digits	\K	\K	matches a file name
character	\f	\f	idem but excluding
digits	\F	\F	matches a printable
character	\p	\p	idem but excluding
digits	\P	\P	matches a white space
character	\s	\s	matches a non-white space
character	\S	\S	
			matches
<Esc>	\e	\e	matches
<Tab>	\t	\t	matches
			matches
<CR>	\r	\r	matches
<BS>	\b	\b	
	*	*	matches 0 or more of the preceding
atom	\+	\+	matches 1 or more of the preceding
atom	\=	\=	matches 0 or 1 of the preceding
atom	\{2,5}	\{2,5}	matches 2 to 5 of the preceding
			separates two
alternatives	\	\	group a pattern into an
atom	\(\)	\(\)	

[search-offset](#) Offsets allowed after
search command

[num] [num] lines downwards, in
column 1

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

[Main](#)
[Commands index](#)
[Quick reference](#)

Quick Reference Guide

- [Left-Right Motions](#)
- [Up-Down Motions](#)
- [Text Object Motions](#)
- [Pattern Searches](#)
- [Marks and Motions](#)
- [Various Motions](#)
- [Using Tags](#)
- [Scrolling](#)
- [Inserting Text](#)
- [Insert Mode Keys](#)
- [Special Keys in Insert Mode](#)
- [Digraphs](#)
- [Special Inserts](#)
- [Deleting Text](#)
- [Copying and Moving Text](#)
- [Changing Text](#)
- [Complex Changes](#)
- [Visual Mode](#)
- [Text Objects \(Only in Visual Mode\)](#)
- [Repeating Commands](#)
- [Key Mapping](#)
- [Abbreviations](#)
- [Options](#)
- [Undo/Redo Commands](#)
- [External Commands](#)

Marks and motions

```

m{a-zA-Z}          mark current position
with mark {a-zA-Z}
\_a{a-z} go to mark {a-z} within current file
\_A{A-Z} go to mark {A-Z} in any file
\_0{0-9} go to the position where Vim was
previously exited
\_`          go to the position
before the last jump
\_quote"    go to the position when last
editing this file
\_\[\[        go to the start of the
previously operated or put text
\_\] \]        go to the end of the previously
operated or put text
\_<<        go to the start of the
(previous) Visual area
\_>>        go to the end of the (previous)
Visual area

```

```

\..          go to the position of the last
change in this file
_           '{a-zA-Z0-9[]' "<>}.}
           same as, but on the
first non-blank in the line
:marks      :marks print the active marks
CTRL-O N CTRL-O      go to Nth older
position in jump list
CTRL-I N CTRL-I      go to Nth newer
position in jump list
:ju         :ju[mps]  print the jump list

```

Q_vm

Various motions

```

%           %          find the next brace,
bracket, comment, or "#if"/
               "#else"/"#endif" in
this line and go to its match
H           N H        go to the Nth line in
the window, on the first
                     non-blank
M           M          go to the middle line
in the window, on the first
                     non-blank
L           N L        go to the Nth line from
the bottom, on the first
                     non-blank

go          N go       go to Nth byte
in the buffer

:go         :[range]go[to] [off]  go to [off]
byte in the buffer

```

Q_ta

Using tags

```

:ta         :ta[g][!] {tag}      jump to tag
{tag}
:ta         :[count]ta[g][!]      jump to
[count]'th newer tag in tag list

```

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

[CTRL-\]](#) [CTRL-\]](#) jump to the tag under cursor, unless changes have been made

[:ts](#) [:ts\[elect\]\[!\]](#) [tag] list matching tags and select one to jump to

[:tjump](#) [:tj\[ump\]\[!\]](#) [tag] jump to tag [tag] or select from list when there are multiple matches

[:ltag](#) [:lt\[ag\]\[!\]](#) [tag] jump to tag [tag] and add matching tags to the list

[:tags](#) [:tags](#) print tag list

[CTRL-T](#) N [CTRL-T](#) jump back from Nth older tag in tag list

[:po](#) [:\[count\]po\[p\]\[!\]](#) jump back from [count]'th older tag in tag list

[:tnext](#) [:\[count\]tn\[ext\]\[!\]](#) jump to [count]'th next matching tag

[:tp](#) [:\[count\]tp\[revious\]\[!\]](#) jump to [count]'th previous matching tag

[:tr](#) [:\[count\]tr\[ewind\]\[!\]](#) jump to [count]'th matching tag

[:tl](#) [:tl\[ast\]\[!\]](#) jump to last matching tag

[:ptag](#) [:pt\[ag\] {tag}](#) open a preview window to show tag {tag}

[CTRL-W_}](#) [CTRL-W }](#) like [CTRL-\]](#) but show tag in preview window

[:pts](#) [:pts\[elect\]](#) like [":tselect"](#) but show tag in preview window

[:ptjump](#) [:ptj\[ump\]](#) like [":tjump"](#) but show tag in preview window

[:pclose](#) [:pc\[lose\]](#) close tag preview window

[CTRL-W_z](#) [CTRL-W z](#) close tag

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)
[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

preview window

Q_sc

Scrolling

[CTRL-E](#) N [CTRL-E](#) window N lines
downwards (default: 1)

[CTRL-D](#) N [CTRL-D](#) window N lines
Downwards (default: 1/2 window)

[CTRL-F](#) N [CTRL-F](#) window N pages
Forwards (downwards)

[CTRL-Y](#) N [CTRL-Y](#) window N lines
upwards (default: 1)

[CTRL-U](#) N [CTRL-U](#) window N lines
Upwards (default: 1/2 window)

[CTRL-B](#) N [CTRL-B](#) window N pages
Backwards (upwards)

[z<CR>](#) z<CR> or zt redraw, current
line at top of window

[z.](#) z. or zz redraw, current
line at center of window

[z-](#) z- or zb redraw, current
line at bottom of window

These only work when ['wrap'](#) is off:

[zh](#) N zh scroll screen N
characters to the right

[zl](#) N zl scroll screen N
characters to the left

[zH](#) N zH scroll screen
half a screenwidth to the right

[zL](#) N zL scroll screen
half a screenwidth to the left

Q_in

Inserting text

[a](#) N a append text after the cursor (N
times)

[A](#) N A append text at the end of the
line (N times)

Main

Commands index

Quick reference

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

line (N times)
i N **i** insert text before the cursor
 (N times) (also: **<Insert>**)
I N **I** insert text before the first
 non-blank in the line (N times)
gI N **gI** insert text in column 1 (N
 times)
o N **o** open a new line below the
 current line, append text (N times)
O N **O** open a new line above the
 current line, append text (N times)
:startinsert :star[tinsert][!] start Insert
 mode, append when [!] used
:startreplace :startr[eplace][!] start Replace
 mode, at EOL when [!] used

in Visual block mode:
v_b_I **I** insert the same text in front
 of all the selected lines
v_b_A **A** append the same text after all
 the selected lines

Q_ai

Insert mode keys

insert-index alphabetical index of Insert
 mode commands

leaving Insert mode:

i_<Esc> **<Esc>** end Insert
 mode, back to Normal mode
i_CTRL-C **CTRL-C** like **<Esc>**,
 but do not use an abbreviation
i_CTRL-O **CTRL-O** {command} execute
 {command} and return to Insert mode

moving around:

i_<Up> cursor keys move cursor
 left/right/up/down
i_<S-Left> shift-left/right one word
 left/right

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

[i_<S-Up>](#) shift-up/down one screenful
backward/forward

[i_<End>](#) [<End>](#) cursor after
last character in the line

[i_<Home>](#) [<Home>](#) cursor to
first character in the line

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

[Q_ss](#) **Special keys in Insert mode**

[i_CTRL-V](#) [CTRL-V {char}..](#) insert
character literally, or enter decimal
byte value

[i_<NL>](#) [<NL>](#) or [<CR>](#) or [CTRL-M](#) or [CTRL-](#)
[J](#) begin new
line

[i_CTRL-E](#) [CTRL-E](#) insert the
character from below the cursor

[i_CTRL-Y](#) [CTRL-Y](#) insert the
character from above the cursor

[i_CTRL-A](#) [CTRL-A](#) insert
previously inserted text

[i_CTRL-@](#) [CTRL-@](#) insert
previously inserted text and stop

Insert
mode

[i_CTRL-R](#) [CTRL-R {register}](#) insert the
contents of a register

[i_CTRL-N](#) [CTRL-N](#) insert next
match of identifier before the
cursor

[i_CTRL-P](#) [CTRL-P](#) insert
previous match of identifier before
the cursor

[i_CTRL-X](#) [CTRL-X ...](#) complete the
word before the cursor in
various
ways

[i_<BS>](#) [<BS>](#) or [CTRL-H](#) delete the character before the cursor

[i_](#) [](#) delete the character under the cursor

[i_CTRL-W](#) [CTRL-W](#) delete word before the cursor

[i_CTRL-U](#) [CTRL-U](#) delete all entered characters in the current line

[i_CTRL-T](#) [CTRL-T](#) insert one shiftwidth of indent in front of the current line

[i_CTRL-D](#) [CTRL-D](#) delete one shiftwidth of indent in front of the current line

[i_0_CTRL-D](#) [0 CTRL-D](#) delete all indent in the current line

[i_^_CTRL-D](#) [^ CTRL-D](#) delete all indent in the current line, restore indent in next line

Q_di

Digraphs

[:dig](#) [:dig\[raps\]](#) show current list of digraphs

[:dig](#) [:dig\[raps\]](#) [{char1}{char2}](#) [{number}](#)

...

 add digraph(s) to the list

In Insert or Command-line mode:

[i_CTRL-K](#) [CTRL-K](#) [{char1}](#) [{char2}](#) enter digraph

[i_digraph](#) [{char1}](#) [<BS>](#) [{char2}](#) enter digraph

Main

[Commands index](#)

[Quick reference](#)

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

Main

Commands index

Quick reference

Special inserts

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

Deleting text

```
:d      :[range]d [x]    delete [range] lines  
[into register x]
```

Copying and moving text

[quote](#) "{char} use register {char} for the next delete, yank, or put

[:reg](#) :reg show the contents of all registers

[:reg](#) :reg {arg} show the contents of registers mentioned in {arg}

[y](#) N y{motion} yank the text moved over with {motion} into a register

[v_y](#) {visual}y yank the highlighted text into a register

[yy](#) N yy yank N lines into a register

[Y](#) N Y yank N lines into a register

Note: Mapped to "y\$" by default.

[default-mappings](#)

[p](#) N p put a register after the cursor position (N times)

[P](#) N P put a register before the cursor position (N times)

[\]p](#) N]p like p, but adjust indent to current line

[\[p](#) N [p like P, but adjust indent to current line

[gp](#) N gp like p, but leave cursor after the new text

[gP](#) N gP like P, but leave cursor after the new text

Q_ch

Changing text

[r](#) N r{char} replace N characters with {char}

[gr](#) N gr{char} replace N characters without affecting layout

[R](#) N R enter Replace mode (repeat the entered text N times)

[gR](#) N gR enter virtual Replace mode: Like Replace mode but

Main

Commands index

Quick reference

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

without affecting layout

`v_b_r` `{visual}r{char}` in Visual block mode: Replace each char of the selected text with `{char}`

(change = delete text and enter Insert mode)

`c` `N c{motion}` change the text that is moved over with `{motion}`

`v_c` `{visual}c` change the highlighted text

`cc` `N cc` change N lines

`S` `N S` change N lines

`C` `N C` change to the end of the line (and N-1 more lines)

`s` `N s` change N characters

`v_b_c` `{visual}c` in Visual block mode: Change each of the selected lines with the entered text

`v_b_C` `{visual}C` in Visual block mode: Change each of the selected lines until end-of-line with the entered text

`~` `N ~` switch case for N characters and advance cursor

`v_~` `{visual}~` switch case for highlighted text

`v_u` `{visual}u` make highlighted text lowercase

`v_U` `{visual}U` make highlighted text uppercase

`g~` `g~{motion}` switch case for the text that is moved over with `{motion}`

`gu` `gu{motion}` make the text that is

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

Q_co

Complex changes

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)
[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert Mode](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in Visual Mode\)](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

```

!          N  !{motion}{command}<CR>
                                filter the lines that
are moved over through {command}
!!         N  !!{command}<CR>
                                filter N lines through
{command}
v_!        {visual}!{command}<CR>
                                filter the highlighted
lines through {command}
:range!    :[range]! {command}<CR>
                                filter [range] lines
through {command}
=          N  ={motion}
                                filter the lines that
are moved over through 'equalprg'
==         N  ==      filter N lines through
'equalprg'
v_=        {visual}=
                                filter the highlighted
lines through 'equalprg'
:s         :[range]s[substitute]/{pattern}/
{string}/[g][c]
                                substitute {pattern} by
{string} in [range] lines;
                                with [g], replace
all occurrences of {pattern};
                                with [c], confirm
each replacement
:s         :[range]s[substitute] [g][c]
                                repeat previous ":s"
with new range and options
&          &          Repeat previous ":s" on
current line without options
:ret       :[range]ret[ab][!] [tabstop]
                                set 'tabstop' to new
value and adjust white space
                                accordingly

```

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

Q_v1**Visual mode****Main**[Commands index](#)[Quick reference](#)[visual-index](#) list of Visual mode commands.[v](#) [v](#) start highlighting
characters } move cursor and use[V](#) [V](#) start highlighting
linewise } operator to affect[CTRL-V](#) [CTRL-V](#) start highlighting blockwise
} highlighted text[v_o](#) [o](#) exchange cursor
position with start of highlighting[gv](#) [gv](#) start highlighting on
previous visual area[v_v](#) [v](#) highlight characters or
stop highlighting[v_V](#) [V](#) highlight linewise or
stop highlighting[v_CTRL-V](#) [CTRL-V](#) highlight blockwise or stop
highlighting**Q_to****Text objects (only in Visual mode or after
an operator)**[v_aw](#) [N](#) [aw](#) Select "a word"[v_iw](#) [N](#) [iw](#) Select "inner word"[v_aW](#) [N](#) [aW](#) Select "a [WORD](#)"[v_iW](#) [N](#) [iW](#) Select "inner [WORD](#)"[v_as](#) [N](#) [as](#) Select "a sentence"[v_is](#) [N](#) [is](#) Select "inner sentence"[v_ap](#) [N](#) [ap](#) Select "a paragraph"[v_ip](#) [N](#) [ip](#) Select "inner

paragraph"

[v_al](#) [al](#) Select all lines[v_il](#) [il](#) Select "inner line"[v_ab](#) [N](#) [ab](#) Select "a block" (from
"[" to "])")[v_ib](#) [N](#) [ib](#) Select "inner block"**Quick Reference Guide**[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

```
(from "[" to "]")
v_aB      N  aB      Select "a Block" (from
[ { to } ])
v_iB      N  iB      Select "inner Block"
(from [ { to } ])
v_a>      N  a>      Select "a <> block"
v_i>      N  i>      Select "inner <> block"
v_at      N  at      Select "a tag block"
(from <aaa> to </aaa>)
v_it      N  it      Select "inner tag
block" (from <aaa> to </aaa>)
v_a'      N  a'      Select "a single quoted
string"
v_i'      N  i'      Select "inner single
quoted string"
v_aquote N  a"      Select "a double quoted string"
v_iquote N  i"      Select "inner double quoted
string"
v_a`      N  a`      Select "a backward
quoted string"
v_i`      N  i`      Select "inner backward
quoted string"
```

Q_re

Repeating commands

```
.      N  .      repeat last change
(with count replaced with N)
q      q{a-z}    record typed characters
into register {a-z}
q      q{A-Z}    record typed
characters, appended to register {a-z}
q      q        stop recording
Q      Q        replay last recorded
macro
@      N  @{a-z}  execute the contents of
register {a-z} (N times)
@@     N  @@     repeat previous @{a-
z} (N times)
:@     :@{a-z}   execute the contents of
```

Main

[Commands index](#)

[Quick reference](#)

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

register `{a-z}` as an Ex

command
`:@@` `:@@` repeat previous `:@{a-z}`
`:g` `:[range]g[lobal]/{pattern}/[cmd]`

execute Ex command

`[cmd]` (default: `":p"`) on the lines

within `[range]` where

`{pattern}` matches

`:g` `:[range]g[lobal]!/{pattern}/[cmd]`
 execute Ex command

`[cmd]` (default: `":p"`) on the lines

within `[range]` where

`{pattern}` does NOT match

`:so` `:so[urce] {file}`

read Ex commands from

`{file}`

`:so` `:so[urce]! {file}`

read Vim commands from

`{file}`

`:sl` `:sl[ee]p [sec]`

don't do anything for

`[sec]` seconds

`gs` `N gs` goto Sleep for `N`

seconds

Q_km

Key mapping

`:map` `:ma[p] {lhs} {rhs}` map `{lhs}` to
`{rhs}` in Normal and Visual mode

`:map!` `:ma[p]! {lhs} {rhs}` map `{lhs}` to
`{rhs}` in Insert and Command-line

mode

`:noremap` `:no[remap][!] {lhs} {rhs}`

same as

`":map"`, no remapping for this `{rhs}`

`:unmap` `:unm[ap] {lhs}` remove the
 mapping of `{lhs}` for Normal and

Visual

mode

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

[:unmap!](#) [:unm\[ap\]!](#) [{lhs}](#) remove the mapping of [{lhs}](#) for Insert and Command-line mode

[:map_l](#) [:ma\[p\]](#) [\[lhs\]](#) list mappings (starting with [\[lhs\]](#)) for Normal and Visual mode

[:map_l!](#) [:ma\[p\]!](#) [\[lhs\]](#) list mappings (starting with [\[lhs\]](#)) for Insert and Command-line mode

[:cmap](#) [:cmap/](#)[:cunmap/](#)[:cnoremap](#) like [":map!"](#)/[":unmap!"](#)/[":noremap!"](#) but for Command-line mode only

[:imap](#) [:imap/](#)[:iunmap/](#)[:inoremap](#) like [":map!"](#)/[":unmap!"](#)/[":noremap!"](#) but for Insert mode only

[:nmap](#) [:nmap/](#)[:nunmap/](#)[:nnoremap](#) like [":map"](#)/[":unmap"](#)/[":noremap"](#) but for Normal mode only

[:vmap](#) [:vmap/](#)[:vunmap/](#)[:vnoremap](#) like [":map"](#)/[":unmap"](#)/[":noremap"](#) but for Visual mode only

[:omap](#) [:omap/](#)[:ounmap/](#)[:onoremap](#) like [":map"](#)/[":unmap"](#)/[":noremap"](#) but only for when an operator is pending

[:mapc](#) [:mapc\[lear\]](#) remove mappings for Normal and Visual mode

[:mapc](#) [:mapc\[lear\]!](#) remove mappings for

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

Insert and Cmdline mode

[:imapc](#) :imapc[lear] remove mappings for

Insert mode

[:vmapc](#) :vmapc[lear] remove mappings for

Visual mode

[:omapc](#) :omapc[lear] remove mappings for

Operator-pending mode

[:nmapc](#) :nmapc[lear] remove mappings for

Normal mode

[:cmapc](#) :cmapc[lear] remove mappings for

Cmdline mode

[:mkexrc](#) :mk[exrc][!] [file] write current mappings, abbreviations, and

settings

to [file] (default: ".exrc";

use ! to

overwrite)

[:mkvimrc](#) :mkv[imrc][!] [file]

same as

:mkexrc, but with default ".nvimrc"

[:mksession](#) :mks[ession][!] [file]

like

":mkvimrc", but store current files,

windows,

etc. too, to be able to continue

this

session later

Q_ab

Abbreviations

[:abbreviate](#) :ab[breviate] {lhs} {rhs} add

abbreviation for {lhs} to {rhs}

[:abbreviate](#) :ab[breviate] {lhs} show

abbr's that start with {lhs}

[:abbreviate](#) :ab[breviate] show

all abbreviations

[:unabbreviate](#) :una[breviate] {lhs}

remove abbreviation for {lhs}

[:noreabbrev](#) :norea[brev] [lhs] [rhs] like

":ab" but don't remap [rhs]

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

```

:ab , but don't remap [INS]

```

```

:iabbrev      :iab/:iunab/:inoreab      like
":ab", but only for Insert mode
:cabbrev      :cab/:cunab/:cnoreab      like
":ab", but only for

```

[Main](#)
[Commands index](#)
[Quick reference](#)

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

Command-line mode

```

:abclear      :abc[lear]
remove all abbreviations
:cabclear      :cab[lear]
remove all abbr's for Cmdline mode
:iabclear      :iabc[lear]
remove all abbr's for Insert mode

```

Q_op

Options

```

:set          :se[t]          show
all modified options
:set          :se[t] all      show
all options
:set          :se[t] {option} set
boolean option (switch it on),

                                show
string or number option
:set          :se[t] no{option} reset
boolean option (switch it off)
:set          :se[t] inv{option}
invert boolean option
:set          :se[t] {option}={value} set
string/number option to {value}
:set          :se[t] {option}+={value}
append {value} to string option, add

{value} to number option
:set          :se[t] {option}-={value}
remove {value} to string option,

subtract {value} from number option
:set          :se[t] {option}?    show
value of {option}

```

<code>:set</code>	<code>:se[t] {option}&</code>	reset	Main
<code>{option}</code>	to its default value		Commands index
<code>:setlocal</code>	<code>:setl[ocal]</code>	like	Quick reference
<code>":set"</code>	but set the local value		
options that have one		for	Quick Reference Guide
<code>:setglobal</code>	<code>:setg[lobal]</code>	like	Left-Right Motions
<code>":set"</code>	but set the global value		Up-Down Motions
local option		of a	Text Object Motions
<code>:options</code>	<code>:opt[ions]</code>	open	Pattern Searches
a new window to view and set			Marks and Motions
options, grouped by functionality,			Various Motions
line explanation and links to		a one	Using Tags
help		the	Scrolling
Short explanation of each			Inserting Text
option:	<code>option-list</code>		Insert Mode Keys
<code>'allowrevins'</code>	<code>'ari'</code>	allow <code>CTRL-_</code> in	Special Keys in Insert
Insert mode			Digraphs
<code>'ambiwidth'</code>	<code>'ambw'</code>	what to do with	Special Inserts
Unicode chars of ambiguous width			Deleting Text
<code>'arabic'</code>	<code>'arab'</code>	for Arabic as a	Copying and Moving Te
default second language			Changing Text
<code>'arabicshape'</code>	<code>'arshape'</code>	do shaping for	Complex Changes
Arabic characters			Visual Mode
<code>'autochdir'</code>	<code>'acd'</code>	change directory to	Text Objects (Only in
the file in the current window			Repeating Commands
<code>'autocomplete'</code>	<code>'ac'</code>	enable automatic	Key Mapping
completion in insert mode			Abbreviations
<code>'autocompletedelay'</code>	<code>'acl'</code>	delay in msec	Options
before menu appears after typing			Undo/Redo Commands
<code>'autocompletetimeout'</code>	<code>'act'</code>	initial decay	External Commands
timeout for autocompletion algorithm			

'autoindent'	'ai'	take indent for new line from previous line
'autoread'	'ar'	autom. read file when changed outside of Vim
'autowrite'	'aw'	automatically write file if changed
'autowriteall'	'awa'	as 'autowrite' , but works with more commands
'background'	'bg'	"dark" or "light", used for highlight colors
'backspace'	'bs'	how backspace works at start of line
'backup'	'bk'	keep backup file after overwriting a file
'backupcopy'	'bkc'	make backup as a copy, don't rename the file
'backupdir'	'bdir'	list of directories for the backup file
'backupext'	'bex'	extension used for the backup file
'backupskip'	'bsk'	no backup for files that match these patterns
'belloff'	'bo'	do not ring the bell for these reasons
'binary'	'bin'	read/write/edit file in binary mode
'bomb'		prepend a Byte Order Mark to the file
'breakat'	'brk'	characters that may cause a line break
'breakindent'	'bri'	wrapped line repeats indent
'breakindentopt'	'briopt'	settings for 'breakindent'
'browse'		
'browse'	'bsdir'	which directory to start browsing in
'bufhidden'	'bh'	what to do when buffer is no longer in window
'buflisted'	'bl'	whether the buffer shows up in the buffer list

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'buftype'	'bt'	special type of buffer	Main
'casemap'	'cmp'	specifies how case of letters is changed	Commands index
'cdhome'	'cdh'	change directory to the home directory by <code>":cd"</code>	Quick reference
'cdpath'	'cd'	list of directories searched with <code>":cd"</code>	Quick Reference Guide
'cedit'		key used to open the command-line window	Left-Right Motions
'charconvert'	'ccv'	expression for character encoding conversion	Up-Down Motions
'chistory'	'chi'	maximum number of quickfix lists in history	Text Object Motions
'cindent'	'cin'	do C program indenting	Pattern Searches
'cinkeys'	'cink'	keys that trigger indent when 'cindent' is set	Marks and Motions
'cinoptions'	'cino'	how to do indenting when 'cindent' is set	Various Motions
'cinscopedcls'	'cinsd'	words that are recognized by <code>'cino-g'</code>	Using Tags
'cinwords'	'cinw'	words where 'si' and 'cin' add an indent	Scrolling
'clipboard'	'cb'	use the clipboard as the unnamed register	Inserting Text
'cmdheight'	'ch'	number of lines to use for the command-line	Insert Mode Keys
'cmdwinheight'	'cwh'	height of the command-line window	Special Keys in Insert
'colorcolumn'	'cc'	columns to highlight	Digraphs
'columns'	'co'	number of columns in the display	Special Inserts
'comments'	'com'	patterns that can start a comment line	Deleting Text
'commentstring'	'cms'	template for comments; used for fold marker	Copying and Moving Text
'complete'	'cpt'	specify how Insert mode completion works	Changing Text

['completefunc'](#) ['cfu'](#) function to be used for Insert mode completion
['completeopt'](#) ['cot'](#) options for Insert mode completion
['completeslash'](#) ['csl'](#) like ['shellslash'](#) for completion
['completetimeout'](#) ['cto'](#) initial decay timeout for [CTRL-N](#) and [CTRL-P](#)
['concealcursor'](#) ['cocu'](#) whether concealable text is hidden in cursor line
['conceallevel'](#) ['cole'](#) whether concealable text is shown or hidden
['confirm'](#) ['cf'](#) ask what to do about unsaved/read-only files
['copyindent'](#) ['ci'](#) make ['autoindent'](#) use existing indent structure
['coptions'](#) ['cpo'](#) flags for Vi-compatible behavior
['cursorbind'](#) ['crb'](#) move cursor in window as it moves in other windows
['cursorcolumn'](#) ['cuc'](#) highlight the screen column of the cursor
['cursorline'](#) ['cul'](#) highlight the screen line of the cursor
['cursorlineopt'](#) ['culopt'](#) settings for ['cursorline'](#)
['debug'](#) set to "msg" to see all error messages
['define'](#) ['def'](#) pattern to be used to find a macro definition
['delcombine'](#) ['deco'](#) delete combining characters on their own
['dictionary'](#) ['dict'](#) list of file names used for keyword completion
['diff'](#) use diff mode for the current window
['diffanchors'](#) ['dia'](#) list of [{address}](#) to force anchoring of a diff
['diffexpr'](#) ['dex'](#) expression used to obtain a diff file

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

'diffopt'	'dif'	options for using diff mode	Main
'digraph'	'dg'	enable the entering of digraphs in Insert mode	Commands index
'directory'	'dir'	list of directory names for the swap file	Quick reference
'display'	'dy'	list of flags for how to display text	
'eadirection'	'ead'	in which direction works	Quick Reference Guide
'equalalways'			Left-Right Motions
'encoding'	'enc'	encoding used internally	Up-Down Motions
'endoffile'	'eof'	write <code>CTRL-Z</code> at end of the file	Text Object Motions
'endofline'	'eol'	write <code><EOL></code> for last line in file	Pattern Searches
'equalalways'	'ea'	windows are automatically made the same size	Marks and Motions
'equalprg'	'ep'	external program to use for "=" command	Various Motions
'errorbells'	'eb'	ring the bell for error messages	Using Tags
'errorfile'	'ef'	name of the errorfile for the QuickFix mode	Scrolling
'errorformat'	'efm'	description of the lines in the error file	Inserting Text
'eventignore'	'ei'	autocommand events that are ignored	Insert Mode Keys
'eventignorewin'	'eiw'	autocommand events that are ignored in a window	Special Keys in Insert
'expandtab'	'et'	use spaces when <code><Tab></code> is inserted	Digraphs
'execrc'	'ex'	read init files in the current directory	Special Inserts
'fileencoding'	'fenc'	file encoding for multibyte text	Deleting Text
'fileencodings'	'fencs'	automatically detected character encodings	Copying and Moving Text
'fileformat'	'ff'	file format used for file I/O	Changing Text

'fileformats'	'ffs'	automatically detected values for 'fileformat'
'fileignorecase'	'fic'	ignore case when using file names
'filetype'	'ft'	type of file, used for autocommands
'fillchars'	'fcs'	characters to use for displaying special items
'findfunc'	'ffu'	function to be called for the :find command
'fixendofline'	'fixeol'	make sure last line in file has <code><EOL></code>
'foldclose'	'fcl'	close a fold when the cursor leaves it
'foldcolumn'	'fdc'	width of the column used to indicate folds
'foldenable'	'fen'	set to display all folds open
'foldexpr'	'fde'	expression used when 'foldmethod' is "expr"
'foldignore'	'fdi'	ignore lines when 'foldmethod' is "indent"
'foldlevel'	'fdl'	close folds with a level higher than this
'foldlevelstart'	'fdls'	'foldlevel' when starting to edit a file
'foldmarker'	'fmr'	markers used when 'foldmethod' is "marker"
'foldmethod'	'fdm'	folding type
'foldminlines'	'fml'	minimum number of lines for a fold to be closed
'foldnestmax'	'fdn'	maximum fold depth for which commands a fold will be opened
'foldopen'	'fdo'	
'foldtext'	'fdt'	expression used to display for a closed fold
'formatexpr'	'fex'	expression used with "gq" command
'formatlistpat'	'flp'	pattern used to recognize a list header

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

'formatoptions'	'fo'	how automatic formatting is to be done
'formatprg'	'fp'	name of external program used with "gq" command
'fsync'	'fs'	whether to invoke fsync() after file write
'grepformat'	'gfm'	format of 'grepprg' output
'grepprg'	'gp'	program to use for ":grep"
'guicursor'	'gcr'	GUI: settings for cursor shape and blinking
'guifont'	'gfn'	GUI: Name(s) of font(s) to be used
'guifontwide'	'gfw'	list of font names for double-wide characters
'guioptions'	'go'	GUI: Which components and options are used
'guitablabel'	'gtl'	GUI: custom label for a tabpage
'guitabtooltip'	'gtt'	GUI: custom tooltip for a tabpage
'helpfile'	'hf'	full path name of the main help file
'helpheight'	'hh'	minimum height of a new help window
'helplang'	'hlg'	preferred help languages
'hidden'	'hid'	don't unload buffer when it is abandoned
'history'	'hi'	number of command-lines that are remembered
'hlsearch'	'hls'	highlight matches with last search pattern
'icon'		let Vim set the text of the window icon
'iconstring'		string to use for the Vim icon text
'ignorecase'	'ic'	ignore case in search patterns

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'imcmdline'	'imc'	use IM when starting to edit a command line
'imdisable'	'imd'	do not use the IM in any mode
'imininsert'	'imi'	use :lmap or IM in Insert mode
'imsearch'	'ims'	use :lmap or IM when typing a search pattern
'include'	'inc'	pattern to be used to find an include file
'includeexpr'	'inex'	expression used to process an include line
'incsearch'	'is'	highlight match while typing search pattern
'indentexpr'	'inde'	expression used to obtain the indent of a line
'indentkeys'	'indk'	keys that trigger indenting with 'indentexpr'
'infercase'	'inf'	adjust case of match for keyword completion
'isfname'	'isf'	characters included in file names and pathnames
'isident'	'isi'	characters included in identifiers
'iskeyword'	'isk'	characters included in keywords
'isprint'	'isp'	printable characters
'joinspaces'	'js'	two spaces after a period with a join command
'jumpoptions'	'jop'	specifies how jumping is done
'keymap'	'kmp'	name of a keyboard mapping
'keymodel'	'km'	enable starting/stopping selection with keys
'keywordprg'	'kp'	program to use for the "K" command
'langmap'	'lmap'	alphabetic characters for other language mode

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

'langmenu'	'lm'	language to be used for the menus
'langremap'	'lrm'	do apply 'langmap' to mapped characters
'laststatus'	'ls'	tells when last window has status lines
'lazyredraw'	'lz'	don't redraw while executing macros
'lhistory'	'lhi'	maximum number of location lists in history
'linebreak'	'lbr'	wrap long lines at a blank
'lines'		number of lines in the display
'linespace'	'lsp'	number of pixel lines to use between characters
'lisp'		automatic indenting for Lisp
'lispoptions'	'lop'	changes how Lisp indenting is done
'lispwords'	'lw'	words that change how lisp indenting works
'list'		show <code><Tab></code> and <code><EOL></code>
'listchars'	'lcs'	characters for displaying in list mode
'loadplugins'	'lpl'	load plugin scripts when starting up
'makeef'	'mef'	name of the errorfile for <code>":make"</code>
'makeencoding'	'menc'	encoding of external make/grep commands
'makeprg'	'mp'	program to use for the <code>":make"</code> command
'matchpairs'	'mps'	pairs of characters that "%" can match
'matchtime'	'mat'	tenths of a second to show matching paren
'maxcombine'	'mco'	maximum nr of combining characters displayed

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'maxfuncdepth'	'mfd'	maximum recursive depth for user functions
'maxmapdepth'	'mmd'	maximum recursive depth for mapping
'maxmempattern'	'mmp'	maximum memory (in Kbyte) used for pattern search
'menuitems'	'mis'	maximum number of items in a menu
'mkspellmem'	'msm'	memory used before <code>:mkspell</code> compresses the tree
'modeline'	'ml'	recognize modelines at start or end of file
'modelineexpr'	'mle'	allow setting expression options from a modeline
'modelines'	'mls'	number of lines checked for modelines
'modifiable'	'ma'	changes to the text are not possible
'modified'	'mod'	buffer has been modified
'more'		pause listings when the whole screen is filled
'mouse'		enable the use of mouse clicks
'mousefocus'	'mousef'	keyboard focus follows the mouse
'mousehide'	'mh'	hide mouse pointer while typing
'mousemodel'	'mousem'	changes meaning of mouse buttons
'mousemoveevent'	'mousemev'	report mouse moves with <code><MouseMove></code>
'mouscroll'		amount to scroll by when scrolling with a mouse
'moushape'	'mouses'	shape of the mouse pointer in different modes
'mousetime'	'mouset'	max time between mouse double-click
'nrformats'	'nf'	number formats recognized for <code>CTRL-A</code> command

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'number'	'nu'	print the line number in front of each line
'numberwidth'	'nuw'	number of columns used for the line number
'omnifunc'	'ofu'	function for filetype-specific completion
'opendevic'	'odev'	allow reading/writing devices on MS-Windows
'operatorfunc'	'opfunc'	function to be called for <code>g@</code> operator
'packpath'	'pp'	list of directories used for packages
'paragraphs'	'para'	nroff macros that separate paragraphs
'patchexpr'	'pex'	expression used to patch a file
'patchmode'	'pm'	keep the oldest version of a file
'path'	'pa'	list of directories searched with "gf" et.al.
'preserveindent'	'pi'	preserve the indent structure when reindenting
'previewheight'	'pvh'	height of the preview window
'previewwindow'	'pvw'	identifies the preview window
'pumheight'	'ph'	maximum number of items to show in the popup menu
'pumwidth'	'pw'	minimum width of the popup menu
'pyxversion'	'pyx'	Python version used for pyx* commands
'quoteescape'	'qe'	escape characters used in a string
'readonly'	'ro'	disallow writing the buffer
'redrawtime'	'rdt'	timeout for <code>'hlsearch'</code> and <code>:match</code> highlighting
'regengine'	're'	default regexp engine to use

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

['relativenumber'](#) ['rnu'](#) show relative line number in front of each line

['report'](#) threshold for reporting nr. of lines changed

['revins'](#) ['ri'](#) inserting characters will work backwards

['rightleft'](#) ['rl'](#) window is right-to-left oriented

['rightleftcmd'](#) ['rlc'](#) commands for which editing works right-to-left

['ruler'](#) ['ru'](#) show cursor line and column in the status line

['rulerformat'](#) ['ruf'](#) custom format for the ruler

['runtimepath'](#) ['rtp'](#) list of directories used for runtime files

['scroll'](#) ['scr'](#) lines to scroll with [CTRL-U](#) and [CTRL-D](#)

['scrollbind'](#) ['scb'](#) scroll in window as other windows scroll

['scrolljump'](#) ['sj'](#) minimum number of lines to scroll

['scrolloff'](#) ['so'](#) minimum nr. of lines above and below cursor

['scrolloffpad'](#) ['sop'](#) vertically center cursor at end of file

['scrollopt'](#) ['sbo'](#) how ['scrollbind'](#) should behave

['sections'](#) ['sect'](#) nroff macros that separate sections

['secure'](#) secure mode for reading .vimrc in current dir

['selection'](#) ['sel'](#) what type of selection to use

['selectmode'](#) ['slm'](#) when to use Select mode instead of Visual mode

['sessionoptions'](#) ['ssop'](#) options for [:mksession](#)

['shada'](#) ['sd'](#) use [shada](#) file upon startup and exiting

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'shell'	'sh'	name of shell to use for external commands
'shellcmdflag'	'shcf'	flag to shell to execute one command
'shellpipe'	'sp'	string to put output of ":make" in error file
'shellquote'	'shq'	quote character(s) for around shell command
'shellredir'	'srr'	string to put output of filter in a temp file
'shellslash'	'ssl'	use forward slash for shell file names
'shelltemp'	'stmp'	whether to use a temp file for shell commands
'shellxescape'	'sxe'	characters to escape when 'shellxquote' is (
'shellxquote'	'sxq'	like 'shellquote' , but include redirection
'shiftround'	'sr'	round indent to multiple of shiftwidth
'shiftwidth'	'sw'	number of spaces to use for (auto)indent step
'shortmess'	'shm'	list of flags, reduce length of messages
'showbreak'	'sbr'	string to use at the start of wrapped lines
'showcmd'	'sc'	show (partial) command somewhere
'showcmdloc'	'sloc'	where to show (partial) command
'showfulltag'	'sft'	show full tag pattern when completing tag
'showmatch'	'sm'	briefly jump to matching bracket if insert one
'showmode'	'smd'	message on status line to show current mode
'showtabline'	'stal'	tells when the tabpages line is displayed
'sidescroll'	'ss'	minimum number of columns to scroll horizontal

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'sidescrollloff'	'siso'	min. nr. of columns to left and right of cursor
'signcolumn'	'scl'	when and how to display the sign column
'smartcase'	'scs'	no ignore case when pattern has uppercase
'smartindent'	'si'	smart autoindenting for C programs
'smarttab'	'sta'	<Tab> in leading whitespace indents by 'shiftwidth'
'smoothscroll'	'sms'	scroll by screen lines when 'wrap' is set
'softtabstop'	'sts'	number of columns between two soft tab stops
'spell'		enable spell checking
'spellcapcheck'	'spc'	pattern to locate end of a sentence
'spellfile'	'spf'	files where zg and zw store words
'spelllang'	'spl'	language(s) to do spell checking for
'spelloptions'	'spo'	options for spell checking
'spellsuggest'	'sps'	method(s) used to suggest spelling corrections
'splitbelow'	'sb'	new window from split is below the current one
'splitkeep'	'spk'	determines scroll behavior for split windows
'splitright'	'spr'	new window is put right of the current one
'startofline'	'sol'	commands move cursor to first non-blank in line
'statuscolumn'	'stc'	custom format for the status column
'statusline'	'stl'	custom format for the status line
'suffixes'	'su'	suffixes that are ignored with multiple match

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'suffixesadd'	'sua'	suffixes added when searching for a file
'swapfile'	'swf'	whether to use a swapfile for a buffer
'switchbuf'	'swb'	sets behavior when switching to another buffer
'synmaxcol'	'smc'	maximum column to find syntax items
'syntax'	'syn'	syntax to be loaded for current buffer
'tabclose'	'tcl'	which tabpage to focus when closing a tab
'tabline'	'tal'	custom format for the console tabpages line
'tabpagemax'	'tpm'	maximum number of tabpages for <code>-p</code> and "tab all"
'tabstop'	'ts'	number of columns between two tab stops
'tagbsearch'	'tbs'	use binary searching in tags files
'tagcase'	'tc'	how to handle case when searching in tags files
'tagfunc'	'tfu'	function to get list of tag matches
'taglength'	'tl'	number of significant characters for a tag
'tagrelative'	'tr'	file names in tag file are relative
'tags'	'tag'	list of file names used by the tag command
'tagstack'	'tgst'	push tags onto the tag stack
'term'		name of the terminal
'termbidi'	'tbidi'	terminal takes care of bi-directionality
'termguicolors'	'tgc'	enable 24-bit RGB color in the TUI
'textwidth'	'tw'	maximum width of text that is being inserted

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

'thesaurus'	'tsr'	list of thesaurus files for keyword completion
'thesaurusfunc'	'tsrfu'	function to be used for thesaurus completion
'tildeop'	'top'	tilde command "~" behaves like an operator
'timeout'	'to'	time out on mappings and key codes
'timeoutlen'	'tm'	time out time in milliseconds
'title'		let Vim set the title of the window
'titlelen'		percentage of 'columns' used for window title
'titleold'		old title, restored when exiting
'titlestring'		string to use for the Vim window title
'ttimeout'		time out on mappings
'ttimeoutlen'	'ttm'	time out time for key codes in milliseconds
'ttytype'	'tty'	alias for 'term'
'undodir'	'udir'	where to store undo files
'undofile'	'udf'	save undo information in a file
'undolevels'	'ul'	maximum number of changes that can be undone
'undoreload'	'ur'	max nr of lines to save for undo on a buffer reload
'updatecount'	'uc'	after this many characters flush swap file
'updatetime'	'ut'	after this many milliseconds flush swap file
'varsofttabstop'	'vsts'	a list of number of columns between soft tab stops
'vartabstop'	'vts'	a list of number of columns between tab stops
'verbose'	'vbs'	give informative

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

messages

['verbosefile'](#) ['vfile'](#) file to write

messages in

['viewdir'](#) ['vdir'](#) directory where to

store files with :mkview

['viewoptions'](#) ['vop'](#) specifies what to

save for :mkview

['virtualedit'](#) ['ve'](#) when to use virtual

editing

['visualbell'](#) ['vb'](#) use visual bell

instead of beeping

['warn'](#) warn for shell

command when buffer was changed

['whichwrap'](#) ['ww'](#) allow specified

keys to cross line boundaries

['wildchar'](#) ['wc'](#) command-line

character for wildcard expansion

['wildcharm'](#) ['wcm'](#) like ['wildchar'](#) but

also works when mapped

['wildignore'](#) ['wig'](#) files matching

these patterns are not completed

['wildignorecase'](#) ['wic'](#) ignore case when

completing file names

['wildmenu'](#) ['wmnu'](#) use menu for

command line completion

['wildmode'](#) ['wim'](#) mode for ['wildchar'](#)

command-line expansion

['wildoptions'](#) ['wop'](#) specifies how

command line completion is done

['winaltkeys'](#) ['wak'](#) when the windows

system handles ALT keys

['window'](#) ['wi'](#) nr of lines to

scroll for [CTRL-F](#) and [CTRL-B](#)

['winfixbuf'](#) ['wfb'](#) keep window focused

on a single buffer

['winfixheight'](#) ['wfh'](#) keep window height

when opening/closing windows

['winfixwidth'](#) ['wfw'](#) keep window width

when opening/closing windows

['winheight'](#) ['wh'](#) minimum number of

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

lines for the current window
['winhighlight'](#) ['winhl'](#) window-local highlighting
['winminheight'](#) ['wmh'](#) minimum number of lines for any window
['winminwidth'](#) ['wmw'](#) minimal number of columns for any window
['winwidth'](#) ['wiw'](#) minimal number of columns for current window
['wrap'](#) long lines wrap and continue on the next line
['wrapmargin'](#) ['wm'](#) chars from the right where wrapping starts
['wrapscan'](#) ['ws'](#) searches wrap around the end of the file
['write'](#) writing to a file is allowed
['writeany'](#) ['wa'](#) write to file with no need for "!" override
['writebackup'](#) ['wb'](#) make a backup before overwriting a file
['writedelay'](#) ['wd'](#) delay this many msec for each char (for debug)

Q_ur**Undo/Redo commands**

[u](#) N u undo last N changes
[CTRL-R](#) N [CTRL-R](#) redo last N undone changes
[U](#) U restore last changed line

Q_et**External commands**

[:!](#) :!{command} execute {command} with a shell
[K](#) K lookup keyword under the cursor with

[Main](#)[Commands index](#)[Quick reference](#)[Quick Reference Guide](#)[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

program (default: "man")

Q_qf

Quickfix commands

[:cc](#) [:cc \[nr\]](#) display error
[nr] (default is the same again)

[:cnext](#) [:cn](#) display the
next error

[:cprevious](#) [:cp](#) display the
previous error

[:clist](#) [:cl](#) list all errors

[:cfile](#) [:cf](#) read errors
from the file ['errorfile'](#)

[:cgetbuffer](#) [:cgetb](#) like [:cbuffer](#)
but don't jump to the first error

[:cgetfile](#) [:cg](#) like [:cfile](#) but
don't jump to the first error

[:cgetexpr](#) [:cgete](#) like [:cexpr](#) but
don't jump to the first error

[:caddfile](#) [:caddf](#) add errors from
the error file to the current
quickfix
list

[:caddexpr](#) [:cad](#) add errors from
an expression to the current
quickfix
list

[:cbuffer](#) [:cb](#) read errors
from text in a buffer

[:cexpr](#) [:cex](#) read errors
from an expression

[:cquit](#) [:cq](#) quit without
writing and return error code (to
the
compiler)

[:make](#) [:make \[args\]](#) start make,
read errors, and jump to first
error

[:aren](#) [:ar\[en\] \[args\]](#) execute

Main

[Commands index](#)

[Quick reference](#)

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

`'grep'` to find matches and jump to the first one

[Main](#)
[Commands index](#)
[Quick reference](#)

Q_vc

Various commands

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

`CTRL-L` `CTRL-L` clear and redraw the screen

`CTRL-G` `CTRL-G` show current file name (with path) and cursor

position

`ga` `ga` show ascii value of character under cursor in

decimal,

hex, and octal

`g8` `g8` for utf-8 encoding: show byte sequence for

character

under cursor in hex

`g_CTRL-G` `g CTRL-G` show cursor column, line, and character

position

`CTRL-C` `CTRL-C` during

searches: Interrupt the search

`<Del>` `<Del>` while entering

a count: delete last character

`:version` `:ve[rsion]` show version

information

`:normal` `:norm[al][!]` `{commands}` execute Normal

mode commands

`gQ` `gQ` switch to "Ex"

mode

`:redir` `:redir >{file}`

redirect messages to `{file}`

`:silent` `:silent[!]` `{command}` execute

`{command}` silently

`:confirm` `:confirm {command}` quit,

write, etc., asking about

unsaved

changes or read-only files

[:browse](#) :browse {command}

open/

read/write file, using a

file

selection dialog

Q_ce

Command-line editing

[c_<Esc>](#)

<Esc>

abandon

command-line (if ['wildchar'](#) is

<Esc> ,

type it twice)

[c_CTRL-V](#)

CTRL-V {char}

insert

{char} literally

[c_CTRL-V](#)

CTRL-V {number}

enter

decimal value of character (up to

three

digits)

[c_CTRL-K](#)

CTRL-K {char1} {char2}

enter

digraph (See [Q_di](#))

[c_CTRL-R](#)

CTRL-R {register}

insert the

contents of a register

[c_<Left>](#)

<Left>/<Right>

cursor left/

right

[c_<S-Left>](#)

<S-Left>/<S-Right>

cursor one

word left/right

[c_CTRL-B](#)

CTRL-B/CTRL-E

cursor to

beginning/end of command-line

[c_<BS>](#)

<BS>

delete the

character in front of the cursor

[c_](#)

delete the

character under the cursor

[c_CTRL-W](#)

CTRL-W

delete the

word in front of the cursor

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

[c_CTRL-U](#) [CTRL-U](#) remove all characters between the cursor and beginning of command-line

[c_<Up>](#) [<Up>/<Down>](#) recall older/newer command-line that starts with current command

[c_<S-Up>](#) [<S-Up>/<S-Down>](#) recall older/newer command-line from history

[c_CTRL-G](#) [CTRL-G](#) next match when ['incsearch'](#) is active

[c_CTRL-T](#) [CTRL-T](#) previous match when ['incsearch'](#) is active

[:history](#) [:his\[tory\]](#) show older command-lines

Context-sensitive completion on the command-line:

[c_wildchar](#) ['wildchar'](#) (default: [<Tab>](#)) do completion on the pattern in front of the cursor; if there are multiple matches, beep and show the first one; further ['wildchar'](#) will show the next ones

[c_CTRL-D](#) [CTRL-D](#) list all names that match the pattern in front of the cursor

[c_CTRL-A](#) [CTRL-A](#) insert all names that match pattern in front of cursor

[c_CTRL-L](#) [CTRL-L](#) insert longest common part of names that match

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)
[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

pattern
[c_CTRL-N](#) [CTRL-N](#) after
['wildchar'](#) with multiple matches: go
to next

match
[c_CTRL-P](#) [CTRL-P](#) after
['wildchar'](#) with multiple matches: go
to previous

match

Q_ra **Ex ranges**

[:range](#) , separates two
line numbers

[:range](#) ; idem, set
cursor to the first line number
before
interpreting the second one

[:range](#) {number} an absolute
line number

[:range](#) . the current
line

[:range](#) \$ the last line
in the file

[:range](#) % equal to 1,\$
(the entire file)

[:range](#) * equal to '<,>'
(visual area)

[:range](#) 't position of
mark t

[:range](#) /{pattern}[/] the next line
where {pattern} matches

[:range](#) ?{pattern}[?] the previous
line where {pattern} matches

[:range](#) +[num] add [num] to
the preceding line number
(default: 1)

[:range](#) -[num] subtract [num]

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)
[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

from the preceding line

number

(default: 1)

[Main](#)

[Commands index](#)

[Quick reference](#)

Q_ex

Special Ex characters

[:bar](#) | separates two commands
(not for ":global" and ":%!")

[:quote](#) " begins comment

[:_%](#) % current file name (only
where a file name is expected)

[:_#](#) #[num] alternate file name
[num] (only where a file name is
expected)

Note: The next seven are typed
literally; these are not special keys!

[:<abuf>](#) [<abuf>](#) buffer number, for use
in an autocommand (only where a
file name is

expected)

[:<afile>](#) [<afile>](#) file name, for use in
an autocommand (only where a
file name is

expected)

[:<amatch>](#) [<amatch>](#) what matched with the
pattern, for use in an

autocommand (only
where a file name is expected)

[:<cword>](#) [<cword>](#) word under the cursor
(only where a file name is
expected)

[:<cWORD>](#) [<cWORD>](#) WORD under the cursor
(only where a file name is

expected) (see [WORD](#))

[:<cfile>](#) [<cfile>](#) file name under the
cursor (only where a file name is
expected)

[:<script>](#) [<script>](#) file name of a

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

`":source"` file, within that file (only where a file name is expected)

After "%", "#", "<cfile>", "<script>" or "<afile>"

`::p` :p full path

`::h` :h head (file name removed)

`::t` :t tail (file name only)

`::r` :r root (extension removed)

`::e` :e extension

`::s` :s/{pat}/ {repl}/ substitute {pat} with {repl}

Q_st

Starting Vim

`-file` vim [options] {file} .. start editing one or more files

`--` vim [options] - read file from stdin

`-tag` vim [options] -t {tag} edit the file associated with {tag}

`-qf` vim [options] -q [fname] start editing in QuickFix mode,

display the first error

Most useful Vim arguments (for full list see [startup-options](#))

`++` +[num] put the cursor at line [num] (default: last line)

`++c` +{command} execute {command} after loading the file

`++/` +/{pat} {file} .. put the cursor at

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

```

the first occurrence of {pat}
-e          -e          Ex mode, start vim
in Ex mode
-R          -R          Read-only mode,
implies -n
-m          -m          modifications not
allowed (resets 'write' option)
-d          -d          diff-mode
-b          -b          binary mode
-l          -l          lisp mode
-A          -A          Arabic mode
('arabic' is set)
-H          -H          Hebrew mode (Hebrew
keymap & 'rightleft' are set)
-V          -V          Verbose, give
informative messages
-r          -r          give list of swap
files
-r          -r {file} .. recover aborted
edit session
-n          -n          do not create a
swap file
-o          -o [num]    open [num] windows
(default: one for each file)
-s          -s {scriptin} first read commands
from the file {scriptin}
-w          -w {scriptout} write typed chars
to file {scriptout} (append)
-W          -W {scriptout} write typed chars
to file {scriptout} (overwrite)
-u          -u {vimrc}  read inits from
{vimrc} instead of other inits
-i          -i {shada}  read info from
{shada} instead of other files
---         --         end of options,
other arguments are file names
--help      --help     show list of
arguments and exit
--version   --version   show version info
and exit

```

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

```

--      -      read file from
stdin

Q_ed Editing a file
-----

Without !: Fail if changes have been
made to the current buffer.

With !: Discard any changes to
the current buffer.

:edit_f :e[dit][!] {file}      edit {file}
:edit   :e[dit][!]            reload the
current file
:enew   :ene[w][!]            edit a new,
unnamed buffer
:find   :fin[d][!] {file}      find {file} in
'path' and edit it

CTRL-^  N  CTRL-^            edit alternate
file N (equivalent to ":e #N")
gf      gf or ]f              edit the file
whose name is under the cursor
:pwd    :pwd                  print the
current directory name
:cd     :cd [path]            change the
current directory to [path]
:cd-    :cd -                  back to previous
current directory
:file   :f[ile]                print the
current file name and the cursor
                               position
:file   :f[ile] {name}        set the current file
name to {name}
:files  :files                 show alternate file
names

```

Q_fl **Using the argument list** [argument-list](#)

```

:args      :ar[gs]            print the

```

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

argument list, with the current file
in "[]"
[:all](#) :all or :sall open a window
for every file in the arg list
[:wn](#) :wn[ext][!] write file and
edit next file
[:wn](#) :wn[ext][!] {file} write to {file}
and edit next file, unless
{file}
exists; With !, overwrite existing
file
[:wN](#) :wN[ext][!] [file] write file and
edit previous file
in current window in new window
[:argument](#) :argu[ment] N :sar[gument]
N edit file N
[:next](#) :n[ext]
[:sn\[ext\]](#) edit next file
[:next_f](#) :n[ext] {arglist} :sn[ext]
{arglist} define new arg list
and edit first file
[:Next](#) :N[ext]
[:sN\[ext\]](#) edit previous file
[:first](#) :fir[st]
[:sfir\[st\]](#) edit first file
[:last](#) :la[st]
[:sla\[st\]](#) edit last file

Q_wq

Writing and quitting

[:w](#) :[range]w[rite][!] write
to the current file
[:w_f](#) :[range]w[rite] {file} write
to {file}, unless it already
exists
[:w_f](#) :[range]w[rite]! {file} write
to {file} Overwrite an existing

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

to `{file}`. Overwrite an existing

`:w_a` `:[range]w[rite][!]` >> file
append
to the current file

`:w_a` `:[range]w[rite][!]` >> `{file}` append
to `{file}`

`:w_c` `:[range]w[rite] !{cmd}` execute
`{cmd}` with `[range]` lines as

standard input

`:up` `:[range]up[date][!]` write
to current file if modified

`:wall` `:wa[ll][!]` write
all changed buffers

`:q` `:q[uit]` quit current
buffer, unless changes have been
made; Exit

Vim when there are no other

non-help
buffers

`:q` `:q[uit]!` quit current
buffer always, discard any
changes.

Exit Vim when there are no other

non-help
buffers

`:qa` `:qa[ll]` exit Vim,
unless changes have been made

`:qa` `:qa[ll]!` exit Vim
always, discard any changes

`:cq` `:cq` quit without
writing and return error code

`:wq` `:wq[!]` write the
current file and exit

`:wq` `:wq[!] {file}` write to `{file}`
and exit

`:xit` `:x[it][!] [file]` like `":wq"` but
write only when changes have
been made

[Main](#)

[Commands index](#)

[Quick reference](#)

[Quick Reference Guide](#)

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

[ZZ](#) ZZ same as `":x"`
[ZQ](#) ZQ same as `":q!"`
[:xall](#) :xa[ll][!] or :wqall[!]
 write all
 changed buffers and exit

[:stop](#) :st[op][!]
 start new shell; if `'aw'` option
 is set and
 [!] not given write the buffer

[CTRL-Z](#) [CTRL-Z](#) same as `":stop"`

Q_ac

Automatic Commands

[shada-file](#) read registers, marks, history
 at startup, save when exiting.

[:rshada](#) :rsh[ada] [file] read
 info from ShaDa file [file]

[:rshada](#) :rsh[ada]! [file] idem,
 overwrite existing info

[:wshada](#) :wsh[ada] [file] add
 info to ShaDa file [file]

[:wshada](#) :wsh[ada]! [file] write
 info to ShaDa file [file]

[modeline](#) Automatic option setting when
 editing a file

[modeline](#) vim:{set-arg}: .. In the
 first and last lines of the
 file
 (see `'ml'` option), `{set-arg}` is
 given
 as an argument to `":set"`

[autocommand](#) Automatic execution of commands
 on certain events.

[:autocmd](#) :au list

Main

Commands index

Quick reference

Quick Reference Guide

[Left-Right Motions](#)

[Up-Down Motions](#)

[Text Object Motions](#)

[Pattern Searches](#)

[Marks and Motions](#)

[Various Motions](#)

[Using Tags](#)

[Scrolling](#)

[Inserting Text](#)

[Insert Mode Keys](#)

[Special Keys in Insert](#)

[Digraphs](#)

[Special Inserts](#)

[Deleting Text](#)

[Copying and Moving Text](#)

[Changing Text](#)

[Complex Changes](#)

[Visual Mode](#)

[Text Objects \(Only in](#)

[Repeating Commands](#)

[Key Mapping](#)

[Abbreviations](#)

[Options](#)

[Undo/Redo Commands](#)

[External Commands](#)

all autocommands			Main
:autocmd :au {event}	list		Commands index
all autocommands for {event}			Quick reference
:autocmd :au {event} {pat}	list		
all autocommands for {event}			
	with		Quick Reference Guide
{pat}			Left-Right Motions
:autocmd :au {event} {pat} {cmd}	enter		Up-Down Motions
new autocommands for {event}			Text Object Motions
	with		Pattern Searches
{pat}			Marks and Motions
:autocmd :au!			Various Motions
remove all autocommands			Using Tags
:autocmd :au! {event}			Scrolling
remove all autocommands for {event}			Inserting Text
:autocmd :au! * {pat}			Insert Mode Keys
remove all autocommands for {pat}			Special Keys in Insert
:autocmd :au! {event} {pat}			Digraphs
remove all autocommands for {event}			Special Inserts
	with		Deleting Text
{pat}			Copying and Moving Text
:autocmd :au! {event} {pat} {cmd}			Changing Text
remove all autocommands for {event}			Complex Changes
	with		Visual Mode
{pat} and enter new one			Text Objects (Only in
Q_wi	Multi-window commands		Repeating Commands
CTRL-W_s CTRL-W s or :split	split		Key Mapping
window into two parts			Abbreviations
:split_f :split {file}	split		Options
window and edit {file} in one of			Undo/Redo Commands
	them		External Commands
:vsplit :vsplit {file}	same,		
but split vertically			
:vertical :vertical {cmd}	make		
{cmd} split vertically			
:sfind :sf[ind] {file}	split		

window, find <code>{file}</code> in <code>'path'</code> edit it :terminal <code>:terminal {cmd}</code> terminal window CTRL-W_] <code>CTRL-W]</code> window and jump to tag under cursor CTRL-W_f <code>CTRL-W f</code> window and edit file name under cursor CTRL-W_^ <code>CTRL-W ^</code> window and edit alternate file CTRL-W_n <code>CTRL-W n</code> or <code>:new</code> new empty window CTRL-W_q <code>CTRL-W q</code> or <code>:q[uit]</code> editing and close window CTRL-W_c <code>CTRL-W c</code> or <code>:clo[se]</code> buffer hidden and close window CTRL-W_o <code>CTRL-W o</code> or <code>:on[ly]</code> current window only one on the screen CTRL-W_j <code>CTRL-W j</code> cursor to window below CTRL-W_k <code>CTRL-W k</code> cursor to window above CTRL-W_CTRL-W <code>CTRL-W CTRL-W</code> cursor to window below (wrap) CTRL-W_W <code>CTRL-W W</code> cursor to window above (wrap) CTRL-W_t <code>CTRL-W t</code> cursor to top window CTRL-W_b <code>CTRL-W b</code> cursor to bottom window CTRL-W_p <code>CTRL-W p</code> cursor to previous active window	 and open a split split the split create quit make make move move move move move move move	Main Commands index Quick reference Quick Reference Guide Left-Right Motions Up-Down Motions Text Object Motions Pattern Searches Marks and Motions Various Motions Using Tags Scrolling Inserting Text Insert Mode Keys Special Keys in Insert Digraphs Special Inserts Deleting Text Copying and Moving Text Changing Text Complex Changes Visual Mode Text Objects (Only in Repeating Commands Key Mapping Abbreviations Options Undo/Redo Commands External Commands
---	--	---

CTRL-W_r	CTRL-W r	rotate
windows downwards		
CTRL-W_R	CTRL-W R	rotate
windows upwards		
CTRL-W_x	CTRL-W x	
exchange current window with next one		
CTRL-W_=	CTRL-W =	make
all windows equal height & width		
CTRL-W_-	CTRL-W -	
decrease current window height		
CTRL-W_+	CTRL-W +	
increase current window height		
CTRL-W_	CTRL-W _	set
current window height (default:		
high)		very
CTRL-W_<	CTRL-W <	
decrease current window width		
CTRL-W_>	CTRL-W >	
increase current window width		
CTRL-W_bar	CTRL-W 	set
current window width (default:		
widest possible)		

[Q_bu](#) **Buffer list commands**

:buffers	:buffers or :files	list
all known buffer and file names		
:ball	:ball or :sball	edit
all args/buffers		
:unhide	:unhide or :sunhide	edit
all loaded buffers		
:badd	:badd {fname}	add
file name {fname} to the list		
:bunload	:bunload [f1] [f2]	unload

Main
Commands index
Quick reference
Quick Reference Guide
Left-Right Motions
Up-Down Motions
Text Object Motions
Pattern Searches
Marks and Motions
Various Motions
Using Tags
Scrolling
Inserting Text
Insert Mode Keys
Special Keys in Insert
Digraphs
Special Inserts
Deleting Text
Copying and Moving Text
Changing Text
Complex Changes
Visual Mode
Text Objects (Only in
Repeating Commands
Key Mapping
Abbreviations
Options
Undo/Redo Commands
External Commands

```

:buffer [N] from memory
:buffer [N] and delete it from
the
buffer list

in current window  in new window
:buffer [N] to arg/buf N :[N]sbuffer
:bnext [N] to Nth next arg/buf :[N]sbnext
:bNext [N] to Nth previous arg/buf :[N]sbNext
:bprevious [N] to Nth previous arg/buf :[N]sbprevious
:bfirst :bfirst :sbfirst
:blast :blast :sblast
:bmodified [N] to Nth modified buf :[N]sbmodified

```

Q_sy

Syntax Highlighting

```

:syn-on :syntax on start
using syntax highlighting
:syn-off :syntax off stop
using syntax highlighting

:syn-keyword {group-name} {keyword} ..
add a
syntax keyword item

:syn-match {group-name} {pattern} ...
add
syntax match item

:syn-region {group-name} {pattern} ...

```

Main

Commands index

Quick reference

Quick Reference Guide

Left-Right Motions

Up-Down Motions

Text Object Motions

Pattern Searches

Marks and Motions

Various Motions

Using Tags

Scrolling

Inserting Text

Insert Mode Keys

Special Keys in Insert

Digraphs

Special Inserts

Deleting Text

Copying and Moving Text

Changing Text

Complex Changes

Visual Mode

Text Objects (Only in

Repeating Commands

Key Mapping

Abbreviations

Options

Undo/Redo Commands

External Commands

add

[Main](#)

syntax region item

[Commands index](#)

[:syn-sync](#) :syntax sync [ccomment | lines
{N} | ...]

[Quick reference](#)

tell

syntax how to sync

[Quick Reference Guide](#)[:syntax](#) :syntax [list]

list

current syntax items

[:syn-clear](#) :syntax clear

clear

all syntax info

[:highlight](#) :highlight clear

clear

all highlight info

[:highlight](#) :highlight {group-name} {key}

={arg} ..

set

highlighting for {group-name}

[:filetype](#) :filetype on

switch

on file type detection, without

syntax

highlighting

[:filetype](#) :filetype plugin indent on

switch

on file type detection, with

automatic indenting and settings

Q_gu

GUI commands

[:menu](#) :menu

list

all menus

[:menu](#) :menu {mpath}

list

menus starting with {mpath}

[:menu](#) :menu {mpath} {rhs}

add

menu {mpath}, giving {rhs}

[:menu](#) :menu {pri} {mpath} {rhs}

idem,

with priorities {pri}

[:menu](#) :menu ToolBar {name} {rhs}[Left-Right Motions](#)[Up-Down Motions](#)[Text Object Motions](#)[Pattern Searches](#)[Marks and Motions](#)[Various Motions](#)[Using Tags](#)[Scrolling](#)[Inserting Text](#)[Insert Mode Keys](#)[Special Keys in Insert](#)[Digraphs](#)[Special Inserts](#)[Deleting Text](#)[Copying and Moving Text](#)[Changing Text](#)[Complex Changes](#)[Visual Mode](#)[Text Objects \(Only in](#)[Repeating Commands](#)[Key Mapping](#)[Abbreviations](#)[Options](#)[Undo/Redo Commands](#)[External Commands](#)

:menu	:menu toolbar {name} {rhs}		Main
		add	Commands index
toolbar item, giving {rhs}			Quick reference
:tmenu	:tmenu {mpath} {text}	add	
tooltip to menu {mpath}			
:unmenu	:unmenu {mpath}	remove	Quick Reference Guide
menu {mpath}			Left-Right Motions
			Up-Down Motions
			Text Object Motions
			Pattern Searches
			Marks and Motions
			Various Motions
			Using Tags
			Scrolling
			Inserting Text
			Insert Mode Keys
			Special Keys in Insert
			Digraphs
			Special Inserts
			Deleting Text
			Copying and Moving Text
			Changing Text
			Complex Changes
			Visual Mode
			Text Objects (Only in
			Repeating Commands
			Key Mapping
			Abbreviations
			Options
			Undo/Redo Commands
			External Commands
Q_fo		Folding	
'foldmethod'	set foldmethod=manual	manual	
folding			
	set foldmethod=indent	folding	
by indent			
	set foldmethod=expr	folding	
by 'foldexpr'			
	set foldmethod=syntax	folding	
by syntax regions			
	set foldmethod=marker	folding	
by 'foldmarker'			
zf	zf {motion}		
operator: Define a fold manually			
:fold	:fold {range} fold	define	
a fold for {range} lines			
zd	zd	delete	
one fold under the cursor			
zD	zD	delete	
all folds under the cursor			
zo	zo	open	
one fold under the cursor			
zO	zO	open	
all folds under the cursor			
zc	zc	close	
one fold under the cursor			
zC	zC	close	
all folds under the cursor			
zm	zm	fold	

```

more: decrease 'foldlevel'
zM              zM
all folds: make 'foldlevel' zero
zr              zr
folding: increase 'foldlevel'
zR              zR
all folds: make 'foldlevel' max.

zn              zn
none: reset 'foldenable'
zN              zN
normal set 'foldenable'
zi              zi
'foldenable'

```

[Main](#)
[Commands index](#)
[Quick reference](#)

[Quick Reference Guide](#)
[Left-Right Motions](#)
[Up-Down Motions](#)
[Text Object Motions](#)
[Pattern Searches](#)
[Marks and Motions](#)
[Various Motions](#)
[Using Tags](#)
[Scrolling](#)
[Inserting Text](#)
[Insert Mode Keys](#)
[Special Keys in Insert](#)
[Digraphs](#)
[Special Inserts](#)
[Deleting Text](#)
[Copying and Moving Text](#)
[Changing Text](#)
[Complex Changes](#)
[Visual Mode](#)
[Text Objects \(Only in](#)
[Repeating Commands](#)
[Key Mapping](#)
[Abbreviations](#)
[Options](#)
[Undo/Redo Commands](#)
[External Commands](#)

Generated at 2026-05-24 07:52
 from [61eddb3](#) 

parse_errors: 0 ([report docs bug...](#))
 noise_lines: 2