

Header: [a link, red](#), in navy text.

Pseudo-classes with a fixed answer in a PDF

html { color }. The heading and every piece of text no other rule colours is navy, not black: html is body's parent.

a:link, and a:link b. The link is red, and the bold word in it large. The anchor after it has only a name, so it is not a link: its bold word is small and navy.

[A link with a **bold** word and an anchor.](#)

:any-link. The link is red.

[Any link](#)

a:visited. No link is visited in a PDF: the link is blue, as links are by default.

[Never visited](#)

:hover, :focus, :active, :focus-visible, :target and :focus-within. Nothing a reader does changes a PDF: the link is blue on no background, and the paragraph is navy.

[Never hovered or focused](#)

a:not(:hover). Always true: the link is green and not underlined.

[Not hovered](#)

:root as an ancestor. The paragraph is red.

[Inside the root](#)

:root > div and body:root. The root is html, not body, so neither matches: the paragraph is navy.

[Not a child of the root](#)

html > body > div. The paragraph is red.

[Inside body inside html](#)

2rem. Twice the default font size, 22pt, although body is 9pt: rem is read against html.

Two rem

td:not(:hover). Every cell is pale yellow.

One	Two	Three
-----	-----	-------

In the page header, the link is red. In the positioned box at the foot of the page, :root div.box p makes the text red.

Positioned box: red