

Child and sibling combinators, and structural pseudo-classes

div > p

Only the paragraph directly inside the box is red and bold. The one inside the nested section stays black.

Child of the box

Grandchild, inside a section

h3 + p

Only the paragraph right after the heading is red and bold. The paragraphs before the heading and after the first one stay black.

Before the heading

Heading

Right after the heading

After that one

h3 ~ p

Every paragraph after the heading is red and bold, even past the div between them. The paragraph before the heading and the one inside the div stay black.

Before the heading

Heading

First after the heading

Inside a div after the heading

After the div

li:first-child

The first item of each list is red and bold, the rest black.

- **First bullet**
 - Second bullet
 - Third bullet
- 1. First number**
 2. Second number

li:nth-child(2n)

The second, fourth and sixth items have a yellow background.

1. One
2. **Two**
3. Three
4. **Four**
5. Five
6. **Six**

li:nth-child(-n+2)

The first two items are blue and italic, the third and fourth black.

- 1. One*
- 2. Two*
3. Three
4. Four

p:first-of-type

The first paragraph is red and bold, though the heading comes before it. The second paragraph stays black.

Heading

First paragraph

Second paragraph

p:nth-of-type(2)

Only the second paragraph is red and bold, counting past the heading between them.

First paragraph

Heading

Second paragraph

Third paragraph

p > b

The bold word directly in the paragraph is red. The one inside the span stays black.

A **direct** bold word and a **nested** one.

td:first-child and td + td + td

The first cell of each row is blue. Every cell from the third on is red and bold, and a cell spanning two columns counts as one cell: R1 C3, R1 C4 and R2 C3.

R1 C1	R1 C2	R1 C3	R1 C4
R2 C1, two columns wide	R2 C2	R2 C3	

table > tbody > tr > td

Rows written straight into the table sit in a tbody, as in a browser: every cell is green.

R1 C1	R1 C2
R2 C1	R2 C2